

# Air to Water Inverter Heat Pump

EWYE-CZ



## AIR TO WATER HEAT PUMP


# High temperature & Low carbon solution

Heat Pump Version



## High temperature Heat Pump

Heat Pump version with One and Two independent refrigerant circuits characterized by the optimised and compact design from 1 to 4 fans in line.



Capacity range and layout



19-25 kW



30-35 kW



50-60 kW



70 kW

## Installation flexibility

The new R-454C Small Inverter Heat Pump EWYE-CZ comes in three different layouts, all providing a very compact footprint despite the capacity they can deliver. That makes the series a great solution for projects dealing with space issues such as: residential, hotels and hospitals. No need for extra safety countermeasures due to the fact that the R-454C is an A2L refrigerant as the largely used R-32.

## Product overview


The most complete and unique solution on the market for Decarbonisation. EWYE-CZ reaches 70 °C of heating water temperature even in extreme ambient conditions. That is, during winter season in Nordic Countries (low ambient temperature) and even in summer when Domestic Hot Water production would still be required. Moreover, EWYE-CZ can work in high delta T conditions allowing the supply of heating water to different heating applications in the installation space.

EWYE-CZ is available in 8 sizes from 16 to 70 kW capacity, all equipped with Daikin inverter scroll compressors. As well, fans used on EWYE-CZ are designed by Daikin. The product range also integrates an inverter water pump, facilitating installation operations and saving space.

The product is also available in reduced noise configuration, particularly suitable for noise-sensitive applications as: residential buildings, hotels and hospitals. Comfort heating can be supplied in many different applications, and on top of that EWYE-CZ allows domestic hot water production, including anti-legionella control function for the external storage tank.

## Operating range

	Min	Max
Heating water	20°C	70°C
Ambient temperature OAT	-25°C	40°C



Outdoor installation



Daikin Tubes and fins (Cu/Al coil)



Daikin VFD scroll



Daikin EC Fans



Integrated VFD Pump



Refrigerant

# Product Benefits

## Daikin Core Technology

**Daikin Scroll Compressors** can benefit from Inverter technology that increases this Series' efficiency performance, while the Vapor Injection with Economizer guarantees the Series Capacity steps and extended operating heating envelope.

Great energy efficiency levels are also granted by the **Daikin Inverter Driven Fans**, with high efficiency design glass reinforced resin to maximize performances.

**Daikin Inverter Scroll Compressors** and Pump with Vapor Injection, make this new R-454C Small Inverter Heat Pump a full Inverter Series.

**Daikin Tube & Fins (Cu/Al) Heat Exchanger:** Reversible heat exchanger optimised for most extreme heating operation. Aluminum fins are covered by acrylic layer to ease flowing of condensate moisture and provide resistance to corrosion and protection from UV.

Daikin Inverter  
Scroll Compressors



Daikin Inverter  
Driven Fans




Daikin Tube & Fins  
(Cu/Al) Heat Exchanger




## New compressor technology with Vapor Injection

Refrigerant piping diagram with economizer for Vapor Injection



Refrigerant cycle with Vapor Injection






### Optimised DeFrost Management

Integrated Defrost logic optimised for multiple units to sequence the non-simultaneity of the defrost cycle. Plant up to 4 units are optimised in terms of overall defrost impact:

- Less plant water content
- Higher customer comfort due to minimized temperature drop
- Heating load uniformity over time



### Low operating costs

Thanks to its Full Inverter design, this new unit can closely follow the cooling and heating load profile of the building. This is particularly important as it ensures low operating costs for the HVAC system at part load conditions, which represent most of the operating time.

### F-Gas Ready Solution

The new Small Inverter Heat Pump provides low direct and indirect CO<sub>2</sub> emissions levels. That makes it an environmentally friendly series, also thanks to the use of R-454C, which is known for being a low GWP (145.5) and sustainable refrigerant, fully compliant with the new F-gas regulation.



### Contribution to Green Building

The most popular green building protocols are BREEAM and LEED. EWYE-CZ can contribute to project's credits when evaluating energy efficiency of the hydronic system, thanks to inverter driven compressors. The limited GWP of R-454C also result in a possible contribution when evaluating the impact of refrigerants. On top of that, the Smart Grid accessory allows to control the heat pump maximizing consumptions when renewable energy is produced. Thereby, potentially resulting in credits under BREEAM and LEED protocols, as carbon footprint would be reduced.

**BREEAM®**

**LEED®**  
LEADERSHIP IN ENERGY AND  
ENVIRONMENTAL DESIGN

# Product applications


## High Temperature Heating for boiler replacement and Domestic Hot Water (DHW)

### Space Heating + DHW configurations

- Centralized heating, eventually in combination with gas boilers. DHW supply managed via integration with centralized heating, or independent DHW supply. Groups of units can be managed in master / slave up to 4 per single master
- Applications: residential, light commercial, hotels, gym
- Installation: replacement and new building
- Possible terminals are:
  - Existing radiators (70 °C)
  - Heating floor (30-35 °C)
  - Fan coils (40-45 °C)


#### Centralized heating

Standard configuration




#### Centralized Heating (Hybrid Solution with Gas Boiler)

Dedicated accessory for bivalent operation to be added




#### Centralized heating and DHW production

Dedicated accessory for DHW to be added



#### Centralized heating and DHW production (dedicated generator for DHW)

Dedicated accessory for DHW to be added




# Product applications

## Seasonal Comfort Heating and Cooling + Domestic Hot Water (DHW)


### Comfort cooling & heating

- Centralized comfort heating and cooling. DHW managed via three way valves (priority on DHW demand) or independent DHW supply. Groups of units can be managed in master / slave up to 4 per single master
- Applications: residential, light commercial, hotels, gym
- Installation: replacement and new building
- Possible terminals are:
  - Cooling (23-18°C) and Heating floor (30-35°C)
  - Heating and Cooling Fan Coils

### Centralized cooling and heating Standard configuration




### Centralized cooling, heating and DHW production Dedicated accessory for DHW to be added



### Centralized cooling, heating, and DHW production (dedicated generator for DHW)

Dedicated accessory  
for DHW to be added



# Product options and accessories

## Standard

### Hydronic Kit

#### Description

The Small Inverter Heat Pump is equipped with an inverter pump on board with electrical protection as standard. Possibility to order the unit also without the pump.



### Plant management & connectivity


Master/Slave or Modbus RTU are standard to ensure a perfect plant Connectivity.

Remote monitoring and system optimization with Daikin proprietary cloud platform Daikin on Site.

- **Predictive maintenance** to prevent breakdowns
- **Visualize energy consumption** to reduce energy costs
- Monitor and control your building no matter where you are via the **Daikin On Site**
- **Remote diagnostic support** to increase your system lifetime
- Manage **Multiple sites**



#### Dashboards




OPERATOR

#### Diagnostics



SERVICE

#### Remote software upgrade



DAIKIN

## Master Slave Control

#### Description

The Small Inverter Heat Pump is able to operate in Master/Slave mode optimizing the plant operation up to 4 units. The Master unit manages the Slave units connected in parallel on the same hydraulic plant balancing the running hours and load of each unit and each compressor.

# Product options and accessories


## On-demand

### mAP Mobile APP for HMI controller extension towards end users



#### Description

HMI APP is available on smartphone and tablet devices for close monitoring of unit parameters up to 5 meters



## Plug & play connectivity


#### Description

When ordering the Connectivity Kit, you will receive a Connectivity card. The card will report a unique Activation ID (QR code) identifying the license for a specific SIC unit controller. The SIC controller has a sticker that must be put on the Connectivity card in order to use it with the app.

## Smart grid ready box

#### Description

The Smart Grid Box is an accessory that allows the integration of the Heat Pump control for a Smart Grid application, maximizing use of green energy to run the Heat Pump.



- A: Solar panels
- B: Grid
- C: Interface-compatible system components (Solar inverter / energy management system)
- D: Smart Grid Box
- E: Heat Pump



# Plant water content

The heating water content of the systems should have a minimum water amount to avoid excessive decrease of the water setpoint during the defrost cycle to guarantee the proper environmental comfort.

As a general indication the system water content should not be less than the values deriving from the following formula:

$$kW_{nominal} = \text{Heating capacity at } 40/45^{\circ}\text{C OAT}=7^{\circ}\text{C}$$

The above rule of thumb derives from the following formula, as the relative volume of water capable of maintaining the system temperature within an acceptable  $\Delta T$  (which depends on the heating application) during the defrost transient:

$$\text{Single circuit Unit} \longrightarrow 16 \frac{\text{lt}}{\text{kW}_{nominal}}$$

$$\text{Dual circuit Unit} \longrightarrow 8 \frac{\text{lt}}{\text{kW}_{nominal}}$$

$$\text{Water volume} = \frac{CC [W] * MDD [s]}{FD \left[ \frac{g}{L} \right] * SH \left[ \frac{J}{g^{\circ}C} \right] * (DT) [^{\circ}C]}$$

**CC = Cooling Capacity during defrost operation**

**MDD = Max Defrost Duration**

**FD = Fluid Density**

**SH = Specific Heat**

**DT = Acceptable Water Temperature Differential**

The water temperature difference is considered acceptable for the Comfort Heating application which allows to operate with the minimum volume mentioned in the previous formula.

However, if a smaller water temperature difference is considered acceptable, a larger minimum water volume will be required.

A properly designed storage tank should be added if the system components do not provide sufficient water volume.

In case of more than one installed unit, the overall capacity of the installation must be considered in the calculation so summing the water content of each unit.

These considerations refer to the water volume always flowing through the unit. If there are bypasses, branch of the system that can be excluded, that parts should not be accounted in the water content calculation.

# Product dimensions



Model	Dimensions (mm)
EWYE019CZ(N)(P)-A1	1878x1152x802
EWYE022CZ(N)(P)-A1	1878x1152x802
EWYE025CZ(N)(P)-A1	1878x1152x802
EWYE030CZ(N)(P)-A1	1878x1753x802
EWYE035CZ(N)(P)-A1	1878x1753x802
EWYE050CZ(N)(P)-A2	1878x2905x814
EWYE060CZ(N)(P)-A2	1878x2905x814
EWYE070CZ(N)(P)-A2	1878x3506x814

Minimum access distances to be respected: 500 mm all around the unit (single unit installation) or 1000 mm from each condensing section in case of multiple units' installation.

# Technical data

Inverter Pump On Board				EWYE019 CZP-A1	EWYE022 CZP-A1	EWYE025 CZP-A1	EWYE030 CZP-A1	EWYE035 CZP-A1	EWYE050 CZP-A2	EWYE060 CZP-A2	EWYE070 CZP-A2
Cooling performance 12/7 35°C		Cooling capacity	kW	14,88	16,42	18,24	22,45	25,66	42,11	46,90	59,62
		Capacity control	Type	Inverter Controlled							
		Unit power input		5,39	6,03	6,64	7,39	8,90	15,69	17,86	22,35
		EER		2,76	2,73	2,75	3,04	2,88	2,68	2,63	2,67
		SEER		3,88	3,94	4,07	4,60	4,66	4,22	4,42	4,66
Heating performance 40/45 7°C		Heating capacity		18,21	20,25	23,93	29,72	34,35	49,89	59,58	73,27
		Unit power input	Heating kW	5,86	6,51	7,66	8,92	10,56	16,35	20,34	24,42
		COP		3,11	3,11	3,13	3,33	3,25	3,05	2,93	3,00
Space heating	Average climate, water outlet 35°C	SCOP	Low Temperature	4,00	4,00	4,00	4,38	4,38	3,87	3,87	4,06
	Average climate, water outlet 55°C	SCOP	Medium Temperature	2,83	2,83	2,83	3,20	3,20	2,83	2,83	3,02
Water heat exchanger cooling		Water flow rate	l/s	0,70	0,77	0,84	1,06	1,21	1,99	2,16	2,77
		Water pressure drop	kPa	6,05	7,19	8,41	9,82	12,41	10,01	11,62	9,51
Water heat exchanger heating		Water flow rate	l/s	0,87	0,97	1,11	1,42	1,61	2,35	2,77	3,45
		Water pressure drop	kPa	9,03	10,89	13,77	16,40	20,53	13,57	18,38	14,38
Air heat exchanger		Type		Al Fins & Cu Tubes							
Water heat exchanger				Braze Plate							
Refrigerant		Type		R454C							
		GWP		145,5							
Compressor		Type		Scroll - Vapor Injection							
		Quantity	N°	1					2		
		Economizer	N°	1					2		
Fan		Type		Axial							
		Drive		VFD							
Dimensions		Quantity	N°	1			2		3		4
		Height	mm								
		Width	mm	1878							
		Length	mm	1152			1752		2906		3506
Sound power		Lw [dB(A)] **		77					78		
		Cooling & Heating Lw [dB(A)]		82	83	83	83	83	86	86	86
Power supply		Phase/Frequency/Voltage		3N~/50&60/400							

No Pump On Board				EWYE019 CZN-A1	EWYE022 CZN-A1	EWYE025 CZN-A1	EWYE030 CZN-A1	EWYE035 CZN-A1	EWYE050 CZN-A2	EWYE060 CZN-A2	EWYE070 CZN-A2
Cooling performance 12/7 35°C		Cooling capacity	kW	14,66	16,18	18,29	22,19	25,39	41,78	46,98	59,21
		Capacity control	Type	Inverter Controlled							
		Unit power input		5,43	6,07	6,69	7,43	8,96	15,81	17,76	22,30
		EER		2,70	2,67	2,73	2,99	2,83	2,64	2,65	2,66
		SEER		3,74	3,80	3,99	4,43	4,54	4,10	4,34	4,56
Heating performance 40/45 7°C		Heating capacity		18,47	20,51	24,21	30,02	34,68	50,24	60,47	73,73
		Unit power input	Heating kW	5,90	6,57	7,72	9,00	10,65	16,48	20,54	24,39
		COP		3,13	3,12	3,14	3,34	3,26	3,05	2,94	3,02
Space heating	Average climate, water outlet 35°C	SCOP	Low Temperature	3,89	3,89	3,89	4,31	4,31	3,72	3,72	4,00
	Average climate, water outlet 55°C	SCOP	Medium Temperature	2,83	2,83	2,83	3,20	3,20	2,83	2,83	3,01
Water heat exchanger cooling		Water flow rate	l/s	0,7	0,77	0,84	1,06	1,21	1,99	2,16	2,77
		Water pressure drop	kPa	6,05	7,19	8,41	9,82	12,41	10,01	11,62	9,51
Water heat exchanger heating		Water flow rate	l/s	0,87	0,97	1,11	1,42	1,61	2,35	2,80	3,45
		Water pressure drop	kPa	9,03	10,89	13,77	16,40	20,53	13,57	18,76	14,38
Air heat exchanger		Type		Al Fins & Cu Tubes							
Water heat exchanger				Braze Plate							
Refrigerant		Type		R454C							
		GWP		145,5							
Compressor		Type		Scroll - Vapor Injection							
		Quantity	N°	1					2		
		Economizer	N°	1					2		
Fan		Type		Axial							
		Drive		VFD							
		Quantity	N°	1			2		3		4
Dimensions		Height	mm				1878				
		Width	mm	1152			1752		2906		3506
		Length	mm								
Sound power		Lw [dB(A)] **		77					78		
		Cooling & Heating Lw [dB(A)]		82	83	83	83	83	86	86	86
Power supply		Phase/Frequency/Voltage		3N~/50&60/400							


\*\* Sound power in heating mode, measured according to the EN12102 and under test method following the ISO9614.  
The sound pressure is calculated from the sound power level and are for information only and not considered binding.

# Pump curves

## Sound Power & Pressure Data

Sound pressure level @ 1 m from the unit (rif. 2 x10 <sup>-5</sup> Pa )										
	Lw [dB(A)]	Lp @ 1m [dB(A)]	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz
EWYE019CZP-A1	77	61,2	70,38	62,89	59,83	59,55	56,81	49,49	46,21	46,26
EWYE022CZP-A1	77	61,2	70,38	62,89	59,83	59,55	56,81	49,49	46,21	46,26
EWYE025CZP-A1	77	61,2	70,38	62,89	59,83	59,55	56,81	49,49	46,21	46,26
EWYE030CZP-A1	77	60,7	69,5	60,6	60,0	59,6	56,2	46,7	46,8	44,7
EWYE035CZP-A1	77	60,7	69,5	60,6	60,0	59,6	56,2	46,7	46,8	44,7
EWYE050CZP-A2	78	60,9	65,6	62,1	60,4	57,4	54,3	51,2	52,4	50,8
EWYE060CZP-A2	78	60,9	65,6	62,1	60,4	57,4	54,3	51,2	52,4	50,8
EWYE070CZP-A2	78	60,5	65,1	61,7	60,0	57,0	53,9	50,8	52,1	50,5
EWYE019CZN-A1	77	61,2	70,38	62,89	59,83	59,55	56,81	49,49	46,21	46,26
EWYE022CZN-A1	77	61,2	70,38	62,89	59,83	59,55	56,81	49,49	46,21	46,26
EWYE025CZN-A1	77	61,2	70,38	62,89	59,83	59,55	56,81	49,49	46,21	46,26
EWYE030CZN-A1	77	60,7	69,5	60,6	60,0	59,6	56,2	46,7	46,8	44,7
EWYE035CZN-A1	77	60,7	69,5	60,6	60,0	59,6	56,2	46,7	46,8	44,7
EWYE050CZN-A2	78	60,9	65,6	62,1	60,4	57,4	54,3	51,2	52,4	50,8
EWYE060CZN-A2	78	60,9	65,6	62,1	60,4	57,4	54,3	51,2	52,4	50,8
EWYE070CZN-A2	78	60,5	65,1	61,7	60,0	57,0	53,9	50,8	52,1	50,5

Model	Pump curve
EWYE019CZP-A1	A
EWYE022CZP-A1	A
EWYE025CZP-A1	A
EWYE030CZP-A1	B
EWYE035CZP-A1	B
EWYE050CZP-A2	C
EWYE060CZP-A2	C
EWYE070CZP-A2	D





**Daikin Europe N.V.** · Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Publisher)

12/2024      ECPEN24-423A



**FSC LOGO**  
TO BE INSERTED BY PRINTER

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.