



Home leave



Whisper guiet

Designed for hotel applications

- > Compact unit (230mm high & 652mm deep), can easily be mounted in narrow ceiling voids
- > Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- > Flexible installation, as the air suction direction can be altered from rear to bottom suction
- > For easy mounting, the drain pan can be located to the left or right of the unit

FDBQ-B + MXS-K/MXS-G/ MXS-E/MXS-F




Indoor unit			FDBQ	25B
Dimensions	Unit	HeightxWidthxDepth	mm	230x652x502
Sound power level	Cooling		dBA	55
	Heating		dBA	55
Sound pressure level	Cooling	High	dBA	35.0
		Low	dBA	28.0
	Heating	High	dBA	35.0
		Low	dBA	29.0
Control systems	Wired remot	e control		BRC1D52 / BRC1E52A/B

Outdoor unit					3MXS40K	3MXS68G	3MXS52E	4MXS80E	5MXS90E	4MXS68F	
Dimensions	Unit	HeightxWidthxDepth mm			735x936x300	735x936x300	735x936x300	770x900x320		735x936x300	
Sound power level	Cooling			dBA	59	61	59	62	66	61	
	Heating	dBA			60		60				
Sound pressure level	Cooling	Nom.		dBA	46	48	46	48	52	48	
	Heating	Nom.		dBA	47	49	47	49	52	49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	-10~46	-10~46			-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18	-15~18	-15~18			-15~18	
Refrigerant	Type/GWP			R-410A/2,087.5							
	Charge		kg/TCO ₃ Eq		2.0/ 4.2	2.59/ 5.4	2.0/4.2	2.99/6.2		2.6/5.4	
Power supply	Phase/Frequency/Voltage Hz/			Hz/V	1~/50/230						

Contains fluorinated greenhouse gases (1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)







Dalkin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

