

Wall mounted unit

FTXL-JV



Guaranteed operation down to -25°C



Online controller via app

Wall mounted unit providing high efficiency and comfort, even at ambient temperatures down to

- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › Whisper quiet in operation down to 23 dBA
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- › Seasonal efficiency values: A+ in cooling and heating

FTXL-JV + RXL-M3



Indoor unit		FTXL	25JV	35JV
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDepth	mm	
			283x770x198	
Sound power level	Heating		dBA	
			57	
Sound pressure level	Cooling		dBA	
			57	
Sound pressure level	Cooling	High/Low/Silent operation	dBA	
			41/27/23	
level	Heating	High/Low/Silent operation	dBA	
			41/29/26	
Control systems	Infrared remote control		ARC433A87	


Efficiency data		FTXL + RXL	25JV + 25M3	35JV + 35M3
Cooling capacity	Nom.	kW	2.5	3.5
Heating capacity	Nom.	kW	3.2	3.8
Power input	Cooling	Nom.	kW	
			0.040 / 0.040 / 0.040	
Heating	Heating	Nom.	0.72	0.90
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A+	
		Pdesign	kW	2.50
	SEER		6.01	5.87
	Annual energy consumption	kWh	146	209
Heating (Average climate)	Heating	Energy efficiency class	A+	
		Pdesign	kW	2.50
	SCOP/A		4.37	4.21
	Annual energy consumption	kWh	793	998
Nominal efficiency	EER		3.12	3.07
	COP		4.43	4.21
	Annual energy consumption	kWh	400	570
	Energy labeling Directive	Cooling	B	
	Heating	A		

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load | Maximum heating capacity at -15°C outdoor temperature

Outdoor unit		RXL	25M3	35M3
Dimensions	Unit	HeightxWidthxDepth	mm	
			550x858x330	
Sound power level	Cooling		dBA	
			61	
Sound pressure level	Heating		dBA	
			61	
Sound pressure level	Cooling	High/Low	dBA	
			48/44	
level	Heating	High/Low	dBA	
			49/45	
Operation range	Cooling	Ambient	Min.-Max.	°CDB
				-10~-46
Heating	Heating	Ambient	Min.-Max.	°CWB
				-25~-18
Refrigerant	Type/Charge/GWP		kg/TCO _{eq}	
			R-410A/1/2.1/2,087.5	
Power supply	Phase/Frequency/Voltage		Hz/V	
			1~/50/220-240	

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

ECPEN16-032

01/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.