





VRV, Purpose-built to support the decarbonisation of commercial buildings



What's new?







BLUEVOLUTION

Extending VRV 5 total solution

NEW


p. 28p. 152p. 176



Extending our market-leading portfolio

- > Integration of AHU's via new extended range of expansion valve kits and control boxes
- Maximum design flexibility, thanks to Shîrudo Technology
- > Top sustainability over the entire lifecycle





UV Streamer kit

BAEF125AWB

NEW


p. 48



- > Purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc
- > Removes 99.90% of viruses in 30 minutes thanks to the Catch and Clean approach
- Highly efficient F7 filter (ISO classification under testing)
- UVC light and Streamer technology for cleaning and decompostion of pollutants
- Available in combination with standard and white Round Flow decoration panels
- > Can be reftrofitted into existing installations

Extention of multi zoning kits

AZEZ6DAIBS07



NEW

p.132



- New lower height range directly connectable to medium ESP concealed ceiling units
- > The multi-zoning system is a room-by-room controller, fitted with motorised dampers
- > Up to 8 individual zones can be served
- Time-saving as plenum comes fully pre-assembled with dampers and control boards

Concealed ceiling unit with high ESP

FXMQ-A

NFW

p. 135

- > Ideal for large sized spaces, ESP up to 270Pa
- > Large capacity up to 31.5 kW



- Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- > Drain pump available as option
- > Pre-filters and high efficiency filter options




Modular T Smart

ATB-L/S

p.160

NEW

> Top connected Air Handling Unit, reducing the unit's footprint



- Plug&Play control solution, for a quick and easy start-up
- > DX coil integration to connect to VRV or ERQ



Plug&Play heat recovery ventilation unit


NEW

p. 169

> For Schools and light commercial applications with an immediate need for fresh air



 Unit does not require any ductwork for supply or return air keeping interior works to a minimum



Intelligent Touch Manager

DCM601B51

UPDATE

p. 194

> New power cut off & Quiet operation control



- > Improved Touch Panel operability
- > New Software version 1.31.00
- > ITM plus adaptor replaced by DIII Plus adaptor & slot with new design



Tightfit – Fireless copper pipe connector

NEW

p. 216

- > Non-brazed connection for refrigerant piping
- > Can be used without any special tools or permits
- Ew
- > Extremely durable: withstands up to 4 times the operation pressure or R-32





Continuing our path to OWER CO₂ equivalent solutions









Innovation and adaptation are at the heart of Daikin's decarbonisation strategy. When it comes to refrigerant selection, we have a diversity of choice that we are constantly evaluating to determine the appropriate refrigerant for each application and convert our portfolio to lower GWP refrigerants.

For VRV heat pumps, Daikin has assessed various refrigerants based on four criteria: overall environmental impact, energy efficiency, safety and cost-effectiveness. R-32 was determined to be the most balanced for direct expansion heat pumps.

Since launching the VRV 5 S-series with R-32 in 2020, we continue to expand our VRV portfolio with the launch of the VRV 5 Heat Recovery system and a VRV 5 heat pump in the near future

Benefits of R-32

R-32 refrigerant has a lower Global Warming Potential and higher efficiency compared to R-410A, making it the most effective sustainable solution for VRF systems today.

- > Lower Global Warming Potential (GWP): only 1/3rd of R-410A
- > Lower refrigerant charge: 15% less compared to R-410A
- > **Higher energy efficiency**, greatly reducing the indirect CO₃ eq. impact
- > Single component refrigerant, easy to handle and recycle.





Benefits of VRV heat pumps

VRV systems offer commercial buildings maximum flexibility and peace of mind thanks to the advantages direct expansion (DX) systems have to offer:

- > More responsive: Immediate reaction to changing conditions helps avoid overheating
- > Highly efficient: Only 2 energy transfer steps are needed (from air to refrigerant, and from refrigerant to air)
- > Quick and easy to install: All-in-one box solution without any requirement for field supplied equipment (e.g. gauges, pumps and valves)
- > Limited space requirements: All components are integrated, and refrigerant piping is compact.







VRV Commercial air-to-air heat pumps

Introduction	6
Building a sustainable legacy together	6
VRV, unique in the market	8
Which VRV offers me the best solution	10
VRV total solution	12
VRV benefits and technologies	15
VRV 5 BLUEVOLUTION	28
VRV 5 Outdoor units	28
VRV 5 Indoor units	45
LOOP	
VRV IV BY DAIKIN	62
VRV IV Outdoor units	62
VRV IV Indoor units, hot water, Biddle Air curtains	121

Commercial air	
purification & ventilation	155
ERV/HRV - Energy/Heat recovery ventilation units	158
Daikin air handling units with DX connection	170
Integration in third party AHU	176
Commercial air purifiers	178
Control systems	181
Application overview	182
Individual control systems	184
Centralised control systems	192
Standard protocol interfaces	200
Daikin Cloud Service	208
Options & Accessories	215
Tightfit fireless joint	216
VRV 5 outdoor	218
VRV 5 indoor	221
VRV IV outdoor	222
VRV IV indoor	227
Ventilation	228
Control systems	230
Tools	233
Technical Drawings	243



Building a sustainable legacy together

Air surrounds us all the time, and in fact our very existence depends on it. At Daikin, the future of the world's indoor air is our greatest concern.

Daikin envisions a world with healthier indoor air while reducing our environmental impact. Driven by a dedication to achieve net zero CO_2 emissions by 2050, we provide **safe**, **healthy and comfortable spaces** throughout the building life cycle using **world-leading technology**.

Building on our **long-term partnerships**, let's build together now to achieve our goals, protecting the health and wellbeing of every individual.

Supporting decarbonization

We must act now to ensure we create a long-lasting legacy. As a company that values sustainability, we want to help to **decarbonize** buildings and create a **healthy** environment for generations to come.

Taking on the sustainable transformation, our solutions reduce the CO₂ footprint of buildings, whether they are new builds or renovations:

- Reusing existing refrigerant through L∞P Daikin, we reuse resources already available in the market, fully supporting the EU circular economy at a low carbon footprint
- If needed we introduce virgin refrigerant through lower GWP refrigerants such as R-32 reducing the direct CO2eg impact
- Maximizing sustainability over the entire life cycle, thanks to market-leading real life seasonal efficiencies
- Ensuring systems run efficiently 24/7 through smart controls

Building for the future

As market leaders in total solutions, we are constantly innovating to offer you a **comfortable**, **healthy and safe** environment, meeting your needs. Reliability, support and precision are characteristics of our future-proof products and services. We offer:

- A wide range of next-generation heat pumps to meet complex demands, including easy upgrading extending the lifetime of our equipment
- Expert indoor air quality solutions through our ventilation and filtration systems to eliminate pollutants and balance humidity levels

A journey we take together

Together we take on the sustainability journey. We provide expert **support** throughout the building life cycle and give **peace of mind** by ensuring what we do is **future-proof** and is helping to build a better future.

- Our team of experts, go beyond product support. Together we reach your green objectives.
- We are there for you, all the time: via our local customer support teams and e-commerce solutions.
- We're in it for the long term.
 We deliver what we commit to, providing clear and trustworthy data



reasons why VRV is unique in the market



Leader in sustainability

- NEW > VRV 5: dedicated R-32 VRV design
 - Less refrigerant charge
 - Higher efficiency
 - Lower CO₂ equivalent
 - > L∞P by Daikin: the creation of a circular economy of refrigerants
 - · Saves over 400,000 kgs of virgin refrigerant being produced every year
 - Greatly reduces the CO₂ foorprint of refrigerant production
 - For all VRV units produced and sold in Europe*

* EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland







Efficiency

- > Variable Refrigerant Temperature for high seasonal efficiency
- > Round flow cassette and concealed ceiling units with auto cleaning filter
- > The best partner for your BREEAM, LEED or Well project







Comfort

- > Provide high Indoor Air Quality though seamless integration of AHU's (For VRV IV models)
- > Variable Refrigerant Temperature preventing cold draughts in cooling thanks to high outblow temperatures
- > True continuous heating during defrost
- > Presence and floor sensors direct the air flow away from persons, while ensuring an even temperature distribution
- > Auto cleaning filters to ensure optimum air quality

NEW > UV Streamer kit, purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc



Reliability

- > Refrigerant cooled PCB
- > Most extensive testing before new units leave the factory
- > Widest sales network with all spare parts available in Europe
- > Preventive maintenance via Daikin Cloud Service
- > Auto cleaning filters to further enhance reliability thanks to clean air-filters
- > True technical cooling





5 Design

- > Widest ever range of cassette panels
- Available in white and black
- Sleek designer panel range
- > Daikin Emura, unique iconic design
- > Fully flat cassette, fully integrated in the ceiling





- Voice control via Amazon Alexa and Google Assistant through BRP069C51 Onecta app (For VRV 5 models)
- Madoka: a sleek wired remote controller with intuitive touch button control
- > Intelligent Touch manager: A cost-effective mini BMS integrating all Daikin products
- > Easy integration in third party BMS via BACnet, LonWorks, Modbus, KNX
- > Dedicated control solutions for applications such as technical cooling, shops, hotels, ...
- Daikin Cloud Service for online control, energy monitoring, comparison of multiple sites and predictive maintenance



7 Installation

- > Automatic refrigerant charge and refrigerant containment check
- > Unique 4-way blow ceiling suspended cassette (FXUQ)
- > Plug & play Daikin Air Handling Unit
- VRV configurator software for the fastest commissioning, configuration and customisation
- Outdoor unit display for quick on-site settings and detailed error readouts for improved customer support





7-segment display

8 Inventor of VRV with over 40 years of history

- > Market leader of VRV systems since 1982
- > Over 90 years of expertise in heat pump technology
- > Designed for and produced in Europe
- > Innovator setting the market standard with technologies such as Variable Refrigerant Temperature, continuous heating, Shîrudo technology, ...





9 For every application a solution

- > Heat recovery for simultaneous cooling and heating
- > Maximum flexibility for geothermal applications with water-cooled systems
- > Hot and cold climate solutions offering efficient cooling up to 52°C and heating down to -25°C
- > Space saving mini VRV solutions, offering the most compact VRV
- > The invisible VRV, a unique solution when the outdoor unit must be compact and completely invisible
- > Replacement solutions to replace existing systems in the most cost-effective way



Which VRV

system offers me the best solution?

Heat recovery or heat pump? VRV Heat recovery

Additional credits for green building certificate



Extracted heat is used to deliver "free" heating and hot water (1)



'



Hot water (1

North

Cooling

Hea

- Simultaneous heating AND cooling from one system
- "Free" heating and hot water production (1) by transferring heat from areas requiring cooling
- > Maximum individual comfort in all areas
- > Technical cooling down to -20°C
- > Running costs of VRV heat recovery system can be 30 to 40% lower compared to water fan coil system (2)





Outdoor unit



Indoor unit



3-pipe refrigerant piping



BS boxes: allows the individual switching of indoor units between heating and cooling

VRV Heat pump

For either heating **OR** cooling operation from one system

Components:




Outdoor unit



Indoor unit



2-pipe refrigerant piping



⁽¹⁾ Hot water hydrobox connection only in combination with VRV IV+ heat recovery (2) According to the Franklin + Andrews construction economics

Air cooled or water cooled? Air Cooled

- > Fast and easy to install; no need for additional components
- > Low maintenance costs
- > Operation range from 25°C~52°C
- > Can be installed both outdoors and indoors
- > Up to 54HP capacity for one system

Components:



Outdoor unit



Indoor unit



Refrigerant piping



Water Cooled

- Suitable for high rise and large buildings because of the nearly unlimited possibilities of water piping
- > Not affected by outdoor temperature/climate conditions
- > Reduce CO₂ emmisions thanks to the use of geothermal energy as a renewable energy source
- > Allows heat recovery in the entire building thanks to the storage of energy in the water circuit
- > Lower refrigerant levels thanks to the limited distance between outdoor and indoor units

Components:



Indoor unit




Refrigerant piping



Outdoor unit



(Geothermal) water loop



VRV total solution

Typically, many buildings today rely on several separate systems for heating, cooling, air curtain heating and hot water. As a result energy is wasted. To provide a much more efficient alternative, VRV technology has been developed into

a total solution managing up to


70%


of a buildings energy consumption giving large potential to cost saving.

- Heating and cooling for year round comfort
- > Hot water for efficient production of hot water
- Underfloor heating / cooling for efficient space heating/cooling
- Fresh air ventilation for high quality environments
- Air curtains for optimum air separation
- Controls for maximum operating efficiency
- \rightarrow Cooling for server rooms, telecom shelters, ... via VRV heat recovery or Sky Air units
- Refrigeration via our VRV based refrigeration units

Average hotel energy consumption

Average office energy consumption





Offices Efficiency in the workplace



Hotel Hospitality with economy

"With Daikin we could perfectly combine the authenticity of the hotel with the latest technology and comfort."


Owner of a 5-star hotel



Shops reducing retail costs

"Together with Daikin's technical team we have optimised the design of our HVAC system, reducing investment levels and operational costs. Daikin has offered us access to the most up to date technology."

Retail shop representative



Residential there is no place like home

"A cost effective, low energy consumption heat pump system for home owners, offering maximum comfort"





VRV benefits & technologies

Drastically reducing your running costs	16
Top reliability	20
Comfort guaranteed at all times	22
Great design flexibility	24
Fast installation and commissioning,	
easy servicing	26

Benefits of direct expansion (DX) systems Highly efficient > Only 2 energy transfer steps maximise efficiency. Running costs of a water-based fan coil unit can be 40 to 72% higher compared to a VRV heat recovery system Refrigerant Precise zone control > Only condition areas in need for cooling or heating > Immediate reaction to changing conditions and precise control to 0.5°C ON ON ON **OFF** OFF ALL **(INVERTER) Compact units** > Avoid the need for T₃× structural reinforcement or special equipment to lift units in place

Quick and easy to install All-in-one box solution without any requirement for field

supplied equipment (e.g. gauges, pumps and valves)

> Up to 20% less space required compared to traditional water-based systems, offering more lettable space

> Small piping diameters

Drastically reducing running costs

- + Innovative technologies to offer market-leading efficiencies
- (+) Flexibility to meet the building load at the highest efficiency

BLUEVOLUTION

Introducing R-32 refrigerant on VRV5

- > Lower Global Warming Potential (GWP): only 1/3rd of R-410A
- > Lower refrigerant charge: 15% less compared to R-410A
- > Higher energy efficiency
- Single component refrigerant, easy to handle and recycle




Only 2 energy transfer steps

- > Maximised efficiency thanks to direct expansion (DX) technology
- Running costs of a water-based fan coil unit can be 40 to 70% higher compared to a VRV heat recovery system

Air Refrigerant Air

Precise zone control





Variable refrigerant temperature

The biggest leap since the inverter compressor

Thanks to its revolutionary variable refrigerant temperature technology (VRT), VRV continuously adjusts both the inverter compressor speed and the refrigerant temperature in cooling AND heating, providing the necessary capacity to meet the building load with the highest efficiency at all times!

- > Seasonal efficiency increased by 28%
- > The first *weather accommodating control* on the market
- Customer comfort is assured thanks to higher outblow temperatures (preventing cold draughts)

How does it work?

VRF standard

Capacity is controlled only with the variation of the inverter compressor.

Daikin VRV


Variable Refrigerant Temperature control for energy saving in partial load condition.

The capacity is controlled by the inverter compressor and variation of the evaporating (Te) and condensing (Tc) temperature of the refrigerant in order to achieve the highest seasonal efficiency.

Evaporating temperature can vary between 3 and 16° which is the widest on the market.








37 patents


Inverter scroll compressor with back pressure control

- > Pressure port increases pressure below the scroll in low load operation, preventing refrigerant leak from the high to low pressure side
- > Increased partial load efficiency





During low load, weak pressure is applied resulting in refrigerant leakage.




The back pressure control port sends high pressure refrigerant to the back of the scroll ensuring optimum pressure on the scroll.

Predictive Control Function (PCF)

- > Reaching targets faster
- > Reaching targets without overshooting, so there is no waste, resulting in improved efficiency

The large number of Daikin systems already in operation and which are monitored by our Daikin Cloud Service put us in the unique position of being able to analyse this data and develop the predictive control function.




DC fan motor

Outer rotor DC motor for higher efficiency

- > Larger rotor diameter results in greater force for the same magnetic field, leading to better efficiency
- > Better control, resulting in more fan steps to match the actual capacity


Sine wave DC inverter

Optimizing the sine wave curve results in smoother motor rotation and improved motor efficiency.




E-Pass heat exchanger

Optimising the heat exchanger's path layout prevents heat being transferred from the overheated gas section to the sub-cooled liquid section which is a more efficient way to use the heat exchanger.



I-demand function

Limit maximum power consumption. The newly introduced current sensor minimizes the difference between the actual power consumption and the predefined power consumption.



Top reliability

- + Most extensive testing before new units leave the factory
- + Designed to perform

Duty Cycling extends operation life

The cyclical start-up sequence of multiple outdoor units systems equalises compressor duty and extends operating life.



Back-up function

In the event of a compressor malfunction another compressor or outdoor unit will take over in order to maintain 8 hour interim capacity, allowing time for maintenance or repair while comfort remains guaranteed.



Auto-cleaning filters

Auto cleaning filters enhance reliability thanks to clean air filters all the time.

Additionally clean filters reduce running costs and improve indoor air quality.



Refrigerant-cooled PCB

- Reliable cooling because it is not influenced by ambient air temperature
- Smaller switchbox for smoother air flow through the heat exchanger increasing heat exchange efficiency with 5%



Sequential Start


Up to 3 outdoor units can be connected to 1 power supply and can be turned on sequentially. This allows the number of breakers and their capacities to remain small and simplifies wiring (for models of 10HP or less).



Only brazed connections


All flange and flare connections inside the unit have been replaced by brazing connections to ensure improved refrigerant containment.

Also the connection of the outdoor in the main pipe is brazed.



Anti Corrosion Treatment

Special anti corrosion treatment of the heat exchanger provides 5 to 6 times greater resistance against acid rain and salt corrosion. The provision of rust proof steel sheet on the underside of the unit gives additional protection.




Performed tests:

- > VDA Wechseltest
- > Contents of 1 cycle (7 days):
- > 24 hours salt spray test SS DIN 50021
- > 96 hours humidity cycle test KFW DIN 50017
- > 48 hours room temperature & room humidity testing period: 5 cycles

Kesternich test (SO2)

- > contents of 1 cycle (48 hours) according to DIN50018 (0.21)
- > testing period: 40 cycles



Comfort guaranteed

at all times

Continuous heating during defrost mode

VRV continues to provide heating even when in defrost mode, providing an answer to any perceived disadvantages of specifying a heat pump as a monovalent heating system.

- > Continuous indoor comfort ensured by the heat accumulating element and alternate defrost
- > An innovative alternative to traditional heating systems




How does it work? UNIQUE Heat accumulating element

For the VRV IV+ heat pump single unit systems a unique heat-accumulating element is used. This element, based upon phase change material, provides the energy to defrost the outdoor unit.

Alternate defrost

On all our multi unit systems only 1 outdoor coil is defrosted at a time, ensuring continuous comfort during the whole process.



Available on: RYYQ8-20U Water cooled VRV has no defrost cycles







the outdoor unit coil is defrosted ...

- ... one at the time ...
- ... so a comfortable temperature is maintained indoors

Available on: REYA10-28A, REYQ10-54U, RYYQ16-54U, RXYQQ16-42U and RQCEQ280-848P3

Smart Control brings comfort


Stable room temperature

An electronic expansion valve continuously adjusts the refrigerant volume in respond to load variations of the indoor units. The VRV system thus maintains comfortable room temperatures at a virtually constant level, without the temperature variations typical of conventional ON/OFF control systems.

Note: the graph shows the data, measured in a test room assuming actual heating load. The thermostat can control stable room temperature at \pm 0.5°C from set point.


No more cold draught

Automatic or manual adjustment of refrigerant temperature leads to higher outblow temperatures which avoid the cold draught coming from the indoor unit.



Ensure optimal IAQ using CO₂ sensors

Enough fresh air is needed to create an enjoyable environment, but ventilating constantly is leading to energy waste. Therefore an optional CO₂ sensor regulates the ventilation system to provide the needed fresh air to the room, avoiding over-ventilation and saving energy.



Low operation sound level



Whisper quiet indoor units

Daikin indoor units have very low sound operation levels, **down to 19dB(A)**, making them ideal for sound sensitive area's as hotel bedrooms, etc.



Connectable to RYYQ-U, RXYQ-U, RXYSCQ-TV1, RXYSQ-TV9/TY9, RXYLQ-T, RWEYQ-T9


Connectable to all VRV heat pumps

Outdoor unit sound reduction

For areas where there are stringent limitations to sound levels, the outdoor unit sound level can be automatically reduced to meet the requirement.

To manually set set the time for low noise operation you can use the external control adaptor DTA104A61/62/53.





Example for VRV IV heat pump, factory setting.

Sound enclosure for VRV5

EKLN140A

- > Sound reduction up to -10 dB(A) on Sound Power values
- > Dedicated Daikin option for VRV 5 RXYSA
- > Fully optimized and tested in Daikin Factory for guaranteed performance
- Very low capacity and pressure drop thanks to separated air intake and discharge
- > Fast and easy installation & servicing




Great design flexibility

Wide operation range

Air cooled


The VRV system can be installed practically anywhere. VRV air cooled outdoor units can cool between -20°C BD and +52°C DB outdoor ambient and can be used as monovalent heating system between -25°C WB and +15.5°C WB.



With the technical cooling function, the operation range in cooling of the VRV IV+ heat recovery system is extended from -5°C to -20°C, making it perfect for integrating server rooms.

Water cooled


Standard water cooled outdoor units operation between 10°C and 45°C for both heating and cooling. In geothermal mode, the operation range is extended to -10°C* during heating and 6°C during cooling. These units are not influenced by external conditions and function well in extreme climates.



* Ethylene glycol should be added to the water when the water inlet temperature is below 5°C.

Flexible piping design

The long piping lengths, high level differences and small refrigerant piping allows for a design with little limitations and leaving maximum space for lettable space.




Example

	Air cooled	Water cooled
Total piping length	1,000 m	500 m
Longest length actual (Equivalent)	165 m (190 m)	165 m (190 m)
Longest length after first branch	90 m ¹	40 m (90 m ¹)
Level difference between indoor and outdoor units	90 m ¹	50 m (40 m²)
Level difference between indoor units	30 m	30 m

¹Contact your local dealer or consult technical literature for more information and restrictions

Phased installation

Installation of the VRV system can be implemented floor by floor, so that sections of the building can be put into use very quickly, or enabling the air conditioning system to be commissioned and operated in stages, rather than on final completion of the project.



² In case outdoor unit is located below indoor units

Indoor installation

Air cooled

Standard outdoor unit installed indoors

The VRV optimised fan blade shape increases output and reduces pressure loss. Together with the **high ESP setting (up to 78.4 Pa)**, it makes VRV outdoor units ideal for indoor installation using ducts.

VRV IV i-series heat pump for indoor installation

The ultimate and unique solution from Daikin is to use the VRV IV i-series. This unit is optimised for indoor installation and is the most flexible solution, without the need for a large technical room to put the outdoor unit and it is complete invisible!

Water cooled

- Seamless integration in the surrounding architecture as you cannot see the unit
- Highly suited for sound sensitive areas as there is no external operation sound
- Superior efficiency, even in the most extreme outside conditions, especially in geothermal operation








Multiple tenants, one outdoor unit

The multi tenant function ensures that the entire VRV system does not shut down when the main power supply of an indoor is switched off.

This means that the indoor unit's main power supply can be turned off when a part of the building is closed or is being serviced without affecting the rest of the building.

2 solutions according to the needs:

- > Service setting, without additional hardware: for service execution within 24 hours
- > PCB option: when tenants leave for a longer period (holiday) and the main power supply is shut down



Compact and light


No structural reinforcement necessary


Thanks to the vibration-free and sufficient light construction of the outdoor units, floors do not need to be reinforced, reducing the overall cost of the building.

Up to 29% less space required compared to traditional water-based systems, offering more lettable space

4-sided, 3-row heat exchanger

Thanks to the large surface of the heat exchanger (up to 235 m²) VRV units are compact, light and highly efficient.





surface up to 235 m²


Fast installation and commissioning

Easy servicing

Automatic charging & testing



After charging, pushing the test operation button initiates a check on the wiring, shut off valves, sensors and refrigerant volume.



If the temperature drops below 20°C* manual charging is necessary.

- * 10°C for heat pump for cold regions
- * Available on REYQ-U, RYYQ-U, RXYQ-U, RQYQ-P, RXYQQ-U, RQCEQ-P3



Easy compliance to F-gas regulation

No leak check requirement

For the majority of VRV 5 S-series no leak check is needed as the total CO₂ eq. of the system is below 5 tonnes (total charge up to 7.4 kgs).

Remote refrigerant containment check

For systems with a total CO₂ eq. above 5 tonnes the refrigerant containment check can be done remotely via the intelligent Touch Manager.



Remotely set the time and start the refrigerant containment check when it is most convenient for you.



Connect to customer site via internet or 3G increasing customer satisfaction as there is no disruption to the air conditioning during business hours.



Check the report once the check has been done

Available on REYQ-U, RYYQ-U, RXYQ-U. Next to remote checking, the function can also be activated on-site via a push button on the PCB.

When activating the refrigerant containment check, the unit switches into cooling mode and duplicates certain reference conditions based on memory data. The result indicates whether or not refrigerant leakage has occurred.

The refrigerant volume of the complete system is calculated based on the following data:

- > Outdoor temperature
- Reference system temperatures
- > Reference system pressures
- > Refrigerant density
- > Types and number of indoor units

7-segment display

for quick and accurate error diagnosis

Outdoor unit display for quick on-site settings and easy read out of errors together with the indication of service parameters for checking basic functions.



7 segment display and configurator available on: REYA-A, REYQ-U, RYYQ-U, RXYQ-U, RXYQQ-U. Only configurator available on: RXYSA-AV1/AY1, RXYSQ-TV1, RXYSQ-TV9/TY9/TY1, SB.RKXYQ-T(8).

Compact design

The compact design of the outdoor units is sufficient to allow them to be taken up to the top of a building in a commercial elevator, overcoming site transportation problem, particularly when outdoor units need to be installed on each floor.







VRV Configurator


Software for simplified commissioning, configuration and customisation

- > Graphical interface
- > Manage systems over multiple sites in exactly the same way
- > Retrieve initial settings






 All-in-one box solution without any requirement for field supplied equipment (e.g. gauges, pumps and valves)



Daikin unified REFNET piping

The unified Daikin REFNET piping system is designed for simple installation.





REFNET joint



REFNET header

Easy wiring

Simplified wiring

Shared use of wiring between indoor units, outdoor units and centralised remote control

- > Easy retrofit of centralised remote control
- Impossible to make incorrect connections thanks to non polarity wiring
- > Sheated wire can be used

Cross wiring check

The cross wiring check function warns operatives of connection errors in inter unit wiring and piping.

Auto Address Setting Function

Wiring can be done without the need of manually setting each address.

* auto adress setting fuction is not available for centralized operation





Continuing our path to lower CO₂

equivalent solutions



















Support the decarbonisation of commercial buildings



Market-leading seasonal efficiency makes VRV5 more sustainable over it's entire lifecycle, reducing the indirect CO, eq. impact



Specifically built for lower GWP R-32 refrigerant, greatly reducing the reducing the potential direct CO₂ impact with 71% compared to R-410A systems



The perfect partner for BREEAM, LEED and other green building schemes

Ultra-flexible climate control



Known R-410A piping flexibility to tackle any building



Connectable to all known Daikin smart controls, including Onecta app



Widest range of dedicated R-32 indoor units on the market



5 low sound steps



Integrates HRV ventilation units



High ESP fans allowing concealed installation

VRV 5 outdoor unit overview


Capacity class (kW) HRV units VAM
HRV units EKVDX
AHU connection
Air curtains
sys Model Product name 10 12 14 16 18 20 22 24 26 28 **VRV** indoor **Cooling Capacity** 22.4 28.0 33.5 40.0 45.0 50.4 56.0 61.5 67.4 73.5 78.5 25.0 31.5 37.5 45.0 50.0 56.5 63.0 69.0 75.0 82.5 87.5 **Heating Capacity** Reduced CO₂ equivalent thanks to the use of lower GWP refrigerant R-32 Top sustainability over the entire lifecycle O O MEM VRV 5 ,Free' heating through heat recovery Tackle small room applications thanks to Shîrudo Technology The perfect personal comfort thanks to simultaneous cooling and heating > Reduced CO₂ equivalent thanks to • • the use of lower GWP refrigerant R-32 Standard O O O Top sustainability over the entire total system connection ratio limit: 50 ~ 130% RXYSA-VRV 5 lifecycle 0 AV1/AY1 0 Unique low -height single fan range S-series Tackle small room applications thanks to Shîrudo technology

• Single unit, • Multi combination

Sound enclosure for VRV5 S-series



- ✓ Specially designed for VRV 5
- ✓ Very low capacity and pressure drop
- ▼ Fully optimized and tested in Daikin Factory
- Fast & easy installation & servicing





Branch selector (BS box) overview

					Cap	oacit	ty cla	ass
Mode	I	Product	name	4	6	8	10	12
Multi port BS box	 Unique range of Branch Selector boxes integrating Shirudo Technology 	BS- A14AV1B	221111	•	•	•	•	•



Shîrudo Technology truly sets VRV 5 apart

- > Complete peace of mind as Daikin provides all required tools to ensure compliance to the IEC product standard
- > Factory-integrated refrigerant control measures make the VRV 5 quick and flexible to design without the need for complex and time consuming calculations
- > For stress free design of any commercial building, validate your project in our Xpress software, featuring floor plan integration





Arteparc office complex

Daikin VRV heat pumps contribute to low carbon footprint and is awarded with the HQE excellent label



The new Arteparc commercial complex situated in the Inovallee tech park in Meylan, Grenoble demonstrates how developers and equipment manufacturers are working together to deliver new low-carbon buildings that align with the highest standards of sustainable development.

This large new commercial complex comprises over 25,000m² of floor space, spread over six buildings.

The first three have now been completed using Daikin's low carbon VRV heat pumps. The project is distinguished by its high-quality design and construction, built to achieve BBC Effinergie E2C-1 certification and comply with the French RE2020 regulations, which are aimed at reducing both energy consumption and the lifetime carbon impact of new buildings.

Daikin's VRV5 solution was selected by ARTEA to provide comfortable climate control with a low carbon footprint to assist in achieving the HOE excellent certification.

The collaboration between the ARTEA Group, the Ingégroup design office, installer Climacool and Daikin technical management, was essential to the successful outcome of this project. Close cooperation ensured that system performance was optimised to meet the high standards of the ARTEA Group, as well as the building requirements and user experience. The system will be monitored in order to further optimise the energy efficiency of the VRV solution.

Hotel St. Annen

sustainable retrofit

- > Retrofit in just 3.5 weeks
- > Individual room heating or cooling
- > VRV 5's compact size and low noise operation minimise visibility and disturbance in the densely populated residential neighbourhood
- Intuitive touch control for guests with central monitoring for staff to optimise energy efficiency





Zome Central hub with multi use offices

- > For the Zome HUB flexibility was key to allow different type of occupation and use of the co-working space
- A sustainable system was essential to align with the brand values
- Zome's city centre location meant the outdoor units could not be higher then 1 meter to remain invisible once installed
- > VRV design software ensured the selected equipment complies to the IEC product standard






Did you know ...


different standards regarding safety exist?


Refrigerants can be classified according to 2 safety groups:

- Flammability (1, 2L, 2, 3): covered by the specific heat pump standard IEC60335-2-40 (Ed. 6) as it prevails over EN378:2016
- > Toxicity (A or B): covered by the generic standard on refrigerants **EN378:2016.**

Shîrudo Technology focuses on offering maximum flexibility within the IEC60335-2-40 (Ed.6) requirements as limitations for flammability of A2L refrigerants are stricter than the ones for toxicity.







Peace of mind




With Shîrudo Technology, Daikin ensures compliance to the product standard IEC60335-2-40 (Ed. 6) for indoor units. With factory-integrated refrigerant control measures, these systems are also the quickest and most flexible to design.

There is **no need for complex and time consuming calculations**, even for small room applications. And BSSV boxes come with a ventilated enclosure for quick and simple integration of any potential additional measures – making installation in demanding spaces easier than ever.

For stress free design of any commercial building, validate your project in our Xpress software, featuring floor plan integration.

Refrigerant control measures factory-integrated

Shîrudo Technology includes 2 factory measures and sensors built into a VRV 5 system.



Compliance taken care of

- > No study or calculations needed on where and how to install outdoor or indoor units.
- > No need for studies to decide if and what safety measures are required.
- > Third party CB certified by a notified body (SGS CEBEC).

Automatic, real time leak detection and refrigerant containment controls

- > Fully compliant to product standard (IEC60335-2-40 (Ed.6)), reducing the risk of direct CO₂ eq. impact from a refrigerant leak.
- > Real time leak detection sensors, triggering refrigerant containment measures in the unlikely event of a leak
- > No leak check requirement for majority of VRV 5 S-series installations (up to 7.4 kg of refrigerant charge) and reduced intervals of leak check for bigger installations.

Check out the Shîrudo Technology video!



VRV 5 Heat Recovery

Greatly reducing the CO₂ footprint of buildings

- > Lower GWP R-32 refrigerant
- > Market-leading, real life seasonal efficiency
- > Highly efficient 3-pipe heat recovery

Maximum design flexibility

- > Installation in rooms down to 10 m² without any additional measures thanks to **Shîrudo technology**
- > Easy to select thanks to VRV Xpress floorplan support
- Completely redesigned BSSV boxes for faster installation and easier servicing

Market-leading portfolio

- > Widest range of dedicated R-32 VRV outdoor and indoor units in the market!
- > Control IAQ with integration of ventilation units

Advantages

of 3-pipe technology


"Free" heat available

An integrated heat recovery system reuses heat from offices and server rooms to warm other areas, minimizing heat waste

Maximum comfort

A VRV heat recovery system allows simultaneous cooling and heating.


- > For hotel guests, this means they can freely choose between cooling or heating to create the perfect environment.
- > For offices, it means a perfect working indoor climate for both north and south-facing offices.



More "free" heat


Daikin 3-pipe technology needs less energy to recover heat, meaning significantly higher efficiency during heat recovery mode. Our system can recover heat at a low condensing temperature because it has dedicated gas, liquid and discharge pipes.

In a 2-pipe system, gas and liquid travel as a mixture so the condensing temperature needs to be higher in order to separate the mixed gas and liquid refrigerant. The higher condensing temperature means more energy is used to recover heat resulting in lower efficiency.



Lower pressure drop means more efficiency

- Smooth refrigerant flow in 3-pipe system thanks to 2 smaller gas pipes results in higher energy efficiency
- Disturbed refrigerant flow in large gas pipe on
 2-pipe system results in larger pressure drop



VRV 5 Heat Recovery

Purpose-built to support the decarbonisation of commercial buildings

- Reduced CO₂ equivalent thanks to the use of lower GWP R-32 refrigerant and lower refrigerant charge
- > Single component refrigerant, easy to re-use and recycle
- > Greatest sustainability over the entire lifecycle, thanks to market leading real-life seasonal efficiency
- > "Free" heating through efficient 3-pipe heat recovery, transferring heat from areas requiring cooling to areas requiring heating
- Tackle small room applications without any additional measures, thanks to Shîrudo Technology
- Specially designed indoor units for R-32, ensuring low sound and maximum efficiency
- Simultaneous cooling and heating for the perfect personal comfort of guests/tenants
- > Like for like R-410A installation flexibility with piping lengths up to 165 meters and a total length of 1,000 meters
- > Sound pressure down to 40 dB(A) thanks to 5 low sound steps
- > ESP up to 78 Pa to allow ducting
- > Wide operation range of up to +46°C in cooling and down to -20°C in heating
- > Incorporates VRV standards & technologies: Variable Refrigerant Temperature, continuous heating, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB



Lower CO₂ equivalents



5 low sound steps

More details and final information can be found by scanning or clicking the QR codes.

. . .





Outdoor unit			REYA	8A	10A	12A	14A	16A	18A	20A
Capacity range			HP	8	10	12	12 14 16 18			20
Cooling capacity	Prated,c		kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0
Heating capacity	Prated,h		kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0
	Max.	6°CWB	kW	25.0	31.5	37.5	45.0	50.0	56.5	63.0
Recommended cor	nbination			4x FXFA50A2VEB	4x FXFA63A2VEB	6x FXFA50A2VEB	+ 5x	+ 2x	3x FXFA50A2VEB + 5x FXFA63A2VEB	+ 6x
ηs,c			%	290.8	282.6	285.3	306.1	281.0	280.6	262.2
ηs,h			%	161.5	170.2	176.4	168.3	167.5	172.5	162.7
SEER				7.35	7.14	7.21	7.73	7.10	7.09	6.63
SCOP				4.11	4.33	4.49	4.28	4.26	4.39	4.14
Maximum number	of connec	table indoor units					64			
Indoor index	Min.			100	125	150	175	200	225	250
connection	Max.			260	325	390	455	520	585	650
Dimensions	Unit	HeightxWidthxDepth	mm		1,685x930x765			1,685x1,	240x765	
Weight	Unit		kg		213		296 319			19
Sound power level	Cooling	Nom.	dBA	78.3	78.8	82.5	78.7	83.7	83.4	87.9
Sound pressure level	Cooling	Nom.	dBA	56.3	58.0	60.8	58.1	61.4	63.0	67.0
Operation range	Cooling	Min.~Max.	°CDB		-5 ~46					
	Heating	Min.~Max.	°CWB		-20 ~16					
Refrigerant	Type/GW	Р		R-32/675.0						
	Charge		kg/TCO2Eq	9.00/6.08 10.6/7.16						
Piping connections	Liquid	OD	mm	9.	9.52 12.70					
	Gas	OD	mm	19.1			22.2			
	HP/LP gas	OD	mm	15.90		19.10			22.20	
	Total piping length	System Actual	m	1,000						
Power supply	Phase/Fre	equency/Voltage	Hz/V	3N~/50/380-415						
Current - 50Hz	Maximur	n fuse amps (MFA)	Α	20	25	3	2	40 50		







Outdoor unit Sys	tem			REYA	10A	13A	16A	18A	20A	22A	24A	26A	28A	
System	Outdoor	unit modu	ıle 1		REM	IA5A		REYA8A		REYA10A	REYA8A	REY	A12A	
	Outdoor	unit modu	ıle 2		REMA5A	REY	A8A	REYA10A	REY	A12A	REYA16A	REYA14A	REYA16A	
Capacity range				HP	10	13	16	18	20	22	24	26	28	
Outdo Capacity range Cooling capacity Prated Heating capacity Prated Max. Recommended combination ns,c ns,h SEER SCOP Maximum number of conn Indoor index connection Min. Max.				kW	28.0	36.4	44.8	50.4	55.9	61.5	67.4	73.5	78.5	
Heating capacity	Prated,h			kW	28.0	36.4	44.8	50.4	55.9	61.5	67.4	73.5	78.5	
	Max.	6°CWB		kW	32.0	41.0	50.0	56.5	62.5	69.0	75.0	82.5	87.5	
Recommended co	mbination				4x FXFA63A2VEB	3x FXFA50A2VEB + 3x FXFA63A2VEB	4x FXFA63A2VEB + 2x FXFA80A2VEB	4x FXFA50A2VEB + 4x FXFA63A2VEB	10x FXFA50A2VEB	6x FXFA50A2VEB - 4x FXFA63A2VEB	4x FXFA50A2VEB + 4x FXFA63A2VEB + 2x FXFA80A2VEB			
ης,ς				%	301.9	296.5	293.0	287.5	287.6	283.6	283.4	296.2	282.8	
ηs,h				%	160.6	161.5	170.9	170.5	172.2	173.3	165.2	172.0	171.5	
SEER					7.62	7.49	7.40	7.26	7.27	7.17	7.16	7.48	7.15	
SCOP				4.09	4.11	4.35	4.34	4.38	4.41	4.20	4.38	4.36		
Maximum number of connectable indoor units									64					
Indoor index	Min.				125	163	200	225	250	275	300	325	350	
connection	Max.				325	423	520	585	650	715	780	845	910	
Piping connection	s Liquid	OD		mm	9.52			12.	.70			15	.90	
	Gas	OD		mm	19.1		22.2				28.6			
	HP/LP OD mm 15.90 gas					19.10			22.20					
Total System Actual piping length		Actual	m	m 500				1,0	000					
Power supply Phase/Frequency/Voltage				Hz/V	Hz/V 3N~/50/3					415				
Current - 50Hz Maximum fuse amps (MFA)				Α		40		5	0		6	53		

Outdoor unit mod	lule		REMA	5A
Dimensions	Unit	HeightxWidthxDepth	mm	1,685x930x765
Weight	Unit		kg	213
Fan	External static pressure	Max.	Pa	78
Sound power level	Cooling	Nom.	dBA	78.3
Sound pressure level	Cooling	Nom.	dBA	56.3
Operation range	Cooling	Min.~Max.	°CDB	-5 ~46
	Heating	Min.~Max.	°CWB	-20 ~16
Refrigerant	Type/GW	P		R-32/675.0
	Charge		kg/TCO2Eq	9.00/6.08
Power supply	Phase/Fre	equency/Voltage	Hz/V	3N~/50/380-415
Current - 50Hz	Maximun	n fuse amps (MFA)	A	20

Actual number of connectable indoor units depends on the indoor unit type and the connection ratio restriction for the system ($50\% \le CR \le 120\%$) | Contains fluorinated greenhouse gases| * EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland

Multi branch selector (BSSV) for VRV 5 Heat Recovery

Specifically developed for lower GWP R-32

- Reduced CO₂ equivalent thanks to the use of lower GWP R-32 refrigerant and lower refrigerant charge
- Unique range of multi BS boxes allowing efficient 3-pipe heat recovery
- > No limitation on room size, thanks to **Shîrudo Technology** (1)

 The integrated shut-off valves in the BSSV box ensure that in case of a refrigerant leak only the specific branch is closed off.






Reduced CO₂ equivalent

Flexibility to take care of every room


Completely redesigned for faster installation and easier servicing

> Faster installation thanks to **Refrigerant Flow Through** reducing the number of brazing points and joint kits

VRV 5: only 24 brazings point and no joint kits




VRV 5: 39 brazing points and 3 joint kits



> Easy servicing in false ceillings thanks to **sliding down PCB**



 Limited ceiling void required as the box can be installed at just 5mm from the ceiling







- Unique range of multi BS boxes allowing efficient 3-pipe heat recovery
- > NEW No limitation on room size, thanks to Shîrudo Technology (1)
- > NEW Faster installation thanks to Refrigerant Flow Through reducing the number of brazing points and joint kits
- > NEW Easy servicing in false ceilings thanks to sliding down PCB
- NEW Limited ceiling void required as the box can be installed at just 5mm from the ceiling
- NEW Quick on-site settings, indication of service parameters and easy read out of errors thanks to 7 segment display
- > Up to 16kW capacity available per port
- > Connect up to 250 class unit (28kW) by combining 2 ports
- > No limit on unused ports allowing phased installation
- > Faster installation thanks to open port connection
- > Allows multi tenant applications
- > Connectable to REYA-A heat recovery units



More details and final information can be found by scanning or clicking the QR codes.



Branch selector				BS	4A14AV1B	6A14AV1B	8A14AV1B	10A14AV1B	12A14AV1B							
Maximum number o	of connectable ind	oor units			20	30	40	50	60							
Maximum number o	of connectable ind	oor units pe	er branch				5									
Number of branches	s				4	6	8	10	12							
Maximum capacity i	ndex of connectal	ble indoor u	ınits		400	600		750								
Maximum capacity i	ndex of connectal	ble indoor u	ınits per branch			140 (250 if 2 ports are comb	ined)								
Dimensions	Unit	HeightxW	idthxDepth	mm	291x600x845	291x1,0	000x845	291x1,4	00x845							
Weight	Unit			kg	40	56	65	83	89							
Casing	Material						Galvanised steel plate	2								
Piping connections	Outdoor unit or	Liquid	Туре				Brazing connection									
	Refrigerant Flow		OD	mm			9.52 (2) / 12.7 (2) / 15.9									
	Through Gas Type Brazing connec								on							
			OD	mm		15.	9 (2) / 19.1(2) / 22.2(2) / 2	28.6								
		Discharge gas	Туре				Brazing connection									
			OD	mm	12.7 (2) / 15.9(2) / 19.1(2) / 22.2											
	Indoor unit	Liquid	Туре		Brazing connection											
		OD mm 6.35(3) / 9.52 (4)														
		Gas	Туре			Brazing connection										
			OD	mm			9.52 (5) / 12.7 (6) / 15.9 (4	1)								
	Drain						VP20 (I.D. 20/O.D. 26)									
BS units connected	Maximum allowe	d amount o	of BS units				4									
in Refrigerant Flow	Maximum total n	umber of po	orts of BS units		16											
Through	Maximum total ca	apacity inde	ex of indoor unit		750											
Sound absorbing th	ermal insulation			Urethane foam, polyethylene foam												
BS box system	Dust connection		n unit	mm	mm 160.0											
safety requirements	Dust connection	positions					Left/Right									
Power supply	Phase						1~									
	Frequency			Hz			50									
	Voltage			V			220-440									
	Maximum fuse ar	mps (MFA)		Α	A 15											

Contains fluorinated greenhouse gases | (1) Refer to Xpress selection software to ensure compliance to specific product standard. Field supplied duct and fan might be required to install the BS box in very small spaces | (2) Accessory pipe required | (3) When connecting indoor units smaller or equal to 80 class (no need to cut the outlet pipe) | (4) When connecting indoor units larger or equal to 100 class (the outlet pipe needs to be cut) | (5) When connecting indoor units smaller or equal to 32 class (no need to cut the outlet pipe) | (6) When connecting indoor units between 40 & 80 class (the outlet pipe needs to be cut)

VRV 5 S-series heat pump



Lower CO₂ equivalent and market-leading flexibility










RXYSA-AV1_AY1

Life is more rewarding with the new VRV 5.

Our new all-round performer covers all of your mini VRV applications in Daikin's most sustainable solution.

- > Maximum flexibility allowing installation in rooms down to 10 m² thanks to Shîrudo technology
- > **Top sustainability** over the entire lifecycle thanks to low GWP R-32 refrigerant and market-leading real life seasonal efficiency
- > **Ergonomic serviceability** and handling, thanks to wide access area to easily reach components within low-profile single fan casing
- Best-in-class design versatility with five sound pressure levels down to 39
 dB(A) and automatic ESP setting up to 45 Pa allowing ductwork
- > Geared for comfort with intuitive online and voice controls plus a new 10 class indoor unit for small rooms



Next generation **JRJ**



New asymmetric fan design

- > Two high ESP settings
- > Low sound levels

Compact dimensions

Easy to transport thanks to compact size and single-fan design




New casing design

New casing design with 4 handles for easy carrying

Specially designed grille

- > Low pressure drop
- > No risk for accidental reach of the fan



heat exchanger
Contributes to top seasonal efficiency


Refrigerant cooled PCB

With integrated:

- > cool/heat selector input
- 7-segment display for quicker and more precise error and setting reading

New stop valves

- Repositioned to allow front or side connection
- > Brazed for increased reliability










VRV 5 S-series

Lower CO₂ equivalent and market-leading flexibility

- > Reduced CO₂ equivalent thanks to the use of lower GWP R-32 refrigerant and lower refrigerant charge
- > Top sustainability over the entire lifecycle, thanks to market leading real-life seasonal efficiency
- > Low-height single fan range
- > Easy to transport thanks to lightweight and compact design
- > Wide access area to easily reach all key components
- > Tackle small room applications without any additional measures, thanks to Shîrudo technology
- > Specially designed indoor units for R-32, ensuring low sound and maximum efficiency











Reduced CO₂ equivalent

Flexibility to take care of every room

Published data with real-life indoor units

More details and final information can be found by scanning or clicking the QR codes.




RXYSA-AV1





Outdoor unit			RXYSA	4AV1	5AV1	6AV1	4AY1	5AY1	6AY1						
Capacity range			HP	4	5	6	4	5	6						
Cooling capacity	Prated,c		kW	12.1	14.0	15.5	12.1	14.0	15.5						
Heating capacity	Prated,h		kW	12.1	14.0	15.5	12.1	14.0	15.5						
	Max.	6°CWB	kW	14.2	16.0	18.0	14.2	16.0	18.0						
Recommended cor	mbination			3x FXSA25A2VEB + 1x FXSA32A2VEB	4x FXSA32A2VEB	2x FXSA32A2VEB + 2x FXSA40A2VEB	3x FXSA25A2VEB + 1x FXSA32A2VEB	4x FXSA32A2VEB	2x FXSA32A2VEB + 2x FXSA40A2VEB						
ηs,c			%	324.5	306.1	301.0	312.5	294.8	289.9						
ηs,h			%	200.5	185.7	183.6	193.1	178.8	176.8						
SEER				8.2	7.7	7.6	7.9	7.4	7.3						
SCOP				5.1	4	l.7	4.9	4	.5						
Maximum number	of connec	table indoor units		13 (1)	16 (1)	18 (1)	13 (1)	16 (1)	18 (1)						
Indoor index	Min.			50.0	62.5	70.0	50.0	62.5	70.0						
connection	Nom.			100	125	140	100	125	140						
	Max.			130.0	162.5	182.0	130.0	162.5	182.0						
Dimensions	Unit	HeightxWidthxDepth	mm			869x1,1	00x460								
Weight	Unit		kg			10	02								
Sound power level	Cooling	Nom.	dBA	67.0	68.1	69.0	67.0	68.1	69.0						
	Heating	Prated,h	dBA	69.0	70.0	71.0	69.0	70.0	71.0						
Sound pressure level	Cooling	Nom.	dBA	49.0	5	1.0	49.0	5	1.0						
Operation range	Cooling	Min.~Max.	°CDB			-5	~46								
	Heating	Min.~Max.	°CWB			-20	~16								
Refrigerant	Type/GW	P				R-32,	/675.0								
	Charge		kg/TCO2Eq			3.40	/2.30								
Piping connections	Liquid	OD	mm		9.52										
	Gas	OD	mm			15	5.9								
	Total piping	g System Actual	m			3	00								
Power supply	Phase/Fre	equency/Voltage	Hz/V	Hz/V 1~/50/220-240 3N~/50/380-415											
Current - 50Hz	Maximur	n fuse amps (MFA)	Α												



BLUEVOLUTION

VRV 5 indoor units

	Indoor unit overview	46
	Benefit overview	47
	Ceiling mounted cassette units	48
NEW	UV Streamer kit	48
UNIQUE	FXFA-A	51
UNIQUE	FXZA-A	53
	Concealed ceiling units	54
	Auto cleaning filter for concealed ceiling units	54
	FXDA-A	55
SLIMMEST IN CLASS	FXSA-A	56
NEW	FXMA-A	57
	Wall mounted unit	58
	FXAA-A	58
	Ceiling suspended units	59
	FXHA-A	59
UNIQUE	FXUA-A	60







VRV 5 indoor unit overview

Capacity class (kW)

Туре	Model	Prod	uct name	10	15	20	25	32	40	50	63	71	80	100	125	140 200 2	250
Ceiling mounted cassette	UNIQUE Round flow cassette	360° air discharge for optimum efficiency and comfort > Auto cleaning function ensures high efficiency Intelligent sensors save energy and maximize comfort > Flexibility to suit every room layout > Lowest installation height in the market! > Widest choice ever in decoration panel designs and colors	FXFA-A			•	•	•	•	•	•		•	•	•		UV Streame kit
Ceiling mou	UNIQUE Fully flat cassette	Unique design that integrates fully flat into the ceiling > Perfect integration in standard architectural ceiling tiles > Blend of iconic design and engineering excellence > Intelligent sensors save energy and maximize comfort > Small capacity unit developed for small or well-insulated rooms > Flexibility to suit every room layout	FXZA-A		•	•	•	•	•	•							
61	Slim concealed ceiling unit	Slim design for flexible installation Compact dimensions enable installation in narrow ceiling voids Medium external static pressure up to 44Pa Only grilles are visible Small capacity unit developted for small of well-insulated rooms Reduced energy consumption thanks to DC fan motor	FXDA-A	•	•	•	•	•	•	•	•						Auto clear filter opti
Concealed ceiling	Concealed ceiling unit with medium ESP	Slimmest yet most powerfull medium static pressure unit on the market! > Slimmest unit in class, only 245mm > Low operating sound level > Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths > Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, guaranteeing comfort	FXSA-A	UE -32	•	•	•	•	•	•	•		•	•	•	•	
	NEW Concealed ceiling unit with high ESP	ESP up to 270 Pa, ideal for extra large sized spaces > Optimum comfort guaranteed no matter the length of ductwork or type of grilles, thanks to automatic air flow adjustment > Large capacity unit: up to 31.5 kW heating capacity	FXMA-A							•	•		•	•	•	•	•
Wall mounted	Wall mounted unit	For rooms with no false ceilings nor free floor space > Flat, stylish front panel is more easy to clean > Small capacity unit developted for small of well-insulated rooms > Reduced energy consumption thanks to DC fan motor The air is comfortably spread up- and downwards thanks to 5 different discharge angles	FXAA-A		•	•	•	•	•	•	•						
spended	NEW Ceiling suspended unit	For wide rooms with no false ceilings nor free floor space > Ideal for comfortable air flow in wide rooms thanks to Coanda effect > Rooms with ceilings up to 3.8m can be heated or cooled very easily! > Can easily be installed in both new and refurbishment projects > Can even be mounted in corners or narrow spaces without any problem	FXHA-A					•		•	•			•			
Ceiling suspended	NEW & UNIQUE 4-way blow ceiling suspended unit	Unique Daikin unit for high rooms with no false ceilings nor free floor space > Rooms with ceilings up to 3.5m can be heated up or cooled down very easily! > Can easily be installed in both new and refurbishment projects > Flexibility to suit every room layout	FXUA-A							•		•		•			
Cooling	g capacity (kW) ¹		1.1	1.7	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0 22.4	28.0
Heating	g capacity (kW	/) ²		1.3	1.9	2.5	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5	16.0	18.0 25.0	31.5

 $^{(1) \} Nominal\ cooling\ capacities\ are\ based\ on:\ indoor\ temperature:\ 27^\circ CDB,\ 19^\circ CWB,\ outdoor\ temperature:\ 35^\circ CDB,\ equivalent\ refrigerant\ piping:\ 5m,\ level\ difference:\ 0m$

 $^{(2) \} Nominal \ heating \ capacities \ are \ based \ on: indoor \ temperature: 20^{\circ}CDB, outdoor \ temperature: 7^{\circ}CDB, 6^{\circ}CWB, equivalent \ refrigerant \ piping: 5m, level \ difference: 0m \ difference:$



VRV 5 indoor unit Wall moun-Ceiling mounted Ceiling suspended Concealed ceiling units cassette units ted unit units benefit overview NEW FXZA-A FXDA-A FXMA-A FXUA-A FXFA-A FXSA-A FXAA-A FXHA-A Home leave Maintains the indoor temperature at your specified operation comfort level during absence, thus saving energy The unit can be used as fan, blowing Fan only air without heating or cooling. The filter automatically cleans itself. Simplicity Auto cleaning of upkeep means optimum energy efficiency o o filter and maximum comfort without the need for expensive or time-consuming maintenance. The presence sensor directs the air away from NFW any person detected in the room, when the air Floor and presence flow control is on. The floor sensor detects the 0 0 0 sensor average floor temperature and ensures an even temperature distribution between ceiling and floor. When starting to warm up or when the thermostat is Draught off, the air discharge direction is set horizontally and prevention the fan to low speed, to prevent draught. fter warming up, air discharge and fan speed are set as desired. Daikin indoor units are whisper quiet. Also Whisper quiet the outdoor units are guaranteed not to disturb the quiet of the neightbourhood Auto cooling-Automatically selects cooling or heating heating mode to achieve the set temperature. changeover Purifies the air of pollutants such as viruses, bacteria, **UV Streamer** fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy and hygienic indoor environment **(**2) **(**2) **(**2) **(**2) **(**2) (Optional high efficiency filter ePM10 60%) Optional pre filter Removes airborne dust particles to Air filter and high efficienensure a steady supply of clean air. cy filter available (200-250) Allows humidity levels to be reduced programme without variations in room temperature. Ceiling soiling Prevents air from blowing out too long in prevention horizontal position, to prevent ceiling stains. Possibility to select automatic vertical moving Vertical auto of the air discharge flaps for efficient air and swing temperature distribution throughout the room. 3 (50-125) Fan speed Allows to select up to the given number of fan speed. 3 + auto 3 3 5 + auto 3 + auto 3 + auto 3 + auto 3 + autosteps (200-250)Individual flap control via the wired remote controller Individual flap enables you to easily fix the position of each flap control individually, to suit any new room configuration. Optional closure kits are available as well. Onecta Control your indoor climate from any controller 0 0 0 0 o 0 0 0 location via smartphone or tablet. (BRP069C51) control & timer Can be set to start heating or cooling Weekly timer 0 0 o 0 0 0 0 0 anytime on a daily or weekly basis. Infrared Starts, stops and regulates the air 0 (1) o (1) o (1) o (1) 0 (1) o (1) o (1) o (1) conditioner from a distance. remote control Remote Wired remote Starts, stops and regulates the air conditioner. (3) **(**3) **(**3) (3) (3) **(**3) (3) **(**3) control Centralised Starts, stops and regulates several air 0 0 0 0 0 0 0 0 control conditioners from one central point. The unit restarts automatically at the Auto-restart original settings after power failure. Other funtcion Simplifies maintenance by indicating Self-diagnosis system faults or operating anomalies. Facilitates condensation draining Drain pump kit o 0 from the indoor unit. The indoor unit's main power supply can be turned Multi tenant 0 (4) (4) (4) (4) (4) 0 (4) (4) off when leaving the hotel or office building.






Breathe healthy air with the round flow

UV Streamer kit


90% of our time is spent indoors. However indoor air is 2 to 5 times more polluted than outdoor air.



These internal pollution effects on people are manifested in the long run. Tackle them now! Our UV streamer kit offers you the solution:


- > It purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy and hygenic indoor environment
- > Thanks to large air flow rate of the Round flow cassette, clean air can be quickly delivered to every corner of your space
- > Can be retrofitted into existing installations
- > Can be used with BYCQ140E and BYCQ140EW decoration panels







Daikin's unique Catch & Clean approach includes an ePM1 50% filter, UV-C light and Streamer technology



UV Streamer filter specifications

Treatment tools	Test Organisation	Classifications	Test Standard and Method	Report Number	Efficiency	Sample Quantity	Contacting Time (hours)	Test Virus suspension
UV Streamer Kit	Phi-X174 (non enveloped virus)	Virus	Non-standardised Test Method: Microbial Reduction Rate Test	102105182COL-001	99.9%		0.5	8x10° PFU
Ionpure IPI Filter	Staphylococcus aureus	Bacteria	GB 21551.2-2010	2021FM05648R01	99.98%	1m³	24	
Ionpure IPI Filter	Escherichia coli	Bacteria	GB 21551.2-2010	2021FM05648R01	99.99%	1m³	24	
lonpure IPI Filter	Aspergillus niger	Fungus	JIS Z 2911:2018	2022FM07084R01	Anti-mildew grade 0 (1)	1m³		
lonpure IPI Filter	Penicillium pinophilum	Fungus	JIS Z 2911:2018	2022FM07084R01	Anti-mildew grade 0 (1)	1m³		
lonpure IPI Filter	Trichoderma viridé	Fungus	JIS Z 2911:2018	2022FM07084R01	Anti-mildew grade 0 (1)	1m³		
lonpure IPI Filter	Chaetomium globosum	Fungus	JIS Z 2911:2018	2022FM07084R01	Anti-mildew grade 0 (1)	1m³		
lonpure IPI Filter	Paecilomyces variotiiv	Mold	JIS Z 2911:2018	2022FM07084R01	Anti-mildew grade 0 (1)	1m³		
lonpure IPI Filter	Infectious bronchitis virus	Virus	ISO 18184:2014(E)	2020FM26047R01	99.99%	1m³	2	
lonpure IPI Filter	SARS-CoV-2	Virus	JIS L 1922	21KB-080395-2(1/5)	99.92%		8	2.2x10 ⁷ PFU
lonpure IPI Filter	H1N1	Virus	ISO 18184:2014(E)	2020FM2434R01	99.94%	1m³	2	



The round flow cassette


- > Maximum comfort thanks to 360° air discharge and intelligent sensors
- > Widest ever choice in panels to match any interior











esence floor sensor sensor

> Auto cleaning panel keeps the filter free of dust for maximum efficiency



> UV streamer kit

- NEW > Purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy and hygienic indoor environment
 - > Highly efficient F7 filter (ISO classification under testing), UVC light and Streamer technology
 - > Can be retrofitted into existing installations






Tested at Intertek

the laboratories of Intertek, in a 28m³ room. Daikin's Round flow cassette (FXFQ125B) removes more than 99.9% of enveloped viruses such as Corona viruses.

* Additional details regarding this function can be found in the unit technical manual.

Tested according to real life sized room





View full test report:








Round flow cassette

360° air discharge for optimum efficiency and comfort

- > Optimised design for R-32 refrigerant
- > Optional automatic filter cleaning panel results in higher efficiency & comfort and lower maintenance costs.
- > Two optional intelligent sensors improve energy efficiency and comfort
- > Widest choice ever in decoration panels: designer panels in white (RAL9010) and black (RAL9005) and standard panels in white (RAL9010) with grey louvers or full white
- > Bigger flaps and unique swing pattern improve equal air distribution
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!
- > Lowest installation height in the market: 214mm for class 20-63
- **NEW** > UV streamer kit, purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy and hygenic indoor environment
 - > Optional fresh air intake
 - > Standard drain pump with 675mm lift increases flexibility and installation speed













White panel

White auto cleaning panel

Black panel

Black design panel

More details and final information can be found by scanning or clicking the QR codes.





Indoor Unit				FXFA	20A	25A	32A	40A	50A	63A	80A	100A	125A
Cooling capacity	Total capacity	At high fa	an speed	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	11.20	14.00
	Total capacity	At high fa	an speed	kW	2.50	3.20	4.00	5.00	6.30	8.00	10.00	12.50	16.00
Power input - 50Hz	Cooling	At high fa	an speed	kW		0.017		0.018	0.023	0.028	0.045	0.078	0.103
	Heating	At high fa	an speed	kW		0.017		0.018	0.023	0.028	0.045	0.078	0.103
Dimensions	Unit	HeightxV	VidthxDepth	mm			204x8	40x840			246x84	10x840	288x840x840
Weight	Unit			kg		18		19	- :	21	2	4	26
Casing	Material							Galva	nised steel	plate			
Decoration panel	Model				Standard p	Auto cl	eaning pan	white with g els: BYCQ140 inels: BYCQ1-	- black E2GFW1 - w	hite / BYCQ	140E2GFW1	B - black	Q140E2W1B
	Dimensions	HeightxV	VidthxDepth	mm	Standar	d panels: 65	x950x950/	Auto cleanir	ng panels: 1	48x950x950	/ Designer	panels: 106	(950x950
	Weight			kg		Stand	dard panels:	5.5 / Auto cl	eaning pan	els: 10.3 / De	esigner pan	els: 6.5	
	Air flow rate - 50Hz	Cooling	At high / medium high / medium / medium low / low fan speed		12.8	3/11.8/10.7/9.				16.6/15.0/13.3/ 12.0/10.7			33.0/30.2/27.4/ 24.0/20.6
		Heating	At high / medium high / medium / medium low / low fan speed	m³/min	12.8	3/11.8/10.7/9.	8/8.9	14.8/13.7/12.6/ 11.5/10.4	15.1/14.0/12.8/ 11.8/10.7	16.6/15.0/13.3/ 12.0/10.7	23.3/21.7/19.3/ 16.5/13.8	29.0/25.1/21.2/ 17.5/13.8	33.0/30.2/27.4/ 24.0/20.6
Air filter	Туре								Resinnet				
Sound power level	Cooling	At high fa	an speed	dBA		49.0		51	1.0	53.0	55.0	60.0	61.0
Sound pressure level	Cooling		medium high / / medium low / peed	dBA	31.0/3	30.0/29.0/29	.5/28.0	33.0/32.0/31	.0/30.0/29.0	35.0/34.0/33.0/ 32.0/30.0	38.0/36.0/34.0/ 32.0/30.0	43.0/41.0/37.0/ 34.0/30.0	45.0/43.0/41.0/ 39.0/36.0
	Heating		medium high / / medium low / peed	dBA	31.0/3	30.0/29.0/29	.5/28.0	33.0/32.0/31	.0/30.0/29.0	35.0/34.0/33.0/ 32.0/30.0	38.0/36.0/34.0/ 32.0/30.0	43.0/41.0/37.0/ 34.0/30.0	45.0/43.0/41.0/ 39.0/36.0
Refrigerant	Type/GW	Р			R-32/675.0								
Piping connections	Liquid	OD		mm				6.35				9.	52
	Gas	OD		mm		9.52			12	.70		15	.90
	Drain							VP25	(O.D. 32 / I.	D. 25)			
Power supply	Phase/Fre	equency/V	oltage	Hz/V				1~/50)/60/220-24	0/220			
Current - 50Hz	Maximun	n fuse amp	s (MFA)	Α					6				
Control systems	Infrared r	emote cor	ntrol				BRC7FA53	2F / BRC7FB5	32F / BRC7I	A532FB / BF	RC7FB532FB		
	Wired ren	note contr	ol		BRC1H52W/S/K								



Why choose fully flat cassette

- Unique design in the market that integrates fully flat into the ceiling
- > Advanced technology and top efficiency combined
- > Most quiet cassette available on the market

FXZQ-A



Choice between grey or white panel

Benefits for the installer

- > Unique product in the market!
- > Most quiet unit (25dBA)
- The user-friendly remote control, available in severa languages, enables the easy set-up of sensor option and control of the individual flap position
- > Meeting Furopean design taste

Benefits for the consultant

- > Unique product in the market!
- Blends seamlessly in any modern office interior design
- in combination with Sky Air (FFA*) or VRV IV heat pump units (FXZQ*).

Benefits for the end user

- > Engineering excellence and unique design in one
- Most quiet unit (25dBA)
- > Perfect working conditions: no more cold draughts
- > Save up to 27% on your energy bill thanks to the optional sensors
- Flexible usage of space and suits any room configuration thanks to individual flap contro
- > User-friendly remote control, available in several languages.


Fully flat cassette

Unique design in the market that integrates fully flat into the ceiling

- > Optimised design for R-32 refrigerant
- > Fully flat integration in standard architectural ceiling tiles, leaving only 8mm
- Remarkable blend of iconic design and engineering excellence with an elegant finish in white or a combination of silver and white
- > Two optional intelligent sensors improve energy efficiency and comfort
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!



- > Optional fresh air intake
- > Standard drain pump with 630mm lift increases flexibility and installation speed






More details and final information can be found by scanning or clicking the QR codes.



Indoor Unit				FXZA	15A	20A	25A	32A	40A	50A			
Cooling capacity	Total capacity	At high fa	an speed	kW	1.70	2.20	2.80	3.60	4.50	5.60			
Heating capacity	Total capacity	At high fa	an speed	kW	1.90	2.50	3.20	4.00	5.00	6.30			
Power input - 50Hz	Cooling	At high fa	an speed	kW	0.0	018	0.020	0.019	0.029	0.048			
	Heating	At high fa	an speed	kW	0.0	018	0.020	0.019	0.029	0.048			
Dimensions	Unit	HeightxV	VidthxDepth	mm			260x5	75x575					
Weight	Unit			kg		15.5		16	i.5	18.5			
Casing	Material						Galvanised	l steel plate					
Decoration panel	Model						BYFQ60	C4W1W					
	Colour						White	(N9.5)					
	Dimensions	HeightxV	VidthxDepth	mm			46x62	0x620					
	Weight			kg			2	.8					
Decoration panel 2	Model						BYFQ6	0C4W1S					
	Colour						SIL	VER					
	Dimensions	HeightxV	VidthxDepth	mm			46x62	0x620					
	Weight			kg			2	.8					
Decoration panel 3	Model					E	BYFQ60B3W1 + w	ire harness EKRS2	3				
	Colour						WHITE (RAL9010)					
	Dimensions	HeightxV	VidthxDepth	mm			55x70	0x700					
	Weight			kg			2	.7					
Fan	Air flow rate -	Cooling	At high / medium / low fan speed	m³/min	8.5/7.0/6.5	8.7/7.5/6.5	9.0/8.0/6.5	10.0/8.5/7.0	11.5/9.5/8.0	14.0/12.5/10.0			
	50Hz	Heating	At high / medium / low fan speed	m³/min	8.5/7.0/6.5	8.7/7.5/6.5	10.0/8.5/7.0	11.5/9.5/8.0 14.0/12.5/10					
Air filter	Type						n net						
Sound power level	Cooling	At high fa	an speed	dBA	4	19	50	51	54	60			
Sound pressure	Cooling	At high / m	nedium / low fan speed	dBA	31.5/28.0/25.5	32.0/29.5/25.5	33.5/30.0/26.0	37.0/32.0/28.0	43.0/40.0/33.0				
level	Heating	At high / m	nedium / low fan speed	dBA	31.5/28.0/25.5	32.0/29.5/25.5	33.0/30.0/25.5	33.5/30.0/26.0	37.0/32.0/28.0	43.0/40.0/33.0			
Refrigerant	Type/GW	Р					R-32/	/675.0					
Piping connections	Liquid	OD		mm			6.	35					
	Gas	OD		mm		9.	.52		12	.70			
	Drain						VP20 (I.D.	20/O.D. 26)					
Power supply	Phase/Fre	equency/V	oltage	Hz/V			1~/50/60/2	20-240/220					
Current - 50Hz	Maximun	n fuse amp	s (MFA)	Α				б					
Control systems	Infrared r	emote con	ntrol		BRC7F5	30W (white panel)) / BRC7F530S (gre	y panel) / BRC7EB	530W (standard p	oanel) (1)			
Control systems	Wired rer	note contr	ol		BRC1H52W/S/K								
Discouries and a set in all		I (1) A A											




The unique automatic cleaning filter achieves higher efficiency and comfort with lower maintenance costs

Reduce running costs

> Automatic filter cleaning ensures low maintenance costs because the filter is always clean

Efficiency profile change for duct indoor unit during operation



Minimal time required for filter cleaning

- > The dust box can be emptied with a vacuum cleaner for fast and easy cleaning
- > No more dirty ceilings

Improved indoor air quality

> Optimum airflow eliminates draft and insulates sound

Superb reliability

> Prevents clogged filters for seamless operation

Unique technology

 Unique and innovative filter technology inspired by the Daikin auto cleaning cassette



Combination table

	Split / Sky Air					VRV												
		FDX	M-F9			F	XDA-	A/FX	DQ-A	3								
	25	35	50 60		15	20	25	32	40	50	63							
BAE20A62	•	•			•	•	•	•										
BAE20A82									•	•								
BAE20A102			•	•							•							

How does it work?

- 1 Scheduled automatic filter cleaning
- 2 Dust collects in a dust box that's integrated into the unit
- 3 The dust can easily be removed with a vacuum cleaner






Specifications	BAE20A62	BAE20A82	BAE20A102
Height (mm)		210	
Width (mm)	830	1,030	1,230
Depth (mm)			

Slim concealed ceiling unit


Slim design for flexible installation

- > Optimised design for R-32 refrigerant
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- Compact dimensions, can easily be mounted in a ceiling void of only 240mm


SERIE A (15, 20, 25, 32)



- Medium external static pressure up to 44Pa facilitates unit use with flexible ducts of varying lengths
- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- > Optional auto cleaning filter option ensures maximum efficiency, comfort and reliability by regular filter cleaning
- > Flexible installation, as the air suction direction can be altered from rear to bottom suction



> Standard drain pump with 600mm lift increases flexibility and installation speed




More details and final information can be found by scanning or clicking the QR codes.









Auto cleaning filter option

Heating capacity	FXDA 10A 15A 20A 25A 32A	10A		10A	10A	A					1	15/	Α			20A	١		2	5A		32A		40	DA		50/	١		63A	
Power input - 50Hz Cooling At high fan speed kW 0.026 0.035 0.030 0.035 0.038 0.049 0.04	ed kW 1.10 1.70 2.20 2.80 3.60	1.10	Т	1.10	1.10)					1	1.70	70			2.20)		2.	.80		3.60		4.	50		5.6)		7.10	
Heating At high fan speed kW 0.026 0.035 0.030 0.035 0.038 0.049 0.049 0.048	ed kW 1.30 1.90 2.50 3.20 4.00	1.30	Т	1.30	1.30	0		Т	Т		1	1.90	90			2.50)		3.	.20		4.00		5.	00		6.3)		8.00	
Required ceiling void >	ed kW 0.026 0.035 0.030 0.035	0.026	Т	0.026	0.026	26	Т	Т	Т		0.	0.03	35				0.	.030)			0.035		0.0)38		0.04	9		0.058	
Dimensions Unit HeightxWidthxDepth mm 200x750x620 200x1;	ed kW 0.026 0.035 0.030 0.035	0.026	Т	0.026	0.026	26	Т	Т	Т		0.	0.03	35				0.	.030)			0.035		0.0)38	T	0.04	9		0.058	
Weight Unit kg 22.0 23.0 26.5 30 26.5 30 26.5 30 26.5 30 26.5 30 26.5 30 26.5 30 26.5 30 26.5 30 30 30 30 30 30 30 3	mm 240																				240										
Casing Material Galvanised steel Galvanised steel	Depth mm 200x750x620														200	0x750	x62	0							200x	950)x620		200	<1,150×	620
Fan Air flow rate - 50Hz	kg 22.0 23.0	22.	22.0	22	22	22	22.0	22.0	22.0	2.0)								2	3.0					:	26.	5			30.5	
Factor F	Galvanised steel																		G	alva	nise	d steel									
Factory set / High Pa 10/30 15/44		5.2/4.9/4.7	1	5.2/4.9/4.7	5.2/4.9/4.7	9/4.7	7	6	6	6.	6.5/6	/6.2	2/5	5.8				8	8.0/7	7.2/6.4	4			10.5/9	0.5/8.5	5 1	2.5/11.0	/10.0	16.5	/14.5/	3.0
pressure - 50Hz Removable / washable Air filter Type Removable / washable Sound power level Cooling At high fan speed dBA 48 50 51 52 53 5 Sound pressure Cooling At high / medium / low fan speed dBA 29.0/28.0/26.0 32.0/31.0/27.0 33.0/31.0/27.0 34.0/32.0/28.0 35.0/33.0/29.0 36.0/33.0/29.0		5.2/4.9/4.7	'	5.2/4.9/4.7	5.2/4.9/4.7	9/4.7	7	6	6	6.	6.5/6	/6.2	2/5	5.8				8	8.0/7	7.2/6.4	4			10.5/9	0.5/8.5	5 1	2.5/11.0	/10.0	16.5	/14.5/	3.0
Sound power level Cooling At high fan speed dBA 48 50 51 52 53 55 Sound pressure Cooling At high / medium / low fan speed dBA 29.0/28.0/26.0 32.0/31.0/27.0 33.0/31.0/27.0 34.0/32.0/28.0 35.0/33.0/29.0 36.0/33.0/29.0	jh Pa 10/30															15/4	4														
Sound pressure Cooling At high / medium / low fan speed dBA 29.0/28.0/26.0 32.0/31.0/27.0 33.0/31.0/27.0 34.0/32.0/28.0 35.0/33.0/29.0 36.0/3	Removable / washable																	F	Rem	ovab	ole /	washab	e								
	ed dBA 48 50 51	48		48	48	3						50	0							51				5	2		53			54	
10 11 11 11 11 11 11 11 11 11 11 11 11 1	low fan speed dBA 29.0/28.0/26.0 32.0/31.0/27.0 33.0/31.0/27.0	29.0/28.0/26.0	.0 3	29.0/28.0/26.0	9.0/28.0/26.0	0/26.0	.0 3	0 32	.0 32	32.	2.0/3	/31.0	.0/2	27.0)			33	3.0/3	1.0/2	7.0			34.0/32	2.0/28	.0 3	5.0/33.0	/29.0	36.0	/34.0/	30.0
level Heating At high / medium / low fan speed dBA 29.0/28.0/26.0 32.0/31.0/27.0 33.0/31.0/27.0 34.0/32.0/28.0 35.0/33.0/29.0 36.0/32.0/28.0 35.0/33.0/29.0 36.0/32.0/28.0 36.0/32.0 36.	low fan speed dBA 29.0/28.0/26.0 32.0/31.0/27.0 33.0/31.0/27.0	29.0/28.0/26.0	.0 3	29.0/28.0/26.0	9.0/28.0/26.0	0/26.0	.0 3	0 32	.0 32	32.	2.0/3	/31.0	.0/2	27.0)			33	3.0/3	1.0/2	7.0			34.0/32	2.0/28	.0 3	5.0/33.0	/29.0	36.0	/34.0/	30.0
Refrigerant Type/GWP R-32/675.0	R-32/675.0																			R-3	32/67	75.0									
Piping connections Liquid OD mm 6.35	mm 6.35	6.35																													
Gas OD mm 9.52 12.70	mm 9.52	n 9.52												12.7)																
Drain VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)									/O.D. 26)																				
Power supply Phase/Frequency/Voltage Hz/V 1~/50/60/220-240/220	Hz/V 1~/50/60/220-240/220																		1~/5	50/60	/220	-240/22	0								
Current - 50Hz Maximum fuse amps (MFA) A 6	.) A 6																				6										
Control systems Infrared remote control BRC4C65 (1)	BRC4C65 (1)																			BRC	4C6	5 (1)									
Wired remote control BRC1H52W/S/K	BRC1H52W/S/K	BRC1H52W/S/K																													


Concealed ceiling unit with medium ESP

Slimmest yet most powerful medium static pressure unit on the market


- > Optimised design for R-32 refrigerant
- > Slimmest unit in class, only 245mm (300mm built-in height) and therefore narrow ceiling voids are no longer a challenge



- > Quiet operation: down to 25dBA sound pressure level
- > Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths
- > Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > Optional fresh air intake
- > Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation device is required
- > Standard built-in drain pump with 625mm lift increases flexibility and installation speed



- Brings in up to 10% of fresh air into the room
- > Standard built-in drain pump with 625mm lift increases flexibility and installation speed






Automatic Airflow Adjustment function

Automatically selects the most appropriate fan curve to achieve the units' nominal air flow within ±10%

Why?
After installation the real ducting will frequently differ from the initially calculated air flow resistance * the real air flow may be much lower or higher than nominal, leading to a lack of capacity or

uncomfortable air temperature Automatic Airflow Adjustment function will adapt

the unit's fan speed to any ducting automatically (10 or more fan curves are available on every model). making installation much faster



More details and final information can be found by scanning or clicking the QR codes.






Indoor Unit				FXSA	15A	20A	25A	32A	40A	50A	63A	80A	100A	125A	140A
Cooling capacity	Total capacity	At high fa	an speed	kW	1.70	2.20	2.80	3.60	4.50	5.60	7.10	9.00	11.20	14.00	16.00
Heating capacity	Total capacity	At high fa	an speed	kW	1.90	2.50	3.20	4.00	5.00	6.30	8.00	10.00	12.50	16.00	18.00
Power input - 50Hz	Cooling	At high fa	an speed	kW		0.046		0.049	0.094	0.096	0.106	0.143	0.176	0.216	0.272
	Heating	At high fa	an speed	kW		0.046		0.049	0.094	0.096	0.106	0.143	0.176	0.216	0.272
Dimensions	Unit	HeightxV	VidthxDepth	mm		245x5	50x800		245x70	008x00	245x1,0	00x800	245x1,4	00x800	245x1,550x800
Weight	Unit			kg		23.5		24.0	28.5	29.0	35.5	36.5	46.0	47.0	51.0
Casing	Material								Galva	nised stee	el plate				
Fan	Air flow rate - 50Hz	Cooling	At high / medium / low fan speed	m³/min	8.7/7.5/6.5	9.0/7	7.5/6.5	9.5/8.0/7.0	15.0/12.5/11.0	15.2/12.5/11.0	21.0/18.0/15.0	23.0/19.5/16.0	32.0/27.0/23.0	36.0/31.5/26.0	39.0/34.0/28.0
		Heating	At high / medium / low fan speed	m³/min	8.7/7.5/6.5	9.0/7	7.5/6.5	9.5/8.0/7.0	15.0/12.5/11.0	15.2/12.5/11.0	21.0/18.0/15.0	23.0/19.5/16.0	32.0/27.0/23.0	36.0/31.5/26.0	42.5/34.0/28.0
	External static pressure - 50Hz	Factory s	et / High	Pa				30/150				40/	150	50/	150
Air filter	Туре				Resin net										
Sound power level	Cooling	At high fa	an speed	dBA		54		55	6	0	59	6	51	6	64
Sound pressure	Cooling	At high / m	edium / low fan speed	dBA	29.5/28.0/25.0	30.0/2	3.0/25.0	31.0/29.0/26.0	35.0/32	2.0/29.0	33.0/30.0/27.0	35.0/32.0/29.0	36.0/34.0/31.0	39.0/36.0/33.0	41.5/38.0/34.0
level	Heating	At high / m	nedium / low fan speed	dBA	31.5/29.0/26.0	32.0/2	9.0/26.0	33.0/30.0/27.0	37.0/34	1.0/29.0	35.0/32.0/28.0	37.0/34.0/30.0	37.0/34.0/31.0	40.0/37.0/33.0	42.0/38.5/34.0
Refrigerant	Type/GWF)								R-32/675.0	0				
Piping connections	Liquid	OD		mm				6.	35					9.52	
	Gas	OD		mm		9	.52			12	.70			15.90	
	Drain							VP20 (I	.D. 20/O.D). 26), drai	n height 6	525 mm			
Power supply	Phase/Fre	quency/V	oltage	Hz/V					1~/50/	/60/220-2	40/220				
Current - 50Hz	Maximum	fuse amp	s (MFA)	Α						6					
Control systems	Infrared re	emote cor	itrol						BRC4C	65 / BRC4	IC66 (1)				
	Wired ren	note contr	ol						BR	C1H52W/	S/K				

Concealed ceiling unit with high ESP


Ideal for large sized spaces ESP up to 250 Pa

- > Optimised design for R-32 refrigerant
- > High external static pressure up to 250Pa facilitates extensive duct and grille network
- > Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- > Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation device is required (50-125 class)


Fresh air intake opening in casing



- Brings in up to 10% of fresh air into the room
- > Flexible installation, as the air suction direction can be altered from rear to bottom suction (50-125 class)



> Standard built-in drain pump with 625mm lift increases flexibility and installation speed (optional for 200-250)



> Large capacity unit: up to 31.5 kW heating capacity




Automatic Airflow Adjustment function

Automatically selects the most appropriate fan curve to achieve the units' nominal air flow within ±10%

Why?
After installation the real ducting will frequently differ from the initially calculated air flow resistance if the real air flow may be much lower or higher

* the real air flow may be much lower or higher than nominal, leading to a lack of capacity or

uncomfortable air temperature Automatic Airflow Adjustment function will adapt the unit's fan speed to any ducting automatically (10 or more fan curves are available on every model), making installation much faster



More details and final information can be found by scanning or clicking the QR codes.





Indoor Unit				FXMA	50A	63A	80A	100A	125A	200A	250A	
Cooling capacity	Total capacity	At high fa	an speed	kW	5.6	7.1	9.0	11.2	14.0	22.4	28.0	
	Nom.			kW			-			22.4	28.0	
Heating capacity	Total capacity	At high fa	an speed	kW	6.3	8.0	10.0	12.5	16.0	25.0	31.5	
	Nom.			kW			-			25.0	31.5	
Power input - 50Hz	Cooling	At high fa	an speed	kW	0.125	0.140	0.198	0.191	0.254	0.54	0.65	
·	Heating	At high fa	an speed	kW	0.125	0.140	0.198	0.191	0.254	0.54	0.65	
Required ceiling vo	id >		•	mm			350					
Dimensions	Unit	HeightxV	WidthxDepth	mm		300x1,000x700		300x1,4	100x700	470x1,49	90x1,100	
Weight	Unit		·	kg		35		4	16	105	115	
Casing	Material											
Fan	Air flow rate - 50Hz	Cooling	At high / medium / low fan speed	m³/min	18.0/16.5/15.0	19.5/17.5/16.0	25.0/22.5/20.0	32.0/27.0/23.0	36.0/30.0/26.0	62/48/41	74/64/52	
		Heating	At high / medium / low fan speed	m³/min	18.0/16.5/15.0	19.5/17.5/16.0	25.0/22.5/20.0	32.0/27.0/23.0	36.0/30.0/26.0	62/48/41	74/64/52	
	External static pressure - 50Hz		et / High / Low	Pa			100/200/-			150/2	50/50	
Air filter	Туре						Resin net			-		
Sound power level	Cooling	At high / n	nedium / low fan speed	dBA	61.0/60.0/58.0	64.0/61.0/59.0	67.0/64.0/62.0	65.0/61.0/56.0	70.0/66.0/62.0	75/74/72	76/75/73	
Sound pressure level	Cooling	At high / n	nedium / low fan speed	dBA	41.0/39.0/37.0	42.0/40.0/38.0	43.0/41	.0/39.0	44.0/42.0/40.0	48/46	5.5/45	
	Heating	At high / n	nedium / low fan speed	dBA	41.0/39.0/37.0	42.0/40.0/38.0	43.0/41	.0/39.0	44.0/42.0/40.0	48/46	5.5/45	
Refrigerant	Type/GW	Р						R-32/675				
Piping connections	Liquid	OD		mm		6.35			9.5	52		
	Gas	OD		mm		12.70		15	.90	19	9.1	
	Drain					VP	25 (I.D. 25/O.D.	32)		BS	P1	
Power supply	Phase/Fre	equency/V	/oltage	Hz/V		1~/	50/60/220-240/	220		1~/50/60/220	-240/220-230	
Current - 50Hz	Maximun	n fuse amp	os (MFA)	Α				6				
Control systems	Infrared r	emote cor	ntrol			BF	C4C65 / BRC4C	66		BRC4	1C65	
*	Wired rer	note contr	ol					BRC1H52W/S/k	(



Wall mounted unit

For rooms with no false ceilings nor free floor space

- > Optimised design for R-32 refrigerant
- > Flat, stylish front panel blends easily within any interior décor and is easier to clean
- > Can easily be installed in both new and refurbishment projects
- The air is comfortably spread up- and downwards thanks to
 5 different discharge angles that can be programmed via the remote control
- > Maintenance operations can be performed easily from the front of the unit



More details and final information can be found by scanning or clicking the QR codes.



Indoor Unit				FXAA	15A	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	At high fa	an speed	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Total capacity	At high fa	an speed	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input – 50Hz	Cooling	At high fa	an speed	kW	0.017	0.019	0.028	0.030	0.025	0.033	0.050
	Heating	At high fa	an speed	kW	0.025	0.029	0.034	0.035	0.030	0.039	0.060
Dimensions	Unit	HeightxV	VidthxDepth	mm		290x79	95x266			290x1,050x269	
Weight	Unit			kg		1	2			15	
Fan	Air flow rate – 50Hz	Cooling	At high/medium/ low fan speed	m³/min	7.1/6.8/6.5	7.9/7.2/6.5	8.3/7.4/6.5	9.4/8.0/6.5	12.2/11.0/9.8	14.2/12.6/10.9	18.2/15.5/12.9
		Heating	At high/medium/ low fan speed	m³/min	7.8/7.1/6.5	8.6/7.5/6.5	9.0/7.7/6.5	9.9/8.2/6.5	12.2/11.0/9.8	15.2/13.7/12.1	18.7/16.4/14.1
Air filter	Туре						Rem	novable / washa	able		
Sound power level	Cooling	At high fa	an speed	dBA	51.0	52.0	53.0	55	.0	58.0	63.0
Sound pressure	Cooling	At high/m	edium/low fan speed	dBA	32.0/30.5/28.5	33.0/31.0/28.5	35.0/32.0/28.5	37.5/33.0/28.5	37.0/35.5/33.5	41.0/38.5/35.5	46.5/42.5/38.5
level	Heating	At high/m	edium/low fan speed	dBA	33.0/31.0/28.5	34.0/31.5/28.5	36.0/32.5/28.5	38.5/33.5/28.5	38.0/36.0/33.5	42.0/39.0/35.5	47.0/43.0/38.5
Refrigerant	Type/GWI)						R-32/675.0			
Piping connections	Liquid	OD		mm				6.35			
	Gas	OD		mm		9.	52			12.70	
	Drain						VP	13 (I.D. 15/O.D. 1	18)		
Power supply	Phase/Fre	quency/V	oltage	Hz/V				1~/50/220-240			
Current – 50Hz	Maximum	fuse amp	s (MFA)	Α				6			
Control systems	Infrared re	emote con	ntrol					BRC7EA630 (1)			
	Wired ren	note contr	ol					BRC1H52W/S/K			


⁽¹⁾ Must be combined with Madoka wired remote controller | Contains fluorinated greenhouse gases




Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

- > Optimised design for R-32 refrigerant
- Ideal for comfortable air flow in wide rooms thanks to Coanda effect: up to 100° discharge angle



- > Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily without capacity loss
- > Can easily be installed in both new and refurbishment projects
- Can easily be mounted in corners and narrow spaces, as it only needs 30mm lateral service space



 Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation device is required Fresh air intake opening in casing



- * Brings in up to 10% of fresh air into the room
- > Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating.



More details and final information can be found by scanning or clicking the QR codes.





Indoor Unit				FXHA	32A	50A	63A	100A
Cooling capacity	Total capacit	y At high fa	an speed	kW	3.6	5.6	7.1	11.2
	Nom.			kW	3.6	5.6	7.1	11.2
Heating capacity	Total capacit	y At high fa	an speed	kW	4.0	6.3	8.0	12.5
	Nom.			kW	4.0	6.3	8.0	12.5
Power input - 50Hz	Cooling	At high fa	an speed	kW	0.033	0.037	0.051	0.086
	Heating	At high fa	an speed	kW	0.033	0.037	0.051	0.086
Dimensions	Unit	HeightxV	WidthxDepth	mm	235x960x690	235x1,2	70x690	235x1,590x690
Weight	Unit			kg	28	3	6	43
Casing	Material					Resin, sh	eet metal	
Fan	Air flow rate - 50H	Cooling	At high / medium / low fan speed	m³/min	12.5/11.0/10.0	16.0/14.0/12.5	17.5/15.0/13.0	27.0/22.0/19.0
		Heating	At high / medium / low fan speed	m³/min	12.5/11.0/10.0	16.0/14.0/12.5	17.5/15.0/13.0	27.0/22.0/19.0
Air filter	Туре			Ī		Resi	n net	
Sound power level	Cooling	At high / m	nedium / low fan speed	dBA	54.0/52.0/49.0	54.0/52.0/50.0	55.0/53.0/52.0	62.0/55.0/52.0
Sound pressure	Cooling	At high / m	nedium / low fan speed	dBA	36.0/34.0/31.0	36.5/34.5/33.0	37.0/35.0/34.0	44.0/37.0/34.0
level	Heating	At high / m	nedium / low fan speed	dBA	36.0/34.0/31.0	36.5/34.5/33.0	37.0/35.0/34.0	44.0/37.0/34.0
Refrigerant	Type/GW	Р				R-32	2/675	
Piping connections	Liquid	OD		mm		6.35		9.52
	Gas	OD		mm	9.52	12	2.7	15.9
	Drain					VF	20	
Power supply	Phase/Fre	equency/V	/oltage	Hz/V		1~/50/60/2	20-240/220	
Current - 50Hz	Maximun	n fuse amp	os (MFA)	Α			5	
Control systems	Infrared r	emote cor	ntrol			BRC70	A53-9	
•	Wired rer	note contr	ol			BRC1H5	52W/S/K	


4-way blow ceiling suspended unit

Unique Daikin unit for high rooms with no false ceilings nor free floor space


- > Optimised design for R-32 refrigerant
- > Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- > Can easily be installed in both new and refurbishment projects
- > Two optional intelligent sensors improve energy efficiency and comfort
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!




- > Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating.
- Optimum comfort guaranteed with automatic air flow adjustment to the required load
- > 5 different discharge angles between 0 and 60°can be programmed via the remote control



 Standard drain pump with 720mm lift increases flexibility and installation speed








More details and final information can be found by scanning or clicking the QR codes.

BRC7CB58 / BRC7CB59

BRC1H52W/S/K





Α

Maximum fuse amps (MFA)

Infrared remote control
Wired remote control

Current - 50Hz

Control systems









Supporting a circular economy of refrigerants



Towards a circular economy of refrigerants

With L∞P by Daikin we want to step away from producing more waste. Instead we will reuse what is already available, in a qualitative way.

- Saves over 400,000 kg of virgin refrigerant being produced every year
- Greatly reduces the CO₂ footprint of refrigerant production with 72%!

For units produced and sold in Europe

- > Exclusive to Daikin reclaimed gas is now used in our units
- > Administratively allocated to VRV and chillers produced and sold in Europe

For more information visit www.daikin.eu/loop-by-daikin



The most extensive VRV range on the market



VRV i-series



VRV S-series



VRV W-series



Heat recovery, heat pump and replacement series

Recover

We recover your **old refrigerant** for you from any unit and any brand.

Reclaim

The refrigerant is reclaimed in Europe, meaning regenerated in a **high-quality** way, in line with F-gas regulation definition.

Reuse

The reclaimed refrigerant is mixed with virgin refrigerant. The refrigerant's quality is **certified** by an independent laboratory. It meets AHRI 700 certified standards.



72% lower CO₂ fooprint for production

For every application, a solution



Heat recovery with unique 3-pipe technology



Heat pump models with unique continuous heating during defrost



Dedicated **hot and cold climate** heat pumps offering efficient cooling up to 52°C and heating down to -25°C



Space saving mini VRV solutions, offering the most compact VRV



The invisible VRV,
a unique solution when
the outdoor unit must
be compact and completely
invisible



existing systems in the most cost-effective way



Water-cooled heat recovery and heat pump units, ideal for high rise buildings using water as heat source



A complete total solution integrating a wide range of indoor units, air curtains, hot water hydroboxes and ventilation units including air handling units

Products overview IN IV LOOP (1)





Model		Product name	4	5	6	8	10	12	13	14	16	18	20	22	24	26	28	30
VRV IV heat recovery	Best efficiency & comfort solution > Fully integrated solution with heat recovery for maximum efficiency > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains > "Free" heating and hot water through heat recovery > The perfect personal comfort for guests/tenants via simultaneous cooling and heating > Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature and continuous heating > Allows technical cooling > Widest range of BS boxes on the market	REYQ-U VRV IV*				•	•	•	•	•	•	•	•	•	•	•	•	•
VRV IV heat pump with continuous heating	Daikin's optimum solution with top comfort Continuous heating during defrost Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains Connectable to stylish indoor units (Daikin Emura, Stylish,) Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature and continuous heating	RYYQ-U* VRV IV*				•	•	•		•	•	•	•	•	•	•	•	•
VRV IV heat pump without continuous heating	Daikin's solution for comfort & low energy consumption Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains Connectable to stylish indoor units (Daikin Emura, Stylish,) Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	RXYQ-U* VRV IV*				•	•	•		•	•	•	•	•	•	•	•	•
VRVIV-S series Compact	The most compact VRV > Compact and lightweight single fan design saves space and is easy to install > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains > Either connect VRV of stylish indoor units (Daikin Emura, Stylish,) > Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	RXYSCQ-TV1 VRY IV S-series Compact	•	•	•													
VRVIV-S series	Space saving solution without compromising on efficiency > Space saving trunk design for flexible installation > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains > Either connect VRV of stylish indoor units (Daikin Emura, Stylish,) > Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	RXYSQ-TV9/ TY9/TY1 VRV IV S-series	/	•	•	•	•	•	· ·									
VRV IVheat pump for indoor installation	The invisible VRV > Unique VRV heat pump for indoor installation > Total flexibility for any shop location and building type as the outdoor unit is invisible and split up in 2 parts > Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation and Biddle air curtains	SB.RKXYQ-T(8) VRV IV i-series		•		•												
VRV IV heat pump, optimised for cold climates	Where heating is priority without compromising on efficiency > Suitable for single source heating Extended operation range down to -25°C in heating > Stable heating capacity without any capacity loss down to -15°C > Very economical solution as a smaller outdoor unit model can be used compared to the standard series	RXYLQ-T					•	•		•	•	•	•	•	•	•	•	•
heat recovery	Quick & quality replacement for R-22 and R-407C systems > Cost-effective and fast replacement through re-use of exisiting piping > Drastically improve your comfort, efficiency and reliability > No interuption of daily business while replacing your system > Replace Daikin and other manufacturers systems safely	RQCEQ-P3					•		•		•	•	•	•	•	•	•	•
heat pump	Ouick & quality replacement for R-22 and R-407C systems Cost-effective and fast replacement through re-use of exisiting piping Drastically improve your comfort, efficiency and reliability No interuption of daily business while replacing your system Replace Daikin and other manufacturers systems safely Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	RXYQQ-U YRY IV Q*series		•		•	•	•		•	•	•	•	•	•	•	•	•
Water cooled VRV IV	Ideal for high rise buildings, using water as heat source > Reduced CQ, emissions thanks to the use of geothermal energy as a renewable energy source > No need for an external heating or cooling source when used in geothermal mode > Compact & lightweight design can be stacked for maximum space saving > Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature > Variable Water Flow control option increases flexibility and control > Mixed connection of HT hydroboxes and VRV indoor units > Either connect VRV of stylish indoor units (Daikin Emura, Stylish,) > 2 analogue input signals allowing external control	RWEYQ-T9 ⁽²⁾ VRV IV W series				•	•	•		•	•	•	•	•	•	•	•	•
	heat pump heat recovery optimised indoor installation of for cold climates	Part Part	UNIOUE Sea efficiency A correlate solution Fig. 19 (A) International Control Content Secure Fire Presting and hot water through heat recovery for maximum efficiency Cooper all thermal needs of a building via a single point of contacts accusate temperature control vendes for the grant presting of the strength of th	UNIOUE Feet efficiency & commiss solution Compared with the many time greated solution who have recovery for maximum efficiency Covers all thermal necks of a building via a single point of contact, accurate proposation control, vendation, but water, a handling units and Biddle air currains Feet Photology and hot water through heat recovery Feet heating and hot water through heat recovery Feet Photology and hot water through heat recovery Feet Commission of the proposation of the proposation of contact, accurate the proposation of the p	UNIOUE Presidence of Comment Section 1 and	UNIOUE lear efficiency & common existation Covers all them of meets of a building you a single point of controls accusate to consequent accoration, ventication, but was as if annihing units and discide an currane of the covers all them of meets of a building you a single point of controls accusate the programment of the covers of the c	UNIOUE Sea embrace out committee selection A cover all themsel needs of a building value as night point of contacts accurate requirement of the control of	UNIOUE Set efficiency & comment values or content to the property of the prope	UNION Description of section of the control of the	UNION Plant and registered solutions with beet exceep for treatment efficiency Cover, dill them altereds of a building via a single print of contact, accounts registered and contact of the county of the contact of	UNIOU De la concentration de conference causant de la contration de la con	UNIOU Personal Section (International Section Control	UNION Descriptions of accordance solution Consideration of accordance solution Consideration of the solution	UNION DESCRIPTION SECURITY AND ADMINISTRATION OF THE PROPERTY	UNION DE L'ANTITION DE L'ANTIT	UNION IN Contract Con	UNION Services of the control of the	UNION Descriptions Automatics and Committee

⁽¹⁾ LOOP by Daikin is applicable for VRV units produced and sold in Europe (EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland). RXYSCQ-TVI, RXYSQ8-10-12TYI and RQCEQ-P3 are not part of the LOOP by Daikin programme.

(2) Range not Eurovent certified.

(3) Multi combinations are not in scope of the Eurovent certificaton programme

Single unit

Multi combination

																					Outdoor units
32	Capacity (HP 34 36 38 40 42 44 46 48 50 52			Description / Combination	VRV indoor units	Residential indoor units	LT Hydrobox HXY-A	HT Hydrobox HXHD-A	HRV units VAM-, VKM-	AHU connection EKEXV-+ EKEQMCBA	AHU connection EKEXV- + EKEQFCBA	Air curtains CYV-DK-	Remarks								
												VRV IV+ Heat Recovery REYQ	0		0	0	0	0		0	> Standard total system connection ratio limit: 50 ~ 130%
												with only VRV indoor units	✓								
												with LT/HT Hydroboxes	✓		✓	√	√				Max 32 indoor units, even on 16HP and larger systems Total system connection ratio with HT hydroboxes up to 200% possible
												HRV units VAM-, VKM-	✓		✓	√	√	✓		✓	
•	•	•	•	•	•	•	•	•	•	•	•	AHU connection EKEXV + EKEQMCBA	\ \				√	✓		√	 Dedicated systems (with only ventilation units) not allowed – a mix with standard VRV indoor units is always necessary
												Biddle air curtain CYV-DK-	✓				√	✓		✓	> Total system connection ratio with AHU is 50 ~ 110%
												VRV IV+ Heat Pump (RYYQ/RXYQ)	0	0	0		0	0	0	0	> Standard total system connection ratio limit: 50 ~ 130%
												with only VRV indoor units	✓								> 200% total system connection ratio possible under special circumstances
	•	•		•								with residential indoor units	✓	✓			✓				Only single-module systems (RYYQ 8~20 T / RXYQ 8~20 T) Max 32 indoor units, even on 16HP, 18HP and 20HP systems Connection ratio: 80 ~ 130%
												with LT Hydroboxes	✓		✓		✓				Max 32 indoor units, even on 16HP and larger systems Contact Daikin in case of multi-module systems (>20HP)
+	+											HRV units VAM-, VKM-	✓	✓	√		✓	✓		✓	Contact Bunkin in Case of Halla module Systems (220 m)
												AHU connection EKEXV + EKEQMCBA	\ \				✓	✓		✓	
												AHU connection EKEXV + EKEQFCBA	١						✓		> Total system connection ratio with AHU is 50 ~ 110%
	•		•	•	•	•	•	•	•	•	•	Biddle air curtain CYV-DK-	✓				✓	✓		✓	
												VRV IV-S RXYSQ-/RXYSCQ-	0	0			0	0		0	> Standard total system connection ratio limit: 50 ~ 130%
												with VRV indoor units only	✓				✓	✓		✓	
												with residential indoor units only		✓							> With residential indoor: connection ratio limit: 80 ~ 130%
												VRV IV i series SB.RKXYQ	✓				✓	✓		✓	> Standard total system connection ratio limit: 50 ~ 130%
												VRV IV-C⁺ series RXYLQ	0	0	0		0	0	0	0	> Standard total system connection ratio limit: 70 ~ 130%
												with VRV indoor units only	√				✓			✓	
•	•	•	•	•	•							with residential indoor units only		✓							> With residential indoor: connection ratio limit: 80 ~ 130%
												with LT hydroboxes AHU connection EKEXV + EKEQMCBA	✓ ✓		√		✓	√		√	Max. 32 indoor units, contact Daikin in case of multi-module systems (> 14HP) Total system connection ratio is 70~110%
												AHU connection EKEXV + EKEQFCBA	√				•	•	√	•	> With AHU only connection ration is 90~110%
												VRV III-Q* series Replacement H/R RQCEQ	4				✓				> Standard total system connection ratio limit: 50 ~ 130%
•	•	•	•	•	•							VRV IV-Q Replacement H/P RXYQQ	~				✓	✓		✓	> Standard total system connection ratio limit: 50 ~ 130%
												VRV IV-W+ series Water-cooled VRV RWEYQ	O	0		0	0	0	0	0	> Standard total system connection ratio limit: 50 ~ 130%
												with VRV indoor units	✓			✓	✓	✓	✓	✓	> Only single-module systems (RWEYOP 14TO)
												with split indoor units	✓	✓			✓				Only single-module systems (RWEYQ8-14T9) Max 32 indoor units Connection ratio: 80 ~ 130% only in heat pump version
•	•	•	•	•	•							with HT hydrobox	✓			✓					
												AHU connection	✓					✓			Total system connection ratio with AHU + X indoor is 50 ~ 110% Total system connection ration with AHU only is 90~ 110%

 $[{]f O}_-$ connection of indoor unit possible, but not neccessarily simultaneously with other allowed indoor units ${f v}_-$ connection of indoor unit possible even simultaneously with other checked units in the same row ${f x}_-$ connection of indoor not possible on this outdoor unit system





Perial Asset Management

L∞P by Daikin is assisting clients in creating their own circular economy of refrigerants



Perial Asset Management (Perial AM) manages a diverse real estate portfolio mainly located in France and increasingly in Europe. The company is committed to reducing energy and water consumption as part of a continuous improvement process.

The arrival of new tenants at an office building in Boulogne-Billancourt spurred Perial Asset Management's decision to carry out renovation work to meet Perial AM's CSR objectives.

Constructed in the 1990s, the refurbished building extends over a surface area of 4,200 m² comprising the ground floor and seven stories, including offices and creating a 1,800 m² ERP area. Working with Perial Asset Management (Perial AM), Daikin installed new VRV units with reclaimed refrigerant at their office building, while recycling the R-410A refrigerant from the old units to use it as a field charge for the new system.

Daikin is the only manufacturer in the market able to offer customers a holistic approach to reusing their refrigerant in new projects via its L∞P by Daikin program.

Las Arenas historic hotel, opts for sustainable upgrade

- Choosing a sustainable replacement solution was on top of the agenda
- Separate temperature zones enable every room to be controlled individually, adjusting the comfort conditions to suit the individual or activity
- 88 outdoor units were replaced in a record six months
- > A true circular economy example:
 - > Reuse of copper piping and indoor units
 - > Reuse of regenerated refrigerant



L1 complex Multifunctional building with BREEAM certification

- A total solution, including VRV heat pumps, multiple scroll chillers and Air Handling Units (AHUs), centrally managed through Daikin's Intelligent Touch Manager mini BMS
- Daikin's Accredited Professionals (AP's)
 collaborated with the project team to maximise the building's BREEAM rating
- Daikin heat pumps can contribute in 6 out of 10 BREEAM categories, adding up to 30 credits





VRV IV+ heat recovery

Best efficiency and comfort solution





VRV IV standards:

Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

Continuous heating

The new standard in heating comfort

VRV configurator

Software for simplified commissioning, configuration and customisation

- > 7 segment display
- > Automatic refrigerant charge
- > Refrigerant containment check
- > Night quiet mode
- > Low noise function
- > Connectable to LT hydrobox for hot water
- > Connectable to HT hydrobox for hot water
- > Full inverter compressors
- > Gas cooled PCB
- > 4 side heat exchanger
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function

VRV IV BS boxes

Maximum design flexibility and installation speed

- > Quickly and flexibly design your system with a unique range of single and multi BS boxes.
- A wide variety of compact and lightweight multi BS boxes greatly reduces installation time.
- > Free combination of single and multi BS boxes

Single port

- > Unique to the market
- > Compact and light to install
- > No drain piping needed
- > Ideal for remote rooms
- > Technical cooling function
- > Connect up to 250 class unit (28 kW)
- > Allows multi-tenant applications

Multi port: 4 - 6 - 8 - 10 - 12 - 16

- > Up to 55% smaller and 41% lighter than previous range
- Faster installation thanks to a reduced number of brazing points and wiring
- > All indoor units connectable to one BS box
- > Fewer inspection ports needed
- > Up to 16 kW capacity available per port
- Connect up to 250 class unit (28kW) by combining 2 ports
- > No limit on unused ports, permitting phased installation
- > Allows multi-tenant applications






Faster installation thanks to open connection

- No need to cut the pipe before brazing for indoor units smaller or equal to 5.6 kW (50 class)
- > Cut and braze the pipe for indoor units bigger or equal to 7.1 kW (63 class)



Maximum comfort at all times

With the VRV BS box, any indoor unit not being used to switch between heating and cooling maintains the constant desired temperature. This is because our heat recovery system does not need to equalise pressure over the entire system after a change-over.



VRV IV+ heat recovery

Best efficiency & comfort solution

- > Fully integrated solution with heat recovery for maximum efficiency with COPs of up to 8!
- > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains
- > "Free" heating and hot water production provided by transferring heat from areas requiring cooling to areas requiring heating or hot water
- > The perfect personal comfort for guests/tenants via simultaneous cooling and heating
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, continuous heating, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB, new DC fan motor
- > Outdoor unit display for quick on-site settings and easy read out of errors together with the indication of service parameters for checking basic functions.

- > Free combination of outdoor units to meet installation space or efficiency requirements
- > Wide piping flexibility: 30m indoor height difference, maximum piping length: 190m, total piping length: 1,000m
- > Possibility to extend the operation range in cooling down to -20°C for technical cooling operation such as server rooms
- > Contains all standard VRV features





Already fully compliant

For units made and sold in Europe*

Published data with real-life indoor units

Outdoor unit			REYQ	8U		10U	12	U	14U	1	6U	18U		20U		
Capacity range			HP	8		10	12	2	14		16	18		20		
Cooling capacity	Prated,c		kW	22.4		28.0	33.	.5	40.0		15.0	50.4		52.0		
Heating capacity	Prated,h		kW	22.4		28.0	33.	.5	40.0	4	15.0	50.4		56.0		
3,,	Max.	6°CWB	kW	25.0		31.5	37.		45.0		0.0	56.5		63.0		
Recommended cor				4x FXFQ50		FXFQ63AVEE			1x FXFQ50AVE 5x FXFQ63AV	B + 4x FXF0		3x FXFQ50AV 5x FXFQ63A				
ης,ς			%	286.	1	264.8	257	7.0	255.8		43.1	250.6		246.7		
ηs,h			%	165.1		169.7	183		168.3		67.5	172.5		162.7		
SEER			,,,	7.2		6.7	1.00	6.			6.2	6.3		6.2		
SCOP				4.2		4.3	4.		.5	4.3	U.E	4.4		4.1		
Maximum number	of connoc	table indeer units		7.2		4.5	7.	,	64 (1)	7.3		7.7		7.1		
Indoor index	Min.	table illuoor ullits		100.0	1	125.0	150	10	175.0	2	0.00	225.0		250.0		
connection	Nom.			100.0	,	123.0	150	7.0	-		00.0	223.0		230.0		
connection	Max.			260.0	1	325.0	390	١.٥	455.0		20.0	585.0		650.0		
Dimensions		HaiahtyWidthyDanth		200.0).0	455.0) 3	20.0 1.685x1.2			030.0		
Dimensions	Unit	HeightxWidthxDepth	mm		1,0	585x930x765)			21.4	1,085X1,2	24UX/65	217			
Weight	Unit		kg	70.0		230				314			317	070		
Sound power level		Nom.	dBA	78.0		79.1	83		80.9		35.6	83.8		87.9		
	Heating	Prated,h	dBA	79.6		80.9	83		83.9		36.9	85.3		89.8		
Sound pressure level	Cooling	Nom.	dBA		57.0		61.	.0	60.0		53.0	62.0		65.0		
Operation range	Cooling	Min.~Max.	°CDB						-5.0 ~43.0							
,	Heating	Min.~Max.	°CWB						-20.0 ~15.5	i						
Refrigerant	Type/GW	P							R-410A/2,08	7.5						
J	Charge		kg/TCO2Eq	9.7/20	.2	9.8/20.5	9.9/2	20.7	,		11.8/	24.6				
Piping connections		OD	mm		9.52				12.7				15.9			
riping connections	Gas	OD	mm	19.1	J.J.	22.2			12.7	-	28.6		13.5			
	HP/LP	OD	mm	15.9			19.1				22.2			28.6		
	gas	OD		15.7			15.1			4	.2.2			20.0		
		g System Actual	m		1				1,000							
Power supply		eguency/Voltage	Hz/V						3N~/50/380-	415						
Current - 50Hz		n fuse amps (MFA)	Α	20		25		3			4	0		50		
Current Sonia	- Triazini a	inase amps (iii,									_			,		
Outdoor unit syst			REYQ	10U	13U	16U	18U	20U	22U	24U	26U	28U	30U	32U		
System		unit module 1			IQ5U		REYQ8U		REYQ10U	_		REYQ12U		REYQ16U		
	Outdoor	unit module 2		REMQ5U		YQ8U	REYQ10U		EYQ12U			J REYQ16U				
Capacity range			HP	10	13	16	18	20	22	24	26	28	30	32		
Cooling capacity	Prated,c		kW	28.0	36.4	44.8	50.4	55.9	61.5	67.4	73.5	78.5	83.9	90.0		
Heating capacity	Prated,h		kW	28.0	36.4	44.8	50.4	55.9	61.5	67.4	73.5	78.5	83.9	90.0		
	Max.	6°CWB	kW	32.0	41.0	50.0	56.5	62.5	69.0	75.0	82.5	87.5	94.0	100.0		
Recommended cor	mbination			4x FXFQ63AVEB	3x FXFQ50AVEB 3x FXFQ63AVE		4x FXFQ50AVEB + 4x FXFQ63AVEB	10x FXFQ50A	VEB 6x FXFQ50AVEB + 4x FXFQ63AVEB	4x FXFQ50AVEB + 4x FXFQ63AVEB + 2x FXFQ80AVEB			9x FXFQ50AVEB + 5x FXFQ63AVEB	8x FXFQ63AVEB 4x FXFQ80AVE		
ns c			%	275.1	301.3	288.6	272.9	266.0	260.4	257.7	257.5	251.9	266.8	243.1		
ηs,c				158.8	160.6	168.2	167.9	175.7	178.5	167.6	175.5	174.8	179.4	169.1		
ηs,h			90					6.7								
SEER				7.0	7.6	7.3	6.9	6./	6.6		5.5	6.4	6.7	6.2		
SCOP		rational and a second re-		4.0	4.1	4	.3		4.5	4.3	4.5	4.4	4.6	4.3		
Maximum number		table indoor units							64 (1)							
Indoor index	Min.			125.0	163.0	200.0	225.0	250.0		300.0	325.0	350.0	375.0	400.0		
connection	Nom.								-							
	Max.			325.0	423.0	520.0	585.0	650.0	715.0	780.0	845.0	910.0	975.0	1,040.0		
Piping connections	Liquid	OD	mm	9.52		12.7			15.9			19	9.1			
	Gas	OD	mm	22.2			28.6					34.9				
	HP/LP	OD	mm	19	9.1	22	2.2				28.6					
	gas										1	000				
		g System Actual	m			500					١,	,000				
Power supply	Total piping length					500			3N~/50/380-	415		,000				
Power supply Current - 50Hz	Total piping length Phase/Fre	g System Actual equency/Voltage in fuse amps (MFA)	m Hz/V A		40	500		50	3N~/50/380-		53	,000		30		







More details and final information can be found by scanning or clicking the QR codes.





Outdoor unit syst	em		REYQ	34U	36U	38U	40U	42U	44U	46U	48U	50U	52U	54U			
System	Outdoor	unit module 1		REYQ16U REYQ8U REYQ10U REYQ12U REYQ14U								REYQ16U		REYQ18U			
	Outdoor	unit module 2		REYQ18U	REYQ20U	REY	Q12U			REYQ16U			REY	Q18U			
	Outdoor	unit module 3			-	REY	Q18U		REY	Q16U			REYQ18U				
Capacity range			HP	34	36	38	40	42	44	46	48	50	52	54			
Cooling capacity	Prated,c		kW	95.4	97.0	106.3	111.9	118.0	123.5	130.0	135.0	140.4	145.8	151.2			
Heating capacity	Prated,h		kW	95.4	101.0	106.4	111.9	118.0	123.5	130.0	135.0	140.4	145.8	151.2			
	Max.	6°CWB	kW	106.5	113.0	119.0	125.5	131.5	137.5	145.0	150.0	156.5	163.0	169.5			
Recommended cor	mbination			9x FXFQ63AVEB+	2x FXFQ50AVEB + 10x FXFQ63AVEB + 2x FXFQ80AVEB			12x FXFQ63AVEB + 4x FXFQ80AVEB	8x FXFQ63AVEB+	1x FXFQ50AVEB + 13x FXFQ63AVEB + 4x FXFQ80AVEB		13x FXFQ63AVEB+		+ 15x FXFQ63AVEB			
ηs,c			%	259.2	255.3	269.2	259.6	250.2	249.3	246.8	243.1	254.4	265.7	275.2			
ηs,h			%	172.0	166.3	176.0	176.1	167.8	171.9	168.8	168.5	170.3	171.7	173.3			
SEER				6.6	6.5	6.8	6.6	6	.3	6	.2	6.4	6.7	7.0			
SCOP				4.4	4.2	4	.5	4.3	4.4		4.3		4	.4			
Maximum number		table indoor units							64 (1)								
Indoor index	Min.			425.0	450.0	475.0	500.0	525.0	550.0	575.0	600.0	625.0	650.0	675.0			
connection	Nom.								-								
	Max.			1,105.0	1,170.0	1,235.0	1,300.0	1,365.0	1,430.0	1,495.0	1,560.0	1,625.0	1,690.0	1,755.0			
Piping connections		OD	mm						19.1								
	Gas	OD	mm	34.9													
	HP/LP ga		mm	28	3.6					34.9							
	Total piping length	g System Actual	m						1,000								
Power supply		equency/Voltage	Hz/V						I~/50/380-	415							
Current - 50Hz	Maximur	n fuse amps (MFA)	Α	8	30			100				1.	25				
Outdoor unit mod	lule		REMQ						5U								
Dimensions	Unit	HeightxWidthxDepth	mm					1,	685x930x7	65							
Weight	Unit		kg						230								
Fan	External stati	ic Max.	Pa						78								
Sound power level	Cooling	Nom.	dBA						78.0								
Sound pressure level	Cooling	Nom.	dBA						57.0								
Operation range	Cooling	Min.~Max.	°CDB						-5.0 ~43.0								
	Heating	Min.~Max.	°CWB						-20.0 ~15.5								
Refrigerant	Type/GW	/P						R-	-410A/2,08	7.5							
	Charge		kg/TCO2Eq	·													
Power supply	Phase/Fr	equency/Voltage	Hz/V														
Current - 50Hz	Maximur	n fuse amps (MFA)	Α														
(1)Actual number of cor		•	the indoc	or unit type a	nd the conne	ction ratio re	striction for	the system (5	0% < CR < 12	10%)							

⁽¹⁾ Actual number of connectable indoor units depends on the indoor unit type and the connection ratio restriction for the system ($50\% \le CR \le 120\%$)

Actual number of connectable indoor units depends on the indoor unit type and the connection ratio restriction for the system ($50\% \le CR \le 120\%$) | Contains fluorinated greenhouse gases

* EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland



Individual branch selector for VRV IV heat recovery

- Unique range of single and multi BS boxes for flexible and fast design
- > Compact & light to install
- > Ideal for remote rooms as no drain piping is needed
- Allows integration of server rooms into the heat recovery solution thanks to technical cooling function
- > Connect up to 250 class unit (28kW)
- > UNIQUE Faster installation thanks to open port connection
- > Allows multi tenant applications
- Connectable to REYQ-T, RQCEQ-P3 and RWEYQ-T8 heat recovery units



More details and final information can be found by scanning or clicking the QR codes.





Indoor Unit				BS1Q	1Q10A	1Q16A	1Q25A
Power input	Cooling	Nom.		kW		0.005	
•	Heating	Nom.		kW		0.005	
Maximum number	of connect	able indo	or units		6	3	3
Maximum capacity	index of c	onnectab	le indoor units		15 < x ≤ 100	100 <x≤160< td=""><td>160<x≤250< td=""></x≤250<></td></x≤160<>	160 <x≤250< td=""></x≤250<>
Dimensions	Unit	Heightx\	WidthxDepth	mm		207x388x326	
Weight	Unit			kg		12	15
Casing	Material					Galvanised steel plate	
Piping connections	Outdoor	Liquid	OD	mm		9.52	
	unit	Gas	OD	mm	1	5.9	22.2
		Discharge g	as OD	mm	1	12.7	19.1
	Indoor	Liquid	OD	mm		9.52	
	unit	Gas	OD	mm	1	5.9	22.2
Sound absorbing th	nermal insu	ulation			Foame	ed polyurethane Flame-resistant nee	edle felt
Power supply	Phase/Fre	quency/\	/oltage	Hz/V		1~/50/220-240	
	Maximum	n fuse amı	os (MFA)	Α		15	

Contains fluorinated greenhouse gases

BS-Q14AV1B

Multi branch selector for VRV IV heat recovery

- > Unique range of single and multi BS boxes for flexible and fast design
- > Major reduction in installation time thanks to wide range, compact size and light weight multi BS boxes
- > Up to 70% smaller and 66% lighter than previous series
- Faster installation thanks to a reduced number of brazing points and wiring
- > All indoor units connectable to one BS box
- > Less inspection ports needed compared to installing single BS boxes
- > Up to 16kW capacity available per port
- > Connect up to 250 class unit (28kW) by combining 2 ports
- > No limit on unused ports allowing phased installation
- > UNIQUE Faster installation thanks to open port connection
- > **UNIQUE** Refrigerant filters for high reliability
- > Allows multi tenant applications
- > Connectable to REYQ-T, RQCEQ-P3 and RWEYQ-T8 heat recovery units



More details and final information can be found by scanning or clicking the QR codes.






Indoor Unit				BS	4Q14AV1B	6Q14AV1B	8Q14AV1B	10Q14AV1B	12Q14AV1B	16Q14AV1B		
Maximum number	of connec	table indo	or units		20	30	40	50	60	64		
Maximum capacity	index of c	onnectab	le indoor units		400	600		50				
Dimensions	Unit	Heightx\	WidthxDepth	mm	298x370x430	298x5	80x430	298x8	20x430	298x1,060x430		
Weight	Unit			kg	17.0	24.0	26.0	35.0	35.0 38.0			
Casing	Material						Galvanised	steel plate	el plate			
Piping connections	Outdoor	Liquid	OD	mm	9.52	12.7	12.7/15.9	15.9	15.9 15.9/19.1			
	unit	Gas	OD	mm	22.2/19.1	28.6/22.2	28.6	28.6	/34.9	34.9		
		Discharge ga	as OD	mm	19.1/15.9	19.1/22.2	19.1/22.2/28.6		28.6			
	Indoor	Liquid	OD	mm			6.35	/9.52				
	unit	Gas	OD	mm			12.7	/15.9				
Sound absorbing tl	nermal ins	ulation					Urethane foam, p	olyethylene foam	lyethylene foam			
Power supply	Phase/Fre	equency/\	/oltage	Hz/V			1~/50/2	220-240				
	Maximun	n fuse amp	os (MFA)	Α			1	5				

VRV IV+ heat pump

Daikin's optimum solution with top comfort





VRV IV standards:

Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

Continuous heating

The new standard in heating comfort

VRV configurator

Software for simplified commissioning, configuration and customisation


- > 7 segment display
- > Automatic refrigerant charge
- > Refrigerant containment check
- > Night quiet mode
- > Low noise function
- > Connectable to stylish indoor units (Only for single modules)
- > Connectable to LT hydrobox (1)
- > Full inverter compressors
- > Gas cooled PCB
- > 4 side heat exchanger
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function

(1) Special order unit needed to connect LT hydroboxes with multi outdoor unit systems For detailed explanation of these functions refer to vrv iv technologies tab



Wide range of indoor units

Freely combine VRV indoor units with stylish indoor units (Daikin Emura, ...)



Connectable stylish indoor units

		20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Daikin Emura - Wall mounted unit	FTXJ-AW/AS/AB	•	•	•		•		
Stylish - Wall mounted unit	FTXA-AW/BS/BB/BT	•	•	•	•	•		
Perfera wall mounted	FTXM-R	•	•	•	•	•	•	•
Perfera floor standing NEW	FVXM-A9	•	•	•		•		

VRV IV


proven in practice: 40% more efficient

A field trial at a German fashion chain store demonstrated how the innovative features of VRV IV have improved energy efficiency dramatically over previous models.

Results: up to 60% less energy consumed

The results of the trial showed that the new VRV IV system consumed much less energy, particularly when cooling, compared with the VRV III system – in some cases up to 60% less. When heating, savings were an average of 20%.

The Unterhaching trial demonstrates how VRV IV heat pump technology uses a renewable energy source – air - to provide a complete and environmentally sustainable solution for heating, cooling, and ventilation in commercial environments. The trial also shows that businesses can only identify and control energy wastage through careful and intelligent monitoring of climate control systems, a service which Daikin can offer.



	VRV III 20HP (2 modules)	VRV IV 18HP (1 module)
Period	March 2012 - February 2013	March 2013 - February 2014
Avg (kWh/Month)	2.797	1.502
Total (KWh)	33.562	18.023
Total (€)	6.041	3.244
Yearly (operation cost/m² (€/m²)	9.9	5.3
	46% saving	gs = € 2.797

Measured data

Fashion store Unterhaching (Germany)

- > Floor space: 607m²
- > Energy cost: 0.18 €/kWh
- > System taken into account for consumption:
- VRV IV heat pump with continuous heating
- Round flow cassettes (without auto cleaning panel)
- VAM for ventilation (2x VAM2000)
- Biddle Air curtain.




Free combination of outdoor units

Freely combine outdoor units to optimise for small footprint, continuous heating, highest efficiency or any other combination

Flexible piping design

Total piping length	1,000m
Longest length actual (Equivalent)	165m (190m)
Longest length after first branch	90m¹
Level difference between indoor and outdoor units	90m¹
Level difference between indoor units	30m

¹ Contact your local dealer for more information and restrictions



² in case outdoor unit is located below indoor units

VRV IV+ heat pump

Daikin's optimum solution with top comfort

- > By choosing a LOOP by Daikin product you support the reuse of refrigerant, for more information visit www.daikin.eu/loop-by-daikin
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains
- > Wide range of indoor units: possibility to combine VRV with stylish indoor units (Daikin Emura, Perfera)
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, continuous heating, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB, new DC fan motor
- > Outdoor unit display for quick on-site settings and easy read out of errors together with the indication of service parameters for checking basic functions.

- > Free combination of outdoor units to meet installation space or efficiency requirements
- > Available as heating only by irreversible field setting
- > Contains all standard VRV features






Published data with real-life indoor units

	RYYC	/RXYQ	8U*	101	J*	12U*	14U*	16U*		8U*	20U*
		HP	8	10)	12	14	16		18	20
Prated.c		kW	22.4	28	.0			45.0		50.4	52.0
Prated,h		kW	22.4			33.5	40.0	45.0		50.4	56.0
Max.	6°CWB	kW	25.0	31.	5	37.5	45.0	50.0		56.5	63.0
							1x FXFQ50AVEB	+ 4x FXFQ63A	VEB + 3x FXF	Q50AVEB + 2	
		%	302.4	267	7.6	247.8	250.7			-	233.7
		%	167.9	168	3.2	161.4	155.4	157.8		163.1	156.6
			7.6	6.	8	6.	3		6.0		5.9
				4.3		4.1		4.0		4.2	4.0
of connect	able indoor units						64 (1)				
Min.			100.0	125	5.0	150.0	175.0	200.0		225.0	250.0
Max.			260.0			390.0	455.0	520.0		85.0	650.0
Unit	HeightxWidthxDepth	mm		1.685x9	30x765			1.6	585x1.240x76	5	
	rieignextriatino epti.			,			RYYO: 31		,		RXYO: 314
	Nom		78.0			83.4					87.9
											89.8
	,		7 7 10								65.0
				57.0		01.0		05.0		02.0	05.0
		CIID						5			
		ka/TCO2Fa	5 0/12 3	6.0/	12.5	6 3/13 2			6 11	7/24 4	11.8/24.6
	OD		3.9/12.3		12.5	0.3/13.2		11.3/23	.0 11		
			10.1		2		12.7	20.6		13.5	<u> </u>
Total piping		m	15.1		.2		1,000	20.0			
	guency/Voltage	Hz/V					3N~/50/380-4	15			
		A	20	2:	5				40		50
em	RYYC	/RXYQ	22U*	24U*	26U*	28U*	30U*	32U*	34U*	36U*	38U*
Outdoor	unit module 1		10	8		12			16		8
Outdoor	unit module 2		12	16	14	16	18	16	18	20	10
Outdoor	unit module 3						-				20
		HP	22	24	26	28	30	32	34	36	38
Prated,c		kW	61.5	67.4	73.5	78.5	83.9	90.0	95.4	97.0	102.4
Prated,h		kW	61.5	67.4	73.5	78.5	83.9	90.0	95.4	101.0	106.4
Max.	6°CWB	kW	69.0	75.0	82.5	87.5	94.0	100.0	106.5	113.0	119.5
nbination			6x FXFQ50AVEB + 4x FXFQ63AVEB	4x FXFQ50AVEB + 4x FXFQ63AVEB + 2x FXFQ80AVEB		3 4x FXFQ63AVEB	+ 5x FXFQ63AVEB	8x FXFQ63AVEB + 4x FXFQ80AVEB	9x FXFQ63AVEB -		+ 10x FXFQ63AVEB
		%	274.5	269.9	264.2	257.8	256.8	251.7	253.3	250.8	272.4
		%	171.2	167.0	164.6	166.0	169.8	163.1	166.2	162.4	167.5
			6.9	6.8	6.7		6.5	6	.4	6.3	6.9
			4.4	4.3		4.2	4.3	4	.2	4.1	4.3
of connect	able indoor units						64 (1)				
			275.0	300.0	325.0	350.0	375.0	400.0	425.0	450.0	475.0
Min.							-				
Min. Nom.											
Nom.			715.0	780.0	845.0	910.0	975.0	1,040.0	1,105.0	1,170.0	1,235.0
	OD	mm	715.0 15		845.0	910.0	975.0	1,040.0 19.1	1,105.0	1,170.0	1,235.0
Nom. Max.	OD OD	mm mm			845.0		975.0	,	1,105.0		1,235.0
Nom. Max. Liquid Gas Total piping			15		845.0			,	1,105.0		
Nom. Max. Liquid Gas Total piping length	OD	mm	15		845.0		34.9	19.1	1,105.0		
	of connect Min. Max. Unit Unit Cooling Heating Cooling Heating Type/GWI Charge Liquid Gas Total piping length Phase/Fre Maximum outdoor o Outdoor o Outdoor o Prated,c Prated,h Max. mbination	Prated,c Prated,h Max. 6°CWB mbination of connectable indoor units Min. Max. Unit HeightxWidthxDepth Unit Cooling Nom. Heating Prated,h I Cooling Nom. Cooling Min.~Max. Heating Min.~Max. Type/GWP Charge Salquid OD Gas OD Total piping System Actual length Phase/Frequency/Voltage Maximum fuse amps (MFA) em RYYC Outdoor unit module 1 Outdoor unit module 3 Prated,c Prated,h Max. 6°CWB mbination	Prated,c kW Prated,h kW Max. 6°CWB kW mbination of connectable indoor units Min. Max. Unit HeightxWidthxDepth mm Unit kg Cooling Nom. dBA Heating Prated,h dBA Heating Prated,h dBA Hooling Min.~Max. °CDB Heating Min.~Max. °CBB Heating Min.~Max. °CBB Heating Min.~Max. nomm Gas OD mm Gas OD mm Total piping System Actual mength Phase/Frequency/Voltage Hz/V Maximum fuse amps (MFA) A em RYYQ/RXYQ Outdoor unit module 1 Outdoor unit module 2 Outdoor unit module 3 Prated,c kW Prated,h kW Max. 6°CWB kW mbination	HP	HP	HP	HP	HP	HP	HP	Prate









Connectable stylish indoor units

		20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Daikin Emura - Wall mounted unit	FTXJ-AW/AS/AB	•	•	•		•		
Stylish - Wall mounted unit	FTXA-AW/BS/BB/BT	•	•	•	•	•		
Perfera wall mounted	FTXM-R	•	•	•	•	•	•	•
Perfera floor standing NEW	FVXM-A9	•	•	•		•		

BPMKS box needed to connect RA indoors to VRV IV (RYYQ / RXYQ)

More details and final information can be found by scanning or clicking the QR codes.







Outdoor unit sys	tem	RYYQ	/RXYQ	40U*	42U*	44U*	46U*	48U*	50U*	52U*	54U*
System	Outdoor	unit module 1		1	0	12	14		16		18
	Outdoor	unit module 2		12			16			1	8
	Outdoor	unit module 3		18		1	6			18	
Capacity range			HP	40	42	44	46	48	50	52	54
Cooling capacity	Prated,c		kW	111.9	118.0	123.5	130.0	135.0	140.4	145.8	151.2
Heating capacity	Prated,h		kW	111.9	118.0	123.5	130.0	135.0	140.4	145.8	151.2
	Max.	6°CWB	kW	125.5	131.5	137.5	145.0	150.0	156.5	163.0	169.5
Recommended co	mbination			9x FXFQ50AVEB + 9x FXFQ63AVEB	12x FXFQ63AVEB + 4x FXFQ80AVEB	6x FXFQ50AVEB + 8x FXFQ63AVEB + 4x FXFQ80AVEB	1x FXFQ50AVEB + 13x FXFQ63AVEB + 4x FXFQ80AVEB	12x FXFQ63AVEB + 6x FXFQ80AVEB	3x FXFQ50AVEB + 13x FXFQ63AVEB + 4x FXFQ80AVEB	6x FXFQ50AVEB + 14x FXFQ63AVEB + 2x FXFQ80AVEB	9x FXFQ50AVEB + 15x FXFQ63AVEB
ης,ς			%	263.5	261.2	255.9	254.9	251.7	252.8	253.7	254.1
ηs,h			%	170.0	165.5	164.5	162.0	162.8	165.2	167.2	169.4
SEER				6.7	6.6	6.5			6.4		
SCOP				4.3	4	.2	4	l.1	4.2	4	.3
Maximum number	r of connec	table indoor units					64	(1)			
Indoor index	Min.			500.0	525.0	550.0	575.0	600.0	625.0	650.0	675.0
connection	Max.			1,300.0	1,365.0	1,430.0	1,495.0	1,560.0	1,625.0	1,690.0	1,755.0
Piping connection	s Liquid	OD	mm				19	9.1			
	Gas	OD	mm				4	1.3			
	Total piping length	System Actual	m				1,0	000			
Power supply	Phase/Fr	equency/Voltage	Hz/V				3N~/50	/380-415			
Current - 50Hz	Maximur	n fuse amps (MFA)	Α		10	00			12	25	

Outdoor unit mod	ule		RYMQ	8U*	10U*	12U*	14U*	16U*	18U*	20U*		
Dimensions	Unit	HeightxWidthxDepth	mm		1,685x930x765			1,685x1,	240x765			
Weight	Unit		kg		198		27	75	30	308		
Fan	External station	c Max.	Pa				78					
Sound power level	Cooling	Nom.	dBA	78.0	79.1	83.4	80.9	85.6	83.8	87.9		
	Heating	Prated,h	dBA	79.6	80.9	83.5	83.1	86.5	85.3	89.8		
Sound pressure level	Cooling	Nom.	dBA	57	7.0	61.0	60.0	63.0	62.0	65.0		
Operation range	Cooling	Min.~Max.	°CDB				-5.0 ~43.0					
	Heating	Min.~Max.	°CWB				-20.0 ~15.5					
Refrigerant	Type/GW	P					R-410A/2,087.5					
	Charge		kg/TCO2Eq	5.9/12.3	6.0/12.5	6.3/13.2	10.3/21.5	11.3/23.6	11.7/24.4	11.8/24.6		
Power supply	Phase/Fre	equency/Voltage	Hz/V						,			
Current - 50Hz	Maximun	n fuse amps (MFA)	Α	20	25	3	2	4	0	50		

⁽¹⁾ Actual number of connectable indoor units depends on the indoor unit type (VRV indoor, Hydrobox, RA indoor, etc.) and the connection ratio restriction for the system (50% <= CR <= 130%) | Contains fluorinated greenhouse gases

* Units sourced from different factories. Depending on your region your model name might be different.

** EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland

VRV IV S-series heat pump

The most compact VRV

Most compact unit on the market 823mm high & 94kg





(such as Daikin Emura)

Indoor units VRV type indoor units Residential type indoor units



Air curtainBiddle Air curtain for VRV (CYV)



Ventilation
Heat Reclaim ventilation
ALB/VAM/VKM AHU
connection kit



RXYSCQ4,5,6TV1



RXYSQ4,5,6TV9/TY9



RXYSQ8, 10, 12TY1



VRV IV standards:

Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

VRV configurator

Software for simplified commissioning, configuration and customisation

- > Refrigerant containment check
- > Night quiet mode
- > Low noise function
- > Connectable to stylish indoor units
- > Full inverter compressors
- > Refrigerant cooled PCB (not available on RXYSQ4,5,6,8 TY9/TY1)
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function

For detailed explanation of these functions refer to vrv iv technologies tab

Widest range of front blow units on the market



Compact: Easy for a two person crew to move and install.

Lowest height on the market

Ideal for roof installations

> The low height mini VRV can be hidden in many places where a twin fan unit cannot due to its height.

Ideal to install below a window on a Balcony

Daikin VRV IV S-series compact can be installed discretely on a balcony thanks to it's compact dimensions, offering you air conditioning while being almost unnoticeable.




Unnoticeable for parapet installation




Low height make the unit invisible from inside and unnoticeable from the outside

Space saving design

The VRV S-series is slimmer and more compact, resulting in significant savings in installation space.






Wide range of indoor units

Connect VRV units...



Connectable stylish indoor units


		15 CLASS	20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Round flow cassette	FCAG-B				•		•	•	•
Fully flat cassette	FFA-A9			•	•		•	•	
Slim concealed ceiling unit	FDXM-F9			•	•		•	•	
Concealed ceiling unit with inverter driven fan	FBA-A(9)			•	•		•	•	
Daikin Emura - Wall mounted unit	FTXJ-AW/AS/AB		•	•	•		•		
Stylish - Wall mounted unit	FTXA-AW/BS/BB/BT		•	•	•	•	•		
Perfera wall mounted	FTXM-R	•	•	•	•	•	•	•	•
Ceiling suspended unit	FHA-A(9)				•		•	•	•
Perfera floor standing	FVXM-A9		•	•	•		•		
Concealed floors tanding unit	FNA-A9	ĺ		•	•		•	•	



High COP values


A major feature of VRV IV S-series is its exceptional energy efficiency. The system achieves high COPs during both cooling and heating operation by the use of refined components and functions.


- Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°C, equivalent refrigerant piping: 5m, level difference: 0m.
- Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m



Flexible piping design

	VRV indoors connected	Stylish indoors connected
Total piping length	300m	140m
Longest length actual	120m (4-8HP)/ 150m (10-12HP)	
Minimum length between outdoor unit and first branch	-	5m
Minimum piping length between BP and indoor unit	-	2m
Maximum piping length between BP and indoor unit	-	15m
Longest length after first branch	40m	40m
Level difference between indoor and outdoor units	50m (40m ¹)	30m
Level difference between indoor units	15m	15m





VRV IV S-series

technologies

Super aero grille

The spiral shaped ribs are aligned with the direction of discharge flow in order to minimise turbulence and reduce noise.



Refrigerantcooled PCB

- Reliable cooling because it is not influenced by ambient air temperature
- Smaller switchbox for smoother air flow through the heat exchanger increasing heat exchange efficiency with 5%


Improved fan blades







Air streams are smoothed around V-cut and reduces air flow loss



Vane fixed to rotor Rotor

Compressor

Swing type > no oil separator Vane & rotor are unified resulting in:

- > Reduced noise level
- > Longer compressor life
- Higher efficiency thanks to the absence of internal refrigerant leakage between high and low pressure side


E-Pass heat exchanger

Optimising the heat exchanger's path layout prevents heat being transferred from the overheated gas section to the sub-cooled liquid section which is a more efficient way to use the heat exchanger.


I-demand function

Limit maximum power consumption.
The newly introduced current sensor minimizes the difference between the actual power consumption and the predefined power consumption.


Standard heat exchanger



e-Pass heat exchanger




Power consumption















VRV IV S-series compact heat pump

The most compact VRV

- > Compact & lightweight single fan design makes the unit almost
- > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air cutains
- > Wide range of indoor units: either connect VRV or stylish indoor units such as Daikin Emura, Perfera...
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature and full inverter compressors
- > Possibility to limit peak power consumption between 30 and 80%, for example during periods with high power demand
- > Night quiet mode reduces sound pressure with up to 8dBa
- > Contains all standard VRV features





Published data with real-life indoor units

Connectable stylish indoor units

		15 CLASS	20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Round flow cassette	FCAG-B				•		•	•	•
Fully flat cassette	FFA-A9			•	•		•	•	
Slim concealed ceiling unit	FDXM-F9			•	•		•	•	
Concealed ceiling unit with inverter driven fan	FBA-A(9)			•	•		•	•	
Daikin Emura - Wall mounted unit	FTXJ-AW/AS/AB		•	•	•		•		
Stylish - Wall mounted unit	FTXA-AW/BS/BB/BT		•	•	•	•	•		
Perfera wall mounted	FTXM-R	•	•	•	•	•	•	•	•
Ceiling suspended unit	FHA-A(9)				•		•	•	•
Perfera floor standing	FVXM-A9		•	•	•		•		
Concealed floors tanding unit	FNA-A9			•	•		•	•	

More details and final information can be found by scanning or clicking the QR codes.





Outdoor unit			RXYSCQ	4TV1	5TV1	6TV1			
Capacity range			HP	4	5	6			
Cooling capacity	Prated,c		kW	12.1	14.0	15.5			
Heating capacity	Prated,h		kW	12.1	14.0	15.5			
	Max.	6°CWB	kW	14.2	16.0	18.0			
Recommended cor	mbination			3x FXSQ25A2VEB + 1x FXSQ32A2VEB	4x FXSQ32A2VEB	2x FXSQ32A2VEB + 2x FXSQ40A2VEB			
ηs,c			%	322.8	303.4	281.3			
ηs,h			%	182.3	185.1	186.0			
SEER				8.1	7.7	7.1			
SCOP				4.6	4	.7			
Maximum number	of connec	table indoor units			64 (1)				
Indoor index	Min.			50.0	62.5	70.0			
connection	Max.			130.0	162.5	182.0			
Dimensions	Unit	HeightxWidthxDepth	mm		823x940x460				
Weight	Unit		kg	89					
Sound power level	Cooling	Nom.	dBA	68.0	69.0	70.0			
	Heating	Prated,h	dBA	69.0	70.0	71.0			
Sound pressure level	Cooling	Nom.	dBA	51.0	52.0	53.0			
Operation range	Cooling	Min.~Max.	°CDB		-5.0 ~46.0				
	Heating	Min.~Max.	°CWB		-20.0 ~15.5				
Refrigerant	Type/GW	Р			R-410A/2,087.5				
	Charge		kg/TCO2Eq		3.7/7.7				
Piping connections	s Liquid	OD	mm		9.52				
	Gas	OD	mm	15	.9	19.1			
	Total piping length	System Actual	m		300				
Power supply		equency/Voltage	Hz/V		1~/50/220-240				
Current - 50Hz	Maximun	n fuse amps (MFA)	A		32				





VRV IV S-series heat pump

Space saving solution without compromising on efficiency

- > By choosing this product with LOOP by Daikin you support the reuse of refrigerant
- > Space saving trunk design for flexible installation
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air cutains
- > Wide range of indoor units: either connect VRV or stylish indoor units such as Daikin Emura, Perfera...
- > Wide range of units (4 to 12HP) suitable for projects up to 200m² with space limitations
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature and full inverter compressors
- > Possibility to limit peak power consumption between 30 and 80%, for example during periods with high power demand
- > Contains all standard VRV features







For units made and sold in Europe*

Published data with real-life indoor units

Connectable stylish indoor units

		15 CLASS	20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Round flow cassette	FCAG-B				•		•	•	•
Fully flat cassette	FFA-A9			•	•		•	•	
Slim concealed ceiling unit	FDXM-F9			•	•		•	•	
Concealed ceiling unit with inverter driven fan	FBA-A(9)			•	•		•	•	
Daikin Emura - Wall mounted unit	FTXJ-AW/AS/AB		•	•	•		•		
Stylish - Wall mounted unit	FTXA-AW/BS/BB/BT		•	•	•	•	•		
Perfera wall mounted	FTXM-R	•	•	•	•	•	•	•	•
Ceiling suspended unit	FHA-A(9)				•		•	•	•
Perfera floor standing	FVXM-A9		•	•	•		•		
Concealed floors tanding unit	FNA-A9	Ì		•	•		•	•	

More details and final information can be found by scanning or clicking the QR codes.



RXYSO-TV9



RXYSO-TY9



Outdoor unit			RXYSQ	4TV9	5TV9	6TV9	4TY9	5TY9	6TY9	8TY1	10TY1	12TY1
Capacity range			HP	4	5	6	4	5	6	8	10	12
Cooling capacity	Prated,c		kW	12.1	14.0	15.5	12.1	14.0	15.5	22.4	28.0	33.5
Heating capacity	Prated,h		kW	12.1	14.0	15.5	12.1	14.0	15.5	22.4	28.0	33.5
	Max.	6°CWB	kW	14.2	16.0	18.0	14.2	16.0	18.0	25.0	31.5	37.5
Recommended cor	nbination			3x FXSQ25A2VEB + 1x FXSQ32A2VEB	4x FXSQ32A2VEB	2x FXSA32A2VEB + 2x FXSA40A2VEB	3x FXSQ25A2VEB + 1x FXSQ32A2VEB	4x FXSQ32A2VEB	2x FXSQ32A2VEB + 2x FXSQ40A2VEB	4x FXMQ50P7VEB	4x FXMQ63P7VEB	6x FXMQ50P7VEB
ηs,c			%	278.9	270.1	278.0	269.2	260.5	268.3	247.3	247.4	256.5
ηs,h			%	171.6	182.9	192.8	154.4	164.5	174.1	165.8	162.4	169.6
SEER				7.0	6.8	7.0	6.8	6.6	6.8	6	.3	6.5
SCOP				4.4	4.6	4.9	3.9	4.2	4.4	4.2	4.1	4.3
Maximum number	of connec	table indoor units						64 (1)				
Indoor index	Min.			50.0	62.5	70.0	50.0	62.5	70.0	100.0	125.0	150.0
connection	Max.			130.0	162.5	182.0	130.0	162.5	182.0	260.0	325.0	390.0
Dimensions	Unit	HeightxWidthxDepth	mm			1,345x9	900x320			1,430x940x320	1,615x9	40x460
Weight	Unit		kg	104 144 175						180		
Sound power level	Cooling	Nom.	dBA	68.0	69.0	70.0	68.0	69.0	70.0	73.0	74.0	76.0
	Heating	Prated,h	dBA	68.0	69.0	70.0	68.0	69.0	70.0	73.0	74.0	76.0
Sound pressure leve	l Cooling	Nom.	dBA	50.0	51	1.0	50.0	51	1.0	55	5.0	57.0
Operation range	Cooling	Min.~Max.	°CDB			-5.0	~46.0				-5.0 ~52.0	
	Heating	Min.~Max.	°CWB					-20.0 ~15.5				
Refrigerant	Type/GW	P					R	-410A/2,087	7.5			
	Charge		kg/TCO2Eq			3.6	/7.5			5.5/11.5	7.0/14.6	8.0/16.7
Piping connections	Liquid	OD	mm				9.	52				12.7
	Gas	OD	mm	15	5.9	19.1	15	5.9	19	9.1	22.2	25.4
	Total piping length	g System Actual	m					300				
Power supply	Phase/Fre	equency/Voltage	Hz/V	11	l~/50/220-2¢	40			3N~/50	/380-415		
Current - 50Hz	Maximun	n fuse amps (MFA)	Α		32			16		2	5	32

⁽I)Actual number of units depends on the indoor unit type (VRV DX indoor, RA DX indoor, etc.) and the connection ratio restriction for the system (being; $50\% \le CR \le 130\%$). | Contains fluorinated greenhouse gases * EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland

VRV IV i-series heat pump

for indoor installation







Ventilation Heat Reclaim ventilation (ALB/VAM/ VKM) AHU connection kit



VRV IV standards:

Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

VRV configurator

Software for simplified commissioning, configuration and customisation $% \left(1\right) =\left(1\right) \left(1\right) \left($

- > Night quiet mode
- > Full inverter compressors
- > Low noise function
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function

For detailed explanation of these functions refer to VRV iv technologies tab

Invisible

- > Consider a wider range of properties because outdoor installation is not a factor
- Open for business sooner because getting building permits is simplified
- > Seamless integration into the surroundings as only the grille is visible
- > No need for a roof installation or back alley installation







Quiet

- > Highly suited to densely populated areas such as city centres thanks to their low operating sound
- > Dedicated modes reduce sound further to comply with inner-city noise regulations




Heat exchanger sound not louder than a normal conversation



Compressor sound not louder than a refrigerator

Lightweight parts







Unique split outdoor unit for indoor installation

Compact and easy to hide, the compressor can be installed at floor level, in a back office, storage room, technical area or in a kitchen, while the heat exchanger can be installed in a false ceiling space. This means that the air conditioning system is completely invisible and does not take up expensive commercial floor space.


Unrivalled flexibility thanks to the fact that the outdoor unit is split into two parts



This means that the air conditioning system is completely invisible and does not take up expensive commercial floor space.



Max. total piping length: 140m (5HP) / 300m (8HP)



The problem solver

for many installation issues


Example 1 High flexibilty


The other way around: install the modules where if fits your customer, not where it is the best fit for the outdoor unit

If there is no flat roof or backgarden available for installation of the outdoor unit, VRV IV i-series offers the solution.

The suction and exhaust can be installed at the façade or at the rear of the building as the inverter fans allows ESP to be adjusted to the length of the ductwork.

The compressor module can be installed up to 30 m from the heat exchanger unit in a storage room,





Flexible installation thanks to inverter fans



Example 2


Shorter pipe runs to the indoor units reduces installation costs compared to rooftop or back alley installation


Back alley or rooftop needs very long piping lengths

- > Long installation time
- > Additional cost
- > Capacity loss

VRV IV i-series can be installed close to the indoor units

- > Quicker installation
- > Lower cost
- > No capacity loss





Example 3


No need for bulky and expensive sound countermeasures


To comply with city regulation countermeasures are needed for standard units

- Expensive sound cages might be needed to reduce sound (standard outdoor unit sound = 50~60 dBA)
- > Inside installation using expensive floor space

With VRV IV i-series you easily comply with city regulation without additional measures

- Operation sound 47 dBA for 5HP model (flexible to install in corridor, shop area, ...) or lower with attenuator
- No floor space is used as units can be installed in false ceiling, against the wall, ...





Patented V-shape heat exchanger

for best surface to volume ratio





Compressor unit with rotating switchbox

Flexible and easy to install








VRV IV heat pump for indoor installation

The invisible VRV

> Unique VRV heat pump for indoor installation



> Unrivalled flexibility because the unit is split up into two elements: the heat exchanger and the compressor



- > Highly suited to densely populated areas thanks to the low operation sound and seamless integration into surrounding architecture as only the grille is visible
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, VRV configurator and full inverter compressors
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains



- > Lightweight units (max. 105kg) can be installed by two people
- > Unique V-shape heat exchanger results in compact dimensions (h/e unit only 400mm high) allowing false ceiling installation, while ensuring top efficiency
- Super efficient centrifugal fans (over 50% efficiency increase compared to sirocco fan)
- > Small footprint compressor unit (760 x 554 mm) maximizing useable floor space
- > Connectable to all VRV control systems





For units made and sold in Europe*

Published data with real-life indoor units

More details and final information can be found by scanning or clicking the QR codes.








Outdoor unit sys	tem		SB.RK	XYQ	5T8	8T
System	Heat exchanger unit				RDXYQ5T8	RDXYQ8T
	Compressor unit				RKXYQ5T8	RKXYQ8T
Capacity range				HP	5	8
Cooling capacity	Prated,c			kW	14.0	22.4
Heating capacity	Prated,h			kW	10.4	12.9
	Max.	6°CWB		kW	16.0	25.0
Recommended co	mbination				4x FXSQ32A2VEB	4x FXMQ50P7VEB
ηs,c				%	200.1	191.1
ηs,h				%	149.3	140.9
SEER					5.1	4.9
SCOP					3.8	3.6
Maximum number	r of connectable indoo	r units			10 (1)	17 (1)
Indoor index	Min.				62.5	100.0
connection	Max.				162.5	260.0
Piping connection	s Between Compressor module (CM)	Liquid	OD	mm	12	.7
	and heat exchanger module (HM)	Gas	OD	mm	19.1	22.2
	Between Compressor module (CM)	Liquid	OD	mm	9.	52
	and indoor units (IU)	Gas	OD	mm	15.9	19.1
	Total piping length	System	Actual	m	140	300

				Heat exchanger	module - RDXYQ	Compressor m	odule - RKXYQ
Outdoor unit mod	lule			5T8	8T	5T8	8T
Dimensions	Unit	HeightxWidthxDepth	mm	397x1,45	56x1,044	701x600x554	701x760x554
Weight	Unit		kg	95	103	79	105
Sound power level	Cooling	Nom.	dBA	77.0	81.0	60.0	64.0
Sound pressure level	l Cooling	Nom.	dBA	47.0	54.0	47.0	48.0
Refrigerant	Type/GWP			R-41	0A/-	R-410A	/2,087.5
	Charge		kg/TCO2Eq	-	/-	2.00/4.20	4.00/8.35
Power supply	Phase/Frequency/Vo	ltage	Hz/V	1N~/50/	/220-240	3N~/50/	380-415
Current - 50Hz	Maximum fuse amps	(MFA)	Α	1	0	16	20

VRV IV C+ series

Where heating is priority without compromising on efficiency





VRV IV standards:


Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

VRV configurator

Software for simplified commissioning, configuration and customisation

- > 7 segment display
- > Automatic refrigerant charge
- > Refrigerant containment check
- > Night quiet mode
- > Low noise function
- > Connectable to stylish indoor units (Only for single modules)
- > Full inverter compressors
- > Gas cooled PCB
- > 4 side heat exchanger
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function



RXYLQ-T


Where heating is priority without compromising on efficiency



High heating capacity at low ambient temperatures

> Stable heating capacity available down to -15°C WB!







High partial load efficiency

- > New vapour injection scroll compressor optimised for low load
 - UNIQUE back-pressure control: Pressure port increases pressure below the scroll in low load operation, preventing refrigerant leak and increasing efficiency
 - UNIQUE Injection structure with check valve: Prevents volume backflow during low load operation typically occuring with standard vapour injection compressors
- > Variable Refrigerant Temperature adjusts refrigerant temperature to match the load





High reliability down to -25°C WB

> Hot gas bypass prevents ice buildup at the bottom of the heat exchanger





High seasonal efficiency

> Measured with indoor units for real applications!

> ALL information for indoor units used available on our eco-design website: Already fully compliant https://energylabel.daikin.eu/eu/en_US/lot21.html







The known VRV IV standards

- ☑ Variable Refrigerant Temperature
- ✓ VRV configurator

Total solution



Daikin Emura Wall mounted unit



Fully flat cassette



Biddle air curtain



intelligent Manager



Air handling unit for ventilation



Low temperature hydrobox

VRV IV heat pump, optimised for heating

Where heating is priority without compromising on efficiency

- > By choosing this product with LOOP by Daikin you support the reuse of refrigerant
- Specifically developed for heating operation in low ambient conditions, making it suitable for single source heating
- > Stable heating capacity down to -15°C, thanks to vapour injection compressor
- > Extended operation range down to -25°C in heating
- > High reliability in severe conditions, thanks to hot gas bypass circuit in the heat exchanger
- > 15% increased heating capacity at high relative humidity (2°CDB/1°CWB and RH=83%) vs previous model
- Shorter defrost and heat up time, compared to standard VRV heat pump
- Very economical solution as a smaller outdoor unit model can be used compared to the standard series
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air cutains

- Wide range of indoor units: possibility to combine VRV with stylish indoor units (Daikin Emura, Perfera)
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB, new DC fan motor, ...
- > Free combination of outdoor units to meet installation space or efficiency requirements
- > Wide piping flexibility: 30m indoor height difference, maximum piping length: 190m, total piping length: 500m
- Less installation time and smaller footprint compared to previous model thanks to removal of function unit





For units made and sold in Europe*


Published data with real-life indoor units

Outdoor unit			RXYLQ	10T		12T		14T	
Capacity range			HP	10		12		14	
Cooling capacity	Prated,c		kW	28.0		33.5		40.0	
Heating capacity	Prated,h		kW	31.5		37.5		45.0	
	Max.	6°CWB	kW	31.5		37.5		45.0	
Recommended cor	mbination			4x FXMQ63P7	VEB	6x FXMQ50P7VE	1x FXMQ50P 5x FXMQ63		
ηs,c			%	251.4		274.4		270.1	
ηs,h			%	144.3		137.6		137.1	
SEER				6.4		6.9		6.8	
SCOP				3.7			3.5		
Maximum number	of connect	able indoor units				64 (1)			
Indoor index	Min.			175		210		245	
connection	Nom.			250		300		350	
	Max.			325		390		455	
Dimensions	Unit	HeightxWidthxDepth	mm			1,685x1,240x765			
Weight	Unit		kg						
Sound power level	Cooling	Nom.	dBA	A 77.0 81.0					
Sound pressure leve	l Cooling	Nom.	dBA	1111					
Operation range	Cooling	Min.~Max.	°CDB	-5 ~43					
	Heating	Min.~Max.	°CWB			-25 ~16			
Refrigerant						R-410A/2,087.5			
	Charge		kg/TCO2Eq			11.8/24.6			
Piping connections	s Liquid	OD	mm	9.52			12.7		
	Gas	OD	mm	22.2			28.6		
	Total piping length	System Actual	m			500			
	Phase/Fre	quency/Voltage	Hz/V			3N~/50/380-415			
Power supply									
Power supply Current - 50Hz		fuse amps (MFA)	A	25			32		

Outdoor unit sys	tem	RXYLQ	16T	18T	20T	22T 24T		26T	28T
System	Outdoor unit module 1		RXMLQ8T		RXYLQ10T		RXYI	_Q12T	RXYLQ14T
	Outdoor unit module 2		RXM	LQ8T	RXYLQ10T	RXYI	_Q12T	RXYI	.Q14T
Capacity range		HP	16	18	20	22	24	26	28
Cooling capacity	Prated,c	kW	44.8	50.4	56.0	61.5	67.0	73.5	80.0
Heating capacity	Prated,h	kW	50.0	56.5	63.0	69.0	75.0	82.5	90.0
	Max. 6°CWB	kW	50.0	56.5	63.0	69.0	75.0	82.5	90.0
Recommended co	mbination		4x FXMQ63P7VEB + 2x FXMQ80P7VEB	3x FXMQ50P7VEB + 5x FXMQ63P7VEB	2x FXMQ50P7VEB + 6x FXMQ63P7VEB	6x FXMQ50P7VEB + 4x FXMQ63P7VEB	4x FXMQ50P7VEB + 4x FXMQ63P7VEB + 2x FXMQ80P7VEB	7x FXMQ50P7VEB + 5x FXMQ63P7VEB	6x FXMQ50P7VEB + 4x FXMQ63P7VEB + 2x FXMQ80P7VEB
ηs,c		%	261.8	255.7	251.4	263.0	274.4	270.8	270.1
ηs,h		%	138.0	140.5	144.3	140.3	137.6	13	7.1
SEER			6.6	6.5	6.4	6.6	6.9	6	.8
SCOP			3.5	3.6	3.7	3.6		3.5	
Maximum numbe	r of connectable indoor units		64 (1)						
Indoor index	Min.		280	315	350	385	420	455	490
connection	Nom.		400	450	500	550	600	650	700
	Max.		520	585	650	715	780	845	910
Piping connection	s Liquid OD	mm	12.7		15	i.9		19	9.1
	Gas OD	mm		28	3.6			34.9	
	Total piping System Actual length	m				500			
Current - 50Hz	Maximum fuse amps (MFA)	Α	40	45	50		6	0	









Connectable stylish indoor units

		20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Daikin Emura - Wall mounted unit	FTXJ-AW/AS/AB	•	•	•		•		
Stylish - Wall mounted unit	FTXA-AW/BS/BB/BT	•	•	•	•	•		
Perfera wall mounted	FTXM-R	•	•	•	•	•	•	•
Perfera floor standing NEW	FVXM-A9	•	•	•		•		

BPMKS box needed to connect RA indoors to VRV IV (RYYQ / RXYQ)

More details and final information can be found by scanning or clicking the QR codes.





Outdoor unit syste			RXYLQ	30T	32T	34T	36T	38T	40T	42T		
System	Outdoor	unit module 1			RXYLQ10T			RXYLQ12T		RXYLQ14T		
	Outdoor	unit module 2			_Q10T		RXYLQ12T			.Q14T		
	Outdoor	unit module 3		RXYLQ10T		RXYLQ12T			RXYLQ14T			
Capacity range			HP	30	32	34	36	38	40	42		
Cooling capacity	Prated,c		kW	84.0	89.5	95.0	100.5	107.0	113.5	120.0		
Heating capacity	Prated,h		kW	94.5	101	107	113	120	128	135		
	Max.	6°CWB	kW	94.5	100.5	106.5	112.5	120.0	127.5	135.0		
Recommended con	nbination			5x FXMQ63P7VEB		3x FXMQ50P7VEB + 9x FXMQ63P7VEB + 2x FXMQ80P7VEB		10x FXMQ63P7VEB	9x FXMQ63P7VEB	12x FXMQ63P7VEB + 4x FXMQ80P7VEE		
ηs,c			%	251.4	259.1	266.8	274.4	271.6	270.3	270.1		
ηs,h			%	144.3	141.6	139.2	137.6		137.1			
SEER				6.4	6.6	6.7	6	.9	6.8			
SCOP				3.7	3	.6		3	.5			
Maximum number	of connect	table indoor units					64 (1)					
Indoor index	Min.			525	560	595	630	665	700	735		
connection	Nom.			750	800	850	900	950	1,000	1,050		
	Max.			975	1,040	1,105	1,170	1,235	1,300	1,365		
Piping connections	Liquid	OD	mm				19.1					
	Gas	OD	mm		34.9			4	1.3			
	Total piping length	System Actual	m				500					
Current - 50Hz	Maximum	n fuse amps (MFA)	Α		8	30			90			
Outdoor unit mod	lule		RXMLQ	.Q 8T								
Dimensions	Unit	HeightxWidthxDepth	mm	1								
Weight	Unit		kg	· · ·								
Fan	External static pressure	Max.	Pa				78					
Sound power level	Cooling	Nom.	dBA				75.0					
Sound pressure level	Cooling	Nom.	dBA				55.0					
Operation range	Cooling	Min.~Max.	°CDB				-5 ~43					
	Heating	Min.~Max.	°CWB				-25 ~16					
Refrigerant	Type/GWI	P					R-410A/2,087.5					
-	Charge		kg/TCO2Eq				11.8/24.6					
D	Phace/Erc	equency/Voltage	Hz/V				3N~/50/380-415	5				
Power supply	111036/116	.queriey, voitage										

(1)Actual number of connectable indoor units depends on the indoor unit type (VRV indoor, Hydrobox, RA indoor, etc.) and the connection ratio restriction for the system (70% <= CR <= 130%) | Contains fluorinated greenhouse gases


* EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland



Replacement VRV

Quick & quality replacement for R-22 and R-407C systems







Air curtainBiddle Air curtain for VRV (CYV)



Ventilation Heat Reclaim ventilation (VAM/VKM) AHU connection kit



__VRV III





Heat pump

Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

VRV configurator

Software for simplified commissioning, configuration and customisation

For more information on these features refer to the VRV IV technologies tab

- > 7 segment display
- > Automatic refrigerant charge
- > Night quiet mode
- > Low noise function
- > Full inverter compressors
- > Gas cooled PCB
- > 4 side heat exchanger
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function

VRVIII-O

Heat pump & Heat recovery

- > Automatic refrigerant charge
- > Night quiet mode
- > Low noise function
- > Full inverter compressors
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > DC fan motor
- > E-pass heat exchanger
- > I demand function
- > Manual demand function

Replacement technology



The quick and quality way of upgrading R-22, R-407C and R-410A systems

These benefits will convince your customer:

Drastically improve your efficiency, comfort and reliability

No disturbance of daily operations

- Reuse of existing pipework results in fast installation
- > Plan phases to avoid loss of business
- > Replace any VRF system

Lower installation costs


- > Shorter installation time
- > Use of existing piping and wiring
- > Reuse of materials

Lower investment and reduced running costs

- > CAPEX: Lower initial investment
- > OPEX: Lower energy consumption and maintenance costs
- > Keep your business running seamlessly

Higher property value

- > Higher property value
- > Improved facilities
 - Subsidies
 - Certifications (BREEAM, LEED and WELL)




The Daikin upgrade solution:

Replace indoor units (optional)

 Depending on model type and condition the indoor units can be kept.

Replace outdoor units





VRV-Q benefits to increase your profit:

Optimise your business

Less installation time

Tackle more projects in less time thanks to faster installation. It is more profitable than replacing the full system with new piping.

Lower installation costs

Reducing installation costs enables you to offer customers the most cost-effective solution and improve your competitive edge.

Replace non-Daikin systems

NON DAIKIN DAIKIN

It is a trouble-free replacement solution for Daikin systems and for systems made by other manufacturers.

Easy as one-two-three

A simple solution for replacement technology enables you to handle more projects for more customers in less time and offer them the best price! Everybody wins.







	VRV-Q , keeping indoor units	VRV-Q , replacing indoor units	Completely new installation with standard VRV
Remove outdoor unit	21 %	21 %	21 %
Install new outdoor unit	14 %	14 %	14 %
Clean cooling circuit and leak test	14 %	14 %	14 %
Remove indoor units	-	8 %	8 %
Remove refrigerant pipes and other tasks	-	-	8 %
Install new refrigerant pipes	-	-	14 %
Install new indoor units and other tasks	_	21 %	21 %
Total installation time	49 %	78 %	100 %

Technology insight - Pipe cleaning and automatic refrigerant charging

Pipe cleaning and automatic refrigerant charging ensures a trouble-free operation.

Thanks to the pipe cleaning, possible contamination in the pipes is collected ensuring a trouble-free operation as with a completely new system.

The automatic charging ensures the correct amount of refrigerant is charged, so knowledge of the exact piping layout is not needed!

One touch convenience:

- Measure and charge refrigerant
- > Test operation







Replacement VRV, heat recovery

Quick & quality replacement for R-22 and R-407C systems

- Cost effective and fast replacement as only the outdoor and indoor unit needs to be replaced, meaning almost no work has to be carried out inside the building
- Efficiency gains of more than 40% can be realized, thanks to technological developments in heat pump technology and the more efficient R-410A refrigerant
- Less intrusive and time consuming installation compared to installing a new system, as the refrigerant piping can be maintained
- > Unique automatic refrigerant charge eliminates the need to calculate refrigerant volume and allows safe replacement of competitor replacement
- > Automatic cleaning of refrigerant piping ensures a clean piping network, even when a compressor breakdown has occurred
- > Possibility to add indoor units and increase capacity without changing the refrigerant piping
- > Possibility to spread the various stages of replacement thanks to the modular design of the VRV system
- Accurate temperature control, fresh air provision, air handling units and Biddle air curtains all integrated in a single system requiring only one single point of contact (RXYQQ-U only)
- > Incorporates VRV IV standards & technologies: Variable Refrigerant
- > Temperature and full inverter compressors (RXYQQ-U only)
- > Free combination of outdoor units to meet installation space or efficiency requirements (RXYQQ-U only)





Published data with real-life indoor units



More details and final information can be found by scanning or clicking the QR codes.

Outdoor unit syst	em		RQCEQ	280P3	460P3	500P3	540P3	712P3	744P3	816P3		
System	Outdoor	unit module 1			RQEQ140P3		RQEQ180P3	RQEC)140P3	RQEQ180P3		
•	Outdoor	unit module 2		RQEC)140P3		RQEC	(180P3		RQEQ212P3		
	Outdoor	unit module 3		-		RQEC	180P3		RQEC	212P3		
	Outdoor	unit module 4				-			RQEQ212P3			
Capacity range			HP	10	16	18	20	24	26	28		
Cooling capacity	Prated,c		kW	28.0	46.0	50.0	54.0	70.0	72.0	78.0		
Heating capacity	Prated,h		kW	32.0	52.0	56.0	60.0	78.4	80.8	87.2		
Recommended cor	mbination			4x FXMQ63P7VEB	4x FXMQ63P7VEB + 2x FXMQ80P7VEB		12x FXSQ40A2VEB	4x FXSQ32A2VEB + 9x FXSQ40A2VEB + 3x FXSQ50A2VEB	4x FXSQ32A2VEB + 6x FXSQ40A2VEB + 6x FXSQ50A2VEB			
ηs,c			%	200	191	201	198	19	94	204		
ηs,h			%	159	161	150	148	153	15	55		
Maximum number	of connec	table indoor units		21	34	39	43	52	56	60		
Indoor index	Min.			140	230	250	270	356	372	408		
connection	Nom.			280	50	00	540	712	744	816		
	Max.			364	598	650	702	926	967.0	1,061		
Piping connections	s Liquid	OD	mm	9.52	12.7		15.9		19	9.1		
	Gas	OD	mm	22.2		28	3.6		34	1.9		
	Total piping length	g System Actual	m				300					
Power supply	Phase/Fre	equency/Voltage	Hz/V				3~/50/400					
Current - 50Hz	Maximur	n fuse amps (MFA)	Α	30	50	6	0	8	30	90		
Outdoor unit mod	dule		ROEO-P3		140P3 180P3				212P3			
Dimensions	Unit	HeightxWidthxDepth	mm				1,680x635x765			-		
Weight	Unit	· · · · · · · · · · · · · · · · · · ·	kg			175	•		179			
Fan	Air flow rate	Cooling Nom.	m³/min		95			110				
	Туре						Propeller fan					
Sound power level	Cooling	Nom.	dBA		79		83		87			
	Heating	According to ENER LOT21	dBA		79			84				
Sound pressure leve	l Cooling	Nom.	dBA				-					
Operation range	Cooling	Min.~Max.	°CDB				-5 ~43					
	Heating	Min.~Max.	°CWB				-20 ~15.5					
Refrigerant	Type/GW	'P					R-410A/2,087.5					
	Charge		kg/TCO2Eq	1	0.3/21.5		10.6/22.1		11.2/23	.4		
Power supply	Phase/Fre	equency/Voltage	Hz/V				3~/50/380-415					
				1								

20

Α

Maximum fuse amps (MFA)

Current - 50Hz





Replacement VRV, heat pump



For units made and sold in Europe* RXYQQ8-12U

More details and final information can be found by scanning or clicking the QR codes.







Outdoor unit		RXYQQ/	RQYQ-P	140P		8U	10U	12U		14U	16U	18	U	20U
Capacity range			HP	5		8	10	12		14	16	18	3	20
Cooling capacity	Prated,c		kW	14.0	2	22.4	28.0	33.5		40.0	45.0	50	.4	52.0
Heating capacity	Prated,h		kW	16.0	2	22.4	28.0	33.5		40.0	45.0	50	.4	56.0
	Max.	6°CWB	kW	-	2	25.0	31.5	37.5		45.0	50.0	56	.5	63.0
Recommended cor	mbination			4x FXSQ32A2	VEB 4x FXF	Q50AVEB	4x FXFQ63AVEB	6x FXFQ50			4x FXFQ63AVEE 2x FXFQ80AVE			FXFQ50AVEB + x FXFQ63AVEB
ηs,c			%	194	3	02.4	267.6	247.8		250.7	236.5	238		233.7
ηs,h			%	137	1	67.9	168.2	161.4		155.4	157.8	163	3.1	156.6
SEER				-		7.6	6.8		6.3			6.0		5.9
SCOP				-		4.3	3	4.1		4.	0	4.	2	4.0
Maximum number	of connec	table indoor units		10						64 (1)				
Indoor index	Min.			62.5	10	0.00	125.0	150.0		175.0	200.0	225	5.0	250.0
connection	Nom.			125						-				
	Max.			162.5	2	60.0	325.0	390.0)	455.0	520.0	585	5.0	650.0
Dimensions	Unit	HeightxWidthxDepth	mm	1,680x635x	765	1	,685x930x76	5			1,685	d,240x765		
Weight	Unit		kg	175			198			27	75		308	
Fan	Air flow rate	Cooling Nom.	m³/min	95						-				
Sound power level	Cooling	Nom.	dBA	79	7	78.0	79.1	83.4		80.9	85.6	83	.8	87.9
	Heating	Prated, h	dBA	79	7	79.6	80.9	83.5		83.1	86.5	85	.3	89.8
Sound pressure leve	l Cooling	Nom.	dBA	-		57.0	0	61.0		60.0	63.0	62	.0	65.0
Operation range	Cooling	Min.~Max.	°CDB	-5~43					-5	0~43.0				
	Heating	Min.~Max.	°CWB	-20~15.	5				-20).0~15.5				
Refrigerant	Type/GW	Р						R-	410A/2,08	7.5				
	Charge		kg/TCO2Eq	11.1/23.2	2 5.9	9/12.3	6.0/12.5	6.3/13	.2 10	.3/21.5	11.3/23.6	11.7/2	24.4	11.8/24.6
Piping connections	s Liquid	OD	mm		9	9.52				12.7			15.9	
	Gas	OD	mm	15.9		19.1	22.2				28.6			
	Total piping length	System Actual	m	300						300				
Power supply	Phase/Fre	equency/Voltage	Hz/V	3~/50/380	-415				3N~/	50/380-415	i			
Current - 50Hz	Maximur	n fuse amps (MFA)	Α	15		20 25 32				40		50		
Outdoor unit syst	em		RXYQQ	22U	24U	26U	28U	30U	32U	34U	36U	38U	40U	42U
System		unit module 1	III. IQQ	RXYQQ10U			RXYQQ12U	500	J_0	RXYQQ16I		RXYQQ8U		'QQ10U
System		unit module 2					U RXYQQ16U	RXYOO18U	RXYOO16U					
		unit module 3		10/1/20/120	IIIIQQIOO	intiggii	o narqqioo	IIXTQQIOO	TIXTQQIOO	intiggioc				J RXYQQ16U
Capacity range	Outdoor	anic module 5	HP	22	24	26	28	30	32	34	36	38	40	42
Cooling capacity	Prated,c		kW	61.5	67.4	73.5	78.5	83.9	90.0	95.4	97.0	111.9	118.0	118.0
Heating capacity	Prated,h		kW	61.5	67.4	73.5	78.5	83.9	90.0	95.4	101.0	111.9	118.0	62.4
ricuting capacity	Max.	6°CWB	kW	69.0	75.0	82.5	87.5	94.0	100.0	106.5	113.0	125.5	131.5	131.5
Recommended cor				6x FXFQ50AVEB + 4x FXFQ63AVEB		7x FXFQ50AVEB	B + 6x FXFQ50AVEB+			3x FXFQ50AVEB -	+ 2x FXFQ50AVEB + + 10x FXFQ63AVEB +	6x FXFQ50AVEB + 10x FXFQ63AVEB		+ 12x FXFQ63AVEB -
ηs,c			%	274.5	269.9	264.2	257.8	256.8	251.7	253.3	250.8	272.4	263.5	261.2
ηs,h			%	171.2	167.0	164.6	166.0	169.8	163.1	166.2	162.4	167.5	170.0	165.5
				6.9	6.8	6.7	6.	5	6	.4	6.3	6.9	6.7	6.6
SEER				4.4	4.3		4.2	4.3	4	.2	4.1	4.3	4.3	4.2
				4.4					64 (1)					
SEER	of connec	table indoor units		4.4					04 (1)					
SEER SCOP	of connec	table indoor units		275.0	300.0	325.0	350.0	375.0	400.0	425.0	450.0	475.0	500.0	525.0
SEER SCOP Maximum number		table indoor units				325.0 845.0	350.0 910.0	375.0 975.0		425.0 1,105.0	450.0 1,170.0	475.0 1,235.0	500.0 1,300.0	525.0 1,365.0
SEER SCOP Maximum number Indoor index	Min. Max.	table indoor units	mm	275.0 715.0	300.0				400.0					
SEER SCOP Maximum number Indoor index connection	Min. Max.		mm	275.0 715.0	300.0 780.0			975.0	400.0	1,105.0		1,235.0		
SEER SCOP Maximum number Indoor index connection	Min. Max. s Liquid Gas	OD		275.0 715.0	300.0 780.0		910.0	975.0	400.0	1,105.0		1,235.0	1,300.0	
SEER SCOP Maximum number Indoor index connection	Min. Max. s Liquid Gas Total piping length	OD OD	mm	275.0 715.0	300.0 780.0		910.0	975.0 .9	400.0 1,040.0	1,105.0 19.1		1,235.0	1,300.0	

(I)Actual number of connectable indoor units depends on the indoor unit type (VRV indoor, Hydrobox, RA indoor, etc.) and the connection ratio restriction for the system (50% <= CR <= 130%) | Contains fluorinated greenhouse gases

* EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland

Water cooled VRV IV W+ series

Ideal for high rise buildings, using water as heat source

Unified range for heat pump & heat recovery and standard & geothermal series





VRV IV standards:

Variable refrigerant temperature

Customize your VRV for best seasonal efficiency & comfort

VRV configurator

Software for simplified commissioning, configuration and customisation

For more information on these features refer to the VRV IV technologies tab

- > 7 segment display
- > Full inverter compressors
- > Connectable to stylish indoor units
- > Connectable to LT hydrobox
- > Connectable to HT hydrobox
- > Reluctance brushless DC compressor
- > Sine wave DC inverter
- > Manual demand function





Welcome a new range of features

More flexibility

- > Mixed connection of HT hydroboxes and VRV indoor units
- > Connects to stylish indoor units such as Daikin Emura, Nexura, ... (no mixed connection with other indoors possible)
- > Extension of the range: 8-10-12-14HP, combinable up to 42HP while keeping the most compact casing in the market
- > Extended piping length up 165m (actual)
- > Extended indoor unit height difference to 30m

Most compact casing in the market!







8 to 14 HP

16 to 28 HP

30 to 42 HP

More capacity

> Up to 72% increased capacity (!) per model thanks to new compressor and larger heat exchanger

Easier commissioning & customisation

- > 7 segment display
- > 2 analogue input signals allowing external control of
- ON-OFF (e.g. compressor)
- Operation mode (cooling / heating)
- Limit of capacity
- Error signal

Unique zero heat dissipation principle



- No need for ventilation or cooing in the technical room
- Control heat dissipation to achive maximum efficiency: set target technical room temperature and unit regulates actual heat dissipation

Total solution



Daikin Emura wall mounted unit



Biddle air curtain



FTXA-AW/BS/BB/BT Stylish



Air handling unit for ventilation



Fully flat cassette



Low temperature hydrobox



Intelligent Manager



High temperature hydrobox

With all existing standard functions





Indoor installation makes unit invisible from the outside

- Seamless integration in the surrounding architecture as you cannot see the unit
- Highly suited for sound sensitive areas as there is no external operation sound
- Very flexible indoor installation as there is no heat dissipation
- Superior efficiency, even in the most extreme outside conditions, especially in geothermal operation

Unified range for heat pump & heat recovery and standard & geothermal series

Variable water flow control

- > The variable water flow control option reduces excessive energy use by the circulation pump.
- > By controlling a variable water valve, the water flow is reduced when possible, saving energy.
- > Via 0~10 volt

Lower refrigerant concentration levels

Water-cooled VRV systems typically have less refrigerant per system making it ideal to comply with the EN378 legislation limiting the amount of refrigerant in hospitals and hotels.

The refrigerant levels remain limited thanks to:

- > limited distance between outdoor and indoor unit
- modularity: enabling small systems per floor instead of one big system. Thanks to the water circuit heat recovery is still possible in the entire building

recovery is still possible in the entire building

Maximum design flexibility and installation speed

- > Quickly and flexibly design your system with a unique range of single and multi BS boxes.
- > A wide variety of compact and lightweight multi BS boxes greatly reduces installation time.
- > Free combination of single and multi BS boxes

Cooling tower (Closed type), boiler Flow Valve Input Signal Inverter Pump

Single port



BS1Q 10,16,25A

Multi port: 4 - 6 - 8 - 10 - 12 - 16




BS 4 Q14 A




BS 10, 12 Q14 A


BS 16 Q14 A

2-stage heat recovery



Stacked configuration







A great and well-known example of a Daikin Total Solution leading to high energy-efficient HVAC consumption

- > A combination of VRV, Sky Air and Applied systems ensuring all offices and common areas are fully air conditioned.
- > Water-cooled VRV as the main contributor to total HVAC energy efficiency due to its two-stage heat recovery system.
- > Flexibility: individual thermal control and comfort with VRV on each floor and space.
- > Problem-free connection between Daikin units and the LonWorks BMS system ensures the building's total energy consumption is properly monitored and controlled.

Location

48 Lancu de Hunedoara Boulevard Bucharest Romania

Building details

Built-up area: 24,728 m²
Total usable area: 20,020 m²
Floors: 4 basements, 15 floors, technical floor
Building height: 72 m
Office space per level: approx. 1,000 m²

Daikin systems installed


- > 67 x VRV water-cooled units
- > 2 x VRV outdoor heat pump units
- > 289 VRV indoor units (265 ducts, 24 x cassettes)
- > 5 x Sky Air with Roundflow Cassettes
- > 4 x air-cooled water chillers
- > 11 x DMS504B51 (LonWorks gateway)

Awards

- > Green Building of the Year 2012 (ROGBC)
- Environmental Social & Sustainability award (ESSA)

Innovations

for maximum flexibility and ease of installation



step 1

Easy access to components

Easy front plate removal

Rotating switchbox

step 2

Zero heat dissipation principle


No need for ventilation or cooling of the technical room



> Enhancing installation flexibility and reliability of parts












- > VRV configurator
- >7 segment display

Application

example

Closed evaporative cooling tower used for cooling, Chiller used for heating



Benefits of this setup

- Chiller is only used when cooling tower capacity is not enough and/or when cooling and heating load of VRV is unbalanced → very energy efficient installation
- > In case the chiller is operating, a renewable heat source (air) is used, contributing to BREEAM score.
- > It is possible to downsize the cooling tower, making the installation more compact


When to use?


- > When there is anyway a chiller used for other purposes in the building
- > When space for outdoor installation is limited
- > Efficiency / green building certification schemes oriented projects

Application

example

Dry cooler used for cooling, boiler used for heating





Benefits of this setup

- Simple, cost efficient. Good option to use VRV technology in high-rise building
- > Does not make any special demand to the building/project/installation location
- > Provides high efficiency as for hotel application it is usual to have simultaneous cooling and heating load.
- > Heat recovery process in the water loop often allows the water temperature to stay within acceptable range even without using drycooler and boiler.


When to use?

 > For high-rise buildings or other places where VRV Water Cooled is preferable because of installation conditions

Application

example

Geothermal operation



Benefits of this setup

- > Very energy efficient
- Ground loop can be in service for a very long time, so future equipment upgrades/replacements are easy
- Vertical boreholes provide more stable water temperature (= Constant high efficiency) and do not occupy a lot of ground

When to use?

- > When the soil is suitable for geothermal loops and there is availability of geothermal installation expertise locally
- For the projects with high requirements to energy efficiency, green building certification oriented

Ground loop

Examples

Open system

Uses water from a well or surface water (river, lake). The water is pumped back to a second well or surface water




Conditions:

- > At 20 m depth water has a constant temperature of 10°C through the year
- > Surface water cools down to 5°C during winter
- Can be the most economical type of geothermal system
- Constant ground water temperature has positive impact on heat pump efficiency
- Risk to damage system components because of water quality → a secondary loop might be required to protect the heat exchanger
- Water should be tested for acidity, mineral content, organic content and corosiveness:
- In many areas open systems are prohibited due to environmental concerns

Closed system

Uses water pipes that are buried in the ground and exchange heat with the ground



Vertical system conditions

- > Typical depth: 30-140 m. Below 15 m, the temperature of the ground is constant around 10°C
- ✓ Less surface space required
- √ Very constant ground temperature
- × Expensive due to drilling cost

For smaller applications also horizontal loops can be used



Horizontal loop system


- > Typical trench depth: 1 2 m. The ground temperature varies, but always above 5°C (Exception: in cold areas)
- Slinky loop: the plastic geothermal loop pipe is coiled in overlapped circles and flattened (Installed where there is not enough space for closed horizontal)
- ✓ Installation is easier and less expensive than vertical closed loops.
- Mainly for small applications as the property land should be large enough
- You cannot plant trees or build constructions over the land containing the loop.
- **x** Glycol is needed to prevent freezing of the water.

VRV IV water cooled+ series

Ideal for high rise buildings, using water as heat source

- > Environmental conscious solution: reduced CO₂ emmisions thanks to the use of geothermal energy as a renewable energy source and typical lower refrigerant levels making it ideal to comply with
- > Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units, Biddle air curtains and hot water
- > Unique zero heat dissipation principle obviates the need for ventilation or cooling in the technical room, maximising installation flexiblity
- > Wide range of indoor units: possibility to combine VRV with stylish indoor units (Daikin Emura, Perfera)
- > Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, VRV configurator, 7-segment display and full inverter compressors
- > Developed for easy installation and servicing: choice between top or front connection for refrigerant piping and rotating switch box for easy access to serviceable parts
- > Compact & lightweight design can be stacked for maximum space saving: 42HP can be installed in less than 0.5m² floorspace
- > 2-stage heat recovery: first stage between indoor units, second stage between outdoor units thanks to the storage of energy in the water circuit

- > Unified model for heat pump and heat recovery version and geothermal and standard operation
- > Variable Water Flow control option increases flexibility and control
- > 2 analogue input signals allowing external control of ON-OFF, operation mode, error signal, ...
- > Contains all standard VRV features







Published data with real-life indoor units

For units made and sold in Europe*

Connectable stylish indoor units

			20 CLASS	25 CLASS	35 CLASS	42 CLASS	50 CLASS	60 CLASS	71 CLASS
Daikin Emura - Wall mounted	unit	FTXJ-AW/AS/AB	•	•	•		•		
Stylish - Wall mounted unit		FTXA-AW/BS/BB/BT	•	•	•	•	•		
Perfera wall mounted		FTXM-R	•	•	•	•	•	•	•
Perfera floor standing	NEW	FVXM-A9	•	•	•		•		

BPMKS box needed to connect RA indoors to VRV IV (RYYO / RXYO)

More details and final information can be found by scanning or clicking the QR codes.






Outdoor unit				RWEYQ	8T9	10T9	12T9	14T9
Capacity range				HP	8	10	12	14
Cooling capacity	Prated,c			kW	22.4	28.0	33.5	40.0
Heating capacity	Prated,h			kW	25.0	31.5	37.5	45.0
	Max.	6°CWB		kW	25.0	31.5	37.5	45.0
Recommended con	nbination				4x FXMQ50P7VEB	4x FXMQ63P7VEB	6x FXMQ50P7VEB	1x FXMQ50P7VEB + 5x FXMQ63P7VEB
ηs,c				%	326.8	307.8	359.0	330.7
ηs,h				%	524.3	465.9	436.0	397.1
SEER					8.4	7.9	9.2	8.5
SCOP					13.3	11.8	11.1	10.1
Maximum number	of connect	able indo	or units			64	(1)	
Indoor index	Min.				100.0	125.0	150.0	175.0
connection	Max.				300.0	375.0	450.0	525.0
Dimensions	Unit	HeightxV	VidthxDepth	mm		980x76	57x560	
Weight	Unit		•	kg	19	95	19	97
Sound power level	Cooling	Nom.		dBA	65.0	71.0	72.0	74.0
Sound pressure level	Cooling	Nom.		dBA	48.0	50.0	56.0	58.0
Operation range	Inlet water	Cooling	Min.~Max.	°CDB		10 ~	~45	
-	temperature	Heating	Min.~Max.	°CWB		10 ~	~45	
	Temperature around casing			°CDB		4	0	
	Humidity around casing	Cooling~ Heating	Max.	%		80 -	~80	
Refrigerant	Type/GW	·				R-410A	/2,087.5	
•	Charge			kg/TCO2Eq	7.9/	16.5	9.6/	20.0
Piping connections	Liquid	OD		mm	9.	52	12	2.7
	Gas	OD		mm	19.1	22.2	28	3.6
	HP/LP gas	OD		mm	15.9/19.1	19.1/22.2	19.1/28.6	22.2/28.6
	Drain	Size				14mm OD	/ 10mm ID	
	Water	Inlet/Outle	t Size			ISO 228-G1 1/4 B/	/ISO 228-G1 1/4 B	
	Total piping length	System	Actual	m		50	00	
Power supply	Phase/Fre	quency/V	oltage	Hz/V		3N~/50/	380-415	
	Maximum			Α	2			5





Stage 1 heat recovery between indoor units



or

Reversible low temperature hydrobox

25°C - 45°C

25℃ - 35℃

Low temp.


Underfloor heating

radiator

Liquid pipe Gas pipe Discharge gas pipe

Hot water





* Above system configuration are for illustration purpose only.

Outdoor unit sys	tem	RWEYQ	16T9	18T9	20T9	22T9	24T9	26T9	28T9
System	Outdoor unit module 1		RWE'	YQ8T	RWE	YQ10T	RWE	/Q12T	RWEYQ14T
	Outdoor unit module 2		RWEYQ8T	RWEY	/Q10T	RWE	/Q12T	RWE	/Q14T
Capacity range		HP	16	18	20	22	24	26	28
Cooling capacity	Prated,c	kW	44.8	50.4	56.0	61.5	67.0	73.5	80.0
Heating capacity	Prated,h	kW	50.0	56.5	62.5	69.0	75.0	82.5	90.0
3 '	Max. 6°CWB	kW	50.0	56.5	62.5	69.0	75.0	82.5	90.0
Recommended co			4x FXMQ63P7VEB + 2x FXMQ80P7VEB	4x FXMQ50P7VEB + 4x FXMQ63P7VEB	8x FXMQ63P7VEB	6x FXMQ50P7VEB + 4x FXMQ63P7VEB	12x FXMQ50P7VEB	7x FXMQ50P7VEB + 5x FXMQ63P7VEB	
ηs,c		%	307.6	308.7	298.1	311.3	342.6	322.5	306.1
ηs,h		%	459.2	491.1	466.8	447.9	434.5	406.9	387.9
SEER		,,	7.		7.7	8.0	8.8	8.3	7.9
SCOP			11.7	12.5	11.9	11.4	11.1	10.4	9.9
	r of connectable indoor units		,	.2.0	,	64 (1)			
Indoor index	Min.		200.0	225.0	250.0	275.0	300.0	325.0	350.0
connection	Max.		600.0	675.0	750.0	825.0	900.0	975.0	1,050.0
Piping connection		mm	12.7	0/3.0	750.0		300.0	975.0	
r iping connection	Gas OD	mm	12.7	28		1.9		34.9	7.1
	HP/LP gas OD	mm	22.2			/28.6		28.6/34.9	
	Total piping System Actual		22.2)	20.0	20.0	500		20.0/34.9	
	length	m							
Power supply	Phase/Frequency/Voltage	Hz/V				3N~/50/380-415			
Current - 50Hz	Maximum fuse amps (MFA)	A	3	2	35	4	0	5	0
Outdoor unit sys	tem	RWEYQ	30T9	32T9	34T9	36T9	38T9	40T9	42T9
System	Outdoor unit module 1			RWEYQ10T			RWEYQ12T		RWEYQ14T
	Outdoor unit module 2		RWE	/Q10T		RWEYQ12T		RWE	/Q14T
	Outdoor unit module 3		RWEYQ10T		RWEYQ12T			RWEYQ14T	
Capacity range		HP	30	32	34	36	38	40	42
Cooling capacity	Prated,c	kW	84.0	89.5	95.0	100.5	107.0	113.5	120.0
Heating capacity	Prated,h	kW	94.5	100.5	106.5	112.5	120.0	127.5	135.0
3 '	Max. 6°CWB	1 144							425.0
	Max. 6 CWB	kW	94.5	100.5	106.5	112.5	120.0	127.5	135.0
Recommended co		kW		100.5 6x FXMQ50P7VEB + 8x FXMQ63P7VEB				127.5 8x FXMQ50P7VEB + 10x FXMQ63P7VEB	3x FXMQ50P7VEB
		kW		6x FXMQ50P7VEB +	12x FXMQ50P7VEB +		13x FXMQ50P7VEB+	8x FXMQ50P7VEB +	3x FXMQ50P7VEB
ηs,c			12x FXMQ63P7VEB	6x FXMQ50P7VEB + 8x FXMQ63P7VEB	12x FXMQ50P7VEB + 4x FXMQ63P7VEB	18x FXMQ50P7VEB	13x FXMQ50P7VEB + 5x FXMQ63P7VEB	8x FXMQ50P7VEB + 10x FXMQ63P7VEB	3x FXMQ50P7VEB 15x FXMQ63P7VE
ηs,c ηs,h		%	12x FXMQ63P7VEB 308.3	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0	18x FXMQ50P7VEB 352.3	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2
ns,c ns,h SEER		%	12x FXMQ63P7VEB 308.3 467.2	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5	352.3 438.5	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9
Recommended co ns,c ns,h SEER SCOP Maximum numbe	ombination	%	308.3 467.2 7.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8	352.3 438.5 9.0 11.2	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5
ns,c ns,h SEER SCOP Maximum numbe	ombination r of connectable indoor units	%	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	352.3 438.5 9.0 11.2 64 (1)	13x FXMQ50P7VEB + 5x FXMQ63P7VEB + 338.8 419.4 8	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ŋs,c ŋs,h SEER SCOP Maximum numbe Indoor index	r of connectable indoor units Min.	%	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	352.3 438.5 9.0 11.2 64 (1) 450.0	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4 8 10.7	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7 10.3	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ηs,c ηs,h SEER SCOP Maximum numbe Indoor index connection	r of connectable indoor units Min. Max.	% %	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	352.3 438.5 9.0 11.2 64 (1) 450.0 1,350.0	13x FXMQ50P7VEB + 5x FXMQ63P7VEB + 338.8 419.4 8	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ηs,c ηs,h SEER SCOP Maximum numbe Indoor index connection	r of connectable indoor units Min. Max. as Liquid OD	% % mm	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6 400.0 1,200.0	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	352.3 438.5 9.0 11.2 64 (1) 450.0	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4 8 10.7 475.0 1,425.0	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7 10.3 500.0 1,500.0	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ηs,c ηs,h SEER SCOP Maximum numbe Indoor index connection	r of connectable indoor units Min. Max. s Liquid OD Gas OD	% % mm mm	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6 400.0 1,200.0	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	18x FXMQ50P7VEB 352.3 438.5 9.0 11.2 64 (1) 450.0 1,350.0 19.1	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4 8 10.7 475.0 1,425.0	8x FXMQS0P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7 10.3 500.0 1,500.0 1.3	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ns,c ns,h SEER SCOP	r of connectable indoor units Min. Max. s Liquid OD Gas OD HP/LP gas OD	% % mm	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6 400.0 1,200.0	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	352.3 438.5 9.0 11.2 64 (1) 450.0 1,350.0	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4 8 10.7 475.0 1,425.0	8x FXMQ50P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7 10.3 500.0 1,500.0	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ns,c ns,h SEER SCOP Maximum numbe Indoor index connection	r of connectable indoor units Min. Max. s Liquid OD Gas OD HP/LP gas OD	% % mm mm mm	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6 400.0 1,200.0	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4	18x FXMQ50P7VEB 352.3 438.5 9.0 11.2 64 (1) 450.0 1,350.0 19.1 28.6/41.3	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4 8 10.7 475.0 1,425.0	8x FXMQS0P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7 10.3 500.0 1,500.0 1.3	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0
ns,c ns,h SEER SCOP Maximum numbe Indoor index connection	r of connectable indoor units Min. Max. as Liquid OD Gas OD HP/LP gas OD Total piping System Actual	% % mm mm mm	308.3 467.2 7.9 11.9	6x FXMQ50P7VEB + 8x FXMQ63P7VEB 318.2 456.1 8.2 11.6 400.0 1,200.0	12x FXMQ50P7VEB + 4x FXMQ63P7VEB 342.5 447.0 8.8 11.4 425.0 1,275.0	18x FXMQ50P7VEB 352.3 438.5 9.0 11.2 64 (1) 450.0 1,350.0 19.1 28.6/41.3	13x FXMQ50P7VEB + 5x FXMQ63P7VEB 338.8 419.4 8 10.7 475.0 1,425.0	8x FXMQS0P7VEB + 10x FXMQ63P7VEB 341.4 404.4 .7 10.3 500.0 1,500.0 1.3	3x FXMQ50P7VEB 15x FXMQ63P7VE 332.9 391.2 8.5 10.0

⁽I)Actual number of units depends on the indoor unit type (VRV DX indoor, RA DX indoor, etc.) and the connection ratio restriction for the system (being; $50\% \le CR \le 130\%$). | Contains fluorinated greenhouse gases * EU member states, UK, Bosnia-Herzegovina, Serbia, Montenegro, Kosovo, Albania, North Macedonia, Iceland, Norway, Switzerland




VRV IV indoor units

			Stylish indoor units	142
	Ceiling mounted cassette units	128	BPMKS	142
UNIQUE	3	128	Accessory to connect stylish indoor units	142
UNIQUE		129	Wall mounted	144
ONIQUE	FXCQ-A	130	PAIKIN FTXJ-AW/AS/AB	144
UNIQUE	_	131	stylish C/FTXA-AW/BS/BT/BB	145
ONIQUE	Concealed ceiling units	132	perfera C/FTXM-R	146
	Multi zoning kit	132	Floor standing	147
	FXDQ-A3	133	perfera C/FVXM-A	147
SLIMMEST IN CLASS	FXSQ-A	134		
NEW	FXMQ-P7 / FXMQ-A	135	Hot water	148
	Wall mounted unit	137	Low temperature hydrobox	148
	FXAQ-A	137	HXY-A8	148
	Ceiling suspended units	138	High temperature hydrobox	149
	FXHQ-A	138	HXHD-A8	149
UNIQUE	FXUQ-A	139	Accessories for hot water	150
	Floor standing units	140		
SLIMMEST IN CLASS	FXNQ-A	140	Biddle Air Curtains	152
	FXLQ-P	141	CYVS/M/L-DK-F/C/R	153














Products overview **JRJ IV**

Capacity class (kW)

	Model	P	roduct name	15	20	25	32	40	50	63	71	80	100	125	140	200	250
	UNIQUE Round flow cassette	360° air discharge for optimum efficiency and comfort > Auto cleaning function ensures high efficiency > Intelligent sensors save energy and maximize comfort > Flexibility to suit every room layout > Lowest installation height in the market! > Widest choice ever in decoration panel designs and colors	FXFQ-B		•	•	•	•	•	•		•	•	•		2	UV Streame kit
Ceiling mounted cassette	UNIQUE Fully flat cassette	Unique design that integrates fully flat into the ceiling > Perfect integration in standard architectural ceiling tiles > Blend of iconic design and engineering excellence Intelligent sensors save energy and maximize comfort > Small capacity unit developed for small or well-insulated rooms > Flexibility to suit every room layout	FXZQ-A		•	•	•	•	•								
כייין פיייושר	2-way blow ceiling mounted cassette	Thin, lightweight design installs easily in narrow ceiling spaces Depth of all units is 620mm, ideal for narrow ceiling spaces Flexibility to suit every room layout Reduced energy consumption thanks to DC fan motor The flaps close entirely when the unit is not operating Optimum comfort with automatic air flow adjustment to the required load	FXCQ-A		•	•	•	•	•	•		•		•			
	Ceiling mounted corner cassette	1-way blow unit for corner installation > Compact dimensions enable installation in narrow ceiling voids > Flexible installation thanks to different air discharge options	FXKQ-MA			•	•	•		•							
	Slim concealed ceiling unit	Slim design for flexible installation Compact dimensions enable installation in narrow ceiling voids Medium external static pressure up to 44Pa Only grilles are visible Small capacity unit developted for small of well-insulated rooms Reduced energy consumption thanks to DC fan motor	FXDQ-A3	TSI)	•	•	•	•	•	•			uto cl lter c				ulti zor optioi
Concealed celling	Concealed ceiling unit with medium ESP	Slimmest yet most powerfull medium static pressure unit on the market! Slimmest unit in class, only 245mm Low operating sound leve! Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, guaranteeing comfort	FXSQ-A		•	•	•	•	•	•		•	•	•	•		ulti zor option
Conce	Concealed ceiling unit with high ESP	ESP up to 200, ideal for large sized spaces > Optimum comfort guaranteed no matter the length of ductwork or type of grilles, thanks to automatic air flow adjustment > Reduced energy consumption thanks to DC fan motor > Flexible installation as the air suction direction can be altered from rear to bottom suction	FXMQ-P7						•	•		•	•	•			
	NEW Concealed ceiling unit with high ESP	ESP up to 250, ideal for extra large sized spaces > Only grilles are visible > Large capacity unit: up to 31.5 kW heating capacity	FXMQ-A	3												•	•
Wall mounted	Wall mounted unit	For rooms with no false ceilings nor free floor space > Flat, stylish front panel is more easy to clean > Small capacity unit developted for small of well-insulated rooms > Reduced energy consumption thanks to DC fan motor > The air is comfortably spread up- and downwards thanks to 5 different discharge angles	FXAQ-A		•	•	•	•	•	•							
Celling suspended	Ceiling suspended unit	For wide rooms with no false ceilings nor free floor space > Ideal for comfortable air flow in wide rooms thanks to Coanda effect > Rooms with ceilings up to 3.8m can be heated or cooled very easily! > Can easily be installed in both new and refurbishment projects > Can even be mounted in corners or narrow spaces without any problem > Reduced energy consumption thanks to DC fan motor	FXHQ-A				•			•			•				
Ceiling s	UNIQUE 4-way blow ceiling suspended unit	Unique Daikin unit for high rooms with no false ceilings nor free floor space Rooms with ceilings up to 3.5m can be heated up or cooled down very easily! Can easily be installed in both new and refurbishment projects Flexibility to suit every room layout Reduced energy consumption thanks to DC fan motor	FXUQ-A								•		•				
anding	Floor standing unit	For perimeter zone air conditioning > Can be installed in front of glass walls or free standing as both the front and the back are finished > Ideal for installation beneath a window > Requires very little installation space > Wall mounted installation facilitates cleaning beneath the unit	FXLQ-P	J	•	•	•	•	•	•							
Floor standing	Concealed floor standing unit	Ideal for installation in offices, hotels and residential applications > Discretely concealed in the wall, leaving only the suction and discharge grilles visible > Can even be installed underneath a window > Requires very little installation space as the depth is only 200mm > High ESP allows flexible installation	FXNQ-A		•	•	•	•	•	•							_
																22.4	

 $⁽¹⁾ Nominal cooling capacities are based on: indoor temperature: 27^{\circ}CDB, 19^{\circ}CWB, outdoor temperature: 35^{\circ}CDB, equivalent refrigerant piping: 5m, level difference: 0m and 100 cooling capacities are based on: indoor temperature: 27^{\circ}CDB, 19^{\circ}CWB, outdoor temperature: 35^{\circ}CDB, equivalent refrigerant piping: 5m, level difference: 0m and 100 cooling capacities are based on: indoor temperature: 27^{\circ}CDB, 10^{\circ}CWB, 10^{\circ}CWB$

 $^{(2) \} Nominal\ heating\ capacities\ are\ based\ on: indoor\ temperature: 20^\circ CDB, outdoor\ temperature: 7^\circ CDB, 6^\circ CWB, equivalent\ refrigerant\ piping: 5m, level\ difference: 0m$

Connectable outdoor unit

Products overview Stylish indoor units

Depending on the application, Split and Sky Air indoor units can be connected to our VRV IV and VRV IV S-series outdoor units. Refer to the **outdoor unit portfolio** for combination restrictions.

outdoor	unit portfolio for combinati	on restrictio	ns.						Capacit	y class	(kW)	RYYQ-U	RXYQ-U	RXYSCQ-TV1³ RXYSQ-TV9³ RXYSQ-TY9/TY1³	RWEYQ-T94	RXYLQ-T
Туре	Model	Product nam	e	15	20	25	35	42	50	60	71	£	× X	222	<u>8</u>	X
	Round flow cassette (incl. auto-cleaning function¹)	FCAG-B					•		•	•		UV Stream kit		✓		
Ceiling mounted cassette	Fully flat cassette	FFA-A9				•	•		•	•				√		
Concealed	Slim concealed ceiling unit	FDXM-F9				•	•		•	•		to clea		√		
ceiling	Concealed ceiling unit with inverter-driven fan	FBA-A(9)					•		•	•	•			✓		
	Daikin Emura Wall mounted unit Verdot award 2014 winner	FTXJ-AW/ AS/AB			•	•	•		•			~	✓	✓	✓	✓
Wall mounted	Stylish Wall mounted unit	FTXA-AW/ BS/BB/BT			•	•	•	•	•			~	✓	✓	✓	✓
	Perfera Wall mounted unit	CTXM-R/ FTXM-R	- 50	RXYS(C)Q only	•	•	•	•	•	•	•	~	✓	✓	✓	✓
Ceiling suspended	Ceiling suspended unit	FHA-A(9)					•		•	•	•			✓		
Floor	Perfera Floor standing unit	FVXM-A9			•	•	•		•			~	✓	✓	✓	✓
standing	Concealed floor standing unit	FNA-A9				•	•		•	•				✓		

¹ Decoration panel BYCQ140DG9 or BYCQ140DGF9 + BRC1E* or BRC1H* needed

Hydrobox range

Capacity class (kW)

Туре	Product name	Model	80	125	200	Leaving water temperature range
Low temperature hydrobox	HXY-A8	For high efficiency space heating and cooling > Ideal for hot or cold water in underfloor, air handling units, low temperature radiators > Hot/cold water from 5° to 45°C > Large operation range (down to -20°C and up to 43°C) > Fully integrated water-side components save time on system design > Space saving contemporary wall hung design	•	•		5 °C - 45 °C
High temperature hydrobox	HXHD-A8	For efficient hot water production and space heating > Ideal for hot water in bathrooms, sinks and for underfloor heating, radiators, air handling units, > Hot water from 25 to 80°C > "Free" heating and hot water through heat recovery > Uses heat pump technology to produce hot water efficiently, providing up to 17% savings compared to a gas boiler > Possibility to connect thermal solar collectors		•	•	25 °C - 80 °C

² To connect stylish indoor units a BPMKS unit is needed

 $^{^{\}scriptscriptstyle 3}~$ A mix of RA indoor units and VRV indoor units is not allowed.

⁴ Only in heat pump operation

Benefits overview **JRJ IV**

		Home leave operation	Maintains the indoor temperature at your specified comfort level during absence, thus saving energy
are	W	Fan only	The unit can be used as fan, blowing air without heating or cooling
We care		Auto cleaning filter	The filter automatically cleans itself. Simplicity of upkeep means optimum energy efficiency and maximum comfort without the need for expensive or time-consuming maintenance
		Presence & floor sensor	The presence sensor directs the air away from any person detected in the room, when the air flow control is on. The floor sensor detects the average floor temperature and ensures an even temperature distribution between ceiling and floor
_			· · · · · · · · · · · · · · · · · · ·
		Draught prevention	When starting to warm up or when the thermostat is off, the air discharge direction is set horizontally and the fan to low speed, to prevent draught. After warming up, air discharge and fan speed are set as desired
Comfort		Whisper quiet	Daikin indoor units are whisper quiet. Also the outdoor units are guaranteed not to disturb the quiet of the neightbourhood
	A	Auto cooling-heating changeover	Automatically selects cooling or heating mode to achieve the set temperature
nent	STREAMER	UV Streamer kit	Purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy and hygienic indoor environment
Air treatment		Air filter	Removes airborne dust particles to ensure a steady supply of clean air
Humidity	B O O DRY	Dry programme	Allows humidity levels to be reduced without variations in room temperature
_			
	\$\frac{1}{2}	Ceiling soiling prevention	Prevents air from blowing out too long in horizontal position, to prevent ceiling stains
Air flow		Vertical auto swing	Possibility to select automatic vertical moving of the air discharge flaps for efficient air and temperature distribution throughout the room
Air		Fan speed steps	Allows to select up to the given number of fan speed
	×	Individual flap control	Individual flap control via the wired remote controller enables you to easily fix the position of each flap individually, to suit any new room configuration. Optional closure kits are available as well
_			
	24/7	Weekly timer	Can be set to start heating or cooling anytime on a daily or weekly basis
		Infrared remote control	Starts, stops and regulates the air conditioner from a distance
		Wired remote control	Starts, stops and regulates the air conditioner
		Centralised control	Starts, stops and regulates several air conditioners from one central point
		Multi zoning	Allows up to 6 individual climate zones with one indoor unit
tions	ALTIO #	Auto-restart	The unit restarts automatically at the original settings after power failure
Other functions	a	Self-diagnosis	Simplifies maintenance by indicating system faults or operating anomalies
Othe	* J	Drain pump kit	Facilitates condensation draining from the indoor unit
		Multi tenant	The indoor unit's main power supply can be turned off when leaving the hotel or office building
_			

C	eiling mounte	ed cassette unit	ts		Concealed	ceiling units		Wall moun- ted unit	Ceiling susp	ended units	Floor star	nding units
FXFQ-B	FXZQ-A	FXCQ-A	FXKQ-MA	FXDQ-A3	FXSQ-A	FXMQ-P7	FXMQ-A	FXAQ-A	FXHQ-A	FXUQ-A	FXNQ-A	FXLQ-P
•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•
0												
0	0									0		
•	•		•							•		
•	•	•		•	•			•				
•	•	•	•	•	•	•	•	•	•	•	•	•
0												
• (2) (Optional high efficiency filter ePM10 60%)	• (1)	• (1)	• (1)	• (1)	• (1)	• (1)	• (1) Optional pre filter and high efficiency filter available	• (1)	• (1)	• (1)	• (1)	• (1)
•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•									
•	•	•	•					•	•	•		
5 + auto	3 + auto	3 + auto	2	3	3 + auto	3	3 + auto	2	3	3 + auto	2	3
•	•									•		
0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0
				0	0							
				I	ı	l				I.	I	
•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	0	0	0	•		

• standard, o optional







Round flow cassette

360° air discharge for optimum efficiency and comfort

- > Optional automatic filter cleaning panel results in higher efficiency & comfort and lower maintenance costs.
- > Two optional intelligent sensors improve energy efficiency and comfort
- > Widest choice ever in decoration panels: designer panels in white (RAL9010) and black (RAL9005) and standard panels in white (RAL9010) with grey louvers or full white
- > Bigger flaps and unique swing pattern improve equal air distribution
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!
- > Lowest installation height in the market: 214mm for class 20-63
- NEW > UV streamer kit, purifies the air of pollutants such as viruses,
 - bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy and hygenic indoor environment
 - > Optional fresh air intake
 - > Branch duct discharge allows to optimize air distribution in irregular shaped rooms or to supply air to small adjacent rooms



> Standard drain pump with 675mm lift increases flexibility and installation speed













Black panel White auto cleaning panel

Black design panel

More details and final information can be found by scanning or clicking the QR codes.





Indoor Unit				FXFQ	20B	25B	32B	40B	50B	63B	80B	100B	125B
Cooling capacity	Total capacity	At high fa	an speed	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	11.20	14.00
Heating capacity	Total capacity	At high fa	an speed	kW	2.50	3.20	4.00	5.00	6.30	8.00	10.00	12.50	16.00
Power input - 50Hz	Cooling	At high fa	an speed	kW		0.017		0.018	0.023	0.028	0.045	0.071	0.103
	Heating	At high fa	an speed	kW		0.017		0.018	0.023	0.028	0.045	0.071	0.103
Dimensions	Unit	HeightxV	WidthxDepth	mm			204x8	40x840			246x8	40x840	288x840x840
Weight	Unit			kg		18		19		21	2	24	26
Casing	Material							Galva	anised steel	plate			
Decoration panel	Model				Standar		o cleaning	hite with gro panels: BYCO panels: BYCO	Q140EGF - w	hite / BYCQ	140EGFB - b	lack	EB - black
	Dimension	s HeightxV	WidthxDepth	mm	Standar	d panels: 65	x950x950/	Auto cleanir	ng panels: 1	48x950x950	/ Designer	panels: 106	x950x950
	Weight			kg		Stand	ard panels:	5.5 / Auto cl	eaning pan	els: 10.3 / De	esigner pan	els: 6.5	
Fan	Air flow rate -	Cooling	At high / medium / low fan speed	m³/min		12.8/10.7/8.9)	14.8/12.6/10.4	15.1/12.9/10.7	16.6/13.4/10.7	23.3/19.2/13.5	27.8/20.4/13.0	31.6/26.0/19.8
	50Hz	Heating	At high / medium / low fan speed	m³/min		12.8/10.7/8.9)	14.8/12.6/10.4	15.1/12.9/10.7	16.6/13.4/10.7	22.5/18.5/13.0	27.8/20.4/13.0	30.3/24.9/18.9
Air filter	Type								Resin net				
Sound power level	Cooling	At high fa	an speed	dBA		49.0		51	1.0	53.0	55.0	60.0	61.0
Sound pressure	Cooling	At high / n	nedium / low fan speed	dBA	:	31.0/29.0/28.	0	33.0/31	.0/29.0	35.0/33.0/30.0	38.0/34.0/30.0	43.0/37.0/30.0	45.0/41.0/36.0
level	Heating	At high / n	nedium / low fan speed	dBA	:	31.0/29.0/28.	0	33.0/31	.0/29.0	35.0/33.0/30.0	38.0/34.0/30.0	43.0/37.0/30.0	45.0/41.0/36.0
Refrigerant	Type/GW	'P						R	-410A/2,087	7.5			
Piping connections	Liquid	OD		mm			6.35				9.	.52	
	Gas	OD		mm			12.7				15	5.9	
	Drain							VP25	(O.D. 32 / I.	D. 25)			
Power supply	Phase/Fre	equency/V	/oltage	Hz/V				1~/50)/60/220-24	0/220			
Current - 50Hz	Maximur	n fuse amp	os (MFA)	Α					16				
Control systems	Infrared r	emote cor	ntrol				BRC7FA53	2F / BRC7FB5	32F / BRC7I	A532FB / BF	RC7FB532FB		
	Wired rer	note contr	rol			E	3RC1H52W/	S/K / BRC1E5	3A / BRC1E5	3B / BRC1E5	3C / BRC1D5	52	

Fully flat cassette

Unique design in the market that integrates fully flat into the ceiling

- Fully flat integration in standard architectural ceiling tiles, leaving only 8mm
- Remarkable blend of iconic design and engineering excellence with an elegant finish in white or a combination of silver and white
- > Two optional intelligent sensors improve energy efficiency and comfort
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!




> Optional fresh air intake


Indoor Unit

> Standard drain pump with 630mm lift increases flexibility and installation speed

FXZQ

15A





25A

20A

32A

BRC1H52W, BRC7F530W-S

FXZQ-A



40A



50A

Cooling capacity	Total capacity	At high fa	in speed	kW	1.70	2.20	2.80	3.60	4.50	5.60
Heating capacity	Total capacity	At high fa	in speed	kW	1.90	2.50	3.20	4.00	5.00	6.30
Power input - 50Hz	Cooling	At high fa	in speed	kW	0.0	018	0.020	0.019	0.029	0.048
	Heating	At high fa	in speed	kW	0.0	018	0.020	0.019	0.029	0.048
Dimensions	Unit	HeightxV	VidthxDepth	mm			260x5	75x575		
Weight	Unit			kg		15.5		16	5.5	18.5
Casing	Material						Galvanised	l steel plate		
Decoration panel	Model						BYFQ60	C2W1W		
	Colour						White	(N9.5)		
	Dimensions	HeightxV	VidthxDepth	mm			46x62	0x620		
	Weight			kg			2	.8		
Decoration panel 2	Model						BYFQ6	OC2W1S		
	Colour						SIL	VER		
	Dimensions	HeightxV	VidthxDepth	mm			46x62	0x620		
	Weight			kg			2	.8		
Decoration panel 3	Model						BYFQ6	0B2W1		
	Colour						White (F	RAL9010)		
	Dimensions	HeightxV	VidthxDepth	mm			55x70	0x700		
	Weight			kg			2	.7		
Decoration panel 4	Model						BYFQ6	60B3W1		
	Colour						WHITE (I	RAL9010)		
	Dimensions	HeightxV	VidthxDepth	mm			55x70	0x700		
	Weight			kg			2	.7		
Fan	Air flow rate - 50Hz	Cooling	At high / medium / low fan speed	m³/min	8.5/7.00/6.5	8.7/7.50/6.5	9.0/8.00/6.5	10.0/8.50/7.0	11.5/9.50/8.0	14.5/12.5/10.0
		Heating	At high / medium / low fan speed	m³/min	8.5/7.0/6.5	8.7/7.5/6.5	9.0/8.0/6.5	10.0/8.5/7.0	11.5/9.5/8.0	14.5/12.5/10.0
Air filter	Type						Resi	n net		
Sound power level	Cooling	At high fa	ın speed	dBA	4	9	50	51	54	60
Sound pressure	Cooling	At high / m	edium / low fan speed	dBA	31.5/28.0/25.5	32.0/29.5/25.5	33.0/30.0/25.5	33.5/30.0/26.0	37.0/32.0/28.0	43.0/40.0/33.0
level	Heating	At high / m	edium / low fan speed	dBA	31.5/28.0/25.5	32.0/29.5/25.5	33.0/30.0/25.5	33.5/30.0/26.0	37.0/32.0/28.0	43.0/40.0/33.0
Refrigerant	Type/GWI)					R-410A	/2,087.5		
Piping connections	Liquid	OD		mm			6.	35		
	Gas	OD		mm			12	2.7		
	Drain						VP20 (I.D.	20/O.D. 26)		
Power supply	Phase/Fre	quency/V	oltage	Hz/V			1~/50/60/2	20-240/220		
Current - 50Hz	Maximum	fuse amp	s (MFA)	Α			1	6		
Control systems	Infrared re	emote con	trol		BRC7F	530W (white pane	el) / BRC7F530S (gr	rey panel) / BRC7E	B530W (standard	panel)
Control systems	Wired ren	note contr	ol			BRC1H52W/S	5/K / BRC1E53A / B	RC1E53B / BRC1E5	3C / BRC1D52	

2-way blow ceiling mounted cassette

Thin, lightweight design installs easily in narrow corridors

- > Depth of all units is 620mm, ideal for narrow spaces
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!



- > Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating and there are no air intake grilles
- > Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation device is required


Fresh air intake opening in casing




- * Brings in up to 10% of fresh air into the room
- > Optimum comfort guaranteed with automatic air flow adjustment to the required load
- > Maintenance operations can be performed by removing the front panel



> Branch duct discharge allows to optimize air distribution in irregular shaped rooms or to supply air to small adjacent rooms



> Standard drain pump with 580mm lift increases flexibility and installation speed



More details and final information can be found by scanning or clicking the QR codes.






Indoor Unit				FXCQ	20A	25A	32A	40A	50A	63A	80A	125A
Cooling capacity	Total capacity	At high far	n speed	kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	14.0
Heating capacity	Total capacity	At high far	n speed	kW	2.5	3.2	4.0	5.0	6.3	8.0	10.0	16.0
Power input - 50Hz	Cooling	At high far	n speed	kW	0.031	0.0	039	0.041	0.059	0.063	0.090	0.149
	Heating	At high far	n speed	kW	0.028	0.0	035	0.037	0.056	0.060	0.086	0.146
Dimensions	Unit	HeightxWi	idthxDepth	mm		305x7	75x620		305x9	90x620	305x1,4	145x620
Weight	Unit			kg		1	9		22	25	33	38
Casing	Material							Galvanised	l steel plate			
Decoration panel	Model					BYBCC	40HW1		BYBCC)63HW1	BYBCQ	125HW1
	Colour							Fresh white	(6.5Y 9.5/0.5)			
	Dimension	s HeightxWi	idthxDepth	mm		55x1,0	70x700		55x1,2	85x700	55x1,74	40x700
	Weight			kg		1	0			11	1	13
Fan	Air flow rate - 50H		At high/medium/ low fan speed	m³/min	10.5/9/7.5	11.5/	9.5/8	12/10.5/8.5	15/13/10.5	16/14/11.5	26/22.5/18.5	32/27.5/22.5
Air filter	Туре						Re	esin net with	mold resistar	nce		
Sound power level	Cooling		speed / At medium At low fan speed	dBA	48/46/44	50/47/45	50/48/46	52/49/47	53/51/47	55/53/48	58/54/49	62/58/54
Sound pressure level	Cooling		speed / At medium 'At low fan speed	dBA	32.0/30.0/28.0	34.0/31.0/29.0	34.0/32.0/30.0	36.0/33.0/31.0	37.0/35.0/31.0	39.0/37.0/32.0	42.0/38.0/33.0	46.0/42.0/38.0
	Heating		speed / At medium At low fan speed	dBA	32.0/30.0/28.0	34.0/31.0/29.0	34.0/32.0/30.0	36.0/33.0/31.0	37.0/35.0/31.0	39.0/37.0/32.0	42.0/38.0/33.0	46.0/42.0/38.0
Refrigerant	Type/GW	P			Ì			R-410A	/2,087.5			
Piping connections	Liquid	OD		mm			6.35				9.52	
	Gas	OD		mm	ĺ		12.7				15.9	
	Drain				Ì			VP25 (O.D.	32 / I.D. 25)			
Power supply	Phase/Fre	equency/Vo	ltage	Hz/V				1~/50/2	220-240			
Current - 50Hz	Maximun	n fuse amps	(MFA)	Α				1	6			
Control systems	Infrared r	emote cont	rol					BRC	7C52			
•	Wired rer	note contro	l			BRC	1H52W/S/K/	BRC1E53A / B	RC1E53B / BR	C1E53C / BRC	1D52	

Contains fluorinated greenhouse gases


Ceiling mounted corner cassette

1-way blow unit for corner installation

- > Compact dimensions, can easily be mounted in a narrow ceiling void (only 220mm ceiling space required, 195 with panel spacer, available as accessory)
- Optimum air flow conditions are created by either downward air discharge or frontal air discharge (via optional grille) or a combination of both



- > Maintenance operations can be performed by removing the front panel
- > Standard drain pump with 330mm lift increases flexibility and installation speed





More details and final information can be found by scanning or clicking the QR codes.



Indoor Unit			FXKQ	25MA	32MA	40MA	63MA		
Cooling capacity	Total capacity	At high fan speed	kW	2.8	3.6	4.5	7.10		
Heating capacity	Total capacity	At high fan speed	kW	3.2	4.0	5.0	8.00		
Power input - 50Hz	Cooling	At high fan speed	kW	0.0	066	0.076	0.105		
	Heating	At high fan speed	kW	0.0)46	0.056	0.085		
Dimensions	Unit	HeightxWidthxDepth	mm		215x1,110x710		215x1,310x710		
Weight	Unit		kg		31		34		
Casing	Material				Galvanised	l steel plate			
Decoration panel	Model				BYK45FJW1		BYK71FJW1		
	Colour				WI	nite			
	Dimensions	HeightxWidthxDepth	mm		70x1,240x800		70x1,440x800		
	Weight		kg		8.5		9.5		
Fan	Air flow rate - 50Hz	Cooling At high fan spe At low fan spe		11	/9	13/10	18/15		
Air filter	Type				Resin net with				
Sound power level	Cooling	At high fan speed/ At low fan speed	dBA	54	/49	56/50	58/53		
Sound pressure level	Cooling	At high fan speed/ At low fan speed	dBA	38.0	/33.0	40.0/34.0	42.0/37.0		
Refrigerant	Type/GW	P			R-410A	/2,087.5			
Piping connections	Liquid	OD	mm		6.35		9.52		
	Gas	OD	mm		12.7		15.9		
	Drain				VP25 (O.D.	32 / I.D. 25)			
Power supply	Phase/Fre	equency/Voltage	Hz/V		1~/50/60/2	20-240/220			
Current - 50Hz	Maximun	n fuse amps (MFA)	Α			15			
Control systems	Infrared r	emote control	ĺ		BRC	4C61			
	Wired ren	note control		BRC	:1H52W/S/K / BRC1E53A / B	RC1E53B / BRC1E53C / BRC	1D52		



The multi-zoning system is a room-by-room controller. It is fitted with motorised dampers, which immediately adapt using Daikin ducted solutions. This system supports control of up to 8 zones via a centralised thermostat located in the main room and individual thermostats for each of the zones.

Benefits


Increased comfort

- > Increases comfort levels by allowing more individual zone control
 - Up to 8 individual zones can be served thanks to separate modulating dampers
 - Individual thermostat for room-by-room or zone-by-zone control

Easy to install

- > Automatic air flow adjustment according to the demand
- > Easy to install, integrates with the Daikin indoor units and system controls
- Time saving as plenum comes fully pre-assembled with dampers, and control boards
- > Reduces the amount of refrigerant required in the installation

How does it work?



Individual zone thermostats

Bluezero - Airzone Main Thermostat

 Color graphic interface for controlling zones



AZCE6BLUEZEROCB (Wired)

Skylir

Airzone Zone Thermostat > Graphic interface with

 Graphic interface with low-energy e-ink screen for controlling zones



AZCE6THINKRB (Wireless)

Airzone Zone Thermostat

 Thermostat with buttons for controlling the temperature



AZCE6LITECB (Wired)
AZCE6LITERB (Wireless)

Compatibility

Number of motorised dampers	Compatii	JI	IILY							•	וכ	V		"											i	罗.	7		₹.	I١	y					
Relication Hand Mark Drawn	•						FDXI	M-F	9			FB/	A-A	(9)			ΑĽ	EA-	A			FX	DQ-	А3							F>	KSQ	-A			
2 AZEIZ/RISOAISTO753			Reference		Ø (mm)	25	35	50	60	35	50	60	71	100	125	140	71	100	125	15	20	25	32	40	50	63	15	20	25	32	40	50	63	80	100	125 140
AZELZ/RIJORAISTOXS3 AZELZ/RIJORAISTOXS3 AZELZ/RIJORAISTOXS3 AZELZ/RIJORAISTOXS3 AZELZ/RIJORAISTOXM4 AZELZ/RIJORAISTOXM4 AZELZ/RIJORAISTOXM4 AZELZ/RIJORAISTOXM4 AZELZ/RIJORAISTOXM5 AZELZ/RIJ		,	AZE(Z/R)6DAIST07XS2																								•	•	•	•						
A ZEIZ/RISODAISTO7XS			AZE(Z/R)6DAIST07S2	200 v 020 v 454						•	•																				•	•				
AZEI/RIJOBAISTONS 4 AZEI/RIJOBAISTONS 5 AZEI/RIJOBAISTONS 5 AZEI/RIJOBAISTONS 6 AZEI/RIJOBAISTONS 6 AZEI/RIJOBAISTONS 7 AZEI/RIJOBAISTONS 8 AZEI/R		,	AZE(Z/R)6DAIST07XS3	300 X 930 X 434																							•	•	•	•						
Standard plenum 4			AZE(Z/R)6DAIST07S3							•	•																				•	•				
AZEZ/RIJOAISTO7M5 AZEZ		4	AZE(Z/R)6DAIST07S4	200 v 1 140 v 454						•	•																				•	•				
Sacial Control		-	AZE(Z/R)6DAIST07M4	300 X 1,140 X 434								•	•				•																•	•		
AZEZ/RIJOAISTO7US AZEZ/RIJOAIS	Standard plenum	_	AZE(Z/R)6DAIST07M5	200 v 1 425 v 454	200							•	•				•																•	•		
AZE(Z/R)6DAISTO7L5 AZE(Z/R)6DAISTO7L7 AZE(Z/R)6DAISTO7L7 AZE(Z/R)6DAISTO7L7 AZE(Z/R)6DAISTO7L8 AZE(Z/R)6DAISTO7L8 AZE(Z/R)6DAISTO7L8 AZE(Z/R)6DAISTO7L8 AZE(Z/R)6DAISTO7L8 AZE(Z/R)6DAISTO7L8 AZEZ6DAIBSO7S2 AZEZ6DAIBSO7S3 AZEZ6DAIBSO7S3 AZEZ6DAIBSO7S3 AZEZ6DAIBSO7S4 AZEZ6DAIBSO7S5 AZEZ6DAIBSO7S5 AZEZ6DAIBSO7M4 AZEZ6DAIBSO7M5 AZEZ6DAIBSO7M5 AZEZ6DAIBSO7M5 AZEZ6DAIBSO7M5 AZEZ6DAIBSO7M6 AZEZ6DAIBSO		3	AZE(Z/R)6DAIST07L5	300 X 1,423 X 434	200									•	•	•		•	•																•	•
AZE(Z/R)GDAISTO7L6 AZE(Z/R)GDAISTO7L7 AZE(Z/R)GDAISTO7L7 AZE(Z/R)GDAISTO7L7 AZE(Z/R)GDAISTO7L8 AZE(Z/R)GDAISTO7XL7 AZE(Z/R)GDAISTO7XL2 AZEZGDAIBSO7XS2 AZEZGDAIBSO7XS2 AZEZGDAIBSO7XS3 AZEZGDAIBSO7XS3 AZEZGDAIBSO7XS4 AZEZGDAIBSO7XS4 AZEZGDAIBSO7XS4 AZEZGDAIBSO7XS4 AZEZGDAIBSO7XS5 AZEZGDAIBSO7XS6 AZEZGDAIBSO7XS6 AZEZGDAIBSO7XS6 AZEZGDAIBSO7XL5 AZEZGRABISOXL5 AZEZGR		_	AZE(Z/R)6DAIST07M6	200 v 1 620 v 454								•	•				•																•	•		
## AZE(Z/R)6DAISTO7XL7 ## AZE(Z/R)6DAISTO7XL8 ## AZE(Z/R)6DAISTO7XL8 ## AZE(Z/R)6DAISTO7XL8 ## AZEZ6DAIBSO7XS2 ## AZEZ6DAIBSO7XS3 ## AZEZ6DAIBSO7XS3 ## AZEZ6DAIBSO7XS3 ## AZEZ6DAIBSO7XS4 ## AZEZ6DAIBSO7XS4 ## AZEZ6DAIBSO7XS4 ## AZEZ6DAIBSO7XS5 ## AZEZ6DA		L	AZE(Z/R)6DAIST07L6	300 X 1,036 X 434										•	•	•		•	•																•	•
8 AZE(Z/R)6DAISTOTXLB 2 AZEZ6DAIBSOTXS2		7	AZE(Z/R)6DAIST07L7											•	•	•		•	•																•	•
## AZE(Z/R)6DAISTOTALE AZE(Z/R)6DAISTOTALE		Ľ	AZE(Z/R)6DAIST07XL7	E1E v 1 42E v 4E4																																•
AZEZGDAIBSO7XS2 AZEZGDAIBSO7XS3 AZEZGDAIBSO7XS3 AZEZGDAIBSO7XS4 AZEZGDAIBSO7XB AZEZGDAIBSO7X			AZE(Z/R)6DAIST07L8	313 X 1,423 X 434										•	•	•		•	•																•	•
AZEZGDAIBSO7XS AZEZGDAIBSO7XS AZEZGDAIBSO7XS AZEZGDAIBSO7XH AZEZGDAIBSO7XH AZEZGDAIBSO7XH AZEZGDAIBSO7XH AZEZGDAIBSO7XH AZEZGDAIBSO7XLS AZEZGDAIBSO7XL		°	AZE(Z/R)6DAIST07XL8																														•			
AZEZGDAIBSO7S2 AZEZGDAIBSO7S3 AZEZGDAIBSO7M3 AZEZGDAIBSO7M4 AZEZGDAIBSO7M4 AZEZGDAIBSO7N5 AZEZGDAIBSO7N6 6 AZEZGDAIBSO7N6 AZEZGDAIBSO7N6 250 x 1,425 x 454 250 x 1,425 x 454 250 x 1,425 x 454 200 Slim plenum 2 AZEZGDAIBSO7XL6 3 AZE(Z/R)6DAISL0153 4 AZE(Z/R)6DAISL0153 4 AZE(Z/R)6DAISL0153 210 x 720 x 444 200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		1	AZEZ6DAIBS07XS2																								•	•	•	•						
Medium plenum AZEZ6DAIBS07M4 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M5 AZEZ6DAIBS07M6 6 AZEZ6DAIBS07M6 AZEZ			AZEZ6DAIBS07S2							•	•																				•	•				
Medium plenum AZEZ6DAIBS07M3 AZEZ6DAIBS07M4 AZEZ6DAIBS07S4 AZEZ6DAIBS07S5 AZEZ6DAIBS07S5 AZEZ6DAIBS07N5 AZEZ6DAIBS07N5 AZEZ6DAIBS07N5 AZEZ6DAIBS07N5 AZEZ6DAIBS07N5 AZEZ6DAIBS07N6 6 AZEZ6DAIBS07N6 AZEZ6DAIBS07N6 250 x 1,425 x 454 250 x 1,425 x 454 250 x 1,638 x 454 250 x 1,63			AZEZ6DAIBS07XS3	250 x 930 x 454																							•	•	•	•						
Medium plenum 4		3	AZEZ6DAIBS07S3							•	•																				•	•				
Medium plenum 4 AZEZGDAIBS07M4 AZEZGDAIBS07L4 AZEZGDAIBS07S5 AZEZGDAIBS07M5 AZEZGDAIBS07M5 AZEZGDAIBS07XL5 AZEZGDAIBS07XL5 AZEZGDAIBS07M6 6 250 x 1,425 x 454 AZEZGDAIBS07M6 AZEZGDAIBS07M6 AZEZGDAIBS07XL6 250 x 1,638 x 454 • • • • • • • • • • • • • • • • • • •			AZEZ6DAIBS07M3									•	•				•																•	•		
AZEZGDAIBSO7L4 AZEZGDAIBSO7S5 AZEZGDAIBSO7M5 AZEZGDAIBSO7N5 AZEZGDAIBSO7N5 AZEZGDAIBSO7N6 6 AZEZGDAIBSO7N6 AZEZ			AZEZ6DAIBS07S4					•	•																				•	•						
AZEZ6DAIBSO7L5 AZEZ6DAIBSO7M5 AZEZ6DAIBSO7N5 AZEZ6DAIBSO7N5 AZEZ6DAIBSO7N6 6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 2 AZEZ6DAIBSO7N6 3 AZEZ6DAIBSO7N6 4 AZEZ6PAIBSO7N4 2 AZEZ6PAIBSO7N4 2 AZEZ6PAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6DAIBSO7N6 AZEZ6PAIBSO7N6 AZEZ6PAIB	Medium plenum	4	AZEZ6DAIBS07M4	250 x 1,140 x 454								•	•				•																•	•		
AZEZGDAIBSO7M5 AZEZGDAIBSO7M5 AZEZGDAIBSO7XL5 AZEZGDAIBSO7XL5 AZEZGDAIBSO7XL6			AZEZ6DAIBS07L4		200									•	•	•		•	•																•	•
AZEZGDAIBSO7L5 AZEZGDAIBSO7XL5 AZEZGDAIBSO7XL6 AZEZGRAIBSO7XL6 AZEZGRAIBSO	99201		AZEZ6DAIBS07S5							•	•																				•	•				
AZEZ6DAIBSO7L5 AZEZ6DAIBSO7M6 6 AZEZ6DAIBSO7M6 AZEZ6DAIBSO7M6 250 x 1,638 x 454 Slim plenum 2 AZE(Z/R)6DAISL01S2 3 AZE(Z/R)6DAISL01S3 4 AZE(Z/R)6DAISL01M4 210 x 720 x 444 200	E. 50 FC.	-	AZEZ6DAIBS07M5	2501 425 454								•	•				•																•	•		
AZEZ6DAIBS07M6 6 AZEZ6DAIBS07L6 AZEZ6DAIBS07XL6 250 x 1,638 x 454 250 x 1,638 x 454 210 x 720 x 444 4 AZEZ6DAISL01S3 4 AZEZ6PAISL01M4 210 x 930 x 444 200 200 200 200 200 200 200 200 200		٥	AZEZ6DAIBS07L5	250 X 1,425 X 454										•	•	•		•	•																•	•
6 AZEZGDAIBS07L6 AZEZGDAIBS07XL6 2 AZE(Z/R)6DAISL01S2 3 AZE(Z/R)6DAISL01M4 2 10 x 720 x 444 2 00 x 930 x 444 2 00 x 930 x 444 2 00 x 930 x 444			AZEZ6DAIBS07XL5																																	•
AZEZGDAIBS07XL6 Slim plenum 2			AZEZ6DAIBS07M6	250 x 1,638 x 454						•	•				•																•	•				
Slim plenum 2 AZE(Z/R)6DAISL01S2 210 x 720 x 444 200		6	AZEZ6DAIBS07L6									•	•	•		•	•																•	•		
3 AZE(Z/R)6DAISL0153 210 x 720 x 444 200 • • • • • • • • • • • • • • • • • •			AZEZ6DAIBS07XL6																																	•
3 AZE(Z/R)6DAISL01S3 4 AZE(Z/R)6DAISL01M4 210 x 930 x 444 200	Slim plenum	2	AZE(Z/R)6DAISL01S2	210 v 720 v 444		•	•													•	•	•	•													
4 AZE(Z/R)6DAISL01M4 210 x 930 x 444	Sim picham	3	AZE(Z/R)6DAISL01S3	210 X /20 X 444	200	•	•													•	•	•	•													
5 AZE(Z/R)6DAISL01L5 210 x 1,140 x 444		4	AZE(Z/R)6DAISL01M4	210 x 930 x 444	200																			•	•											
		5	AZE(Z/R)6DAISL01L5	210 x 1,140 x 444				•	•																	•										


(1) Z models are reversible; R models are heating only

(2) Medium Ceiling Void reversible units can be blocked to heating only via AZX6MCS module


Slim concealed ceiling unit

Slim design for flexible installation


Compact dimensions, can easily be mounted in a ceiling void of only 240mm




- Medium external static pressure up to 44Pa facilitates unit use with flexible ducts of varying lengths
- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > Auto cleaning filter option ensures maximum efficiency, comfort and reliability by regular filter cleaning
- > Multi zoning kit allows multiple individually-controlled climate zones to be served by one indoor unit
- > Flexible installation, as the air suction direction can be altered from rear to bottom suction



> Standard drain pump with 600mm lift increases flexibility and installation speed







Auto cleaning filter option

More details and final information can be found by scanning or clicking the QR codes.



Indoor Unit				FXDQ	15A3	20A3	25A3	32A3	40A3	50A3	63A3
Cooling capacity	Nom.			kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.			kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	At high fa	an speed	kW		0.036		0.041	0.042	0.053	0.062
	Heating	At high fa	n speed	kW		0.036		0.041	0.042	0.053	0.062
Required ceiling vo	id >			mm				240			
Dimensions	Unit	HeightxV	VidthxDepth	mm		200x7	50x620		200x9	50x620	200x1,150x620
Weight	Unit			kg		2	22		2	6	29
Casing	Material						(Galvanised stee	el		
Fan	Air flow rate - 50Hz	Cooling	At high / medium / low fan speed	m³/min	7.5/7.0/6.4		8.0/7.2/6.4		10.5/9.5/8.5	12.5/11.0/10.0	16.5/14.5/13.0
	External static pressure - 50Hz	Factory s	et / High	Pa		10/	30.0			15/44.0	
Air filter	Type						Ren	novable / wash	able		
Sound power level	Cooling	At high fa	an speed	dBA	50		51		52	53	54
Sound pressure level	l Cooling	At high / m	nedium / low fan speed	l dBA	32.0/31.0/27.0		33.0/31.0/27.0		34.0/32.0/28.0	35.0/33.0/29.0	36.0/34.0/30.0
Refrigerant	Type/GW	P						R-410A/2,087.5			
Piping connections	Liquid	OD		mm			6.	35			9.52
	Gas	OD		mm			12	2.7			15.9
	Drain						VP	20 (I.D. 20/O.D.	26)		
Power supply	Phase/Fre	equency/V	oltage	Hz/V			1~/	50/60/220-240/	220		
Current - 50Hz	Maximun	n fuse amp	s (MFA)	Α				16			
Control systems		emote con					BF	C4C65 / BRC4C	.66		
	Wired ren	note contr	ol				BF	RC1D528 / BRC1	E51		

Concealed ceiling unit with medium ESP

Slimmest yet most powerful medium static pressure unit on the market

> Slimmest unit in class, only 245mm (300mm built-in height) and therefore narrow ceiling voids are no longer a challenge




- > Quiet operation: down to 25dBA sound pressure level
- Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths
- > Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- Discretely concealed in the wall: only the suction and discharge grilles are visible
- 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- Multi zoning kit allows multiple individually-controlled climate zones to be served by one indoor unit
- Reduced energy consumption thanks to specially developed DC fan motor and drain pump
- > Optional fresh air intake

Fresh air intake opening in casing



* Brings in up to 10% of fresh air into the room Optional fresh air intake kit




 Allow larger quantities of fresh air to be brought in


More details and final information can be found by scanning or clicking the QR codes.








 Flexible installation: air suction direction can be altered from rear to bottom suction and choice between free use or connection to optional suction grilles




 Standard built-in drain pump with 625mm lift increases flexibility and installation speed



Automatic Airflow Adjustment function Automatically selects the most appropriate fan curve to achieve the units' nominal air flow within ±10%

Why

After installation the real ducting will frequently differ from the initially calculated air flow resistance ** the real air flow may be much lower or higher than nominal, leading to a lack of capacity or uncomfortable air temperature Automatic Airflow Adjustment function will adapt the unit's fan speed to any ducting automatically (10 or more fan curves are available on every model), making installation much faster




Indoor Unit				FXSQ	15A	20A	25A	32A	40A	50A	63A	80A	100A	125A	140A
Cooling capacity	Total capacity	At high fa	n speed	kW	1.70	2.20	2.80	3.60	4.50	5.60	7.10	9.00	11.20	14.00	16.00
Heating capacity	Total capacity	At high fa	an speed	kW	1.90	2.50	3.20	4.00	5.00	6.30	8.00	10.0	12.5	16.0	18.0
Power input - 50Hz	Cooling	At high fa	an speed	kW		0.041		0.045	0.087	0.089	0.101	0.135	0.173	0.237	0.247
	Heating	At high fa	n speed	kW		0.041		0.045	0.087	0.089	0.101	0.135	0.173	0.237	0.247
Dimensions	Unit	HeightxV	VidthxDepth	mm		245x5	50x800		245x70	008x00	245x1,0	008x000	245x1,4	00x800	245x1,550x800
Weight	Unit			kg		23.5		24.0	28.5	29.0	35.5	36.5	46.0	47.0	51.0
Casing	Material									nised stee					
Fan	Air flow rate - 50Hz	Cooling	At high / medium / low fan speed	m³/min	8.7/7.50/6.5	9.0/7	.50/6.5	9.5/8.00/7.0	15.0/12.5/11.0	15.2/12.5/11.0	21.0/18.0/15.0	23.0/19.5/16.0	32.0/27.0/23.0	36.0/31.5/26.0	39.0/34.0/28.0
		Heating	At high / medium / low fan speed	m³/min	8.7/7.5/6.5	9.0/7	7.5/6.5	9.5/8.0/7.0	15.0/12.5/11.0	15.2/12.5/11.0	21.0/18.0/15.0	23.0/19.5/16.0	32.0/27.0/23.0	36.0/31.5/26.0	39.0/34.0/28.0
	External static pressure - 50Hz		et / High	Pa				30/150				40/	150	50/	150
Air filter	Туре									Resin net					
Sound power level	Cooling	At high fa	n speed	dBA		54		55	6	0	59	(51	6	54
Sound pressure	Cooling	At high / m	nedium / low fan speed	dBA	29.5/28.0/25.0	30.0/2	8.0/25.0	26.0/29.0/26.0	35.0/32	2.0/29.0	33.0/30.0/27.0	35.0/32.0/29.0	36.0/34.0/31.0	39.0/36.0/33.0	41.5/38.0/34.0
level	Heating	At high / m	nedium / low fan speed	dBA	31.5/29.0/26.0	32.0/2	9.0/26.0	33.0/30.0/27.0	37.0/34	1.0/29.0	35.0/32.0/28.0	37.0/34.0/30.0	37.0/34.0/31.0	40.0/37.0/33.0	42.0/38.5/34.0
Refrigerant	Type/GWF)							R-	410A/2,08	37.5				
Piping connections	Liquid	OD		mm			6	5.35					9.52		
	Gas	OD		mm			1	2.7					15.9		
	Drain							VP20 (I	.D. 20/O.D). 26), drai	n height (625 mm			
Power supply	Phase/Fre	quency/V	oltage	Hz/V					1~/50/	/60/220-24	40/220				
Current - 50Hz	Maximum	fuse amp	s (MFA)	Α						16					
Control systems	Infrared re	emote con	itrol							BRC4C65					
	Wired ren	note contr	ol					BRC1E5	3A / BRC1	E53B / BR	C1E53C / E	3RC1D52			


Concealed ceiling unit with high ESP


Ideal for large sized spaces: ESP up to 250 Pa

- > High external static pressure up to 250Pa facilitates extensive duct and grille network
- > Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- > Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation device is required (50-125 class)




- > Flexible installation, as the air suction direction can be altered from rear to bottom suction






> Standard built-in drain pump with 625mm lift increases flexibility and installation speed (optional for 200-250)



> Large capacity unit: up to 31.5 kW heating capacity

Automatic Airflow Adjustment function Automatically selects the most appropriate fan curve to achieve the units' nominal air flow within ±10%

After installation the real ducting will frequently differ from the initially calculated air flow resistance * the real air flow may be much lower or higher than nominal, leading to a lack of capacity or uncomfortable air temperature Automatic Airflow Adjustment function will adapt the unit's fan speed to any ducting automatically (10 or more fan curves are available on every model), making installation



More details and final information can be found by scanning or clicking the QR codes.







Indoor Unit				FXMQ	50P7	63P7	80P7	100P7	125P7	200A	250A
Cooling capacity	Total capacity	At high f	an speed	kW			-			22.4	28.0
	Nom.			kW	5.6	7.1	9.0	11.2	14.0	22.4	28.0
Heating capacity	Total capacity	At high f	an speed	kW			-			25.0	31.5
	Nom.			kW	6.3	8.0	10.0	12.5	16.0	25.0	31.5
Power input - 50Hz	Cooling	At high f	an speed	kW	0.110	0.120	0.171	0.176	0.241	0.54	0.65
	Heating	At high f	an speed	kW	0.098	0.108	0.159	0.164	0.229	0.54	0.65
Required ceiling vo	id>			mm			350				
Dimensions	Unit	Heightx\	WidthxDepth	mm		300x1,000x700		300x1,4	00x700	470x1,49	90x1,100
Weight	Unit			kg		35		4	-6	105	115
Fan	Air flow	Cooling	At high/medium/low fan speed	m³/min	18.0/16.5/15.0	19.5/17.8/16.0	25.0/22.5/20.0	32.0/27.5/23.0	39.0/33.5/28.0	62/48/41	74/64/52
	rate - 50Hz	Heating	At high/medium/low fan speed	m³/min	18.0/16.5/15.0	19.5/17.8/16.0	25.0/22.5/20.0	32.0/27.5/23.0	39.0/33.5/28.0	62/48/41	74/64/52
	External static pressure - 50Hz	Factory s	et / High	Pa			100/200			150/	250
Air filter	Туре						Resin net				
Sound power level	Cooling	At high/m	nedium/low fan speed	dBA	61.0/-/-	64.0/-/-	67.0/-/-	65.0/-/-	70.0/-/-	75/74/72	76/75/73
	Heating	At high/m	nedium/low fan speed				-			75/74/72	76/75/73
Sound pressure	Cooling	At high/m	nedium/low fan speed	dBA	41.0/39.0/37.0	42.0/40.0/38.0	43.0/41	1.0/39.0	44.0/42.0/40.0	48/46	5.5/45
level	Heating	At high/m	nedium/low fan speed	dBA	41.0/39.0/37.0	42.0/40.0/38.0	43.0/41	.0/39.0	44.0/42.0/40.0	48/46	5.5/45
Refrigerant	Type/GW	Р					R-410A/-			R-410A	/2,087.5
Piping connections	Liquid	OD		mm	6.35			9.	52		
	Gas	OD		mm	12.7		15	i.9		19.1	22.2
	Drain					VP	25 (I.D. 25/O.D.	32)		BS	P1
Power supply	Phase/Frequency/Voltage Hz/V						50/220-240/220	+/-10%		1~/50/2	20-240
Current - 50Hz	Maximun	n fuse amp	os (MFA)	Α				6			
Control systems	Infrared r	emote cor	ntrol					BRC4C65			
	Wired ren	note conti	rol			BRC11	H52W/S/K/BRC1	E53A/BRC1E53I	3/BRC1E53C/BR	22.4 25.0 25.0 0.54 0.54 470x1,4 105 62/48/41 150 75/74/72 75/74/72 48/4 48/4 R-410A 19.1 8:	



Wall mounted unit

For rooms with no false ceilings nor free floor space

- > Flat, stylish front panel blends easily within any interior décor and is easier to clean
- > Can easily be installed in both new and refurbishment projects
- > The air is comfortably spread up- and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- > Maintenance operations can be performed easily from the front of the unit



More details and final information can be found by scanning or clicking the QR codes.






Indoor Unit				FXAQ	15A	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	At high fa	n speed	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Total capacity	At high fa	an speed	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	At high fa	an speed	kW	0	.02	0.	.03	0.02	0.03	0.05
	Heating	At high fa	an speed	kW		0.03		0.04	0.02	0.04	0.06
Dimensions	Unit	HeightxW	VidthxDepth	mm		290x7	95x266			290x1,050x269	ı
Weight	Unit			kg		1	12			15	
Fan	Air flow rate - 50Hz	Cooling	At high fan At low fan s	speed/ m³/min peed	8.4/7.0	9.1/7.0	9.4/7.0	9.8/7.0	12.2/9.7	14.4/11.5	18.3/13.5
Air filter	Type						W	ashable resin r	iet		
Sound power level	Cooling	At high fa	an speed	dBA	51.0	52.0	53.0	55	5.0 58.0 37.0/33.5 41.0/35.5		63.0
Sound pressure level	Cooling	At high fa At low far		dBA	32.0/28.5	33.0/28.5	35.0/28.5	37.5/28.5	37.0/33.5	41.0/35.5	46.5/38.5
	Heating	At high fa At low far		dBA	33.0/28.5	34.0/28.5	36.0/28.5	38.5/28.5	38.0/33.5	42.0/35.5	47.0/38.5
Refrigerant	Type/GWI)						R-410A/2,087.5			
Piping connections	Liquid	OD		mm			6	.35			9.52
	Gas	OD		mm			12	2.7			15.9
	Drain						VI	P13 (I.D. 15/O.D.	18)		
Power supply	Phase/Fre	quency/V	oltage	Hz/V				1~/50/220-240			
Current - 50Hz	Maximum	fuse amp	s (MFA)	Α				16			
Control systems	Infrared re	emote con	itrol				BRC	7EA628 / BRC7E	A629		
•	Wired rem	note contr	ol			BRC1H5	2W/S/K / BRC1I	53A / BRC1E53I	B / BRC1E53C / E	3RC1D52	

Contains fluorinated greenhouse gases


Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

> Ideal for comfortable air flow in wide rooms thanks to Coanda effect: up to 100° discharge angle



- > Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily without capacity loss
- > Two optional intelligent sensors improve energy efficiency and
- > Can easily be installed in both new and refurbishment projects
- > Can easily be mounted in corners and narrow spaces, as it only needs 30mm lateral service space



> Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation device is required Fresh air intake opening in casing



- * Brings in up to 10% of fresh air into the room
- > Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating and there are no air intake grilles visible

More details and final information can be found by scanning or clicking the QR codes.



The state of the s

BRC1H52W, BRC7GA53-9

FXHQ63A



Indoor Unit				FXHQ	32A	63A	100A				
Cooling capacity	Total capacity	At high fa	an speed	kW	3.6	7.1	11.2				
Heating capacity	Total capacity	At high fa	an speed	kW	4.0	8.0	12.5				
Power input - 50Hz	Cooling	At high fa	an speed	kW	0.107	0.111	0.237				
	Heating	At high fa	n speed	kW	0.107	0.111	0.237				
Dimensions	Unit	HeightxW	VidthxDepth	mm	235x960x690	235x1,270x690	235x1,590x690				
Weight	Unit			kg	24	33	39				
Casing	Material					Resin					
Fan	Air flow rate - 50H	Cooling	At high / medium / low fan speed	m³/min	14.0/12.0/10.0	20.0/17.0/14.0	29.5/24.0/19.0				
		Heating	At high / medium / low fan speed	m³/min	14.0/12.0/10.0	20.0/17.0/14.0	29.5/24.0/19.0				
Air filter	Туре					Resin net with mold resistance					
Sound power level	Cooling	At high / m	edium / low fan speed	dBA	54/52/49	55/53/52	62/55/52				
Sound pressure	Cooling	At high / m	edium / low fan speed	dBA	36.0/34.0/31.0	37.0/35.0/34.0	44.0/37.0/34.0				
level	Heating	At high / m	nedium / low fan speed	dBA	36.0/34.0/31.0	37.0/35.0/34.0	44.0/37.0/34.0				
Refrigerant	Type/GW	P				R-410A/2,087.5					
Piping connections	Liquid	OD		mm	6.35	9.5	52				
	Gas	OD		mm	12.7	15	.9				
	Drain					VP20 (I.D. 20/O.D. 26)					
Power supply	Phase/Fre	equency/V	oltage	Hz/V	· ·						
Current - 50Hz	Maximum fuse amps (MFA) A 16										
Control systems	Infrared r	emote con	itrol			BRC7GA53 / BRC7GA56					
	Wired rer	note contr	ol		BRC1H52W/S	/K / BRC1E53A / BRC1E53B / BRC1E53	BC / BRC1D52				

Contains fluorinated greenhouse gases


4-way blow ceiling suspended unit

Unique Daikin unit for high rooms with no false ceilings nor free floor space


- > Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- > Can easily be installed in both new and refurbishment projects
- > Individual flap control: flexibility to suit every room layout without changing the location of the unit!



- > Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating and there are no air intake grilles
- > Optimum comfort guaranteed with automatic air flow adjustment to the required load
- > 5 different discharge angles between 0 and 60° can be programmed via the remote control




> Standard drain pump with 720mm lift increases flexibility and installation speed




More details and final information can be found by scanning or clicking the QR codes.

Indoor Unit









Cooling capacity	lotal capacity	At high fa	an speed	kW	8.0	11.2
Heating capacity	Total capacity	At high fa	an speed	kW	9.0	12.5
Power input - 50Hz	Cooling	At high fa	an speed	kW	0.090	0.200
	Heating	At high fa	an speed	kW	0.073	0.179
Dimensions	Unit	HeightxV	WidthxDepth	mm	198x95	50x950
Weight	Unit			kg	26	27
Casing	Material				Re	sin
Fan	Air flow rate -	Cooling	At high/medium/ low fan speed	m³/min	22.5/19.5/16.0	31.0/26.0/21.0
	50Hz	Heating	At high/medium/ low fan speed	m³/min	22.5/19.5/16.0	31.0/26.0/21.0
Air filter	Туре				Resin net with r	mold resistance
Sound power level	Cooling	At high/m	nedium/low fan speed	dBA	58/56/54	65/62/58
Sound pressure	Cooling	At high/m	nedium/low fan speed	dBA	40.0/38.0/36.0	47.0/44.0/40.0
level	Heating	At high/m	nedium/low fan speed	dBA	40.0/38.0/36.0	47.0/44.0/40.0
Refrigerant	Type/GW	P			R-410A	/2,087.5
Piping connections	Liquid	OD		mm	9.:	52
	Gas	OD		mm	15	.9
	Drain				I.D. 20/	O.D. 26
Power supply	Phase/Fre	Drain Phase/Frequency/Voltage H			1~/50/60/220	-240/220-230
Current - 50Hz	Maximun	n fuse amp	os (MFA)	Α	1	6
Control systems	Infrared r	emote cor	ntrol		BRC	7C58
	Wired rer	note contr	rol		BRC1H52W/S/K / BRC1E53A / BI	RC1E53B / BRC1E53C / BRC1D52

71A


FXUQ

Concealed floor standing unit

Designed to be concealed in walls

- > Discretely concealed in the wall: only the suction and discharge grilles are visible
- > Requires very little installation space as the depth is only 200mm









More details and final information can be found by scanning or clicking the QR codes.




Indoor Unit				FXNQ	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	At high f	an speed	kW	2.20	2.80	3.60	4.50	5.60	7.10
	Total capacity	At high f	an speed	kW	2.50	3.20	4.00	5.00	6.30	8.00
Power input - 50Hz	Cooling	At high f	an speed	kW		0.071		0.078	0.099	0.110
	Heating	At high fa	an speed	kW		0.068		0.075	0.096	0.107
Dimensions	Unit	Heightx\	WidthxDepth	mm		620/720x790x200)	620/720>	(990x200	620/720x1,190x200
Weight	Unit			kg		23.5		27	7.5	32.0
Casing	Material						Galvanise	d steel plate		
	Air flow rate -	Cooling	At high/medium/ low fan speed	m³/min		8.0/7.20/6.4		10.5/9.50/8.5	12.5/11.0/10.0	16.5/14.5/13.0
	50Hz	Heating	At high/medium/ low fan speed	m³/min		8.0/7.2/6.4		10.5/9.5/8.5	12.5/11.0/10.0	16.5/14.5/13.0
	External station pressure - 50Hz	Factory s	set / High	Pa	10	/41.0	10/42.0	15/52.0	15/59.0	15/55.0
Air filter	Туре						Res	in net		
Sound power level	Cooling	At high f	an speed	dBA		51		52	54	
Sound pressure	Cooling	At high/m	nedium/low fan speed	dBA		30.0/28.5/27.0		32.0/30.0/28.0	33.0/31.0/29.0	35.0/33.0/32.0
level	Heating	At high/m	nedium/low fan speed	dBA		30.0/28.5/27.0		32.0/30.0/28.0	33.0/31.0/29.0	35.0/33.0/32.0
Refrigerant	Type/GW	Р					R-410A	1/2,087.5		
Piping connections	Liquid	OD		mm			6.35			9.52
	Gas	OD		mm			12.7			15.9
	Drain						VP20 (I.D.	20/O.D. 26)		
Power supply	Phase/Fre	equency/V	/oltage	Hz/V			1~/50/60/2	220-240/220		
Current - 50Hz	Maximun	n fuse amp	os (MFA)	Α				16		
Control systems	Infrared r	emote cor	ntrol				BRC	4C65		
	Wired rer	note conti	rol			BRC1H52W/S	S/K / BRC1E53A / E	RC1E53B / BRC1E5	3C / BRC1D52	

Contains fluorinated greenhouse gases


Floor standing unit

For perimeter zone air conditioning

- > Unit can be installed as free standing model by use of optional back plate
- > Its low height enables the unit to fit perfectly beneath a window
- > Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7012) blends easily with any interior
- > Requires very little installation space



> Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate



> Wired remote control can easily be integrated in the unit



More details and final information can be found by scanning or clicking the QR codes.






Indoor Unit			FXLQ	20P	25P	32P	40P	50P	63P
Cooling capacity	Total capacity	At high fan speed	kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Total capacity	At high fan speed	kW	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	At high fan speed	kW	0	.05	0.	09	0	.11
	Heating	At high fan speed	kW	0	.05	0.	09	0	.11
Dimensions	Unit	HeightxWidthxDepth	mm	600x1,	000x232	600x1,1	40x232	600x1,4	420x232
Weight	Unit		kg	:	27	3	2	3	88
Fan	Air flow rate - 50H	Cooling At high fan spe z At low fan spee		7/	6.0	8/6.0	11/8.5	14/11.0	16/12.0
Air filter	Туре					Resi	n net		
Sound power level	Cooling	At high fan speed	dBA		54		57	58	59
Sound pressure level	Cooling	At high fan speed/ At low fan speed	dBA		35/32		38/33	39/34	40/35
	Heating	At high fan speed/ At low fan speed	dBA		35/32		38/33	39/34	40/35
Refrigerant	Type/GW	P				R-410A	/2,087.5		
Piping connections	Liquid	OD	mm			6.	35		
	Gas	OD	mm			12.7			15.9
	Drain					O.D. 21 (Vin	yl chloride)		
Power supply	Phase/Fre	equency/Voltage	Hz/V			1~/50/60/2	20-240/220		
Current - 50Hz	Maximun	n fuse amps (MFA)	Α			1	5		
Control systems	Infrared r	emote control				BRC	4C65		
	Wired rer	note control			BRC1H52W/	S/K / BRC1E53A / B	RC1E53B / BRC1E5	3C / BRC1D52	

VRV heat pump combined with

stylish indoor units

Combine VRV indoor units with stylish indoor units



Connect <u>only</u> stylish indoor units to VRV IV S-series or VRV IV W-series outdoor units



^{*} Special order unit, contact your local sales representative for more information

BPMKS967A

Branch provider

To connect Split and Sky Air indoor units to VRV outdoor units



Branch provide	er		BPMKS967A2	FBPMKS967A2
Connectable in	door units		1~2	1~3
Max. indoor uni	it connectable capacity			
Max. connectab	ole combination			
Dimensions	Height x Width x Depth	mm	180x29	94x350
Weight		kg		





Wall mounted unit

Design that speaks for itself

- > Remarkable blend of iconic design and engineering excellence with an elegant finish in matt crystal white, silver and black
- > The Coanda effect optimises the airflow for a comfortable climate. By using specially designed flaps, a more focused airflow allows a better temperature distribution throughout the whole room
- > The intelligent thermal sensor determines the current room temperature and distributes air evenly throughout the room before switching to an airflow pattern that directs warm or cool air to areas that need it
- > Using electrons to trigger chemical reactions with air borne particles, the Flash Streamer breaks down allergens such as pollen and fungal allergens and removes bothersome odours providing a better, cleaner air
- > Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc.
- > Onecta app: control your indoor from any location with an app, via your local network or internet
- > Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!



More details and final information can be found by scanning or clicking the QR codes.













Indoor unit				FTXJ	20AW/S/B	25AW/S/B	35AW/S/B	42AW/S/B	50AW/S/B
Dimensions	Unit	HeightxV	WidthxDepth	mm			305x900x212		
Weight	Unit			kg			12		
Air filter	Type					F	Removable / washabl	e	
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m³/min	4.6/6.0/8.4/11.0	4.6/6.0/8.6/11.4	4.6/6.0/8.6/11.8	4.6/7.2/9.5/13	5.2/7.6/10.4/13.5
		Heating	Silent operation/ Low/Medium/High	m³/min	4.6/6.4/8.7/11.1	4.6/6.4/9.0/11.3	4.6/6.4/9.0/11.7	5.2/7.7/10.5/14.4	5.7/8.2/11.1/15.0
Sound power level	Cooling			dBA	57	57	60	60	60
	Heating			dBA	-	-	-	-	-
Sound pressure	Cooling	Silent op	eration/Low/High	dBA	19/25/39	19/25/40	19/25/41	21/29/45	24/31/46
level	Heating	Silent op	eration/Low/High	dBA	19/25/39	19/25/40	19/25/41	21/29/45	24/33/46
Control systems	Infrared r	emote cor	ntrol				ARC488A1W/S/K		

^{* +2} dBA in Multi combination

stylish

Wall mounted unit

Most compact design wall mounted unit

- > A compact and functional design suitable for all interiors in a white, black, silver and blackwood coloured elegant finish
- > The Coanda effect optimises the airflow for a comfortable climate. By using specially designed flaps, a more focused airflow allows a better temperature distribution throughout the whole room
- > The intelligent thermal sensor determines the current room temperature and distributes air evenly throughout the room before switching to an airflow pattern that directs warm or cool air to areas that need it



- Onecta app: control your indoor from any location with an app, via your local network or internet
- > Powerful air purification increases indoor air quality with Daikin Flash Streamer technology
- > Practically inaudible: the unit runs so quietly, you will almost forget it is there.









More details and final information

can be found by scanning or clicking the QR codes.



FTXA-AW









Indoor unit			FTXA	CTXA15 AW/BS/BT/BB	20AW/BS/BT/BB	25AW/BS/BT/BB	35AW/BS/BT/BB	42AW/BS/BT/BB	50AW/BS/B	BT/BB	
Dimensions	Unit	HeightxWidthxDepth	mm			295x7	98x189				
Weight	Unit		kg		12						
Air filter	Type				Removable / washable						
Fan	Air flow rate	Cooling Silent operation/ Low/Medium/ High	m³/min	4.6/6.1/8.2/11.0	4.6/6.1/8/11.0	4.6/6.1/9/11.5	4.6/6.1/9/11.9	4.6/7.2/10/13.1	5.2/7.6/10/	/13.5	
		Heating Silent operation/ Low/Medium/ High	m³/min	4.5/6.4/8.7/10.9		4.5/6.4/9.0/11.1	4.5/6.4/9.0/11.5	5.2/7.7/10.5/14.6	5.7/8.2/11.1	/15.1	
Sound power level	Cooling	-	dBA		57			60			
Sound pressure	Cooling	Silent operation/Low/High	dBA	19/2	5/39	19/25/40	19/25/41	21/29/45	24/31/4	6	
level	Heating	Silent operation/Low/High	dBA	19/2	5/39	19/25/40	19/25/41	21/29/45	24/31/46	24/33/46	
Control systems	Infrared re	emote control		ARC466A58							
	Wired ren	note control				BRO	073				

perfero

Wall mounted unit

Attractive, wall mounted design with perfect indoor air quality

- Using electrons to trigger chemical reactions with air borne particles, the Flash Streamer breaks down allergens such as pollen and fungal allergens and removes bothersome odours providing a better, cleaner air
- > Silver allergen removal and air purifying filter captures allergens such as pollen to ensure a steady supply of clean air
- > Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- Onecta app: control your indoor from any location with an app, via your local network or internet.
- > Quiet operation: down to 19dBA sound pressure level
- 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces
- 2-area motion detection sensor: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting. (larger capacity area)












Indoor unit				FTXM	CTXM15R	20R	25R	35R	42R	50R	60R	71R
Dimensions	Unit	HeightxV	VidthxDepth	mm			295x778x272	2			299x998x292	2
Weight	Unit			kg			10.0				14.5	
Air filter	Туре							Removable	e/washable			
Fan	Air flow rate	Cooling Silent operation/ m³/min Low/Medium/High		4.3/5.7/	4.3/5.7/7.5/10.5 4.1/5.7/7.6/10.5		4.2/6.0/7.8/11.3	4.3/6.5/9.0/11.9	8.3/11.4/14/15.8	9.1/11.8/14/16.7	10.0/12.2/15/16.9	
'		Heating	Silent operation/ Low/Medium/High	m³/min	5.1/6.2/	8.2/9.3	4.9/6.3/8.0/9.8	4.9/6.5/8.5/9.8	4.9/6.5/9.7/12.4	10.5/12.0/14.2/15.8	11.1/12.4/15.2/16.5	11.6/12.7/15.8/17.7
Sound power level	Cooling			dBA		57		58	60	58.0	60	0.0
	Heating			dBA		5	54		60	58.0	59.0	61.0
Sound pressure	Cooling	Silent op	eration/Low/High	dBA		19/25/41		19/29/45	21/30/45	27.0/36.0/44.0	30.0/37.0/46.0	32.0/38.0/47.0
	Heating	Silent op	eration/Low/High	dBA	20/2	6/39	20/27/39	20/28/39	21/29/45	31.0/34.0/43.0	33.0/36.0/45.0	34.0/37.0/46.0
Control systems	Infrared r	remote cor	ntrol			27,27,27			ARC466A67			

Floor standing unit

Design floor standing unit for optimal heating comfort thanks to unique heating features

- Seasonal efficiency values up to A++ in heating, resulting in low running costs compared to gas boilers and electric heating
- > Excellent contemporary design
- > Heat boost quickly heats up your home when starting up your air conditioner. Set temperature is reached 14% faster than a regular air conditioner (pair only)
- > The floor warming function optimises convection by distributing hot air from the bottom of the unit
- > The heat plus function provides 30 minutes cosy heating by simulating radiant heat
- > Dual air discharge flow for better air distribution
- > Using electrons to trigger chemical reactions with air borne particles, the Flash Streamer breaks down allergens such as pollen and fungal allergens and removes bothersome odours providing a better, cleaner air
- > Onecta app: control your indoor from any location with an app, via your local network or internet.





- > Quiet operation: down to 19dBA sound pressure level
- > Combinable with 2 and 3 port multi outdoor units (except 2-3MXM68)








Indoor unit				FVXM	CVXM20A	25A	35A	50A
Dimensions	Unit	HeightxV	WidthxDepth	mm		600x7	750x238	
Weight	Unit			kg			17	
Air filter	Type					Removabl	e / washable	
Fan	Air flow rate	Cooling Silent operation/ m³/min Low/Medium/High			4.1/4.9	9/7/8.7	4.1/4.9/7/9.2	5.4/6.6/9/11.6
		Heating Silent o		m³/min	4.1/5.6/7.2/9.2		4.1/5.6/7.2/9.8	5.9/8.4/10.0/12.8
Sound power level	Cooling	dBA			52	2.0	53.0	61.0
	Heating	dBA			52	2.0	53.0	62.0
Sound pressure	Cooling	Silent op	eration/Low/High	dBA	22.0/25.0/38.0	20.0/25.0/38.0	20.0/25.0/39.0	27.0/31.0/44.0
level	Heating	Silent operation/Low/High dBA		dBA	21.0/25.0/38.0	21.0/25.0/38.0 19.0/25.0/38.0		29.0/35.0/46.0
Control systems	Infrared r	remote control						

Low temperature hydrobox for VRV

For high efficiency space heating and cooling

- > Air to water connection to VRV for applications such as underfloor, air handling units, low temperature radiators, ...
- > Leaving water temperature range from 5°C to 45°C without electric heater
- Super wide operating range for hot/cold water production from -20 to +43°C ambient outdoor temperature
- Saves time on system design as all water-side components are fully integrated with direct control over leaving water temperature
- > Space saving contemporary wall mounted design
- > No gas connection or oil tank needed
- > Connectable to VRV IV heat pump and heat recovery









Indoor Unit			HXY	080A8	125A8			
Cooling capacity	Nom.		kW	8.0 (1)	12.5 (1)			
Heating capacity	Nom.		kW	9.00 (2)	14.00 (2)			
Casing	Colour			White				
	Material			Precoated s	heet metal			
Dimensions	Unit	HeightxWidthxDepth	mm	890x48	30x344			
Weight	Unit		kg	44.0				
Operation range	Heating	Ambient Min.~Max.	°C	-20	~24			
		Water side Min.~Max.	°C	25 -	-45			
	Cooling	Ambient Min.~Max.	°CDB	10 ~43				
		Water side Min.~Max.	°C	5~20				
Refrigerant	Type			R-410A				
	GWP		ĺ	2,08	37.5			
Sound pressure leve	l Nom.		dBA	31				
Refrigerant circuit	Gas side	diameter	mm	15	9			
	Liquid sid	de diameter	mm	9.5				
Water circuit	Piping connections diameter inch		inch	G 1"1/4 (female)				
Power supply	Phase / F	requency / Voltage	Hz/V	1~/50/220-240				
Current	Recomm	ended fuses	Α	6~	16			

High temperature hydrobox for VRV

For efficient hot water production and space heating

- Air to water connection to VRV for applications such as bathrooms, sinks, underfloor heating, radiators and air handling units
- > Leaving water temperature range from 25 to 80°C without electric heater
- "Free" heating and hot water production provided by transferring heat from areas requiring cooling to areas requiring heating or hot water
- > Uses heat pump technology to produce hot water efficiently, providing up to 17% savings compared to a gas boiler
- > Possibility to connect thermal solar collectors to the domestic hot water tank
- Super wide operating range for hot water production from -20 to +43°C ambient outdoor temperature
- Saves time on system design as all water-side components are fully integrated with direct control over leaving water temperature
- Various control possibilities with weather dependant set point or thermostat control
- The indoor unit and domestic hot water tank can be stacked to save space, or installed next to each other, if only limited height is available
- > No gas connection or oil tank needed
- > Connectable to VRV IV heat recovery







Indoor Unit		HXHD	125A8	200A8				
Heating capacity	Nom.	kW	14.0	22.4				
Casing	Colour		Metallic grey					
	Material		Precoated sheet metal					
Dimensions	Unit HeightxWidthxDepth	mm	705x6	00x695				
Weight	Unit	kg	92.0	147				
Operation range	Heating Ambient Min.~Max.	°C	-20.0 ~2	20 (3) / 20				
	Water side Min.~Max.	°C	25 ~80.0					
	Domestic Ambient Min.~Max.	°CDB	-20.0 ~43.0					
	hot water Water side Min.~Max.	°C	45 ~75					
Refrigerant T	Type / GWP		R-134a	a / 1,430				
	Charge	kg	2.00	2.60				
Sound power level	Nom.	dBA	55.0 (1)	60.0 (1)				
Sound pressure	Nom.	dBA	42.0 (1) / 43.0 (2)	46.0 (1) / 46.0 (2)				
level	Night quiet Level 1 mode	dBA	38 (1)	45 (1)				
Water circuit	Piping connections diameter	inch	G 1" (f	emale)				
	Heating Water volume Max. ~ Min. water system	I	200 ~ 20	400 ~ 20				
Power supply	Phase / Frequency / Voltage	Hz/V	1~ / 50 / 220-240	3~/50/380-415				
Current	Recommended fuses	Α	20	16				

Daikin Altherma ST Thermal store

Plastic domestic hot water tank with solar support

- > Fresh water principle: receive domestic hot water on demand while eliminating the risk of contamination and sedimentation
- Optimal domestic hot water performance: the low temperature evolution enables high tapping performance
- > Fit for the future: possibility to integrate with renewable solar energy and other heat sources, e.g. fireplace
- > Lightweight and robust build of the unit combined with the cascade principle offers flexible installation options
- > Available in 300 and 500 liters









Accessory			EKHWP	300B	500B	300PB	500PB	54419B			
Casing	Colour				Traffic white	e (RAL9016) / Dark grey	(RAL7011)				
	Material			Impact resistant polypropylene							
Dimensions	Unit	Width	mm	595	790	595	79	90			
		Depth	mm	615	790	615	79	90			
		Height	mm	1,646	1,658	1,646	1,6	558			
Weight	Unit	Empty	kg	53	76	56	82	71			
Tank	Water volu	me	L	294	477	294	4	77			
	Material	Material				Polypropylene					
	Maximum	Maximum water temperature °C				85					
	Insulation	Heat loss	kWh/24h	1.50	1.70	1.50	1.1	70			
	Energy efficiency class			В							
	Standing h	Standing heat loss W			72	64	72				
	Storage vo	Storage volume L			393	290	3!	93			
Heat exchanger	Domestic	Quantity				1					
	hot water	Tube material		Stainless steel (DIN 1.4404)							
		Face area	m²	5.60	5.80	5.60	5.90	5.80			
		Internal coil volume	L	27.80	28.90	27.80	29	28.90			
		Operating pressure	bar			10					
	Charging	Quantity				1					
		Tube material			Sta	inless steel (DIN 1.440-	4)				
		Face area	m²	2.66	3.70	2.66	3.70	1.95			
		Internal coil volume	L	12.90	18.10	12.90	18.10	10			
		Operating pressure	bar		6			3			
	Auxiliary solar	Tube material		-	Stainless steel (DIN 1.4404)	-		ss steel .4404)			
	heating	Face area	m²	-	0.76	-	0.	76			
		Internal coil volume	L	-	3.90	-	3.	90			
		Operating pressure	bar	-	3	-		3			

Solar collector

Thermal solar collector for hot water production

- Solar collectors can produce up to 70% of the energy needed for hot water production - a major cost saving
- > Horizontal solar collector for domestic hot water production
- > Vertical solar collector for domestic hot water production
- > High efficiency collectors transfer all the short-wave solar radiation into heat as a result of their highly selective coating
- > Easy to install on roof tiles
- > Can be used for drain-back and pressurised applications

More details and final information can be found by scanning or clicking the QR codes.









Accessory			EKSV21P	EKSV26P	EKSH26P		
Mounting			Vertio	cal	Horizontal		
Dimensions	Unit HeightxWidthxDepth	mm	2,000x1,006x85	2,000x1,300x85	1,300x2,000x85		
Weight	Unit	kg	33		42		
Volume		L	1.30	1.70	2.10		
Surface	Outer	m²	2.01	2	.60		
	Aperture	m²	1,800	2,	360		
	Absorber	m²	1.80	2	.36		
Coating			Micro-therm	(absorption max. 96%, Emission	ca. 5% +/-2%)		
Absorber			Harp-shaped copper pipe regis	ster with laser-welded highly sel	ective coated aluminium plate		
Glazing			Single	/- 92%			
Allowed roof an	gle Min. ~ Max.	٥	15 ~ 80				
Operating press	sure Max.	bar		6			
Stand still temperature	Max.	°C		192			
Thermal	Collector efficiency (ηcol)	%		53			
performance	Zero loss collector efficiency η0	%		0.71			
	Heat loss coefficient a1	W/m².K		4,300			
	Temperature dependence of the heat loss coefficient a2	W/ m².K²		0.006			
	Thermal capacity	kJ/K	4.90	.50			

EKSRPS4A/EKSRDS2A

Pump station

- > Save energy and reduce CO_2 emissions with a solar system for domestic hot water production
- > Pump station connectable to drain-back solar system
- > Pump station and control provide the transfer of solar heat to the domestic hot water tank

More details and final information can be found by scanning or clicking the QR codes.



EKSRPS4








Accessory			EKSRPS4A	EKSRDS2A		
Mounting			On side of tank	On wall		
Dimensions	Unit HeightxWi	dthxDepth mm	815x142x230	410x314x154		
Weight	Unit	kg	6.40	6		
Operation range	Ambient temperature Min. ~ N	1ax. °C	5 ~ 40	-~40		
Operating pressure	e Max.	bar	-	6		
Stand still temperature	e Max.	°C	85	120		
Control	Type		Digital temperature difference of	controller with plain text display		
	Power consumption	W	2	5		
Sensor	Solar panel temperature senso	r	Pt10	000		
	Storage tank sensor		PTC	-		
	Return flow sensor		PTC	-		
	Feed temperature and flow se	nsor	Voltage signal (3.5V DC)	-		
Power supply	Phase/Frequency/Voltage	Hz/V	1 ~/50/230	-/50/230		
Power supply intal	(e		Indoo	or unit		
Auxiliary	Solpump	W	37.3	23		
	Annual auxiliary electricity consump	otion Qaux kWh	92.1	89		
	Solstandby	w	2.00	5.00		


Biddle air curtains Biddle air curtains provide highly efficient solutions for retailers and consultants to combat the issue of climate separation across their outlet or office doorway.

Biddle air curtain portfolio



Туре	Product name	Features	
Biddle standard air curtain free hanging	CYV S/M/L-DK-F	- CYQ - Biddle air curtain for connection to ERQ - Connectable to ERQ heat pump - Cassette model (C): mounted into a false ceiling leaving only	
Biddle		the decoration panel visible - Free-hanging model (F): easy wall mounted installation	
standard air curtain cassette	CYV S/M/L-DK-C	Recessed model (R): neatly conceiled in the ceiling	
		A payback period of less than 1.5 years compared to installing an electric air curtain	
Biddle standard air curtain recessed	CYV S/M/L-DK-R	- Easy and quick to install at reduced costs since no additional water systems, boilers and gas connections are required	(1)

Biddle air curtain nomenclature



Biddle air curtain for VRV and Conveni-pack

- > Connectable to VRV heat recovery, heat pump and Conveni-pack
- > VRV is among the first DX systems suitable for connection to air curtains
- > Free-hanging model (F): easy wall mounted installation
- > Cassette model (C): mounted into a false ceiling leaving only the decoration panel visible
- > Recessed model (R): neatly concealed in the ceiling
- > A payback period of less then 1.5 years compared to installing an electric
- > Provides virtually free air curtain heating via recovered heat from indoor units in cooling mode (in case of VRV heat recovery)
- > Easy and quick to install at reduced costs since no additional water systems, boilers and gas connections are required
- > PATENTED TECHNOLOGY: Maximum energy efficiency stemming from almost zero down flow turbulence, optimised air flow and the application of advanced discharge rectifier technology
- > Around 85% air separation efficiency, greatly reducing both heat loss and required indoor unit heating capacity





More details and final information can be found by scanning or clicking the QR codes.

in 2023



Medium

	BIDDLE COMFOR	T AIR CURTAIN (CA)		CYVS100DK80 *BC/*SC	CYVS150DK80 *BC/*SC	CYVS200DK100 *BC/*SC	CYVS250DK140 *BC/*SC	CYVM100DK80 *BC/*SC	CYVM150DK80 *BC/*SC	CYVM200DK100 *BC/*SC	CYVM250DK140 *BC/*SC
Heating capacity	Speed 3		kW	7.40	9.0	11.6	16.2	9.2	11.0	13.4	19.9
Power input	Fan only	Nom.	kW	0.23	0.35	0.46	0.58	0.37	0.56	0.75	0.94
	Heating	Nom.	kW	0.23	0.35	0.46	0.58	0.37	0.56	0.75	0.94
Delta T	Speed 3		K	19	1	5	16	17	14	13	15
Casing	Colour						BN: RAL9010 /	SN: RAL900	5		
Dimensions	Unit	Height F/C/R	mm	270/270/270							
		Width F/C/R	mm	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548
		Depth F/C/R	mm				590/8	21/561			
Required ceiling vo	oid >		mm	420							
Door height	Max.		m	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)
Door width	Max.		m	1.0	1.5	2.0	2.5	1.0	1.5	2.0	2.5
Weight	Unit		kg	56	66	83	107	57	73	94	108
Fan-Air flow rate	Heating	Speed 3	m³/h	1,164	1,746	2,328	2,910	1,605	2,408	3,210	4,013
Sound pressure level	Heating	Speed 3	dBA	47	49	50	51	50	51	53	54
Refrigerant	Type / GWP						R-410A	/ 2,087.5			
Piping connections	Liquid/OD/Gas/0	DD	mm	9.52/15.9 9.52/19.1 9.52/15.9					9.52/19.1		
Required accessori	es (should be orde	ered separately)		Daikin wired remote control (BRC1H51(9)W/S/K / BRC1E53A/B/C / BRC1D52)							
Power supply	Voltage		V				23	30			

Small

					La	rge				
				CYVL100DK125*BC/*SC	CYVL150DK200*BC/*SC	CYVL200DK250*BC/*SC	CYVL250DK250*BC/*SC			
Heating capacity	Speed 3		kW	15.6	23.3	29.4	31.1			
Power input	Fan only	Nom.	kW	0.75	1.13	1.50	1.88			
	Heating	Nom.	kW	0.75	1.13	1.50	1.88			
Delta T	Speed 3		K	1.	5	14	12			
Casing	Colour				BN: RAL9010	/ SN: RAL9006				
Dimensions	Unit	Height F/C/R	mm		370/3	70/370				
		Width F/C/R	mm	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548			
		Depth F/C/R	mm		774/1,105/745					
Required ceiling vo	oid >		mm	520						
Door height	Max.		m	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)			
Door width	Max.		m	1.0	1.5	2.0	2.5			
Weight	Unit		kg	76	100	126	157			
Fan-Air flow rate	Heating	Speed 3	m³/h	3,100	4,650	6,200	7,750			
Sound pressure level	Heating	Speed 3	dBA	53	54	56	57			
Refrigerant	Type / GWP			R-410A / 2,087.5						
Piping connections	Liquid/OD/Ga	as/OD	mm	mm 9.52/15.9 9.52/19.1 9.52/22.2						
Required accessories (should be ordered separately)				Daikin wired remote control (BRC1H51(9)W/S/K / BRC1E53A/B/C / BRC1D52)						
Power supply	Voltage		V		2:	30				

⁽¹⁾ Favorable conditions: covered shopping mall or revolving door entrance (2) Normal conditions: little direct wind, no opposite open doors, building with ground floor only

(3) Unfavorable conditions: location at a corner or square, multiple floors and/or open stairway





Commercial Ventilation & Air Purification

	Why choose Daikin ventilation	156					
	ERV / HRV - Energy/Heat recovery						
	ventilation units	158					
NEW	ATB-L/S - Modular Top Smart	160					
	ALB-LBS/RBS - Modular L Smart	162					
	Electrical heater for Modular L Smart	163					
	VAM-FC9/J8	164					
	Electrical heater for VAM	165					
	EKVDX - DX coil for air processing	166					
	VKM-GBM	168					
NEW	Plug & Play Heat Recovery Ventilation Unit	169					
	Daikin air handling units with DX connection						
	Advantages	170					
	Overview of VRV & ERQ condensing units	171					
	Control possibilities	172					
	Integration in third party AHU	176					
	Expansion valves & Control boxes	177					
	Commercial air purifier	178					
	Advantages	178					
	BR00000554/676/749/751 -	170					

Want to know more about ventilation systems and how Indoor Air Quality can be secured by ventilation? Follow our online webinar!







Market leading controls& connectivity

- > Interlock of ventilation and air conditioning system
 - Control ERV/HRV and air conditioning from the same controller
 - Aligns the operation mode between the systems to save energy
- > Easy integration in the total solution
 - Online control and monitoring via the Daikin Cloud Service
 - Full portfolio integration in the intelligent Touch Manager, Daikin's cost-effective mini BMS
- > User-friendly controller with premium design
 - · Intuitive touch button control















- > Integrates seamlessly in the Daikin total solution, ensuring a single point of contact
- > Total fresh air solution with Daikin supplying the VAM/Modular L Smart, Modular Top (smart) and the electrical heater
- > Daikin AHU and condensing unit connect Plug & Play thanks to same pipe diameters, factory mounted controls, expansion valves, etc.







- > Energy recovery of up to 92%, reducing running costs
- > Free nighttime cooling using fresh outside air
- > Inverter driven centrifugal fans
- > ErP compliant



4 Best comfort

- > Wide range of units to control fresh air and humidity
- > Wide range of optional filters to suit the application available up to ePM, 80% (F9)
- Special paper heat exchanger recovers heat and moisture from extract air to warm up and humidify fresh air to comfortable levels (VAM, VKM)



5 Top reliability

- > Most extensive testing before new units leave the factory
- > Widest support network and after sales service
- > All spare parts available in Europe



Did you know?

CO₂ levels and ventilation rates all have significant, independent impacts on cognitive function:

COGNITIVE FUNCTION SCORES ...



+ 61%
IN GREEN BUILDING
CONDITIONS



IN ENHANCED

GREEN BUILDING CONDITIONS

Widest range of DX integrated ventilation on the market

Daikin offers a variety of solutions from small energy recovery ventilation to large-scale air handling units for the provision of fresh air ventilation to homes, or commercial premises.

Ventilation solutions

Daikin offers state-of-the-art ventilation solutions that can easily be integrated into any project:

- > Unique portfolio within DX manufacturers
- > High-quality solutions complying with the highest Daikin quality standards
- > Seamless integration of all products to provide the best indoor climate
- > All Daikin products connected to a single controller for **complete control** of the HVAC system.

Energy Recovery Ventilation


Our energy recovery units **recover sensible energy** (Modular L Pro / Modular L Smart / Modular Top / Modular Smart) or **total (sensible + latent) energy** (VAM/ EKVDX/VKM-GBM), substantially reducing the load on the air conditioning system up to 40%.

Ventilation with DX connection - Control over fresh air temperature

Daikin offers a range of inverter condensing units to be used in combination with Daikin AHUs for ultimate control over the fresh air. There are 4 control possibilities when **combining AHU and Daikin outdoor units** hence offering all the required flexibility for any installation. Indoor units can be combined to the same outdoor unit to reduce the installation costs. For **false-ceiling installations** where space is a constraint, the VKM can fit perfectly to deliver fresh air at a comfortable temperature and it has an optional humidification element.

Indoor Environment Quality Components

- > Ventilation: Ensures the provision of fresh and clean air
- > **Energy recovery:** Delivers energy savings by transferring heat and moisture between airflows thus helping to bring supply air to the required indoor conditions for temperature and humidity
- > **Air processing:** Delivers the required conditioned air to optimize the energy efficiency of indoor HVAC equipment
- > Humidification: Ensures the desired moisture level in the conditioned space
- > Filtration: Ensures clean and healthy air by filtering out pollen, dust, odors and other contaminants that are harmful to our health



Modular T Smart

Top connected Air Handling Unit

Highlights

- > Duct connections are located at the top, reducing the unit's footorint
- > Low power consumption and low SFP (Specific Fan Power) for a very efficient unit operation
- Superior IAQ level: up to three stage filtration on supply side (more than the 90% of PM1 is removed from outdoor air)
- > Plug&Play control solution, for a quick and easy start-up
- > Very compact unit, starting from 550 mm width, for an air flow up to $1,100 \text{ m}^3/\text{h}$
- DX coil integration for a unique Daikin fresh air package available for connection to VRV or ERQ

IAQ matters

An excellent IAQ improves people's performance and well-being, and decreases risk factors for various diseases. Modular T satisfies the ventilation and filtration needs of the indoor environment, guaranteeing an outstanding level of IAQ.

The future of ventilation

The Modular T, with its unique features, represents the latest product developed by Daikin for fresh air treatment and not only. Thanks to its optimized design, it can be easily transported and installed into new projects or existing buildings.



More details and final information can be found by scanning or clicking the QR codes.



Technical details

MODULAR T Pro & Smart	Size (1)	03	04	05	06	07
Airflow	m³/h	800	1,650	2,300	2,700	3,900
HE Thermal efficiency (2)	%	89.3	88.3	85.1	85.5	90.8
External static pressure	Pa			100		
Current	Α	1.70	3.39	4.61	5.17	7.87
Power input	kW	0.39	0.78	1.06	1.19	1.81
SFPv (2)	kW/m³/s	1.47	1.5	1.49	1.41	1.5
	Phase (ph)			1		
Electrical supply	Frequency (Hz)			50/60		
	Voltage (V)			220/240 Vac		
	Width (mm)	550		790		890
Main unit Dimensions	Height (3) (mm)	1,6	00	1,900	1,850	2,050
	Length (mm)	1,580	1,650	2,170 (4)	2,620 (5)	2,950 (5)
Circular duct flange	Diameter (mm)	255	315	355	400	500
Unit sound power level	dBA	57	52	5	5	58
Unit sound pressure level (6)	dBA	50	45	4	8	51
Weight unit	Kg	200	250	400	500	620


(1) All size available in Smart or Pro version and right or left handing | (2) Outdoor condition: -5°C, 90% Indoor condition: 25°C, 50% | (3) Including feet and duct connections | (4) Size 05 is provided in two sections | (5) Size 06 and 07 are provided in three sections | (6) Simple source reference value at 1 meter, directivity factor Q=4 (quarter sphere) and non-reverberant field. Allowances on declared values: +/- 3dB

Air flow range

Modular T is available in 5 sizes covering a wide range of applications such as hotels, offices, schools, gyms and light commercial buildings.

Sectioning

To ensure an easy and quick installation Modular T size 05 will be provided in two sections, while size 06 and 07 in three sections to pass smoothly through standard doors¹.



1. Please refer to technical data table at page 6 for more details



Modular L Smart

Premium efficiency heat recovery unit

Highlights

- > Connects Plug&Play into the Sky Air and VRV control network
- > Easy installation and commissioning
- Internal pre-filter stage (up to ePM₁ 50% (F7) + ePM₁ 80% (F9)) making the unit reach highest indoor air quality requirements.
- Wide air flow coverage from 150m³/h to 3,400m³/h
- > Exceeding ErP 2018 requirements
- Best choice when compactness is needed (only 280 mm height up to 550 m³/h)
- > 50 mm double skin panel (120 kg/m³) for a maximum sound and thermal insulation

EC centrifugal fan

- Maximum ESP available 600 Pa (depending on model sizes and airflow)
- > Inverter driven with IE4 premium efficiency motor
- > High-efficient blade profiling
- > Reduced energy consumption
- Optimized SFP (Specific Fan Power) for an efficient unit operation

Heat exchanger

- > Premium quality counter flow plate heat exchanger
- > Up to 91% of the thermal energy recovered
- > High grade aluminum allowing optimum corrosion protection



Right drain connection (ALB-RBS)



Left drain connection (ALB-LBS)

More details and final information can be found by scanning or clicking the QR codes.







Technical details

D-AHU Modular L Smart			ALB02*BS	ALB03*BS	ALB04*BS	ALB05*BS	ALB06*BS	ALB07*BS
Airflow		m³/h	300	600	1,200	1,600	2,300	3,000
Heat exchanger thermal ef	fficiency (1)	%	8	16		87		86
External static pressure	Nom.	Pa			10	00		
Current	Nom.	Α	0.61	1.35	2.26	2.83	4.39	6.22
Power input	Nom.	kW	0.14	0.31	0.52	0.65	1.01	1.43
SFPv (2)		kW/m³/s	1.25	1.52	1.3	1.35	1.35	1.51
Electrical supply	Phase	ph				1		
	Frequency	Hz			50	/60		
	Voltage	V			220/2	40 Vac		
Main unit dimensions	Width	mm	920	1,100	1,6	500	2,0	000
	Height	mm	280	350	4	15	5	00
	Length	mm	1,660	1,800		2,0	000	
Rectangular duct flange	Width	mm	250	400	50	00	70	00
J	Height	mm	150	200	30	00	4	00
Weight unit		kg	125	180	270	280	355	360

⁽¹⁾ Winter design condition: Outdoor: -5°C, 90% Indoor: 22°C, 50% | (2) SFPv is a parameter that quantifies the fan efficiency (the lower it is the better will be). This reduces if airflow decreases.

Electrical heater for Modular L Smart

- > Total solution for fresh air with Daikin supply of both Modular L Smart and electrical heaters
- > Increase comfort in low outdoor temperature thanks to the heated outdoor air
- Integrated electrical heater concept (no additional accessories required)
- > Standard dual flow and temperature sensor
- > Heater only consumes what is required to pre-heat to the desired minimum fresh air temperature; thus saving energy





Electrical heater for Modular L Smart (ALD)	02HEFB	03HEFB	05HEFB	07HEFB
Capacity kW	1.5	3	7.5	15
Connectable Modular L Smart size	02	03	04, 05	06, 07
Supply voltage	230\	/,1ph	400\	/,3ph
Output current (maximum) (A)	6.6	13.1	10.9	21.7
Temperature sensor	15k ohms at -20 °C 10k ohms at +10 °C	16k ohms at -20 °C 10k ohms at +10 °C	17k ohms at -20 °C 10k ohms at +10 °C	18k ohms at -20 °C 10k ohms at +10 °C
Temperature control range		- 20 °C	to 10 °C	
Control fuse		Mini Circuit	Breaker 6 A	
LED indicators		Yellow = A Red = F		
Mounting holes		Depends o	n duct size	
Maximum ambient adjacent to terminal box		30°C (during	g operation)	
Auto high temperature cutout		75°C P	re-set	
Manual reset high temperature cutout		120°C F	Pre-set	
Width (mm)	470	620	720	920
Depth (mm)	370	370	370	370
Height (mm)	193	243	343	443


Energy recovery ventilation

Ventilation with heat recovery as standard

- Thinnest High Efficiency Enthalpy Heat Exchanger in the market (J-series)
- Energy saving ventilation using indoor heating, cooling and moisture recovery
- Free cooling possible when outdoor temperature is below indoor temperature (eg. during nighttime)
- Prevent energy losses from over-ventilation while improving indoor air quality with optional CO, sensor (J-series)
- > Possibility to change ESP via wired remote control allows optimisation of the supply air volume (J series)
- > Can be used as stand alone or integrated in the Sky Air or VRV system
- \rightarrow Wide range of units: air flow rate from 150 up to 2,000 m³/h
- Shorter installation time thanks to easy adjustment of nominal air flow rate, so less need for dampers compared with traditional installation
- > No drain piping needed
- > Can operate in over- and under pressure
- > Total solution for fresh air with Daikin supply of both VAM / VKM and electrical heaters
- > VAM-J8 series are connectable to EKVDX DX coil for air processing
- Possibility of CO₂ concentration when combining VAM-J8 with optional BRYMA CO₂ sensor and Madoka remote controller (with or without EKVDX)

More details and final information can be found by scanning or clicking the QR codes.

Ventilation







VAM/VAM 150FC9 250FC9 350J8 500J8 650J8 800J8 1000J8 1500J8 2000J8





Ventuation			V/1	IVI/ V /\IVI	1501 65	2301 63	33030	30030	05050	00030	100030	150050	200030
Power input - 50Hz	Heat exchange mode	Nom.	Ultra high/High/Low	kW	0.132/0.111/ 0.058	0.161/0.079/ 0.064	0.097/0.070/ 0.039	0.164/0.113/ 0.054	0.247/0.173/ 0.081	0.303/0.212/ 0.103	0.416/0.307/ 0.137	0.548/0.384/ 0.191	0.833/0.614/ 0.273
	Bypass mode	Nom.	Ultra high/High/Low	kW	0.132/0.111/ 0.058	0.161/0.079/ 0.064	0.085/0.061/ 0.031	0.148/0.100/ 0.045	0.195/0.131/ 0.059	0.289/0.194/ 0.086	0.417/0.300/ 0.119	0.525/0.350/ 0.156	0.835/0.600/ 0.239
Temperature exchange efficiency - 50Hz	Ultra high/	/High/Lo	w	%		74.9(1)/69.5(2)/ 76.0(1)/70.0(2)/ 80.1(1)/72.0(2)	85.1/86.7/ 90.1	80.0/82.5/ 87.6	84.3/86.4/ 90.5	82.5/84.2/ 87.7	79.6/81.8/ 86.1	83.2/84.8/ 88.1	79.6/81.8/ 86.1
Enthalpy exchange efficiency - 50Hz	Cooling	Ultra hig	gh/High/Low	%	60.3(1)/61.9(1)/ 67.3(1)	60.3(1)/61.2(1)/ 64.5(1)	65.2/67.9/ 74.6	59.2/61.8/ 69.5	59.2/63.8/ 73.1	67.7/70.7/ 76.8	62.6/66.4/ 74.0	68.9/71.8/ 77.5	62.6/66.4/ 74.0
	Heating	Ultra hig	gh/High/Low	%	66.6(1)/67.9(1)/ 72.4(1)	66.6(1)/67.4(1)/ 70.7(1)	75.5/77.6/ 82.0	69.0/72.2/ 78.7	73.1/76.3/ 82.7	72.8/75.3/ 80.2	68.6/71.7/ 77.9	73.8/76.1/ 80.8	68.6/71.7/ 77.9
Operation mode							Heat exc	hange mod	le, bypass m	node, fresh-	up mode		
Heat exchange syst	em					Ai		flow total h				nge	
Heat exchange elen	nent						Spe	cially proce			aper		
Dimensions	Unit	Heightx	WidthxDepth	mm		76x525	301x1,1	13x886	368x1,354x920		54x1,172	731x1,3	54x1,172
Weight	Unit			kg	24	4.0	46	6.5	61.5		9.0	15	57
Casing	Material								nised steel				
Fan	Air flow rate - 50Hz		nge Ultra high/High/ Low	m³/h		250/230/155	350 (1)/300 (1)/ 200 (1)	500 (1)/425 (1)/ 275 (1)	650 (1)/550 (1)/ 350 (1)	800 (1)/680 (1)/ 440 (1)	1,000 (1)/850 (1)/ 550 (1)	1,500 (1)/1,275 (1)/ 825 (1)	2,000 (1)/1,700 (1)/ 1,100 (1)
		Bypass mode	Ultra high/High/ Low	m³/h	150/140/105	250/230/155	350 (1)/300 (1)/ 200 (1)	500 (1)/425 (1)/ 275 (1)	650 (1)/550 (1)/ 350 (1)	800 (1)/680 (1)/ 440 (1)	1,000 (1)/850 (1)/ 550 (1)	1,500 (1)/1,275 (1)/ 825 (1)	2,000 (1)/1,700 (1)/ 1,100 (1)
	External static pressure - 50Hz		gh/High/Low	Pa	90/87/40	70/63/25			90	(1)/70.0/50.0) (1)		
Air filter	Туре				Multidirection	al fibrous fleeces			Multidirecti	onal fibrous	fleeces (G3	3)	
Sound pressure level - 50Hz	Heat exchange mode	Ultra hig	gh/High/Low	dBA	27.0/26.0/ 20.5	28.0/26.0/ 21.0	34.5 (1)/32.0 (1)/ 29.0 (1)	37.5 (1)/35.0 (1)/ 30.5 (1)	39.0 (1)/36.0 (1)/ 31.0 (1)	39.0 (1)/36.0 (1)/ 30.5 (1)	42.0 (1)/38.5 (1)/ 32.5 (1)	42.0 (1)/39.0 (1)/ 33.5 (1)	45.0 (1)/41.5 (1)/ 36.0 (1)
	Bypass mode	Ultra hig	gh/High/Low	dBA	27.0/26.5/ 20.5	28.0/27.0/ 21.0	34.5 (1)/32.0 (1)/ 28.0 (1)	38.0 (1)/35.0 (1)/ 29.5 (1)	38.0 (1)/34.5 (1)/ 30.5 (1)	40.0 (1)/36.5 (1)/ 30.5 (1)	42.5 (1)/40.0 (1)/ 32.5 (1)	42.0 (1)/39.0 (1)/ 32.5 (1)	45.0 (1)/41.0 (1)/ 35.0 (1)
Operation range	Around un	it		°CDB		-			0°C~40°	CDB, 80% R	H or less		
Connection duct di	ameter			mm	100	150	20	00		250		2x2	250
Power supply	Phase/Free	quency/\	/oltage	Hz/V				1~; 50	0/60; 220-24	0/220			
Current	Maximum	fuse amp	os (MFA)	Α	15	5.0				16.0			
Specific energy	Cold clima	te		kWh/(m².a)	-56.0 (5)	-60.5 (5)				-			
consumption (SEC)	Average cl	imate		kWh/(m².a)	-22.1 (5)	-27.0 (5)				-			
	Warm clim	ate		kWh/(m².a)	-0.100 (5)	-5.30 (5)				-			
SEC class					D / See note 5	B / See note 5				-			
Maximum flow rate	Flow rate			m³/h	130	207				-			
at 100 Pa ESP	Electric po	wer inpu	it	W	129	160				-			
Sound power level	(Lwa)			dB	40	43	51	54	5	8	61	62	65
Annual electricity of	onsumptio	n		kWh/a	18.9 (5)	13.6 (5)				-			
Annual heating	Cold clima	te		kWh/a	41.0 (5)	40.6 (5)				-			
saved	Average cl	imate		kWh/a	80.2 (5)	79.4 (5)				-			
	Warm clim	ate		kWh/a	18.5 (5)	18.4 (5)				-			

Electrical heater for VAM

- > Total solution for fresh air with Daikin supply of both VAM and electrical heaters
- > Increased comfort in low outdoor temperature thanks to the heated outdoor air
- Integrated electrical heater concept (no additional accessories required)
- > Standard dual flow and temperature sensor
- > Flexible setting with adjustable setpoint
- > Increased safety with 2 cut-outs: manual & automatic



More details and final information can be found by scanning or clicking the QR codes.

Capacity

Duct diameter



35530⁽¹⁾

355

25030

3.0

250

Connectable VAM				VAM150FC9	VAM250FC9	VAM350,500J8	VAM650J8, VAM800J8, VAM1000J8	VAM1500J8, VAM2000J8
				GSIEKA10009	GSIEKA15018	GSIEKA20024	GSIEKA25030	GSIEKA35530
		Height	mm	171	221	271	321	426
Dimensions		Depth	mm	100	150	200	250	355
		Width	mm	370	370	370	370	373
			m/s			1.5		
Minimum air velocity / airflow			m³/h	45	100	170	265	535
Power supply					ı	1~230 VAC/50Hz		ı
Nominal current			Α	4.1	8.2	10.9	13.1	13.1
Heating power			kW	0.9	1.8	2.4	3.0	3.0
Connection duct diameter			mm	100	150	200	250	355
		Min.	°C			-40°C		
Operation range		Max.	°C			40°C		
		Rel. Humidity	%			90%		
Temperature sensor		·			10) kΩ at +25°C / TJ-K10	OK	
Temperature sensor range						- 30°C to 105°C		
Temperature set point range						- 10°C to 50°C		
		flashing every 5	seconds			heater is starting up)	
	LED 1	flashing every	second		air flow	detected, heating a	allowed	
LED indicators	LED 1	OFF			noı	power supply or no	flow	
LED Indicators		ON		problem with	duct temperature	sensor, set point pot	entiometer or PTC a	airflow sensor
	LED 2	OFF			h	eater is not operation	n	
	LED 2	ON				heater is operating		
Ambient temperature adjacent to	controller					0°C to +50°C		
Auto high temperature cut-out						50°C		
Manual reset high temperature cu	t-out					100°C		

10009

0.9

100

GSIEKA

kW

mm

15018

1.8

150


20024

2.4


200


EKVDX-A


DX coil for post treatment of fresh air



- > Creates a high quality indoor environment by pre conditioning of incoming fresh air
- > Maximum installation flexibility thanks to separate DX coil
 - Different installation possibilities to suit the application








- > Fresh air flows from 500 up to 2,000 m³/h
- > High ESP up to 150 Pa
- > Can be integrated in both R-32/R-410A VRV systems
- > Replaces VKM-GB range, delivering increased capacity range and reduced sound levels

DX coil for air processing

Post heating or cooling of fresh air to lower the load on the air conditioning system

- Creates a high quality indoor environment by pre conditioning of incoming fresh air
- > Maximum installation flexibility thanks to separate DX coil
- > Wide range of units covering fresh air flows of 500 up to 2,000 m³/h
- > High ESP up to 150 Pa
- > Can be integrated in both R-32/R-410A VRV systems



More details and final information can be found by scanning or clicking the QR codes.



					EKVDX32A	EKVDX50A	EKVDX80A	EKVDX100A
Power input - 50Hz	Cooling	Nom.		kW	0.035	0.035	0.035	0.035
	Heating	Nom.		kW	0.035	0.035	0.035	0.035
Casing	Material					Galvanised	d steel plate	
Insulation material						Opcell and ant	i-sweat material	
Dimensions	Unit	Height		mm		2	50	
		Width		mm	550	700	1,000	1,400
		Depth		mm		8	09	
Weight	Unit			kg	19	23.4	30.1	37.7
Operation range	Around u	nit		°CDB		10°C~40°CDB,	80% RH or less	
	On coil	Cooling	Max.	°CDB		3	35	
	temperatur	e Heating	Min.	°CDB		•	11	
Piping connections	Liquid	OD		mm		6.	.35	
	Gas	OD		mm		12	2.7	
	Drain					VP20 (I.D. 20/O.D. 26)	, drain height 625 mm	
Refrigerant	Type					R410.	A/R32	
	GWP					2,087	7.5/675	
Heat exchange syst	em					Direct e	xpansion	
Power supply	Phase					single	phase	
	Frequenc	у		Hz		50	/60	
	Voltage			V		220-2	40/220	

					EKVDX32A + VAM500J8	EKVDX50A + VAM650J8	EKVDX50A + VAM800J8	EKVDX80A + VAM1000J8	EKVDX100A + VAM1500J8	EKVDX100A + VAM2000J8
Cooling capacity	Total (VAM	+DX coil)	At ultra high fan speed	kW	5.1	7.1	8.6	9.3	15.4	18.4
	DX coil		At ultra high fan speed	kW	3.4	4.8	5.5	5.7	9.5	11.2
			At high fan speed	kW	2.7	4.1	4.4	4.5	8.8	9.2
Heating capacity	Total (VAM	+DX coil)	At ultra high fan speed	kW	6.7	8.5	11	11.9	18.7	22.9
	DX coil		At ultra high fan speed	kW	4.2	5.1	6.9	7	10.8	13
			At high fan speed	kW	3.6	4.6	5.8	6.3	9.6	11.7
Fan	Air flow	Heat exchange	Ultra high	m³/h	500	650	800	1,000	1,500	2,000
	rate -	mode	High	m³/h	425	550	680	850	1,275	1,700
	50Hz	Bypass	Ultra high	m³/h	500	650	800	1,000	1,500	2,000
		mode	High	m³/h	425	550	680	850	1,275	1,700
	External static	Maximum		Pa	81.9	73.0	133.7	106.0	153.6	92.1
	pressure -	Ultra high		Pa	51.9	43.0	23.7	26.0	43.6	12.1
	50Hz	High		Pa	39.0	33.9	19.4	21.4	35.1	11.9
Sound pressure	Cooling		Ultra high	dBA	32	34	35.5	40.5	38.5	43.5
level - 50Hz			High	dBA	30.5	32	34	38	37	40
	Heating		Ultra high	dBA	32.5	34.5	36	40.5	39	44
			High	dBA	31.5	32	34	38.5	37	40.5
Current	Maximum	fuse amps ((MFA)	Α	6	6	6	6	16	16

 $The heat \, reclaim \, ventilation \, unit \, and \, the \, EKVDX \, indoor \, unit \, \, MUST \, share \, the \, same \, electrical \, safety \, devices \, and \, power \, supply \, and \, safety \, devices \, and \, power \, supply \, devices \, and \, po$

Energy recovery ventilation, humidification and air processing

Post heating or cooling of fresh air for lower load on the air conditioning system

- > Energy saving ventilation using indoor heating, cooling and moisture recovery
- > Creates a high quality indoor environment by pre conditioning of incoming fresh air
- > Humidification of the fresh air results in comfortable indoor humidity level, even during heating
- > Free cooling possible when outdoor temperature is below indoor temperature (eg. during nighttime)
- > Low energy consumption thanks to DC fan motor
- > Prevent energy losses from over-ventilation while improving indoor air quality with optional CO₂ sensor
- Shorter installation time thanks to easy adjustment of nominal air flow rate, so less need for dampers compared with traditional installation
- Specially developed heat exchange element with High Efficiency Paper (HEP)
- > Can operate in over- and under pressure



80GBM

More details and final information can be found by scanning or clicking the QR codes.

Ventilation



ventilation		VKI	n-GBM	DUGBIN	BUGBINI	IUUGBINI
Power input - 50Hz	Heat exchange mode N	lom. Ultra high/ High/Low	kW	0.270/0.230/0.170	0.330/0.280/0.192	0.410/0.365/0.230
	Bypass mode N	lom. Ultra high/ High/Low	kW	0.270/0.230/0.170	0.330/0.280/0.192	0.410/0.365/0.230
Fresh air	Cooling		kW	4.71 / 1.91 / 3.5	7.46 / 2.96 / 5.6	9.12 / 3.52 / 7.0
conditioning load	Heating		kW	5.58 / 2.38 / 3.5	8.79 / 3.79 / 5.6	10.69 / 4.39 / 7.0
Temperature exchange efficiency - 50Hz	e Ultra high/High/Lo	w	%	76/76/77.5	78/78/79	74/74/76.5
Enthalpy exchange	Cooling L	lltra high/High/Low	%	64/64/67	66/66/68	62/62/66
efficiency - 50Hz	Heating L	lltra high/High/Low	%	67/67/69	71/71/73	65/65/69
Operation mode				Heat exch	nange mode / Bypass mode / Fresh-	-up mode
Heat exchange sys	tem			Air to air cross	flow total heat (sensible + latent h	eat) exchange
Heat exchange ele	ment			Spe	cially processed non-flammable pa	per
Humidifier	System				Natural evaporating type	
Dimensions	Unit H	leightxWidthxDepth	mm	387x1,764x832	387x1,76	54x1,214
Weight	Unit		kg	100	119	123
Casing	Material				Galvanised steel plate	
Fan-Air flow rate	Heat exchange mode U	lltra high/High/Low	m³/h	500/500/440	750/750/640	950/950/820
· 50Hz	Bypass mode L	lltra high/High/Low	m³/h	500/500/440	750/750/640	950/950/820
Fan-External static pressure - 50Hz	Ultra high/High/Lo	W	Pa	200/150/120	205/155/105	110/70/60
Air filter	Type				Multidirectional fibrous fleeces	
Sound pressure	Heat exchange mode U	lltra high/High/Low	dBA	38/36/34	40/37.5/35.5	40/38/35.5
level - 50Hz	Bypass mode L	lltra high/High/Low	dBA	39/36/34.5	41/38/36	41/39/35.5
Operation range	Around unit		°CDB		0°C~40°CDB, 80% RH or less	
	Supply air		°CDB		-15°C~40°CDB, 80% RH or less	
	Return air		°CDB		0°C~40°CDB, 80% RH or less	
	On coil temperature C	ooling/Max./Heating/Min.	°CDB		-15/43	
Refrigerant	Control				Electronic expansion valve	
	Type				R-410A	
	GWP				2,087.5	
Connection duct d	iameter		mm	200	25	50
Piping connection	s Liquid C	D	mm		6.35	
	Gas C	D	mm		12.7	
	Water supply		mm		6.35	
	Drain				PT3/4 external thread	
Power supply	Phase/Frequency/	/oltage	Hz/V		1~/50/220-240	
Current	Maximum fuse am	os (MFA)	Α		15	


50GBM

VKM-GBM




For Schools and light commercial applications with an immediate need for fresh air

In a public space without ventilation the CO_2 concentrations will quickly rise above 2,000ppm, while a safe and comfortable treshhold is around 1,000ppm. Staying regularly in a space above this treshold leads to fatigue and lower concentration, and can result in long-term health consequences ranging from mild allergies to serious respiratory illnesses.



The Plug & Play Heat Recovery Ventliation Unit solves your fresh air needs without the need for renovation

- > Quick installation gives your building fast access to fresh air
- > Unit does not require any ductwork for supply or return air keeping interior works to a minimum
- Premium quality counter flow plate heat exchanger recovering indoor thermal energy
- > Ceiling mounted installation
 - > Does not require space on the floor
 - > Unit is out of reach of persons or children
- Air flow range up to 930m³/h covering the typical need of a class room
- > Double skin insulated panel for a maximum sound insulation
- > Left and right version for maximum flexibility
- > Free cooling allows to cool down the room at night
- > Optional CO₂ sensor and electrical heater



Typical layout with right connection Adjacent classroom Fresh air Exhaust air Outdoors

Daikin's

air handling units solutions

You will find your match

Why choose Daikin air handling units with a DX connection?



Simplifying business

The unique total solution approach by Daikin helps businesses to propose better cross-pillar solutions, to increase their success ratio by providing unmatchable product combinations to the end-user and to simplify the life of installers by supplying high-quality products coming from the same manufacturer. Contrary to other manufacturers, Daikin does not use OEM products in its AHU with DX offer. Many competitors are either offering OEM DX outdoor units or OEM AHU which create additional problems when warranties or faults arise. **Having a single interface for your business makes Daikin the right choice.**

One-stop shop

Daikin is the only global manufacturer in the market **capable of offering a true Plug & Play solution** where Daikin AHUs manufactured by Daikin Applied Europe and certified by Eurovent, offer off-the-shelf compatibility with Daikin's unique VRV outdoor unit range for the best performance in the market. This unique integration of cross-pillar products under the same umbrella, gives the customer both peace-of-mind and added value when promoting a total solution approach.

Complete range of possibilities

Thanks to the **most complete offer in the market**, Daikin has the solution for all types of commercial applications requiring fresh air. Daikin provides ventilation solutions based on AHU from 2,500 m³/h up to 140,000 m³/h either with natural heat recovery or more advanced ventilation solutions where a VRV outdoor unit can be connected to the Daikin AHU for ultimate climate control. The harmonized control, between the VRV outdoor unit and the AHU, offer outstanding reliable operation of the system when connected to an iTM.


Advantages

- Unique manufacturer offering a complete range
- > Plug & Play solution
- Direct iTM compatibility

Why use VRV and ERQ condensing units for connection to air handling units?

High Efficiency

Daikin heat pumps are renowned for their high energy efficiency. Integrating the AHU with a high efficiency heat pump system lower the carbon footprint of the building.



Fast response to changing loads resulting in high comfort levels


Daikin ERQ and VRV units respond rapidly to fluctuations in supply air temperature, resulting in a steady indoor temperature and resultant high comfort levels for the end user. The ultimate is the VRV range which improves comfort even more by offering continuous heating, also during defrost.

Easy Design and Installation

The system is easy to design and install since no additional water systems such as boilers, tanks and gas connections etc. are required. This also reduces both the total system investment and running cost.

Daikin Fresh air package

- > Plug & Play connection between VRV/ERQ and the entire D-AHU modular range.
- > Factory fitted and welded DX coil control and expansion valve kits.



In order to maximise installation flexibility, 4 types of control systems are offered

W control: Off the shelf control of air temperature (discharge temperature, suction temperature, room temperature) via any DDC controller, easy to setup

X control: Precise control of air temperature (discharge temperature, suction temperature, room temperature) requiring


a preprogrammed DDC controller (for special applications)

Z control: Control of air temperature (suction temperature, room temperature) via Daikin control (no DDC controller needed)
Y control: Control of refrigerant (Te/Tc) temperature via Daikin control (no DDC controller needed)

1. W control $(T_d/T_s/T_{room}$ control):

Air temperature control via DDC controller


Room temperature is controlled as a function of the air handling unit suction or discharge air (customer selection). The DDC controller is translating the temperature difference between set point and air suction temperature (or air discharge temperature or room temperature) into a proportional 0-10V signal which is transferred to the Daikin control box (EKEQFCBA). This voltage modulates the capacity requirements of the outdoor unit.



3. Y control (T_e/T_c control):

By fixed evaporating / condensing temperature


A fixed target evaporating or condensing temperature can be set by the customer. In this case, room temperature is only indirectly controlled. A Daikin wired remote control (BRC1* - optional) have to be connected for initial set-up but not required for operation.



2. X control ($T_d/T_s/T_{room}$ control):

Precise air temperature control via DDC controller


Room temperature is controlled as a function of the air handling unit suction or discharge air (customer selection). The DDC controller is translating the temperature difference between set point and air suction temperature (or air discharge temperature or room temperature) into a reference voltage (0-10V) which is transferred to the Daikin control box (EKEQFCBA). This reference voltage will be used as the main input value for the compressor frequency control.



4. $Z control T_d / T_{room} control$):

Control your AHU just like a VRV indoor unit (100% recirculation air application)

Allows the possibility to control the AHU just like a VRV indoor unit. Meaning temperature control will be focused on return air temperature from the room into the AHU. Requires BRC1* for operation. The only control that allows the combination of other indoor units to the AHU at the same time.



$T_d = Discharge (supply) air temperature$	$T_s = Suction$ (return) air temperature
T _{ext} = Extraction air temperature	T _e = Evaporating temperature

 T_{oa} = Outdoor air temperature T_{c} = Condensing temperature $T_{room} = Room air temperature$

	Option kit	Features
Possibility W		Off-the-shelf DDC controller that requires no pre-configuration
Possibility X	EKEQFCBA	Pre-configured DDC controller required
Possibility Y		Using fixed evaporating temperature, no set point can be set using remote control
Possibility Z	EKEQDCB EKFOMCBA*	Using Daikin infrared remote control BRC1* Temperature control using air suction temperature or room temperature (via remote sensor)

^{*} EKEQMCB (for 'multi' application)



JRJ - for larger capacities (from 8 to 54HP)

An advanced solution for both pair and multi application

- > Inverter controlled units
- > Heat pump
- Heat recovery only for mix application with indoor units without hydrobox. For 100% recirculation AHUs only used as a VRV indoor unit.
- > R-410A
- > Control of room temperature via Daikin control

- > Large range of expansion valve kits available
- BRC1H* is used to set the set point temperature (connected to the EKEQMCBA).
- Connectable to all VRV heat recovery and heat pump systems (VRV H/R and VRV-i only connectable with Z control)

Pair application


One ERQ or VRV IV **heat pump** (system) connected to **one** AHU through **one** refrigerant **circuit**

- > with W, X, Y and Z control
- > not allowed for VRV H/R




One VRV IV heat pump (system) connected to the interlaced coil of one AHU through several refrigerant circuits

- > with W, X and Y control
- > not allowed for VRV H/R and VRV-i



Several ERQ or VRV IV **heat pumps** connected to the **interlaced coil** of one AHU through **several** refrigerant **circuits**


- > with W, X and Y control
- > not allowed for VRV H/R and VRV-i



Multi application

One VRV IV heat pump connected to several AHUs


- > with Z control
- > not allowed for VRV H/R
- > no interlaced coil possible



Mix application

VRV indoor units and AHU(s) mixed in the same VRV IV heat pump or heat recovery system

- > with Z control
- > no interlaced coil possible
- > hydrobox not possible





ERQ - for smaller capacities (from 100 to 250 class)

A basic fresh air solution for pair application

- > Inverter controlled units
- > Heat pump
- > R-410A
- > Wide range of expansion valve kits available
- > Perfect for the Daikin Modular air handling unit

The "Daikin Fresh Air Package" provides a complete Plug & Play Solution including AHU, ERQ or VRV Condensing Unit and all unit control (EKEQ, EKEX, DDC controller) factory mounted and configured. The easiest solution with only one point of contact.









ERQ-AW1

Ventilation			ERQ	100AV1	125AV1	140AV1
Capacity range			HP	4	5	6
Cooling capacity	Nom.		kW	11.2	14.0	15.5
Heating capacity	Nom.		kW	12.5	16.0	18.0
Power input	Cooling	Nom.	kW	2.81	3.51	4.53
·	Heating	Nom.	kW	2.74	3.86	4.57
EER				3.	.99	3.42
COP				4.56	4.15	3.94
Dimensions	Unit	HeightxWidthxDepth	n mm		1,345x900x320	
Weight	Unit	. reignextriating ept.	kg		120	
Casing	Material		9		Painted galvanized steel plate	
Fan-Air flow rate	Cooling	Nom.	m³/min		106	
ran An now rate	Heating	Nom.	m³/min	102		05
Sound power level		Nom.	dBA	66	67	69
			dBA	50	51	
Sound pressure level	Cooling	Nom.				53
	Heating	Nom.	dBA	52	53	55
Operation range	Cooling	Min./Max.	°CDB		-5/46	
	Heating	Min./Max.	°CWB		-20/15.5	
		Heating/Min./Cooling/Max.	°CDB		10/35	
Refrigerant	Type				R-410A	
	Charge		kg		4.0	
			TCO₂eq		8.4	
	GWP				2,087.5	
	Control				Expansion valve (electronic type)	
Piping connections	Liquid	OD	mm		9.52	
	Gas	OD	mm	15	5.9	19.1
	Drain	OD	mm		26x3	
Power supply	Phase/Frequency		Hz/V		1N~/50/220-240	
Current	Maximum fuse a		Α Α		32.0	
	Widali Tabe a	mps (ivii 7 i)				
Ventilation			ERQ	125AW1	200AW1	250AW1
Capacity range			HP	5	8	10
Cooling capacity	Nom.		kW	14.0	22.4	28.0
Heating capacity	Nom.		kW	16.0	25.0	31.5
			kW	3.52	5.22	7.42
	Cooling	Nom.				
Power input	Cooling Heating	Nom.	kW	4.00	5.56	7.70
Power input EER			kW	3.98	4.29	3.77
Power input EER			kW			-
Power input EER COP Dimensions				3.98	4.29 4.50	3.77
Power input EER COP Dimensions	Heating	Nom.		3.98 4.00	4.29 4.50	3.77 4.09
Power input EER COP Dimensions Weight	Heating Unit	Nom.	n mm	3.98 4.00 1,680x635x765	4.29 4.50 1,680x9	3.77 4.09 930x765
Power input EER COP Dimensions Weight Casing	Unit Unit Material	Nom. HeightxWidthxDepth	n mm kg	3.98 4.00 1,680x635x765 159	4.29 4.50 1,680x9 187 Painted galvanized steel plate	3.77 4.09 930x765 240
Power input EER COP Dimensions Weight Casing	Unit Unit Material Cooling	Nom.	n mm kg m³/min	3.98 4.00 1,680x635x765 159	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171	3.77 4.09 930×765 240
Power input EER COP Dimensions Weight Casing Fan-Air flow rate	Unit Unit Material Cooling Heating	Nom. HeightxWidthxDepth	m mm kg m³/min m³/min	3.98 4.00 1,680x635x765 159 95 95	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171	3.77 4.09 9330x765 240 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level	Unit Unit Material Cooling Heating Nom.	Nom.	m mm kg m³/min m³/min dBA	3.98 4.00 1,680x635x765 159 95 95 72	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171	3.77 4.09 930x765 240 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level	Unit Unit Material Cooling Heating Nom. Nom.	Nom. HeightxWidthxDepth Nom. Nom.	m mm kg m³/min m³/min dBA dBA	3.98 4.00 1,680x635x765 159 95 95	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 7	3.77 4.09 9330x765 240 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level	Unit Unit Material Cooling Heating Nom. Nom. Cooling	Nom. HeightxWidthxDepth Nom. Nom. Min./Max.	m³/min m³/min dBA dBA °CDB	3.98 4.00 1,680x635x765 159 95 95 72	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 7 57 -5/43	3.77 4.09 930x765 240 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min dBA dBA °CDB	3.98 4.00 1,680x635x765 159 95 95 72	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 57 57 -5/43 -20/15	3.77 4.09 930x765 240 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature	Nom. HeightxWidthxDepth Nom. Nom. Min./Max.	m³/min m³/min dBA dBA °CDB	3.98 4.00 1,680x635x765 159 95 95 72	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 7 57 -5/43 -20/15 10/35	3.77 4.09 930x765 240 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature Type	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min m³/min dBA dBA °CDB °CWB	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171 7 57 -5/43 -20/15 10/35 R-410A	3.77 4.09 9330x765 240 185 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min m³/min dBA dBA °CDB °CWB	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171 57 57 -5/43 -20/15 10/35 R-410A 7.7	3.77 4.09 930x765 240 185 185 78 58
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature Type Charge	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min m³/min dBA dBA °CDB °CWB	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 7 57 -5/43 -20/15 10/35 R-410A 7.7 16.1	3.77 4.09 9330x765 240 185 185 185
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature Type	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min m³/min dBA dBA °CDB °CWB	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171 57 57 -5/43 -20/15 10/35 R-410A 7.7	3.77 4.09 930x765 240 185 185 78 58
Power input EER COP Dimensions Weight Casing Fan-Air flow rate	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature Type Charge	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min m³/min dBA dBA °CDB °CWB	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 7 57 -5/43 -20/15 10/35 R-410A 7.7 16.1	3.77 4.09 930x765 240 185 185 78 58
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range Refrigerant	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature Type Charge GWP Control	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max.	m³/min m³/min dBA dBA °CDB °CWB	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 57 -5/43 -20/15 10/35 R-410A 7.7 16.1 2,087.5 Electronic expansion valve	3.77 4.09 930x765 240 185 185 78 58
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range	Unit Unit Material Cooling Heating Nom. Cooling Heating On coil temperature Type Charge GWP Control Liquid	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max. Heating/Min./Cooling/Max.	m³/min dBA dBA °CDB °CWB TCO ₂ eq	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x5 187 Painted galvanized steel plate 171 171 57 -5/43 -20/15 10/35 R-410A 7.7 16.1 2,087.5 Electronic expansion valve 9.52	3.77 4.09 930x765 240 185 185 78 58 8 58
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range Refrigerant	Unit Unit Material Cooling Heating Nom. Nom. Cooling Heating On coil temperature Type Charge GWP Control Liquid Gas	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max. Heating/Min./Cooling/Max.	m³/min m³/min dBA dBA °CDB °CWB TCO2eq mm mm	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171 7 57 -5/43 -20/15 10/35 R-410A 7,7 16.1 2,087.5 Electronic expansion valve 9,52 19.1	3.77 4.09 930x765 240 185 185 78 58
Power input EER COP Dimensions Weight Casing Fan-Air flow rate Sound power level Sound pressure level Operation range Refrigerant	Unit Unit Material Cooling Heating Nom. Cooling Heating On coil temperature Type Charge GWP Control Liquid	Nom. HeightxWidthxDepth Nom. Nom. Min./Max. Min./Max. Heating/Min./Cooling/Max.	m³/min dBA dBA °CDB °CWB °CDB TCO2eq mm	3.98 4.00 1,680x635x765 159 95 95 72 54	4.29 4.50 1,680x9 187 Painted galvanized steel plate 171 171 57 -5/43 -20/15 10/35 R-410A 7.7 16.1 2,087.5 Electronic expansion valve 9.52 19.1 3N~/50/400	3.77 4.09 930x765 240 185 185 78 58 8 58

Integration of ERQ and VRV in third party air handling units

a wide range of expansion valve kits and control boxes

Combination table

			Control box	(Expansion valve kit										
		EKEQDCB	EKEQFCBA	EKEQMCBA	EKEXV50	EKEXV63	EKEXV80	EKEXV100	EKEXV125	EKEXV140	EKEXV200	EKEXV250	EKEXV400	EKEXV500	Mixed connection
		Z control	W,X,Y control	Z control	-	-	-	-	-	-	-	-	-	-	with VRV indoor units
	ERQ100	P (1)	Р	-	-	Р	Р	Р	Р	-	-	-	-	-	
1-phase	ERQ125	P (1)	Р	-	-	Р	Р	Р	Р	Р	-	-	-	-	Not possible
	ERQ140	P (1)	Р	-	-	-	Р	Р	Р	Р	-	-	-	-	
	ERQ125	P (1)	Р	-	-	Р	Р	Р	Р	Р	-	-	-	-	
3-phase	ERQ200	P (1)	Р	-	-	-	-	Р	Р	Р	Р	Р	-	-	
	ERQ250	P (1)	Р	-	-	-	-	-	Р	Р	Р	Р	-	-	
(RYYQ, RX	V H/P YQ, RXYSQ, 'LQ, RWEYQ)	-	Р						P (1) / n2 (1))					Possible (not mandatory)
VRV IV	i-series	-	-												
VRV IV H/R					n1									Mandatory (no hydrobox)	

Capacity table

Cooling

EKEXV Class		ed heat exch capacity (kW	Allowed heat exchanger volume (dm³)			
	Minimum	Standard	Maximum	Minimum	Maximum	
50	5.0	5.6	6.2	1.33	1.65	
63	6.3	7.1	7.8	1.66	2.08	
80	7.9	9.0	9.9	2.09	2.64	
100	10.0	11.2	12.3	2.65	3.30	
125	12.4	14.0	15.4	3.31	4.12	
140	15.5	16.0	17.6	4.13	4.62	
200	17.7	22.4	24.6	4.63	6.60	
250	24.7	28.0	30.8	6.61	8.25	
400	35.4	45.0	49.5	9.26	13.2	
500	49.6	56.0	61.6	13.2	16.5	

Saturated evaporating temperature: 6°C

Air temperature: 27°C DB / 19°C WB

Heating

EKEXV Class		ed heat exch capacity (kW	Allowed heat exchanger volume (dm³)			
	Minimum	Standard	Maximum	Minimum	Maximum	
50	5.6	6.3	7.0	1.33	1.65	
63	7.1	8.0	8.8	1.66	2.08	
80	8.9	10.0	11.1	2.09	2.64	
100	11.2	12.5	13.8	2.65	3.30	
125	13.9	16.0	17.3	3.31	4.12	
140	17.4	18.0	19.8	4.13	4.62	
200	19.9	25.0	27.7	4.63	6.60	
250	27.8	31.5	34.7	6.61	8.25	
400	39.8	50.0	55.0	9.26	13.2	
500	55.1	63.0	69.3	13.2	16.5	

Saturated condensing temperature: 46°C Air temperature: 20°C DB

EKEXV - Expansion valve kit for air handling applications

Ventilation			EKEXV	50	63		80	100	125	140	200	250	400	500
Dimensions Unit			mm	401x215x78										
Weight Unit ko			kg	2.9										
Sound pressure level Nom. dBA				45										
Operation range	On coil Heating Min.		°CDB		10 (1)									
	temperatur	e Cooling Max.	°CDB						35	(2)				
Refrigerant Type / GWP				R-410A / 2,087.5										
Piping connections Liquid OD mm				6.35 9.52 12.7						15.9				

⁽¹⁾ The temperature of the air entering the coil in heating mode can be reduced to -5°CDB. Contact your local dealer for more information. (2) 45% Relative humidity.

EKEQ - Control box for air handling applications

Ventilation		EKEQ	FCBA	DCB	MCBA
Application			Pair	Pair	Pair/Multi/Mix
Outdoor unit			ERQ / VRV	ERQ	VRV
Dimensions	Unit	mm		132x400x200	
Weight	Unit	kg	3.9	3	.6
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/230	

The combination of EKEQFCBA and ERQ is in pair application. The EKEQFCBA can be connected to some type of VRV IV outdoor units with a maximum of 3 control boxes. The combination with DX indoor units, hydroboxes, RA outdoor units, ... is not allowed. Refer to the combination table drawing of the outdoor unit for details.



P (pair application) - One or more outdoor units connected to an (interlaced) coil of one AHU. To determine exact configuration please refer to the engineering data book.
 n1 (only mix application) - Combination of (multiple) AHU(s) and VRV DX indoor(s) is mandatory. To determine the exact configuration please refer to the engineering data book.
 n2 (mix or multi application) - Combination of (multiple) AHU(s) with (mix application) or without (multi application) VRV DX indoor(s). To determine the exact configuration please refer to the engineering data book.
 Control box EKEQFA can be connected to some types of VRV W outdoor units (with a maximum of 3 boxes per unit). Do not combine EKEQFA control boxes with VRV DX indoor units, RA indoor units or hydroboxes

⁽¹⁾ No interlaced coil possible with Z control



Integrating third party Air Handling Units in the VRV 5 total solution (EKEXVA* / EKEA*)





Refrigerant piping F1-F2 P1-P2

- > Unified EXV range connectable to both VRV 5 R-32 and VRV IV / ERQ R-410A units
- > 3 new EXV capacities: 300, 350 and 450, allowing maximum flexibility
- > Unified control box, offering all existing W,X,Y,Z controls + new advanced Z control
- > Complete peace of mind as Daikin provides all required tools to ensure compliance to the IEC product standard
- > Extension of operation range of EKEA: Outside installation possible down to -25°C
- > Lower connection ratio limit for pair application





Plug & play, mobile recirculation unit with high efficiency filtration – for better indoor air quality in commercial spaces

- > For areas where additional, extra high, filtration performance is needed.
- > Airflow rate up to 2,000 m³/h
- > HEPA H14 filter in accordance with EN1822
- > Pre-filter options up to ISO Coarse 70%
- > Insulated double-wall construction provides whisper-quiet operation down to 35 dB(A)
- > Easy installation, operation, and maintenance in a totally self-contained system
- > For commercial areas up to 200m²





Models

Model	BR00000554	BR00000749	BR00000676	BR00000751	
Plug type	EU	UK	EU	UK	
HEPA Filter (H14)	▼		✓		
LCD Screen			,		
Activ. Carbon (Gas phase) pre-filter			,		

Providing high-efficiency 2-stage filtration

Standard prefilter

All units are delivered with a prefilter, increasing filter life and protecting the installed HEPA filter

RedPleat - 4531002424

- > Delivered with BR00000554/749
- > ISO 16890: ISO coarse 70%
- Available with Antimicrobial treated media (RedPleat ULTRA)



RedPleat Carb - 4139002424

- > Delivered with BR00000676/751
- > ISO 16890: ISO coarse 65%
- > Effectively removes offensive odors

Applications

Universities

Commercial Buildings

Healthcare

Hospitality

Shopping malls

Main filter

The HEPA filter features eFRM filtration media which combines ultra-high efficiency and particulate loading to remove 99.99% of dust, pollen, mold, bacteria, viruses, and any airborne particle with a size of 0.3 microns or greater.

AstroCel III - 1493299990

- > H14 filtration efficiency according EN 1822
- > V-shaped filter configuration, combined with microglass media, delivers higher flow and the lowest possible pressure drop vs traditional box style HEPA filters
- > Compatible with Discrete Particle Counter (DPC) and photometric test methods as access and instrumentation allow



Astropure 2000, Air Purifier for Commercial Applications

Plug & play, mobile recirculation unit with high efficiency filtration – for better indoor air quality in commercial spaces

- > Airflow rate up to 2,000 m³/h
- > HEPA H14 filter in accordance with EN1822
- > Optional touch sensitive LCD Display (BR00000676/751)
- Insulated double-wall construction provides whisper-quiet operation
- > Activated carbon filter
- > Sliding tray design provides easy access and servicing of filters
- > Designed with internal variable fan speed (electronically commutated) to meet specific application requirements
- > Suitable for in-room use or sheltered outdoor installation
- > CE-compliance, VDI 6022 guided design









Ventilation				BR00000554	BR00000749	BR0000676	BR00000751				
	Plug type			EU	UK	EU	UK				
	HEPA Filter (H14)			•		•					
Features	LCD Screen			✓							
Activ. Carbon (Gas phase) pre-filter						,	/				
Design air flow rat	te		m³/h	2,000							
Application					Floor st	anding type					
Casing	Colour				Painted galv	anized steel finish					
Dimensions	Unit	HxWxD	mm		1,628	3x720x770					
Weight	Unit		kg		150 (depen	ding on version)					
Pre-filter	Dust collecting method			Prefilter RedPlea	SO Coarse 65% gas phase ter						
HEPA filter	Bacteria filtering method			Astrocel III HEPA H14							
Air purifying operation	Power input High fan speed kW			0.379							
Sound pressure level	Air purifying operation	High fan speed	dBA			55.9					
Fan Motor					Steples	ss adjustable					
Safety devices	Item			Saf	ety switch (operation st	ops when the back door is op	oen)				
Standard	Prefilter			1							
Accessories	HEPA filter			1							
	Quick Start and Mai	intenance Guide		1							
	Installation and Op	eration Manual		1 (download)							
Power cord			m			3					
Power supply	Phase			1~							
	Frequency		Hz	50/60							
	Voltage		V	230							
Running current	Air purifying operation	High fan speed	Α			1.73					



If you are a user or installer it is important you can **interact with our systems** in the easiest way, from **anywhere you are**. For any user our interfaces create **peace of mind** that their system is running in the best possible way.

Depending on the type of user and application Daikin develops controls and cloud services to ensure the best experience.

- > For home owners it means **app and voice control** of their home comfort.
- > For hotel owners it means easy and stylish **personal control for guests**, with an integration in hotel booking software for central control
- > For technical managers it means **cloud access** to all sites, with the possibility to benchmark, optimize performance
- For installers it means easy transfer of settings during commissioning, remote retrieval of errors and preventive alerts to save time on maintenance or interventions

Our controls enable you to **connect with your customer**, save time, improve your comfort intelligently and reduce energy bills.



Remote monitoring



Control Systems

Application overview	18
Individual control systems	184
Onecta app	18
Madoka wired remote controller	18
Wired / infrared remote controllers	18
Multi-zone controller	19
Centralised control systems	19
ntelligent Controller	19
Intelligent Manager	19
Centralised remote controller /	
Schedule timer / Unified ON/OFF controller	19
ntelligent Controller	19
Standard protocol interfaces	20
Modbus interface	20
KNX Interface	20
PMS Interface for hotels	20
BACnet Interface	20
LonWorks Interface	20
Daikin Configurator Tool	20
Daikin Cloud Service for commercial DX systems	20
Other devices	210
Wireless room temperature sensor	21
Wired room temperature sensor	21
Other integration devices	21
Indoor Environmental Sensor	21

Control solutions summary

Daikin offers various control solution adapted to the requirements of even the most demanding commercial application.

- > Basic control solutions for those customers with few requirements and limited budget
- > Integrating control solutions for those customers that would like to integrate Daikin units into their existing BMS system
- Advanced control solutions for those customers that expect Daikin to deliver a mini BMS solution, including advance energy management

Shop		Unit control		lı	ntegrating con	trol	Advanc	ed control
	(a)	-21		***	- Q - III		intelligent Controller	Intelligent Manager
	BRP069*	BRC1H52W/S/K	RTD-20	RTD-Net	KLIC DI V2	EKMBDXA	DCC601A51	DCM601B51
	Smartphone control for up to 50 indoor units	1 remote controller for 1 indoor unit (group)	1 gateway for 1 indoor unit (group)	1 gateway for 1 indoor unit (group)	Two additional probes can be connected	1 gateway for max. 64 indoor unit(s) (groups) & 10 outdoors	1 unit for 32 indoor unit(s) (5)	1 iTM for 64 indoor unit(s) (groups) (1)
Automatic control of A/C	•	•	•	•	•	•	•	•
Limit control possibilities for shop staff	•	•	•	•	•	•	•	•
Create zones within the shop			•				•	•
Interlock with eg. Alarm, PIR sensor			•				(limited)	•
Integration into smart home systems	• (7)							
Integrate Daikin units into existing BMS via Modbus				•		•		
Integrate Daikin units into existing BMS via KNX					•			
Integrate Daikin units into existing BMS via HTTP								•
Monitor energy consumption	• (4)	• (4)					• (2)	•
Advanced energy management							• (2)	• (6)
Allows free cooling								•
Voice control	• (6)							
Integrate Daikin products cross pillars into Daikin BMS								•
Integrate third party products into Daikin BMS							•	•
Online control	•						• (2)	• (3)
Manage multiple sites							• (2)	• (3)

(1) 7 iTM plus adapters (DCM601A52) can be added to have 512 indoor groups and 80 outdoor (systems) (2) Via Daikin cloud service (3) Through own IT set-up (not Daikin cloud server) (4) Not available on all indoors (5) Up to 10 DCC601A51 can be combined as a single site on Daikin Cloud Service (6) Only for BRP069C51, connection to Google Assistant and Amazon Alexa; (7) only for BRP069C51, contact your local sales representative for an overview of available services.

Unit control	Integratir	ig control	Advance	d control
				facility of Manager
BRC1H52W/S/K	RTD-HO	KLIC DI V2	DCM010A51	DCM601B51
1 remote controller for 1 indoor unit (group)	1 gateway for 1 indoor unit (group)	Two additional probes can be connected	1 interface for up to 2,500 indoor units	1 iTM for 64 indoor unit(s) (groups) (1)
n •	•	• (3)		•
•	•	•	•	•
• (2)	•			•
• (2)	•			•
	•			
		•		
				•
			Oracle Opera PMS	
				•
				•
				•
				•
				•
	BRC1H52W/S/K 1 remote controller for 1 indoor unit (group)	BRC1H52W/S/K RTD-HO 1 remote controller for 1 indoor unit (group) 1 gateway for 1 indoor unit (group)	BRC1H52W/S/K RTD-HO KLIC DI V2 1 remote controller for 1 indoor unit (group) 1 gateway for 1 probes can be connected (group) (3)	BRC1H52W/S/K 1 remote controller for 1 indoor unit (group) (group) (group) (2) (2) (2)

Office	Unit control		Integrating control		Advance	d control
	•21 ×			Former and	一 の の の の の の の の の の の の の	Lagificacy France
			LonWorks Interface	BACnet Interface	Intelligent Controller	futelligent Manager
	BRC1H52W/S/K	EKMBDXB	DMS504B51	DMS502A51	DCC601A51	DCM601B51
	1 remote controller for 1 indoor unit (group)	1 gateway for max. 64 indoor unit(s) (groups) & 10 outdoors	1 gateway for 64 indoor unit(s) (groups)	1 gateway for 128 indoor unit(s) (groups), 20 out- doors (2)	1 unit for 32 indoor unit(s) (groups) (5)	1 iTM for 64 indoor unit(s) (groups) (1)
Automatic control of A/C	•	•	•	•	•	•
Centralised control for management		•	•	•	•	•
Local control for office staff	•				• (4)	through Web
Limit control possibilities for office staff	•	•	•	•	•	•
Integrate Daikin units into existing BMS via Modbus		•				
Integrate Daikin units into existing BMS via HTTP						•
Integrate Daikin units into existing BMS via LonTalk			•			
Integrate Daikin units into existing BMS via BACnet				•		
Energy consumption read out	• (3)					
Monitor energy consumption					• (4)	•
Advanced energy management					• (4)	•
PPD software to distribute used kWh/indoor unit				• (6)		• (7)
Integrate Daikin cross pillar products into Daikin BMS						•
Integrate third party products into Daikin BMS					•	•
Online control					• (4)	•
Manage multiple sites					• (4)	• (5)

(1) 7 iTM plus adapters (DCM601A52) can be added to have 512 indoor groups and 80 outdoor (systems) (2) extension (DAM411B51) needed to have up to 256 indoor unit(s) (groups), 40 outdoors (3) Not available on all indoor units (4) Via Daikin cloud service (5) Through own IT set-up (not Daikin cloud sever) (5) Up to 10 DCC601A51 can be combined as a single site on Daikin Cloud Service (6) via DAM412B51 option (7) via DCM002A51 option

Infrastructure cooling	Unit	Integrating	Advanced
	21:	The state of the s	From Stock Manager
	BRC1H52W/S/K	RTD-10	DCM601B51
	1 remote controller for 1 indoor unit (group) (2)	1 gateway for 1 indoor unit (group) Up to 8 gateways can be linked together	1 iTM for 64 indoor unit(s) (groups) (1)
Automatic control of A/C	•	•	•
Back-up operation	•	•	•
Duty rotation	•	•	•
Limit control possibilities in the technical cooling room	•	•	•
If room temperature above max., then show alarm & start standby unit.		•	•
If an error occurs, an alarm will be shown.	•	•	•
If an error occurs, activate an alarm output	Via KRP2/4A option (3)	•	Via WAGO I/O

^{(1) 7} iTM plus adapters (DCM601A52) can be added to have 512 indoor groups and 80 outdoor (systems) (2) Infrastructure cooling functions only compatible with indoor units connected to RZQG*/RZAG* outdoor units. (3) See option list of indoor unit



The Onecta App is for those who live their life on the go and who want to manage their Daikin system from their smartphone.



onecto


NEW

Voice control


To provide users with even more comfort and ease, the Onecta App now offers voice control. This hands-free feature cuts down on clicks to manage units faster than ever before.

Cross-functional and multilingual, voice control pairs well with any smart device, including Google Assistant and Amazon Alexa.





Example of using the voice control via Google Assistant



Example of using the voice control via Amazon Alexa









Schedule

Set up a programme outlining when the system should operate, and create up to six actions per day.

- ✓ Schedule room temperature and operation mode
- Enable holiday mode to save costs



Control

Customise the system to fit your lifestyle and year-round comfort levels.

- ✓ Change room and domestic hot water temperature
- ▼ Turn on powerful mode to boost hot water production



Monitor

Receive a thorough overview of how the system is performing and how much energy it consumes.

✓ Check the status of the heating system

Access energy consumption graphs (day, week, month)

Function availability depends on the system type, configuration and operation mode. The app functionality is only available if both the Daikin system and the app have a reliable internet connection.





Scan the QR code to download the app now







Onecta connectable units

BRP069C51 *

VRV 5 indoor units

- > FXFA-A
- > FXAA-A
- > FXZA-A > FXDA-A
- > FXMA-A
- > FXSA-A
- > FXHA-A > FXUA-A

* Must be combined with BRC1H52W/S/K

Madoka wired remote controller

Madoka

The beauty of simplicity.







Black RAL 9005 (matte)



User-friendly wired remote controller with premium design

Madoka combines refinement and simplicity

- Sleek and elegant design
- Intuitive touch-button control
- Three display options: standard, detailed and **new symbolic view**
- Three colours to match any interior
- Compact, measures only 85 x 85 mm
- Advanced settings **copy function** and commissioning via smartphone

NEW > CO₂ concentration visualisation







Madoka Assistant









Simplifies the advanced settings such as schedule or set point limitation

- ✓ Visual interface simplifies advanced settings such as schedule setting, energy saving activation, setting restrictions, etc.
- Save field settings and schedules on your phone and upload to multiple controllers, saving time and cost
- ✓ Easy and quick commissioning
- ✓ Featuring Bluetooth® low energy technology

Easy setting of schedules



Advanced user settings



NEW

Bluetooth strength indication



Field settings



BRC1H52W / BRC1H52S / BRC1H52K

Madoka wired remote controller for Sky Air and VRV





BRC1H52S Standard view



A complete redesigned controller focussed to enhance user experience


- > Sleek and elegant design
- > Intuitive touch-button control
- > Three display options: standard, detailed and new symbolic view
- Direct access to basic functions
 (on/off, set point, mode, target values, fan speed, louvres, filter icon & reset, error & code)
- > Three colours to match any interior
- > Compact, measures only 85 x 85 mm
- > Real time clock with auto update to daylight saving time

Hotel application features

- > Energy saving through key card, window contact integration and set point limitation (BRP7A*)
- > Flexible setback function ensures room temperature remains within comfortable limits to ensure quest comfort









Madoka Assistant: Advanced settings can be easily done via your smartphone

A range of energy-saving functions that can be selected individually

- Temperature range restriction:
 Save on energy by setting the low temperature limit in cooling mode and the high temperature limit in heating mode (1)
- > Setback function
- Adjustable presence detector and floor sensor (available on the Round Flow and Fully Flat Cassettes)
- > Automatic temperature reset
- > Auto off timer

Kilowatt-hour consumption tracking (2)

The kWh indicator displays indicative power consumption for the last day/month/year.

Other functions

- > NEW Three user access levels: Basic user, Advanced and Installer to match user requirements and prevent improper use.
- > Save field settings and schedules on your phone and upload to multiple controllers, saving time and cost
- » NEW Mark frequently used menu's as favourites for direct access
- Up to three independent schedules can be programmed, allowing you to switch easily between them throughout the year (e.g. summer/winter/ mid-season)
- > Menu settings can be individually locked or restricted
- The outdoor unit can be set to quiet mode and power consumption limit control by schedule (3)
- Real-time clock that updates automatically for daylight saving



Cost-effective solution for infrastructure cooling applications

- → Only in combination with RZAG* / RZQG*
- > Duty rotation

After a certain period of time, the operating unit will go into standby and the standby unit will take over, extending the system lifetime. Rotation interval can be set for 6, 12, 24, 72 or 96 hours, as well as weekly.

Back-up operation: if one unit fails, the other unit will start automatically

BRC1E53A

User friendly remote control for Sky Air and VRV



Graphical display of indicative electricity consumption (Function available in combination with FBA-A, FCAG and FCAHG)

A series of energy saving functions that can be individually selected

- > Demand control (1)
- > Temperature range limit
- > Setback function
- Presence & floor sensor connection (available on round flow and fully flat cassette)
- > kWh indication (2)
- > Set temperature auto reset
- > Off timer

Cost-effective solution for infrastructure cooling applications

> Only in combination with RZAG* / RZQG*

Other functions

- > Up to 3 independent schedules
- > Possibility to individually restrict menu functions
- > Choice of display between symbol or text
- Real time clock with auto update to daylight saving time
- Built-in backup power for clock (up to 48 hours).
 Settings are always kept in case of power loss.
- Supports multiple languages:
 BRC1E53A: English, German, French, Dutch, Spanish,
 Italian, Portuguese

(1) Only available on RZAG*, RZASG*, RZQG*, RZQSG* I (2) For Sky Air FBA, FCAG and FCAHG pair combinations only

BRC1D52

Wired remote control for Sky Air and VRV



BRC1D52

- > Schedule timer: Five day actions can be set
- > Home leave (frost protection): during absence, the indoor temperature can be maintained at a certain level. This function can also switch the unit ON/OFF
- > User friendly HRV function, thanks to the introduction of a button for ventilation mode and fan speed
- > Immediate display of fault location and condition
- > Reduction of maintenance time and costs

ARC4*/BRC4*/BRC7*

Infrared remote control



ARC466A1 BRC4*/BRC7*

Operation buttons: ON/OFF, timer mode start/stop, timer mode on / off, programme time, temperature setting, air flow direction (1), operating mode, fan speed control, filter sign reset (2), inspection (2)/test indication (2)


Display: Operating mode, battery change, set temperature, air flow direction (1), programmed time, fan speed, inspection / test operation (2)

- 1. Not applicable for FXDQ, FXSQ, FXNQ, FBDQ, FDXM, FBA
- 2. For FX** units only
- 3. For all features of the remote control, refer to the operation manual

Multi-zone controller

The multi-zoning system is a room-by-room controller. It is fitted with motorised dampers, which immediately adapt using Daikin ducted solutions. This system supports control of up to 8 zones connected to one indoor unit via a centralised thermostat located in the main room and individual thermostats for each of the zones.





Compatik	lic	lity							3	S/	k	//	lit	-											¥	1	?!	1	I۱	V	 																					
•						FDX	M-F9)			FB	A-A	(9)			Α	DEA	-A			FX	DQ	-A3							FΣ	ζSQ	-A																				
Numbe motorised dam		Reference	Dimensions H x W x D (mm)	Ø (mm)	25	35	50	60	35	50	60	71	100	125	140	71	100	125	15	20	25	32	40	50	63	15	20	25	32	40	50	63	80	100	125	140																
	2	AZE(Z/R)6DAIST07XS2																								•	•	•	•																							
		AZE(Z/R)6DAIST07S2	300 x 930 x 454						•	•																				•	•																					
	3	AZE(Z/R)6DAIST07XS3	300 X 930 X 454																							•	•	•	•																							
	ے	AZE(Z/R)6DAIST07S3							•	•																				•	•																					
		AZE(Z/R)6DAIST07S4	300 x 1,140 x 454						•	•																				•	•																					
		AZE(Z/R)6DAIST07M4	300 X 1,140 X 434								•	•				•																•	•																			
Standard plenum	5	AZE(Z/R)6DAIST07M5	300 x 1,425 x 454	200							•	•				•																•	•																			
	٦	AZE(Z/R)6DAIST07L5	300 X 1,423 X 434	200									•	•	•		•	•																•	•																	
	6	AZE(Z/R)6DAIST07M6	300 x 1,638 x 454				Ш				•	•				•																•	•		Ш																	
	L	AZE(Z/R)6DAIST07L6	300 X 1,030 X 434										•	•	•		•	•															Ш	•	•																	
	7	AZE(Z/R)6DAIST07L7											•	•	•		•	•																•	•																	
	Ľ	AZE(Z/R)6DAIST07XL7	515 x 1,425 x 454																														Ш			•																
	8	AZE(Z/R)6DAIST07L8	313 X 1,423 X 434										•	•	•		•	•															Ш	•	•																	
	0	AZE(Z/R)6DAIST07XL8																																		•																
	2	AZEZ6DAIBS07XS2																								•	•	•	•																							
	Ľ	AZEZ6DAIBS07S2	250 x 930 x 454	250 x 930 x 454						•	•																				•	•		Ш																		
		AZEZ6DAIBS07XS3			250 x 930 x 454																						•	•	•	•																						
	3	AZEZ6DAIBS07S3																													•	•																				•
		AZEZ6DAIBS07M3									•	•				•																•	•																			
		AZEZ6DAIBS07S4							•	•																				•	•																					
Medium plenum	4	AZEZ6DAIBS07M4	250 x 1,140 x 454								•	•				•																•	•																			
•		AZEZ6DAIBS07L4		200									•	•	•		•	•															Ш	•	•																	
9920		AZEZ6DAIBS07S5							•	•																				•	•																					
ELECTED TO	5	AZEZ6DAIBS07M5	250 x 1,425 x 454								•	•				•																•	•																			
	٦	AZEZ6DAIBS07L5	230 X 1,423 X 434										•	•	•		•	•															Ш	•	•																	
		AZEZ6DAIBS07XL5																															Ш			•																
		AZEZ6DAIBS07M6									•	•				•																•	•																			
	6	AZEZ6DAIBS07L6	250 x 1,638 x 454										•	•	•		•	•																•	•																	
		AZEZ6DAIBS07XL6																																		•																
Slim plenum	2	AZE(Z/R)6DAISL01S2	210 x 720 x 444		•	•													•	•	•	•																														
	3	AZE(Z/R)6DAISL01S3	210 x /20 x 444	200	•	•													•	•	•	•											Ш																			
	4	AZE(Z/R)6DAISL01M4	210 x 930 x 444	200																			•	•									Ш		Ш																	
	5	AZE(Z/R)6DAISL01L5	210 x 1,140 x 444				•	•																	•																											

⁽¹⁾ Z models are reversible; R models are heating only

⁽²⁾ Medium Ceiling Void reversible units can be blocked to heating only via AZX6MCS module

Controls

3 controller versions are available to choose from: Colour, touch or simplified



AZCE6BLUEZEROCB (Wired)

Bluezero - main thermostat

 Intuitive graphical, colour touch screen for controlling multiple zones



AZCE6THINKRB (Wireless)

Think - zone thermostat

 Graphic touch button with low-energy e-ink screen for controlling single zones



AZCE6LITECB (Wired)
AZCE6LITERB (Wireless)

Lite - zone thermostat

- > Simplified thermostat with touch buttons for temperature control
- \rightarrow Optional bus cable (2 x 0.5 mm² | 2 x 0.22 mm²), 15 m length: AZX6CABLEBUS15, 100m length: AZX6CABLEBUS100



∆7Y6\WSDHI IR



Webserver for remote control

- > Cloud based remote control of multizoning kit(s)
- > Configruation and control of zones (temperature, operation mode, ...)
- > Access via webportal, or Android/IOS application
- > Supports Ethernet and WIFI
- > AZX6WSPHUB:
 - > For installation on DIN rail
 - > 32 zoning boxes can be controlled
- > AZX6WSC5GER:
 - > For installation in the unit
 - > Controls one zoning box



AZX6WSPBAC



AZX6KNXGTWAY

BACnet or KNX gateway

- > Allows ON/OFF control of each zone
- > Control of temperature for each zone
- > Status indication of operation mode
- > One gateway needed per system

Grilles and plenums

Supply air grilles and plenums



RDHV040015BKX

Wall type supply grille

 With horizontal and vertical adjustable flaps



RRFR050050BTX

Return air grilles and plenums

Return air grille with integrated filter

> Filters particles from the air



Ceiling type supply grille

- > With horizontal flaps angled at 15°
- Vertical flaps can be adjusted manually



Plenum for return grille

- To connect 1 up to 4 circular ducts to the return air grille
- > Diameter 250mm



Plenum for supply grille

- To connect circular ducts to discharge grille
- > Insulated, galvanised steel
- > Diameter 250mm



AZCEZDAPR07*

Plenum for return air

- To connect 1 up to 4 circular ducts to the Daikin concealed ceiling units
- Diameter 250mm
- > Different sizes (XS, S, M, L, XL) to fit the indoor unit

DCC601A51



Advanced

centralised controller

- Intuitive and user-friendly interface
- Flexible concept for stand alone and multi site applications
- Total solution thanks to integration of 3rd party equipment
- Monitor & control your small commercial building, no matter where you are

with Cloud connection

2 solutions:


Local solution

- > Offline centralised control
- > Stylish optional screen fits any interior

Cloud solution

- > Flexible online control from any device (Laptop, tablet...)
- > Monitor & control one or multiple sites
- Benchmark the energy consumption of different installations (1)
- > Energy consumption follow-up to comply with local regulations

System layout



Total solution

- > Total solution thanks to a large integration of Daikin products and 3rd party equipment
- > Connect a wide range of units (Split, Sky Air, VRV, Ventilation, Biddle air curtains)
- > Simply control your entire building centrally
- > Increased customer shopping experience by better management of your shop comfort level

Daikin Cloud Services

- > Control your building no matter where you are
- > Monitor and control multiple sites
- > Installer or technical manager can remotely login to the cloud for first troubleshooting
- > Benchmark the energy consumption of different installations (1)
- > Manage & track your energy use

User friendly touch control

- > Stylish Daikin supplied optional screen for local control fits any interior
- > Intuitive and user-friendly interface
- > Full solution with simple control
- > Easy commissioning

Flexible

- > Pulse/digital inputs for 3rd party equipment such as kWh meters, emergency input, window contact, ...
- > Modular concept allows your cloud to grow with your business
- > Control up to 32 indoor units per controller and 320 units per site **NEW** > Integrates the supervisor alarm for R-32 VRV 5 systems











Functions overview

		Local solution	Cloud solution
Languages		Depends on local device	EN, DE, FR, NL, ES, IT, EL, PT, RU, TR, DA, SV, NO, FI, CS, HR, HÚ, PL, RO, SL, BG, SK
System layout	N° of connectable indoor units	32	32
	Multiple sites control		•
Monitoring & control	Basic control functions (ON/OFF, mode, filter sign, setpoint, fan speed, ventilation mode, room temperature,)	•	•
	Remote control prohibition	•	•
	All devices ON/OFF	•	•
	Zone control		•
	Group control	•	•
	Weekly schedule	•	•
	Yearly schedule		•
	Interlock control	•	•
	Set point limitation		•
	Visualisation of energy use per operation mode		•
Connectable to	DX split, Sky Air, VRV	•	•
	Modular L Smart, VAM, VKM ventilation	•	•
	Air curtains	•	•



Mini BMS

with full integration across all product pillars

DCM601B51

Intelligent Manager

Price competitive mini BMS

Cross-pillar integration of Daikin products

Integration of third party equipment

Download the WAGO selection tool from my.daikin.eu


- > Easy selection of WAGO materials
- > Material list creation
- > Time savino
- Includes wiring scheme
- Contains commissioning/preset data for iTM







System overview



Intelligent Manager

User friendliness

- > Intuitive user interface
- Visual lay out view and direct access to indoor unit main functions
- All functions direct accessible via touch screen or via web interface
- Simplified electrical wiring, only one power supply & one connection wiring required

Smart energy management


- > Monitoring if energy use is according to plan
- > Helps to detect origins of energy waste
- > Powerful schedules guarantee correct operation throughout the year
- Save energy by interlocking A/C operation with other equipment such as heating
- > Peak Power Cut off Control: Activating this feature in schedule function allows users to operate the outdoor unit in 4 settings i.e. 100%,70%, 40% and 0%


Flexibility

- > Cross-pillar integration (heating, air conditioning, applied systems, refrigeration, air handling units)
- > BACnet protocol for 3rd party products integration
- > I/O for integration of equipment such as lights, pumps... on WAGO modules
- > Modular concept for small to large applications
- Control up to 512 indoor unit groups via one ITM and combine multiple ITM via web interface


Easy servicing and commissioning

- Remote refrigerant containment check reducing on site visit
- > Simplified troubleshooting
- Save time on commissioning thanks to the pre-commissioning tool
- > Auto registration of indoor units









Functions overview

Languages

- > English
- > French
- › German
- > Italian
- > Spanish
- > Dutch
- > Portuguese

Management

- > Web access via html 5
- Power Proportional Distribution (option)
- Operational history (malfunctions, ...)
- > Smart energy management
 - monitor if energy use is according to plan
- detect origins of energy waste
- > Setback function
- > Sliding temperature

WAGO Interface

- Modular integration of
 3rd party equipment
- Large variety of input and outputs available. For more details refer to the options list

Open http interface

 Communication to any third party controller (domotics, BMS, etc.) is possible via http open interface (http option DCM007A51)

System layout

 Up to 512 unit groups can be controlled (ITM + 7 iTM Plus adapters)

Control


- Individual control (512 groups)
- Schedule setting (Weekly schedule, yearly calender, seasonal schedule)
- > Interlock control
- > Setpoint limitation
- > Temperature limit
- Schedule function to activate quiet operation mode on outdoor unit

DALI integration

- > Control and monitor the lights
- Easier facility management: receive error signal when light or light controller has a malfunction
- Flexible approach and less wiring needed, compared to classic light scheme
- Easier to make groups and control scenes
- Connection between intelligent Touch Manager and DALI through WAGO BACnet / IP interface

Connectable to

- > DX Split, Sky Air, VRV
- > HRV
- Chillers (via MT3-EKCMBACIP controller)
- Daikin AHU (via MT3-EKCMBACIP controller)
- > Fan coils
- > LT and HT hydroboxes
- > Biddle Air curtains
- > WAGO I/O
- > BACnet/IP protocol
- Daikin PMS interface (option DCM010A51)



Centralised remote controller

Centralised control of the Sky Air and VRV system can be achieved via 2 user friendly compact remote controllers. These controls may be used independently or in combination with:

1 group = several (up to 16) indoor units in combination

1 zone = several groups in combination.

A centralised remote control is ideal for use in tenanted commercial buildings subject to random occupation, enabling indoor units to be classified in groups per tenant (zoning).

DCS302C51

Centralised remote control



Providing individual control of 64 groups (zones) of indoor units.

- > a maximum of 64 groups (128 indoor units, max. 10 outdoor units) can be controlled
- > a maximum of 128 groups (128 indoor units, max. 10 outdoor units) can be controlled via 2 centralised remote controls in separate locations
- > zone control
- > group control
- > malfunction code display
- > maximum wiring length of 1,000m (total: 2,000m)
- > air flow direction and air flow rate of HRV can be controlled
- > expanded timer function

DCS301B51

Unified ON/OFF control




Providing simultaneous and individual control of 16 groups of indoor units.

- > a maximum of 16 groups (128 indoor units) can be controlled
- > 2 remote controls in separate locations can be used
- > operating status indication (normal operation, alarm)
- > centralised control indication
- > maximum wiring length of 1,000m (total: 2,000m)

DCS601C51



Detailed & easy monitoring and operation of VRV systems (max. 64 indoor units groups).



Languages

- > English
- > French
- › German
- > Italian
- > Spanish
- > Dutch
- > Portuguese

System layout

- Up to 64 indoor units can be controlled
- Touch panel (full colour LCD via icon display)

Control

- Individual control
 (set point, start/stop,
 fan speed)
 (max. 64 groups/indoor units)
- > Set back shedule
- Enhanced scheduling function (8 schedules, 17 patterns)
- > Flexible grouping in zones
- > Yearly schedule
- > Fire emergency stop control
- > Interlocking control
- Increased HRV monitoring and control function
- Automatic cooling / heating change-over
- > Heating optimization
- > Temperature limit
- Password security: 3 levels (general, administration & service)
- Quick selection and full control
- > Simple navigation

Monitoring

- Visualisation via Graphical User Interface (GUI)
- Icon colour display change function
- > Indoor units operation mode
- > Indication filter replacement

Cost performance

- > Free cooling function
- > Labour saving
- > Easy installation
- Compact design: limited installation space
- > Overall energy saving

Open interface

 Communication to any third party controller (domotics, BMS, etc.) is possible via open interface (http option DCS007A51)

Connectable to

- > VRV
- > HRV
- > Sky Air
- > Split (via interface adapter)

Standard protocol interfaces

RTD

Modbus Interface

RTD-RA

 Modbus interface for monitoring and control of residential indoor units

RTD-NET

Modbus interface for monitoring and control of Sky Air, VRV, VAM and VKM

RTD-10

- Advanced integration into BMS of Sky Air, VRV, VAM and VKM through either:
 - Modbus
 - Voltage (0-10V)
 - Resistance
- > Duty/standby function for server rooms

RTD-20

- > Advanced control of Sky Air, VRV, VAM/VKM and air curtains
- > Clone or independent zone control
- > Increased comfort with integration of CO₂ sensor for fresh air volume control
- > Save on running costs via
 - pre/post and trade mode
 - set point limitation
 - overall shut down
 - PIR sensor for adaptive deadband

RTD-HO

- Modbus interface for monitoring and control of Sky Air, VRV, VAM and VKM
- > Intelligent hotel room controller

RTD-W


 Modbus interface for monitoring and control of Daikin Altherma Flex Type, VRV HT hydrobox and small inverter chiller

DCOM-LT/MB

 Modbus interface of Daikin Altherma air-to-water heat pumps, hybrid heat pumps and ground source heat pumps

DCOM/LT-IO

> Voltage & resistance control in addition to Modbus



Overview functions











Main functions	RTD-RA	RTD-NET	RTD-10	RTD-20	RTD-HO
Dimensions HxWxD mm	80 x 80 x 37.5		100 x1	00 x 22	
Key card + window contact					✓
Set back function	✓				✓
Prohibit or restrict remote control functions (setpoint limitation,)	✓	✓	✓	√ **	✓
Modbus (RS485)	✓	✓	✓	✓	✓
Group control	✓(1)	✓	✓	✓	✓
0 - 10 V control			✓	✓	
Resistance control			✓	✓	
IT application	✓		✓		
Heating interlock			✓	✓	
Output signal (on/defrost, error)			✓	√	✓
Retail application				✓	
Partitioned room control				✓	
Air curtain		√ ***	√ ***	✓	

(1): By combining RTD-RA devices

Control functions	RTD-RA	RTD-NET	RTD-10	RTD-20	RTD-HO
On/Off	M,C	M	M,V,R	M	M*
Set point	M	M	M,V,R	M	M*
Mode	M	M	M,V,R	M	M*
Fan	M	M	M,V,R	M	M*
Louver	M	M	M,V,R	M	M*
HRV Damper control		M	M,V,R	M	
Prohibit/Restrict functions	M	M	M,V,R	M	M*
Forced thermo off	M				

Monitoring functions	RTD-RA	RTD-NET	RTD-10	RTD-20	RTD-HO
On/Off	M	M	M	M	М
Set point	M	M	M	M	M
Mode	M	M	M	M	M
Fan	M	M	M	M	M
Louver	M	M	M	M	M
RC temperature		M	M	M	M
RC mode		M	M	M	M
N° of units		M	M	M	M
Fault	M	M	M	M	M
Fault code	M	M	M	M	M
Return air temperature (Average/Min/Max)	M	M	M	M	M
Filter alarm		M	M	M	M
Termo on	M	M	M	M	M
Defrost		M	M	M	M
Coil In/Out temperature	M	M	M	M	M



Main functions		RTD-W
Dimensions	HxWxD mm	100x100x22
On/off prohibition		✓
Modbus RS485		✓
Dry contact control		✓
Output signal (operation error)		✓
Space heating / cooling operation		✓
Domestic hot water control		✓
Smart Grid control		

Control functions	
On/Off Space heating/cooling	M,C
Set point leaving water temperature (heating / cooling)	M,V
Room temperature setpoint	M
Operation mode	M
Domestic Hot water ON	
Domestic Hot Water reheat	M,C
Domestic Hot Water reheat setpoint	
Domestic Hot Water storage	M
Domestic Hot Water Booster setpoint	
Quiet mode	M,C
Weather dependent setpoint enable	M
Weather dependent curve shift	M
Fault/pump info relay choice	
Control source prohibition	M

Smart grid mode control	
Prohibit Space heating/cooling	
Prohibit DHW	
Prohibit Electric heaters	
Prohibit All operation	
PV available for storage	
Powerful boost	

toring functions	
On/Off Space heating/cooling	• M.C
Set point leaving water temperature (H/C)	• M
Room temperature setpoint	• M
Operation mode	• M
Domestic Hot Water reheat	• M
Domestic Hot Water storage	• M
Number of units in the group	• M
Average leaving water temperature	• M
Remocon room temperature	• M
Fault	• M,C
Fault code	• M
Circulation pump operation	• M
Flow rate	
Solar pump operation	
Compressor status	• M
Desinfection operation	• M
Setback operation	• M
Defrost/ start up	• M
Hot start	
Booster Heater operation	
3-Way valve status	
Pump running hours accumulated	• M
Compressor running hours accumulated	
Actual leaving water temperature	• M
Actual return water temperature	• M
Actual DHW tank temperature (*)	• M
Actual refrigerant temperature	
Actual outdoor temperature	• M

- M : Modbus / R: Resistance / V: Voltage / C: control
 * : only when room is occupied / **: setpoint limitation / (*) if available
 : no fan speed control on the CYV air curtain / *: run & fault


EKMBDXB

DIII-net Modbus interface

Integrated control system for seamless connection between Split, Sky Air, VRV and small inverter chillers and BMS systems

- > Communication via Modbus RS485 protocol
- > Detailed monitoring and control of the VRV total solution
- > Easy and fast installation via DIII-net protocol
- > As the Daikin DIII-net protocol is being used, only one modbus interface is needed for a group of Daikin systems (up to 10 outdoor units systems).







			EKMBDXB7V1
Maximum number of connectable indoor units			64
Maximum number of connectable outdoor units			10
Communication	DIII-NET - Remark		DIII-NET (F1F2)
	Protocol - Remark		2 wire; communication speed: 9,600 bps or 19,200 bps
	Protocol - Type		RS485 (modbus)
	Protocol - Max. Wiring length	m	500
Dimensions	HeightxWidthxDepth	mm	124x379x87
Weight		kg	2.1
Ambient temperature - operation	Max.	°C	60
	Min.	°C	0
Installation			Indoor installation
Power supply	Frequency	Hz	50
	Voltage	V	220-240

KLIC-DDV3 KLIC-DI_V2

KNX interface

Integration of Split, Sky Air and VRV in HA/BMS systems





KNX interface line-up

The integration of Daikin indoor units through the KNX interface allows monitoring and control of several devices, such as lights and shutters, from one central controller. One particularly important feature is the ability to programme a 'scene' - such as "Home leave" - in which the end-user selects a range of commands to be executed simultaneously once the scenario is selected. For instance in "Home leave", the air conditioner is off, the lights are turned off, the shutters are closed and the alarm is on.


KNX interface for KLIC-DDV3 size 45x45x15mm KLIC-DI_V2 size 90x60x35mm Split Sky Air Basic control On/Off Mode Auto, heat, dry, fan, cool Auto, heat, dry, fan, cool Auto, heat, dry, fan, cool Temperature Fan speed levels 3 or 5 + auto 2 or 3 2 or 3 Stop or movement Swing or fixed positions (5) Stop or movement Advanced functionalities Error management Communication errors, Daikin unit errors Scenes Auto switch off Temperature limitation Initial configuration Master and slave configuration

DCM010A51

PMS Interface

Hotel interface connecting Daikin HVAC

Property Management Systems




Features

- User-friendly interface for easy front desk support in hotels, conference centers, ...
- Compatible with Oracle Opera PMS (formerly known as Micros Fidelio)
- Automated push of indoor unit settings based on the Opera PMS Check-In and Check-Out commands
- Energy saving thanks to the possibility to limit temperature setpoint
- Up to 5 customized operation profiles based on weather conditions
- Available in 23 languages
- Up to 2,500 units / rooms can be managed
- The Daikin PMS is using the FIAS protocol, designed by Oracle, to interface with the Property Management System.


Hotel case example:

- On check-in the HVAC for the room is automatically switched on
- On check-out the HVAC for the room is automatically switched off.
- Increased hotel customer experience by pre-heating / cooling of booked rooms

Hotel front desk



Simplified configuration of Daikin PMS interface




DMS502A51 / EKACBACMSTP / EKCMBACIP / EKCMBACMSTP

BACnet Interface

Integrated control system for seamless connection between VRV, applied systems, air handling units and BMS systems

- > Interface for BMS system
- Communication via BACnet protocol (connection via Ethernet)
- > Unlimited site size
- > Easy and fast installation
- PPD data is available on BMS system (only for VRV)




DMS504B51

LonWorks Interface

Open network integration of VRV monitoring and control functions into LonWorks networks

- Interface for Lon connection to LonWorks networks
- Communication via Lon protocol (twisted pair wire)
- > Unlimited sitesize
- > Quick and easy installation



EKPCCAB4

Daikin Configurator Tool + Software

Simplified commissioning: graphical interface to configure, commission and upload system settings

Simplified commissioning

The Daikin configurator for Daikin Altherma and VRV is an advanced software solution that allows for easy system configuration and commissioning:

- > Less time is required on the roof configuring the outdoor unit
- Multiple systems at different sites can be managed in exactly the same way, thus offering simplified commissioning for key accounts
- > Initial settings on the outdoor unit can be easily retrieved







Retrieve initial system settings







Daikin Cloud Service to achieve optimal operation (DAIKIN)

Daikin Cloud Service is a cloud-based remote control and monitoring solution for DX systems. Using enhanced control, monitoring and predictive logic, Daikin Cloud Service provides real-time data and support from Daikin experts to help you identify cost-saving opportunities, increase the lifetime of your equipment and reduce the risk of unexpected issues.

Monitor & control* your system no matter where you are while teaming up with Daikin experts

Remote control and energy visualisation

Puts you in the driving seat of your energy management

- ✓ Control and monitor your premises, wherever you are
- ✓ Centralised control and monitoring of all your premises
- ✓ Check errors remotely without having to go on site
- ✓ Visualise energy consumption and reduce energy waste by comparing different premises
- ✓ Graphical visualization of IEQ parameters (frequency day, week, month, year)
- ▼ Export & print IEQ parameters

Multi-site monitoring

From one to an ∞ number of sites



Remote support and diagnostics

Daikin specialist supervision, so you can focus on your core business

- ☑ Early warning of system deviations to maximise system uptime and avoid emergency repairs**
- Service providers have access to operational data so they arrive on site prepared
- ▼ Remote expert assistance in case of errors



Advice and optimisation

Get the best out of your system through expert advice

✓ Periodical analysis and optimisation report by experts

Personalised actions to maximise energy efficiency and comfort

✓ Increased system lifetime as the system runs as it should

Daikin Cloud Service requires a subscription. Contact your local sales representative for more information.

^{*} Remote Control function via Daikin Cloud Service only available for sites with an Intelligent Tablet controller

^{**} Only available for VRV systems

Daikin Cloud Service packages	Control and monitoring	Remote support and diagnostics	Advice and optimisation
Remote control, scheduling and interlocking	(DCC601A51 only)	(DCC601A51 only)	(DCC601A51 only)
Energy monitoring	✓	√	✓
Multi-site benchmark	✓	✓	✓
Alarm history and e-mail notifications**	Х	✓	✓
Predictions and e-mail notifications**	Х	✓	✓
Operational data access	Х	✓	✓
Indoor use analysis	Х	✓	✓
Outdoor use analysis	X	✓	✓
Remote diagnostic and support from Daikin	×	✓	✓
Periodical analysis and optimisation advice from Daikin	Х	Х	✓
Can be combined with maintenance programmes: - Technical inspection - Preventive Maintenance Plan - Comprehensive Maintenance Plan	Х	×	✓

Packages subject to local availability
Daikin Cloud Service replaces VRV Cloud and i-Net services.

Flexible solution

Manage your premises according to your needs, using a local control or remotely via Daikin Cloud Service, or a combination of both.

Control*, no matter where you are

Daikin Cloud Service gives you full control of one or more premises wherever you are, using your PC, tablet or smartphone.

Predictive logic for VRV to prevent breakdowns


The operational data is continuously analysed by Daikin algorithms to predict potential failures and avoid unexpected costs.

Compatible with:

- > Intelligent Tablet Controller (DCC601A51)
- > Intelligent Touch Manager (DCM601B51) + IoT gateway
- > LC8 + IoT gateway



1. Clear dashboard overview



3. Easy setting of schedules



5. Multi site management



2. Monitor and control your system



4. Energy management and consumption follow up



IEQ dashboard on DCS



DCS IEQ Sensor Monitoring

 $^{{}^{*}\}operatorname{Remote Control function via Daikin Cloud Service only available for sites with an Intelligent Tablet controller}$

^{**} Only available for VRV systems

K.RSS

Wireless room temperature sensor

Flexible and easy installation

- > Accurate temperature measurement thanks to flexible placement of the sensor
- > No need for wiring
- > No need to drill holes
- > Ideal for refurbishment



Connection diagram Daikin indoor unit PCB (FXSQ example)




Specifications

			Wireless room tempera	ature sensor kit (K.RSS)	
			Wireless room temperature receiver	Wireless room temperature sensor	
Dimensions		mm	50 x 50	ø 75	
Weight		g	40	60	
Power supply			16VDC, max. 20 mA	N/A	
Battery life			N/A	+/- 3 years	
Battery type			N/A	3 Volt Lithium battery	
Maximum range		m	1	0	
Operation range		°C	0~	-50	
Communication	Туре		RF		
	Frequency	MHz	868.3		

 $\Rightarrow Room\ temperature\ is\ sent\ to\ the\ indoor\ unit\ every\ 90\ seconds\ or\ if\ the\ temperature\ difference\ is\ 0.2^\circ C\ or\ larger.$

KRCS*

Wired room temperature sensor



 Specific model code for each indoor unit can be found in the option tables



Specifications

Dimensions (HxW)	mm	60 x 50
Weight	g	300
Length of branch wiring	m	12

ADAPTER PCBs

Simple solutions for unique requirements Concept and benefits

Low cost option to satisfy simple control requirements

Connectable to:

requirements		connectable to.			
Deployed	on single or multiple	e units	Split	Sky Air	VRV
	(E)KRP1B* adapter for wiring	> Facilitates integration of auxiliary heating apparatus, humidifiers, fans, damper > Powered by and installed at the indoor unit		•	•
	KRP2A*/KRP4A* Wiring adapter for electrical appendices	 Remotely start and stop up to 16 indoor units (1 group) (KRP4A* via P1 P2) Remotely start and stop up to 128 indoor units (64 groups) (KRP2A* via F1 F2) Alarm indication/ fire shut down Remote temperature setpoint adjustment Cannot be used in combination with a central controller 		•	•
	SB.KRP58M2	 Low noise and demand control option for RZAG-N* and RZASG-M* series. Obligatory mounted plate EKMKSA2 needs to be ordered separately 		•	
m s	KRP58M51	 Low noise and demand control option for RZA-D series. Includes obligatory mounted plate EKMKSA3 Obligatory mounting plate EKMKSA3 needs to be ordered separately 		•	
	DTA104A* Outdoor Unit External Control Adapter	 Individual or simultaneous control of VRV system operating mode Demand control of individual or multiple systems Low noise option for individual or multiple systems 			•
EREC.	DCS302A52-9 Unification adapter for computerized control	Enables unified display (operation/malfunction) and unified control (ON/OFF) from BMS system Must be used together with Intelligent Touch Controller or intelligent Touch Manager Cannot be combined with KRP2/4* Can be used for all VRV indoor models			•
	KRP928* Interface adapter for DIII-net	> Allows integration of split units to Daikin central controls	•		
	KRP980* Adapter for split units without an S21 port	Connect a wired remote control Connect to Daikin central controls Allow external contact	•		
	KRP413* Wiring adapter normal open contact / normal open pulse contact	> Switch off auto restart after power failure > Indication of operation mode / error > Remotely start / stop > Remotely change operation mode > Remotely change fan speed	•		

Some adapters require an installation box, refer to the option lists for more information

Accessories

EKRORO	0	> External ON/OFF or forced off > Example: door or window contact
EKRORO 3		> External ON/OFF or forced off > F1/F2 contact > Example: door or window contact
KRC19-26A	Planature 0	 Mechanical cool/heat selector Allows switching over an entire system between cooling/heating/fan only Connects to the A/B/C terminals of the unit
BRP2A81	EBOSOBIA)	> Cool/heat selector PCB > Required to connect KRC19-26A to a VRV IV outdoor unit

IEQ Sensor

Our New Indoor Environmental Quality Sensor



Features

The Daikin IEQ Sensor measures your well-being by tracking indoor air quality values, environmental comfort, and electromagnetic pollution. It is available with 12 sensors and 15 parameter measures, and connects through your Wi-Fi network or via NB-IoT technology.

▼ Complete Standalone Installation

The Daikin IEQ Sensor does not have to be paired with another product, for an extremely easy and completely standalone installation that takes about a minute. The device can be powered up with microUSB power supply (included). The material code is AIRSENSEPROPLUS.

✓ Caelum Monitoring Platform

The device connects to Caelum, Daikin's monitoring platform, at www.daikiniaq.com. This enables you to easily monitor Indoor Air Quality levels and create regular reports based on the data detected by the sensor. You can even use the platform to show your indoor air quality levels to your visitors.

✓ Mobile App

The configuration app is available as Daikin AirSense on both the App Store and Play Store. Once installed on your mobile device and logged in, scan the QR code on the IEQ sensor and the app will guide you through the entire configuration process. Once your sensor is configured, you will have access to the entire set of functions from your mobile.

▼ Connectivity

The IEQ sensor ensures perfect integration with Daikin on Site and Daikin Cloud Service, Daikin's remote monitoring and smart maintenance platform. It gives you perfect control over the entire heating, ventilation and air conditioning system installed in your building. You can use interlock function between IAQ sensor and AHUs.

✓ Available ReFilter tools

Product Hierarchy

- > Material Product hierarchy: Accessory
- > Material name: AIRSENSEPROPLUS
- > Business Pillar: SERVICES

✓ Green Building Certification

Installing the Daikin IEQ sensor can help you achieve better sustainability ratings and green building projects certified with LEED and WELL certification thanks to Indoor Environmental Quality credits.

▼ Video wall

The video wall is a great tool to have a general overview of the measurements conducted by the device. This screen can be shared with the occupants of the buildings to show in each moment the Indoor Air Quality status.

▼ Communication capability

NB-IoT: This technology can reach devices in areas where reception is poor or difficult to reach. Complete standalone installation. This is a perfect solution for service purposes where access to local Wi-Fi is not allowed or not available.

Wi-Fi: Easy and complete standalone installation.

Daikin IEQ Sensor kit

The IEQ sensor kit comes in a carton box containing the following items:

- › Power Supply plug
- > USB Micro USB Cables
- > Wall fixing kit
- > Quick installation guides




NB-IoT or WiFi?

Communication is either Wifi or NB-IoT network (mobile network). The NB-IoT services is available in the following 18 countries: Austria, Belgium, Czech Republic, Denmark, Estonia, Germany, Greece, Hungary, Ireland, Italy, the Netherlands, Norway, Portugal, Romania, Spain, Switzerland, United Kingdom. NB-IoT services carry a fee (invoiced after the first year of usage).









Options & Accessories


NEW	Tightfit fireless joint	216
	VRV 5 outdoor	218
	VRV 5 indoor	22
	VRV IV outdoor	222
	VRV IV indoor	227
	Ventilation	228
	Control systems	230


Tightfit NEW


Daikin Tightfit is a non-brazed connection suitable for refrigerant piping. Pipes can be joined easily and quickly without brazing or using any special tools. It meets stringent safety requirements and provides leak-free tightness.


- > Double edged claw catches the pipe to form tight, mechanical sealing
- > 2 types of connectors suitable for most pipe sizes and applications
- > Specially developed REFNET allows direct connection to Tightfit joints
- > Unique mechanical and resin sealings prevent any leak.
- > Extremely durable: can withstand up to 4 times (17.2MPa) the maximum operating pressure of R-32 refrigerant

Installation in 4 easy steps

















1 Mark the insertion line

Mark the insertion 'T' or 'L' standard line with the marking gauge and marker pen at the proper position of each pipe size.

2 Insert the pipe

- 1. Insert firmly by hand until the pipe stops.
- 2. Make sure that the insertion standard line is no longer visible.


3 Tighten the nut

- 1. Hold the main body and tighten the nut by hand
- 2. Hold the main body and tighten the nut with a monkey wrench, until the green indicator disappears and the nut comes into contact with the flat face of the body.

4 Check

- 1. Green indicator should be hidden.
- 2. Place the marking gauge on the end face of the nut and make sure that the 'T' or 'L' shaped mark falls completely within the notch in the marking gauge.

Tightfit Mechanism



Range and specifications

Standard joints (same size piping on each side)								
	Box Model Name No. of joints/box							
	box model name	No. of joints/box	Diameter	L (mm)	W (mm)	Single Weight (g)		
	SDGTB06	100	1/4" (6.35mm)	50.4	15	43		
	SDGTB09	90	3/8" (9.52mm)	55	19.9	79		
□ □ □ □ W	SDGTB12	70	1/2" (12.7mm)	59	23.5	113		
←	SDGTB15	60	5/8" (15.9mm)	74	30	210		
	SDGTB19	45	3/4" (19.1mm)	76.8	34.6	273		
□ □ □ □ W	SDGTB22	30	7/8" (22.2mm)	83.4	40.2	292		
	SDGTB28	24	11/8" (28.6mm)	88	46.7	515		
**************************************	BDGTA34	20	13/8" (34.9mm)	101.5	51.1	686		
	BDGTA41	16	15/8" (41.3mm)	103.5	58.3	881		

Asymmetricjoints (different size piping on each side)								
	Box Model Name No. of joints/box Dimensions							
	BOX WIGGE INTILE	No. of joints/box	Diameter	L (mm)	W (mm)	Single Weight (g)		
	SDGTB0906	90	1/4"-3/8" (6.35-9.52mm)	52.7	19.9	67		
	SDGTB1209	70	3/8"-1/2" (9.42-12.7mm)	57.5	23.5	101		
	SDGTB1512	60	1/2"-5/8" (12.7-15.9mm)	65	30	164		
□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	SDGTB1915	45	5/8"-3/4" (15.9-19.1mm)	76.8	34.6	244		
	SDGTB2219	30	3/4"-7/8" (19.1-22.2mm)	81.5	40.2	358		
	SDGTB2522	30	7/8"-1" (22.2-25.4mm)	85.8	43.5	444		
L	SDGTB2825	24	1"-11/8" (25.4-28.6mm)	88.1	46.7	505		
	SDGTB3428	20	11/8"-13/8" (28.6-34.9mm)	101.5	51.1	645		

Refnets compatible with Tightfit joints		
	Tightfit REFNET	Standard Refnet (for reference only)
-		KHRQ22M20TA
	BHRG26A33T	KHRQ22M20T
		KHRQ22M29T9
	BHRG26A72T	KHRQ22M64T
	BHRG26A73T	KHRQ22M75T
	BHRG25A33T	KHRQ23M20T
	BITROZDADO	KHRQ23M29T9
Possible to connect Tightfit directly	BHRG25A72T	KHRQ23M64T
	BHRG25A73T	KHRQ23M75T

Accessories				
	New Measuring Tool			
MJ-A 38.41 28 9 31.41 BDGIA34.41 31.34 25 112	SDGT_GAUGE			





		VRV 5 hea	t recovery	VRV S-series
		REYA8-20 REMA5	2 module systems	RXYSA-AV1/AY1
	Multi-module connection kit (obligatory) - Connects multiple modules into a single refrigerant system		2 modules: BHFQ23P907A	
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units			
Kits	Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan.			
	Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed)	5/8-12: EKBPH012T 14-20: EKBPH020T		EKBPH250D
	External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the FI/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-Will outdoor unit.		DTA104A53/61/62 door unit: exact adapter type deper nouting plate is required. See Optio	
Adapters	KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box.			•
	Cool/heat selector PCB (required to connect KRC19-26)			Standard on unit
	KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined)			
	KJB111A Installation box for remote cool/heat selector KRC19-26			•
	EKCHSC - Cool/heat selector cable			
	EKPCCAB4 VRV configurator			•
S	KKSB26B1* Demand PCB mounting plate. Needed to mount Demand PCB for one or more outdoor units.			
Others	DTA109A51 DIII-net expander adapter			
	BPMKS967A2/A3 Branch provider (for connection of 2/3 RA indoor units)			
	EKDK04 Drain plug kit			
	EKLN140A Sound enclosure			•

Refnets & branch selector boxes

			Refnet Joints Refnet Headers			Refnet Joints Refnet Headers		Refnet Joints			oints Refnet Headers		Refnet Headers			VRV 5 Heat Recovery Branch Selector (BSSV) boxes R-32
		Capacity index	Capacity index	Capacity index	Capacity index	Capacity index	Capacity index	Capacity index	Multi port							
		< 200	200 ≤ x < 290	290 ≤ x < 640	> 640	< 290	290 ≤ x < 640	> 640	BS-A14AV1B							
Refnets	Imperial-size connections for heat recovery pump (2-pipe)	For all R-410A VRV: KHRQ22M20T For all R-410A+R-32 VRV: KHRQ22M20TA	KHRQ22M29T9	KHRQ22M64T	KHRQ22M75T	KHRQ22M29H	KHRQ22M64H	KHRQ22M75H								
Ref	Imperial-size connections for heat recovery pump (2-pipe) (1)	KHRQ23M20T	KHRQ23M29T9	KHRQ23M64T	KHRQ23M75T	KHRQ23M29H	KHRQ23M64H	KHRQ23M75H								
Options for Branch selector boxes (BS box) (only for connection with VRV heat recovery system)	Closed pipe kit															
	Joint kit								EKBSJK							
	Quiet kit															
is for Brancn : inection with	Duct connection: To connect extraction of BSSV boxes in serial								EKBSDCK							
Option	Drain pump kit								K-KDU303KVE							

⁽¹⁾ For metric size connections, contact your local sales responsible

Juon	s & accessories - 1717 indoor R-32	Ceiling mounted	
	BLUEVOLUTION	Round flow (800x800)	4-way (600x600)
		FXFA-A	FXZA-A R-410A model:
<u>s</u>	Decoration panel (obligatory for cassette units, optional for others, rear panel for FXLQ)	Standard panels: BYCQ140E (white) / BYCQ140EW (full white)(3) / BYCQ140EB (black) Auto cleaning (5)(6): BYCQ140EGF (white) / BYCQ140EGFB (black) Designer panels: BYCQ140EP (white) / BYCQ140EPB (black)	BYFQ60C2WIW (white panel) BYFQ60C2WIW (white panel) BYFQ60C2WIS (grey panel) BYFQ60B3WI (standard panel) R-32 model: BYFQ60C4WIW (white panel) (19) BYFQ60C4WIS (grey panel) (19) BYFQ60B3WI (standard panel) (20)
Panels	Panel spacer for reducing required installation height		KDBQ44B60 (Standard panel)
	Sealing kit for 3- or 2-directional air discharge Sensor kit	KDBHQ56B140 (7) BRYQ140B (white panels) BRYQ140BB (black panels) BRYQ140C (white designer panel) BRYQ140CB (black designer panel)	BDBHQ44C60 (white & grey panel) R-410A models: BRYQ60A2W (white) BRYQ60A2S (grey) R-32 models: BRYQ60A3W (white) BRYQ60A3S (grey)
systems	Infrared remote control (incl. receiver)	BRC7FA532F (white panels) (7)(15) BRC7FA532FB (black panels) (7)(15) BRC7FB532F (white designer panel) (7)(15) BRC7FB532FB (black designer panel) (7)(15)	BRC7F530W (9) (10) (white panel) BRC7F530S (9) (10) (grey panel) BRC7EB530W (9) (10) (standard panel)
ţ	BRP069C51 - Onecta app	•	•
Individual control systems	Madoka BRC1H52W (White) / BRC1H52S (Silver) / BRC1H52K (Black) User-friendly wired remote controller with premium design BRC1E53A/B/C - Wired remote control with full-text interface and back-light	• (mandatory)	• (mandatory)
프	BRC1D52 (4) - Standard wired remote control with weekly timer		
- 22	DCC601A51 - intelligent Tablet Controller	•	•
stem		•	•
control systems	DCS601C51 (12) - intelligent Touch Controller DCS302C51 (12) - Central remote controller	_	
ontrc .		•	•
_ ნ	DCS301B51 (12) (13) - Unified ON/OFF controller PTD NET Modbus interface for monitoring and control	•	•
<u>ē</u>	RTD-NET - Modbus interface for monitoring and control	•	•
vidu	RTD-10 - Modbus interface for infrastructure cooling	•	•
for individual control	RTD-20 - Modbus interface for retail	•	•
fo	RTD-HO - Modbus interface for hotel	•	•
_	KLIC-DI - KNX Interface	•	•
control	DCM601B51 - intelligent Touch Manager	•	•
<u>5</u>	EKMBDXB - Modbus interface	•	•
central control for individu	DCM010A51 - Daikin PMS interface	•	•
ŭ	DMS502A51 - BACnet Interface	•	•
fo	DMS504B51 - LonWorks Interface	•	•
	Auto cleaning filter	see decoration panel	
	UV Streamer kit (purifies the air of pollutants such as viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy indoor environment) Replacement filter	BAEF125AWB (22) BAFP55A160	
Filters	Replacement high efficiency filter	BAFF52AA160 BAF552AA160 ePM10 60% (7) (BAF552AA160-5: box of 5 filters) (BAF552AA160-10: box of 10 filter)	
	Replacement long life filter, non-woven type	KAF5511D160	KAF441C60
	Pre-filter Eilter chamber		
2 ,	Filter chamber	WDCCCC ED	WOCCOL CD
Wiring and sensors	KRCS - External wired temperature sensor K.RSS - External wireless temperature sensor	KRCS01-5B SB.K.RSS_RFC	KRCS01-6B SB.K.RSS_FDA
≥	Adapter with 2 output signals (Compressor / Error, Fan output)	(EKEWTSC-2 + K.RSS) KRP1BA58 (2)(7)	(EKEWTSC-1 + K.RSS) ERP02A50 (2)
	Adanter With 2 Output Signals (COMDIESSOL/ ELLO), Fall Output)		EKRP1C14 (2)
	Adapter with 4 output signals	EKRP1C12 (2)(7)	
**	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140 Ω (for dedicated indoor)	KRP4A53 (2)(7)	KRP4A53 (2)
pters	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system)	KRP4A53 (2)(7)	KRP2A52
Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140 Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for keycard and/or window contact connection (2)(11) Adapter for multi-tenant applications (24VAC PCB power supply interface)		
Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for keycard and/or window contact connection (2)(11)	KRP4A53 (2)(7) BRP7A53	KRP2A52 BRP7A53 (2) DTA114A61
Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for keycard and/or window contact connection (2)(11) Adapter for multi-tenant applications (24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit) Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox)	KRP4A53 (2)(7) BRP7A53 DTA114A61 KRP1H98A (7) KRP1BC101	KRP2A52 BRP7A53 (2) DTA114A61 KRP1BC101
Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140 Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for keycard and/or window contact connection (2)(11) Adapter for multi-tenant applications (24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit) Installation box / Mounting plate for adapter PCBs	KRP4A53 (2)(7) BRP7A53 DTA114A61 KRP1H98A (7)	KRP2A52 BRP7A53 (2) DTA114A61
Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for keycard and/or window contact connection (2)(11) Adapter for multi-tenant applications (24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit) Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox) Wiring kit for Remote ON/OFF or Forced OFF	KRP4A53 (2)(7) BRP7A53 DTA114A61 KRP1H98A (7) KRP1BC101 Standard	KRP2A52 BRP7A53 (2) DTA114A61 KRP1BC101 Standard
Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux., heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for external central monitoring/control (controls 1) Adapter for external central monitoring/control (controls 1) Adapter for multi-tenant applications (24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit) Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox) Wiring kit for Remote ON/OFF or Forced OFF Relay PCB for output signal of refrigerant sensor	KRP4A53 (2)(7) BRP7A53 DTA114A61 KRP1H98A (7) KRP1BC101 Standard ERP01A51 (2)	KRP2A52 BRP7A53 (2) DTA114A61 KRP1BC101 Standard ERP01A50 (2)
Others Adapters	Adapter with 4 output signals (Compressor / Error, Fan, Aux., heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for external central monitoring/control (controls 1) Adapter for external central monitoring/control (controls 1) Adapter for multi-tenant applications (24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit) Installation box / Mounting plate for adapter PCBS (For units where there is no space in the switchbox) Wiring kit for Remote ON/OFF or Forced OFF Relay PCB for output signal of refrigerant sensor	KRP4A53 (2)(7) BRP7A53 DTA114A61 KRP1H98A (7) KRP1BC101 Standard ERP01A51 (2)	KRP2A52 BRP7A53 (2) DTA114A61 KRP1BC101 Standard ERP01A50 (2)
	Adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output) Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140Ω (for dedicated indoor) Adapter for external central monitoring/control (controls 1 entire system) Adapter for rexternal central monitoring/control (controls 1 entire system) Adapter for multi-tenant applications (24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit) Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox) Wiring kit for Remote ON/OFF or Forced OFF Relay PCB for output signal of refrigerant sensor Drain pump kit Multi zoning kit (for detailed model code overview refer to multizoning argue card in this catalogue) Fresh air intake kit (direct installation type)	KRP4A53 (2)(7) BRP7A53 DTA114A61 KRP1H98A (7) KRP1BC101 Standard ERP01A51 (2) Standard	KRP2A52 BRP7A53 (2) DTA114A61 KRP1BC101 Standard ERP01A50 (2) Standard

⁽¹⁾ pump station is necessary for this option
(2) Installation box is necessary for these adapters
(3) The BYCQ140EW has white insulation. Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140EW decoration panel in environments exposed to concentrations of dirt*
(4) Not recommended because of the limitation of the functions
(5) To be able to control the BYCQ140EGF(B) the controller BRC1E or BRC1H* is needed

⁽⁶⁾ The BYCQ140EGF(B) is not compatible with Multi and Split Non-Inverter Outdoor units (7) Option not available in combination with BYCQ140EGF(B) (8) Both parts of the fresh air intake are needed for each unit (9) Cannot be combined with sensor kit (10) Independently controllable flaps function not available (11) Only possible in combination with BRC1H* / BRC1E* (12) When fixing box is required, use KJB212A, KJB311A or KJB411A depending on the size of the

Slim	ncealed ceiling units (duct u Medium ESP	High ESP	1-way blow	pended units 4-way blow	
FXDA-A	FXSA-A	FXMA-A	FXHA-A	FXUA-A	FXAA-A
FXUA-A	FX5A-A	FAMA-A	гапа-а	FXUA-A	FXAA-A
				WEELEN AND WEELEN	
				KDBHP49B140 + KDBTP49B140	
				BRE49B2F	
BRC4C65	BRC4C65	BRC4C65	BRC7GA53-9	BRC7C58	BRC7EA630
•	•	•	•	•	•
• (mandatory)	• (mandatory)	• (mandatory)	• (mandatory)	• (mandatory)	(mandatory)
(mandatory)	(manuatory)	(mandatory)	(mandatory)	(manuatory)	(manuatory)
•	•	•	•	•	•
				1	
•	•	•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
•	•		•	•	•
•			•	•	•
	_			•	
•	•	•	•		•
•	•	•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
15-32: BAE20A62	-	_		-	
40-50: BAE20A82					
63: BAE20A102					
		BAFM503A250 (65%) (21)			
		BAFH504A250 (90%) (21)			
			32: KAF501B56		
		200~250: BAFL502A250 (21)	50~63: KAF501B80	KAFP551K160	
	-	BAFL501A250 (21)	71~100: KAF501B160		
		BDD500B250			
KRCS01-6B	KRCS01-6B	KRCS01-6B	KRCS01-6B	KRCS01-6B	KRCS01-6B
SB.K.RSS_FDA EKEWTSC-1 + K.RSS)	SB.K.RSS_FDA (EKEWTSC-1 + K.RSS)	SB.K.RSS_FDA (EKEWTSC-1 + K.RSS)	•	SB.K.RSS_FDA (EKEWTSC-1 + K.RSS)	SB.K.RSS_FDA (EKEWTSC-1 + K.RSS)
EREW 15C 1 1 R.H55)	(EREWISE IT KINSS)	(EREWISE I I RINSS)	KRP1BA58	(EREWISE IT RINSS)	(EREWISE IT KINSS)
ERP02A50 (2)	EKRP1C14 (2)	EKRP1C14 (2)		EKRP1C14 (2)	ERP02A50 (2)
		50~125: KRP4A52			
KRP4A54-9 (2)	KRP4A52(2)	200~250: KRP4A51	KRP4A52 (2)	KRP4A53 (2)	KRP4A51 (2)
KRP2A53 (2)	KRP2A51(2)	KRP2A51	KRP2A62		KRP2A61(2)
BRP7A54 DTA114A61	BRP7A51 DTA114A61	BRP7A51 DTA114A61	BRP7A52 (2) DTA114A61	BRP7A53 DTA114A61	BRP7A51 (2) DTA114A61
DTA104A53	DTA104A61 (2)	DTA104A61 (2)	DTA104A61	DIMI-MUI	DTA104A51(2) / DTA104A61(
KRP1BC101	KRP1BC101	KRP1BC101	KRP1D93A/KRP4B93	KRP1B97	KRP4A93
	Standard	Standard	standard	standard	Standard
ERP01A51 (2)	ERP01A50 (2)	ERP01A50	ERP01A51 (2)	ERP01A51 (2)	ERP01A51 (2)
Standard	Standard	200~250: BDU510B250VM	32-50-63: KDU50R63		K-KDU572KVE
			100: KDU50R160		
	15~32: KDAP25A36A				
	40~50: KDAP25A56A	50~80: KDAJ25K71 100~125: KDAJ25K140			
	63~80· KDAD25 4714	IVV: IZJ. NIZMJZDNIHU			
	63~80: KDAP25A71A 100~125: KDAP25A140A	200~250: -			
	100~125: KDAP25A140A		32: KHFP5M35 50~63: KHFP5N63		

controller
(13) Option KEK26-1A (Noise filter) is required when installing DCS301B51
(14) Wire harnass EKEWTSC is necessary
(15) The active airflow circulation function is not available for this controller.
(16) Up to 2 adaptor PCBs can be installed per installation box
(17) Only one installation box can be installed per indoor unit
(18) VRV R-32 indoor units cannot be connected to this controller

⁽¹⁹⁾ The BYFQ60C4* R-32 panels can be connected to R-410A indoor units with wire harness EKRS22 (20) Wire harness EKRS23 is necessary (21) Filter chamber needed (22) Only possible in combination with BYCQ140E and BYCQ140EW



		REYQ8-20 REMQ5		2/	3 module systems
	Multi-module connection kit (obligatory) - Connects multiple modules into a single refrigerant system				odules: BHFQ23P907A odules: BHFQ23P1357
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units		Special ord		
Kits	Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan.				
	Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed)	5/8-12: EKBPH012T7 14-20: EKBPH020T7/			
	External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit.	11 20 210 11020 11			
Adapters	KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box.				
	Cool/heat selector PCB (required to connect KRC19-26)				
	KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined)				
	KJB111A Installation box for remote cool/heat selector KRC19-26				
	EKCHSC - Cool/heat selector cable EKPCCAB4				
	VRV configurator				
srs	KKSB26B1* Demand PCB mounting plate. Needed to mount Demand PCB for one or more outdoor units.				
Others	DTA109A51 DIII-net expander adapter				
	BPMKS967A2/A3 Branch provider (for connection of 2/3 RA indoor units)				
	EKDK04 Drain plug kit				
	EKLN140A				
	Sound enclosure				
					IV S-series
	Multi-module connection kit (obligatory) - Connects multiple modules into a single refrigerant	RXYSCQ-TV1	RXYSQ4-	6TV9	RXYSQ4-6TY9
	Multi-module connection kit (obligatory) - Connects multiple modules into a single refrigerant system	RXYSCQ-TV1	RXYSQ4-	6TV9	RXYSQ4-6TY9
22	system Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units	RXYSCQ-TV1	RXYSQ4-	6TV9	RXYSQ4-6TY9
Kits	system Extended level difference kit - Allows outdoor unit to be more than 50m	RXYSCQ-TV1	RXYSQ4-	6TV9	RXYSQ4-6TY9
Kits	system Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by	RXYSCQ-TV1	RXYSQ4-	6TV9	RXYSQ4-6TY9
Kits	system Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor	For installation into an in	DTA104A5	3/61/62 pter type depenc	ls on type of indoor unit.
Adapters Kits	system Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-Willi outdoor	For installation into an in	DTA104A5 door unit: exact ada	3/61/62 pter type depenc	ls on type of indoor unit.
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector - allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26)	For installation into an in	DTA104A5 door unit: exact ada	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIll outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape	For installation into an in	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined)	For installation into an in	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-Will outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined) KJB11A Installation box for remote cool/heat selector KRC19-26	For installation into an in	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined) KJB111A Installation box for remote cool/heat selector KRC19-26	For installation into an in Se	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
Adapters	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector - allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined) KJB111A Installation box for remote cool/heat selector KRC19-26 EKCHSC Cool/heat selector cable (Required to connect KRC19-26) EKPCCAB4 VRV configurator	For installation into an in	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB2681* Cool/heat selector cable (Required to connect KRC19-26) EKPCCAB4 VRV configurator KKSB2681* Demand PCB mounting plate. Needed to mount Demand PCB for one or more outdoor units.	For installation into an in Se	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
Adapters	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB2681* KKC19-26 EKCHSC Cool/heat selector able (Required to connect KRC19-26) EKCCAB4 VRV configurator KKSB2681*	For installation into an in Se	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
Adapters	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-Will outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined) KJB111A Installation box for remote cool/heat selector KRC19-26 EKCHSC Cool/heat selector cable (Required to connect KRC19-26) EKPCCAB4 VRV configurator KKSB26B1* Demand PCB mounting plate. Needed to mount Demand PCB for one or more outdoor units.	For installation into an in Se	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.
Adapters	Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed) External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit, BSVQ box, or VRV-WIII outdoor unit. KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box. Cool/heat selector PCB (Required to connect KRC19-26) KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined) KJB111A Installation box for remote cool/heat selector KRC19-26 EKCHSC Cool/heat selector cable (Required to connect KRC19-26) EKPCCAB4 VRV configurator KKSB26B1* Cool/heat selector cable (Required to connect KRC19-26) EKPCCAB4 VRV configurator KKSB26B1* Dill-net expander adapter BPMKS967A2/A3	For installation into an in Se	DTA104A5 door unit: exact ada e Options & Accesso	3/61/62 pter type depend ries of indoor uni	ls on type of indoor unit.

VRV IV+ heat recovery

	VRV IV+ heat pump			VRV IV C	+series
RYYQ8-20 RYMQ8-20	2/3 module sys	tems	RXY RXM		2/3 module systems
RXYQ8-20	2 modules: BHFQ2		n An		2 modules: BHFQ22P1007
	3 modules: BHFQ2	22P1517			3 modules: BHFQ22P1517
0 12. EKDDI 1012T7A					
8-12: EKBPH012T7A 14-20: EKBPH020T7A					
	For installation into a For 14-20 HP the demand Po	DTA104A. n indoor unit: exact ad CB mouting plate is rec	apter type depends on typ	e of indoor unit. ssories of indoor units	
•	1 kit per system	1	•	•	1 kit per system
BRP2A81	1 kit per system	1	BRP2	2A81	1 kit per system
(14-20)	1 kit				1 kit
(14-20)	per system 1 kit				per system 1 kit
	per system	<u> </u>			per system
•					
(14-20)					
•			•	•	
			VRV IV i-seri SB.RKXYQ		
RXYSQ8-12TY1	RDXYQ5	RDX	YQ8	RKXYQ5	RKXYQ8
	EKDPHIRDX	EKDPH	HIRDX		
	For installation into a	DTA104A n indoor unit: exact ad See Options & Access	apter type depends on typ	e of indoor unit.	
	1				
				•	•
				•	BRP2A81
				•	
				•	
					BRP2A81
•				•	BRP2A81
•				•	BRP2A81
•				•	BRP2A81
•				•	BRP2A81

		VRV	IV-Q Heat Pump Replacement V	RV
		RQYQ 140P	RXYQQ8-20	2/3-module systems
	Multi-module connection kit (obligatory) Connects multiple modules into a single refrigerant system			2 modules: BHFQ22P1007 3 modules: BHFQ22P1517
Kits	Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan.	KWC26B160		
	Bottom plate heater - To keep drain holes ice-free in extreme weather conditions (one per outdoor unit needed)		8-12: EKBPH012T7A 14-20: EKBPH020T7A	
rs	External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of demand control, limiting power consumption via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit*, BSVQ box, or VRV-WIII outdoor unit.	DTA104A53/61/62 For installation into an indoor unit: exact adapter type depends on type of indoor unit. For 14-20 HP the demand PCB mouting plate is required. See Options & Accessories of indoor units	For installation into an in type depends on 1 For 14-20 HP the demand PC	A53/61/62 Idoor unit: exact adapter type of indoor unit. B mouting plate is required. sories of indoor units
Adapters	KRC19-26 Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box.	•	•	1 kit per system
	BRP2A81 Cool/heat selector PCB (required to connect KRC19-26 to VRV IV outdoor)		•	1 kit per system
	KKSB26B1* Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined)		(8-12)	1 kit per system
	KJB111A Installation box for remote cool/heat selector KRC19-26	•	•	1 kit per system
Others	EKPCCAB4 VRV configurator		•	
oth	KKSB2B61* Demand PCB mounting plate. Needed to mount Demand PCB for one or more outdoor units.		(8-12)	
	DTA109A51 DIII-net expander adapter			
(1) F	ar installations with special requirements towards fire regulations, the insulation material can be replaced w	sing kits EKLIDEO1 and EKLIDEO2		

⁽¹⁾ For installations with special requirements towards fire regulations, the insulation material can be replaced using kits EKHBFQ1 and EKHBFQ2. The kits contain insulation material that complies with ENI3501-1:8-53,dO and BS476-7 (class 1)

Refnets & branch selector boxes

	Refnet Joints			
	Capacity index	Capacity index	Capacity index	Capacity index
	< 200	200 ≤ x < 290	290 ≤ x < 640	> 640
Imperial-size connections for heat recovery pump (2-pipe)	For all R-410A VRV: KHRQ22M20T For all R-410A+R-32 VRV: KHRQ22M20TA	KHRQ22M29T9	KHRQ22M64T	KHRQ22M75T
Imperial-size connections for heat recovery pump (2-pipe) (1)	KHRQ23M20T	KHRQ23M29T9	KHRQ23M64T	KHRQ23M75T
Closed pipe kit				
Joint kit				
Quiet kit				
Duct connection: To connect extraction of BSSV boxes in serial				
Drain pump kit				
	Imperial-size connections for heat recovery pump (2-pipe) (1) Closed pipe kit Joint kit Quiet kit Duct connection: To connect extraction of BSSV boxes in serial	Imperial-size connections for heat recovery pump (2-pipe) Imperial-size connections for heat recovery pump (2-pipe) Imperial-size connections for heat recovery pump (2-pipe) (1) KHRQ22M20TA KHRQ23M20T Closed pipe kit Quiet kit Duct connection: To connect extraction of BSSV boxes in serial	Capacity index Cap	Capacity index Capa

⁽¹⁾ For metric size connections, contact your local sales responsible

VRV III-Q Heat Recovery Replacement VRV		VRV-W IV Water-cooled VRV						
VKV III-Q Heat Rec	overy Replacement VRV		Heat Pump application	Heat Recovery application				
RQEQ 140~212	RQEQ 140~212 2/3/4-module systems		2/3-module systems	2/3-module systems				
	2/3 modules: BHFP26P36C 4 modules: BHFP26P84C		BHFQ22P1007 / BHFQ22P1517 (1)	BHFQ23P907 / BHFQ23P1357 (1)				

DTA104A53/61/62
Installation in the RWEYQ outdoor unit possible. For installation in indoor units, use appropriate type (DTA104A53/61/62) for particular indoor unit. See Options & Accessories of indoor units

	(for H/P only)	1 kit per system	
	(for H/P only)	1 kit per system	
•	(for H/P only)	1 kit per system	
	•	•	•
	•	•	•

	Refnet Headers	Branch Selec	at Recovery tor (BS) boxes 10A	
Capacity index	Capacity index	Capacity index	1-port	Multi port
< 290	290 ≤ x < 640	> 640	BS1Q-A	BS-Q14AV1B
KHRQ22M29H	KHRQ22M64H	KHRQ22M75H		
KHRQ23M29H	KHRQ23M64H	KHRQ23M75H		
				KHFP26A100C
				KHRP26A250T
			EKBSVQLNP	4 port: KDDN26A4 6-8 port: KDDN26A8 10-12 port: KDDN26A12 16 port: KDDN26A16

Option	ns & accessories -		Ceiling mounted cassette units		
VR.	indoor & hot water R-410A	Round flow (800x800)	4-way (600x600)	2-way blow	Corner (1-way blow)
_	That of a flot hate.	FXFQ-B	FXZQ-A	FXCQ-A	FXKQ-MA
els	Decoration panel (obligatory for cassette units, optional for others, rear panel for FXLQ)	Standard panels: BYCQ140E (white) / BYCQ140EW (full white)(3) / BYCQ140EB (black) Auto cleaning (5)(6): BYCQ140EGF (white) / BYCQ140EGFB (black) Designer panels: BYCQ140EP (white) / BYCQ140EPB (black)	R-410A model: BYFC60C2W1W (white panel) BYFC60C2W1S (grey panel) BYFC60B3W1 (standard panel) R-32 model: BYFC60C4W1W (white panel) (19) BYFC60C4W1S (grey panel) (19) BYFC60B3W1 (standard panel) (20)	20~40: BYBCQ40H 50~63: BYBCQ63H 80~125: BYBCQ125H	25~40: BYK45F 63: BYK71F
Panels	Panel spacer for reducing required installation height		KDBQ44B60 (Standard panel)		25~40: KPBJ52F56 63: KPBJ52F80
_	Sealing kit for 3- or 2-directional air discharge	KDBHQ56B140 (7)	BDBHQ44C60 (white & grey panel)		031111 2222. 23
	Sensor kit	BRYQ140B (white panels) BRYQ140BB (black panels) BRYQ140C (white designer panel) BRYQ140CB (black designer panel)	R-410A models: BRYQ60A2V (white) BRYQ60A2S (grey) R-32 models: BRYQ60A3V (white) BRYQ60A3S (grey)		
Individual control systems	Infrared remote control including receiver BRP069C51 - Onecta app	BRC7FA532F (white panels) (7)(15) BRC7FA532FB (black panels) (7)(15) BRC7FB532F (white designer panel) (7)(15) BRC7FB532FB (black designer panel) (7)(15)	BRC7F530W (9) (10) (white panel) BRC7F530S (9) (10) (grey panel) BRC7EB530W (9) (10) (standard panel)	BRC7C52	BRC4C61
ontr	Madoka				
ual c	BRC1H52W (White) / BRC1H52S (Silver) / BRC1H52K (Black) User-friendly wired remote controller with premium design	•	•	•	•
νį	BRC1E53A/B/C - Wired remote control with full-text interface and	• (18)	• (18)	•	•
ם	back-light BRC1D52 (4) - Standard wired remote control with weekly timer	• (15)(18)	• (18)	•	•
ed s	DCC601A51 - Intelligent Tablet Controller	(13)(10)	•	•	•
Centralised control systems	DCS601C51 (12) - intelligent Touch Controller	•	•	•	•
entr con syst	DCS302C51 (12) - Central remote control	•	•	•	•
	DCS301B51 (12) (13) - Unified ON/OFF control	•	•	•	•
ement System scol interface for individual control	RTD-NET - Modbus interface for monitoring and control RTD-10 - Modbus interface for infrastructure cooling	•	•	•	•
& Standard protocol interfaces for central for individual control control	RTD-10 - Modbus interface for infrastructure cooling	•	•	•	•
	RTD-HO - Modbus interface for hotel	•	•	•	•
15 S	KLIC-DI - KNX Interface	•	•	•	•
pro =	DCM601B51 - intelligent Touch Manager	•	•	•	•
ndard pi central	EKMBDXB - Modbus interface	•	•	•	•
ig s	DCM010A51 - Daikin PMS interface	•	•	•	•
for of	DMS502A51 - BACnet Interface DMS504B51 - LonWorks Interface	•	•	•	•
∞	Auto cleaning filter	see decoration panel	•	•	•
	UV Streamer kit (purifies the air of pollutants such as UV Streamer kit	·			
	viruses, bacteria, fine dust (PM1.0), oudeurs, allergens, etc ensuring a healthy indoor environment) Replacement filter	BAFP55A160			
Filters	Replacement high efficiency filter	BAF552AA160 ePM10 60% (7) (BAF552AA160-5: box of 5 filters) (BAF552AA160-10: box of 10 filter)		20~40: KAF531C50	
	Replacement long life filter, non-woven type	KAF5511D160	KAF441C60	20~40: KAF531C50 50~63: KAF531C80 80~125: KAF531C160	
	Pre-filter Filter chamber				
d d	KRCS - External wired temperature sensor	KRCS01-5B	KRCS01-4	KRCS01-4	KRCS01-1
Wiring and sensors	K.RSS - External wireless temperature sensor	K.RSS	K.RSS	•	•
	Adapter with 2 output signals (Compressor / Error, Fan output)	KRP1BA58 (2)(7)	KRP1B57 (2)		
	Adapter with 4 output signals	EKRP1C12 (2)(7)	EKRP1B2 (2)	EKRP1B2 (2)	KRP1B61
	[Compressor / Error, Fan, Aux. heater, Humidifier output] Adapter for centralised external monitoring/control via dry contacts and setpoint control via 0-140 Ω (for dedicated indoor)	KRP4A53 (2)(7)	KRP4A53 (2)	KRP4A51 (2)	KRP4A51
ya .	Adapter for external central monitoring/control		KRP2A52	KRP2A51 (2)	KRP2A61
ote.	(controls 1 entire system) Adapter for keycard and/or window contact connection (2)(11)	BRP7A53	BRP7A53 (2)	BRP7A51	BRP7A51
Adapters	Adapter for multi-tenant applications		DTA114A61	BIII 7ASI	DIII 7ASI
•	(24VAC PCB power supply interface) External control adapter for outdoor unit (installation on indoor unit)	DTA114A61	UIAII4A0I	DTA104A61 (2)	DTA104A61
	Installation box / Mounting plate for adapter PCBs	KRP1H98A (7)			
	(For units where there is no space in the switchbox)	KRP1BC101	KRP1BC101	KRP1C96 (16) (17)	
	Wiring kit for Remote ON/OFF or Forced OFF Relay PCB for output signal of refrigerant sensor	Standard	Standard	Standard	Standard
	Drain pump kit	Standard	Standard	Standard	Standard
	Multi zoning kit (for detailed model code overview refer to				
	multizoning argue card in this catalogue) Fresh air intake kit (direct installation type)	KDDP55C160-1 + KDDP55D160-2 (7)(8)	KDDQ44XA60		
Others	Air discharge adapter for round duct				
5	L-type piping kit				
				20~40: KDDFP53B50	
	Filter chamber for bottom suction			50~63: KDDFP53B80 80~125: KDDFP53B160	
	Insulation kit for high humidity				

⁽¹⁾ pump station is necessary for this option
(2) Installation box is necessary for these adapters
(3) The BYCQ140EW has white insulation. Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140EW decoration panel in environments exposed to concentrations of dirt*
(4) Not recommended because of the limitation of the functions
(5) To be able to control the BYCQ140EGF(B) the controller BRCIE or BRCIH* is needed

⁽⁶⁾ The BYCQ140EGF(B) is not compatible with Multi and Split Non-Inverter Outdoor units (7) Option not available in combination with BYCQ140EGF(B)

⁽⁸⁾ Both parts of the fresh air intake are needed for each unit

⁽⁹⁾ Cannot be combined with sensor kit
(10) Independently controllable flaps function not available
(11) Only possible in combination with BRC:I+* / BRC:I=*
(12) When fixing box is required, use KJB212A, KJB311A or KJB411A depending on the size of the controller
(13) Option KEY26-1A (Noise filter) is required when installing DCS301B51
(14) Wire harnass EKEWTSC is necessary
(15) The active airflow circulation function is not available for this controller.
(16) Up to 2 adaptor PCBs can be installed per installation box
(17) Only one installation box can be installed per indoor unit
(18) VRV R-32 indoor units cannot be connected to this controller

	Concealed ceiling	units (duct units)		Ceiling susp	ended units	Wall mounted units	Floor star	iding units
Slim	Medium ESP	High	ESP	1-way blow	4-way blow		Concealed	Free-standing
FXDQ-A3	FXSQ-A	FXMQ-P7	FXMQ-A	FXHQ-A	FXUQ-A	FXAQ-A	FXNQ-A	FXLQ-P
·		·						20~25: EKRDP25A5 32~40: EKRDP40A5 50~63: EKRDP63A5
					KDBHP49B140 + KDBTP49B140			
BRC4C65	BRC4C65	BRC4C65	BRC4C65	BRC7GA53-9	BRC7C58	BRC7EA629 / BRC7EA628	BRC4C65	BRC4C65
•	•	•	•	•	•	•	•	•
• (18)	• (18)	•	•	•	•	•	•	•
• (18)	• (18)	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•		•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
15-32: BAE20A62 40- 50: BAE20A82 63: BAE20A102								
			BAFM503A250 (65%) (21) BAFH504A250 (90%) (21)					
			BAFL502A250 (21)	32: KAF501B56 63: KAF501B80 71~100: KAF501B160	KAF5511D160			20~25: KAF361L28 32~40: KAF361L45 50~63: KAF361L71
			BAFL501A250 (21) BDD500B250					
KRCS01-4	KRCS01-4	KRCS01-4	KRCS01-6B	KRCS01-4	KRCS01-4	KRCS01-1	KRSC01-4	KRCS01-1
K.RSS	K.RSS	•	SB.K.RSS_FDA (EKEWTSC-1 + K.RSS)	•	•	K.RSS + EKEWTSC	•	•
		KRP1C64 (2)	KRP1C65	KRP1B54				
KRP1B56	EKRP1B2 (2)	EKRP1B2 (2)	EKRP1C14 (2)			KRP1B56	KRP1B56	KRP1B61
KRP4A54-9 (2)	KRP4A52 (2)	KRP4A51 (2)	KRP4A51	KRP4A52 (2)	KRP4A53 (2)	KRP4A51 (2)	KRP4A54-9	KRP4A51
KRP2A53 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51	KRP2A62 (2)		KRP2A51 (2)/ KRP2A61(2)	KRP2A53	KRP2A51
BRP7A54	BRP7A51	BRP7A51	BRP7A51	BRP7A52	BRP7A53	BRP7A51 (2)	BRP7A54	BRP7A51
DTA114A61	DTA114A61 (2)	DTA114A61 (2)	DTA114A61	DTA114A61	DTA114A61	DTA114A61	DTA114A61	EKMTAC
DTA104A53	DTA104A61	DTA104A61 (2)	DTA104A61	DTA104A62-9		DTA104A51 / DTA104A61	DTA104A53	DTA104A61
KRP1BC101	KRP1BC101	KRP4A96		KRP1D93A (19)	KRP1B97	KRP4AA93 (16)(17)	KRP1BC101	
	Standard	Standard	Standard	EKRORO4	EKRORO5	Standard	Standard	Standard
Standard	Standard	Standard	BDU510B250VM	32: KDU50R63 63~100: KDU50R160		K-KDU572KVE		
•	•					<u> </u>		
	15~32: KDAP25A36A				-			
	40~50: KDAP25A56A 63~80: KDAP25A71A 100~125: KDAP25A140A	50~80: KDAJ25K71 100~125: KDAJ25K140			Drain pan Digital I/O PCB		HXY080-125A8 EKHBDPCA2 EKRP1HBAA	HXHD125-200A8 - EKRP1HBAA
	140: -				Demand PCB - Require thermostat	ed to connect room	EKRP1AHTA	EKRP1AHTA

35: KHFP5M35 63: KHFP5N63 71~100: KHFP5N160

KDT25N32 / KDT25N50 / KDT25N63

(19) The BYFQ60C4* R-32 panels can be connected to R-410A indoor units with wire harness EKRS22
(20) Wire harness EKRS23 is necessary
(21) Filter chamber needed
(22) Only possible in combination with BYCQ140E and BYCQ140EW
(23) Requires demand PCB
(24) Can only be used in combination with wireless room thermostat
(25) If tank is NOT mounted on top of the HXHD unit, then option EKFMAHTB is needed to install tank as stand alone

	HXY080-125A8	HXHD125-200A8
Drain pan	EKHBDPCA2	-
Digital I/O PCB	EKRP1HBAA	EKRP1HBAA
Demand PCB - Required to connect room thermostat	EKRP1AHTA	EKRP1AHTA
Remote user interface (remocon) - Same controller as supplied with cascade unit can be mounted parallel or on other location. If 2 controllers are installed, the installer needs to select 1 master &1 slave	EKRUAHTB	EKRUAHTB
Back-up heater	EKBUHAA6(W1/V3)	-
Wired room thermostat	EKRTWA (23)	EKRTWA (23)
Wireless room thermostat	EKRTR1 (23)	EKRTR1 (23)
Remote sensor for room thermostat	EKRTETS (24)	EKRTETS (23)
Stainless domestic hot water tank - 2001	-	EKHTS200AC (24)
Stainless domestic hot water tank - 260l	-	EKHTS260AC (24)
PP domestic hot water tank - 300l	-	EKHWP300B
PP domestic hot water tank - 500l	-	EKHWP500B
Solar collector	-	EKSV26P (vertical) EKSH26P (horizontal)
Pump station	-	EKSRPS

Options - Ventilation

		Ha	eat Recovery \	/entilation - M	odular T (Sma	urt)	Heat Rec	overy Ventilat	ion - Modular	I (Smart)
					_					ALB06,07LBS/RBS
	BRC301B61	AI BOSKAS/LAS	AT BUTKAS/LAS	3B.ATBUJRAJ/LA3	3B.AI BUUNA3/LA3	35.AI BU/RA3/LA3	ALBUZLB3/NB3	ALBUSLBS/RBS	ALBU4,U3LB3/NB3	ALBOO,07LB3/RB3
SE .	VAM wired remote control	•	•	•	•	•	•	•	•	•
ol syst	Madoka BRC1H52W (White) / BRC1H52S (Silver) / BRC1H52K (Black) User-friendly wired remote controller with premium design	•	•	•	•	•	•	•	•	•
vidual co	BRC1E53A/B/C Wired remote control with full-text interface and back-light	•	•	•	•	•	•	•	•	•
	BRC1D52 Standard wired remote control with weekly timer	•	•	•	•	•	•	•	•	•
Centralised control systems	DCC601A51 intelligent Tablet Controller	•	•	•	•	•	•	•	•	•
alised co	DCS601C51 intelligent Touch Controller	•	•	•	•	•	•	•	•	•
ralise	DCS302C51 Central remote control	•	•	•	•	•	•	•	•	•
Cent	DCS301B51 Unified ON/OFF control	•	•	•	•	•	•	•	•	•
e d	DCM601A51 intelligent Touch Manager	•	•	•	•	•	•	•	•	•
ng ment tanda iterfa	EKMBDXB Modbus interface	•	•	•	•	•	•	•	•	•
Building Management System & Standard protocol interface	DMS502A51 BACnet Interface	•	•	•	•	•	•	•	•	•
Ma yster	DMS504B51	•	•	•	•	•		•	•	•
V 1 —	LonWorks Interface									_
	Coarse 55% (G4)	ATF03G4A	ATF04G4A	ATF05G4A	ATF06G4A	ATF07G4A	ALF02G4A	ALF03G4A	ALF05G4A	ALF07G4A
	ePM10 75% (M5)	ATF03M5A	ATF04M5A	ATF05M5A	ATF06M5A	ATF07M5A	ALF02M5A	ALF03M5A	ALF05M5A	ALF07M5A
	ePM10 70% (M6)									
	ePM1 50% (F7)	ATF03F7A	ATF04F7A	ATF05F7A	ATF06F7A	ATF07F7A	ALF02F7A	ALF03F7A	ALF05F7A	ALF07F7A
Filters	ePM1 60% (F7)									
	ePM ₁ 70% (F8)									
	ePM1 80% (F9)	ATF03F9A	ATF04F9A	ATF05F9A	ATF06F9A	ATF07F9A	ALF02F9A	ALF03F9A	ALF05F9A	ALF07F9A
	High efficiency filter									
	Replacement air filter									
ies	Rail						ALA02RLA	ALA03RLA	ALA05RLA	ALA07RLA
Mechanical accessories	Rectangular to round duct transition						ALA02RCA	ALA03RC	ALA05RCA	ALA07RCA
Mec	Separate plenum									
CO ₂ sensor		BRYMA200	BRYMA200	BRYMA200	BRYMA200	BRYMA200	BRYMA200	BRYMA200	BRYMA200	BRYMA200
Electrical h	eater for pre treatment of fresh air	ATD03HEFBU	ATD04HEFBU	ATD05HEFBU	ATD06HEFBU	ATD07HEFBU	ALD02HEFB	ALD03HEFB	ALD05HEFB	ALD07HEFB
DX coil for	post treatment of fresh air									
Silencer (90	00mm depth)	ATA0360A	ATA0460A	ATA0560A	ATA0660A	ATA0760A	ALS0290A	ALS0390A	ALS0590A	ALS0790A
s	Wiring adapter for external monitoring/control (controls 1 entire system)									
ssori	Adapter PCB for humidifier									
Electrical accessories	Adapter PCB for third party heater									
rica	External wired temperature sensor									
Elect	Adapter PCB Mounting plate									
Notes	Installation box for adaptor PCB									

Note:

 $⁽¹⁾ Do \ not \ connect \ the \ system \ to \ DIII-net \ devices \ LONWorks \ interface, BACnet \ interface, ...; \ (intelligent \ Touch \ Manager, EKMBDXA \ are \ allowed)$

⁽²⁾ Installation box needed

⁽³⁾ Adapter PCB mounting plate needed, applicable model can be found in the table above

^{(4) 3}rd party heater and 3rd party humidifier cannot be combined

⁽⁵⁾ Contains 1 plenum and can be used for half side of the unit (up to 4 plenums can be used on 1 unit)

⁽⁶⁾ Available only with optional plenum

			Energy reco	overy ventil	ation - VAM				Energy rec	overy venti	lation VKM	Air hand	ing unit app	olications
VAM 150FC9	VAM 250FC9	VAM 350J8	VAM 500J8	VAM 650J8	VAM 800J8	VAM 1000J8	VAM 1500J8	VAM 2000J8	VKM 50GBM	VKM 80GBM	VKM 100GBM	EKEQFCBA (1)	EKEQDCB (1)	EKEQMCBA (1)
•	•	•	•	•	•	•	•	•						
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	_		_	_	_	_	_	_	_	_	_	_	_	
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•			
•	•	•	•	•	•	•	•	•	•	•	•			
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•			
•	•	•	•	•	•	•	•	•	•	•	•			
		EKAFVJ50F6	EKAFVJ50F6	EKAFVJ65F6	EKAFVJ100F6	EKAFVJ100F6	EKAFVJ100F6×2	EKAFVJ100F6 x2						
		EKAFVJ50F7	EKAFVJ50F7	EKAFVJ65F7	EKAFVJ100F7	EKAFVJ100F7	EKAFVJ100F7x2	EKAFVJ100F7x2						
		EKAFVJ50F8	EKAFVJ50F8	EKAFVJ65F8	EKAFVJ100F8	EKAFVJ100F8	EKAFVJ100F8 x2	EKAFVJ100F8 x2						
									K45242110044	KAESASI HOOM	KAF242H100M			
									KAF242H80M	KAF242H100M	KAF242HI00M			
									KAF241H80M	KAF241H100M	KAF241H100M			
							EKPLEN200 (5)	EKPLEN200 (5)						
		BRYMA65	BRYMA65	BRYMA65	BRYMA100	BRYMA100	BRYMA200	BRYMA200	BRYMA65	BRYMA100	BRYMA100			
GSIEKA10009	GSIEKA15018	GSIEKA20024	GSIEKA20024	GSIEKA25030	GSIEKA25030	GSIEKA25030	GSIEKA	35530 (6)	GSIEKA20024 (8)	GSIEKA20024 (8)	GSIEKA20024 (8)			
			EKVDX32A	EKVDX50A	EKVDX50A	EKVDX80A	EKVDX100A	EKVDX100A						
KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	KRP2A51 (2)	BRP4A50A (4)	BRP4A50A (4)	BRP4A50A (4)			
									BRP4A50A (4)	BRP4A50A (4)	BRP4A50A (4)			
BRP4A50A	BRP4A50A	BRP4A50A (4)	BRP4A50A (4)	BRP4A50A (3/4)	BRP4A50A (4)	BRP4A50A (4)	BRP4A50A (3/4)	BRP4A50A (3/4)	BRP4A50A (4)	BRP4A50A (4)	BRP4A50A (4)			
													KRCS01-1	
EKMP25VAM	EKMP25VAM			EKMP65VAM			EKMI	PVAM						
KRP1BB101	KRP1BB101	KRP1BB101	KRP1BB101	KRP1BB101	KRP1BB101	KRP1BB101	KRP1BB101	KRP1BB101						

Individual and centralised controls

	BRC1D*	BRC1E*	BRC1H*	DCS301B51	DST301B51	DCS302C51	DCS601C51			
Madoka Assistant app for advanced settings			•							
Electical box KJB111A	•	•	•							
Electical box KJB212A(A) (1)	•	•		•	•					
Electical box KJB311A(A)						•				
Electical box KJB411AA							•			

⁽¹⁾ recommended as wider (more stable mounting)

Intelligent Tablet Controller - DCC601A51

		intelligent Controller					
		Options for local control	Daikin Cloud Service options	Software			
Wired screen for local control	AL-CCD07-VESA-1	•	-	_			
Control and monitoring package		-	•	-			
Remote support and diagnostics package		-	•	_			
Advise and optimisation package		-	•	_			
Commissioning tool		-	-	•			
Software update tool		-	-	•			

Daikin Cloud Service requires a subscription. Contact your local sales representative for more information

Standard protocol interfaces - DMS502A51

		BACnet Interface
DIII-net expansion board (2 ports), connects up to 128 additional indoor units	DAM411B51	•
Digital pulse inputs (12) for PPD functionality	DAM412B51	•

Intelligent Touch Manager - DCM601B51

		Intelligent Manager	Daikin Cloud Service options (2)
DIII Plus Adaptor - Allows connection of additional 64 indoor units/groups. Only one adaptor can be connected (for more units, use DIII Plus Adaptor Slots)	DGE601A52	•	
DIII Plus Adaptor - Allows connection of additional 64 indoor units/groups. Up to 6 Adaptor Slots can be added to a DIII Plus Adaptor	DGE601A53		
iTM plus adapter – Allows connection of an additional 64 indoor units/groups. Up to 7 adapters can be connected	DCM601A52	•	
iTM PPD software – Allows distribution of used kWh by indoor units connected to the iTM	DCM002A51	•	
iTM HTTP interface - Allows communication to any third party controller via http interface	DCM007A51	•	
iTM Energy navigator – Energy management option	DCM008A51	•	
iTM BACnet Client option – Enables integration of third party devices to the iTM via the BACnet/IP protocol. (This is not a gateway and cannot replace DMS502A51)	DCM009A51	•	
Property Management System (PMS) interface option - Enables to connect to third party PMS systems	DCM010A51	Oracle Opera PMS	
Monitoring package			•
Remote support and diagnostics package			•
Advise and optimisation package			•

WAGO interface options for intelligent Touch Manager

Required or optional WAGO base modules


Module type	Model code	Specifications	
24 V DC power supply	787-712	100 to 240 V AC —> 24 V DC, 2.5 A	Required
Communications unit (Bus coupler)	WGDCMCPLR2	RS-485, Max:115.2kbps, not programmable	Required
Connector (1)	750-960		Required
Terminator module	750-600		Required
Power supply module	750-613	IN: 24 V DC, OUT: 5 V DC	Optional

Supported WAGO I/O modules


I/0 module type	Model code	Specifications	N° of contacts
	750-400	No-voltage contact input	2
Di	750-432	Contact rating: 24 V DC / 4.5 mA"	4
	750-430	No-voltage contact input Contact rating: 24 V DC / 2.8 mA	8
Do	750-513/000-001	No-voltage contact output Contact rating: 230 V AC / 30 V DC, 2 A	2
50	750-504	No-voltage contact output Contact rating: 24 V DC / 0.5 A	4
	750-454	Rated at 4 to 20 mA: 12-bit resolution	2
Ai	750-455	Rated at 4 to 20 mA: 12-bit resolution	4
AI	750-479	Rated at –10 to 10 V: 13-bit resolution	2
	750-459	Rated at 0 to 10 V: 12-bit resolution	4
	750-554	Rated at 4 to 20 mA: 12-bit resolution	2
٨٠	750-555	Rated at 4 to 20 mA: 12-bit resolution	4
Ao	750-560	Rated at -10 to 10 V: 10-bit resolution	2
	750-559	Rated at 0 to 10 V: 12-bit resolution	4
	750-461/020-000	NTC20K thermistor	2
	750-461	Pt 100/RTD	2
	750-460	PUIOUKID	4
Thermistor	750-461/000-003	Pt 1000/RTD	2
Thermistor	750-460/000-003	Pt 1000/RTD	4
	50-461/000-004	Ni 100/RTD	2
	750-461/000-005	Ni1000 TK6180/RTD	2
	750-460/000-005	NITUUU TKOISU/KTD	4
Pi	750-638	Minimum pulse width: 1 ms	2

 ⁽¹⁾ This connector must be attached to a communications unit that is connected to the RS485 port (2-pin) of the iTM unit.

⁽²⁾ To connect intelligent Touch Manager to the Daikin Cloud Service, the loT gateway (EU.SB.5000072) and AC/DC converter (999175A) is needed.



Full BIM object library available



Tools & platforms

Literature overview	234
Supporting tools, software and apps	236
30 years of history	240

Literature overview

for professional network

Solutions catalogues:

Reference books:



Reference catalogue Daikin commercial and industrial references

213

Product profiles:



VRV IV S-series Main benefits, application examples and specs of VRV IV S-series product range



VRV IV i-series Main benefits, application examples and specs of VRV IV i-series product range

207



gmug VRV IV W-series, application examples, technical system design background 209

Water-to-air heat



VRV5 S-Series VRV 5 Main benefits and specs of VRV 5

Focus topics:



Replacement Technolog Clear installer benefits of VRV replacement technology

214

208



Infrastructure cooling Clear installer benefits why to choose Daikin for infrastructure cooling 140

F-gas regulation Details on the F-gas regulation and how Daikin is prepared for the future HVAC-R market

605



L∞P by Daikin Detailed info on L∞P by Daikin where reclaimed refrigerant is reused

223

210

Product flyers:



Mini Sky Air RZAG-A mini Skv Air Alpha-series Main benefits and specs of RZAG-A 146



Low height Sky RZAG-N* Sky Air Alpha-series Main benefits and specs of the low height RZAG-N* 147



Low height large Sky RZA-D Sky Air Advance-series Main benefits and specs of the low height . RZA-D* series

Madoka Detailed info on BRC1H* remote control



RTD modbus interface Detailed info on RTD controls and applications

306

Sky Air Catalogue Detailed technical information & benefits on Sky Air 100

VRV Catalogue Detailed technical information & benefits of the VRV total solution 200



Ventilation Detailed info on Ventilation products

203

Product

catalogues:

for your customers

Solutions catalogues:



Commercial Solutions
Daikin offers solutions for commercial applications

100



Green Building Solutions Clear building owner/ investor benefits why to choose Daikin for a green building, with emphasis on BREEAM

216



Maximise your BREEAM score BREEAM categories Overview of how to score BREEAM points with Daikin

221



Hotel Solutions Clear building owner/investor benefits why to

Reference books:



Success Case study Vandervalk hotel case In depth info on the VRV total solution at a Vandervalk hotel

Product profiles:



Intelligent Touch Manager Intelligent Touch Manager

302



Intelligent Tablet Controller Detailed benefits of Intelligent Tablet Controller

303



Focus topics:



Replacement technology Clear building owner/investor benefits of replacement technology

15-215



Technical documentation:
Download all technical documentation such as engineering databooks, selection software, installation and operation manuals and service manuals directly from our business portal: my.daikin.eu

Supporting tools, software and apps


www.daikineurope.com/ support-and-manuals/ software-downloads

Eu


Web based Xpress selection software


Making selection easy, anytime, anywhere

- > Web & cloudbased, access to your projects from anywhere, anyplace...
- > Platform (Windows, Mac, ...) and hardware (laptop, desktop, tablet) independent
- > Re-engineered GUI for maximum easy of use
- > No need to do local installation
- No tool updates required (always latest version available)
- > Possibility to copy / share projects



Main functions









Clear overview of control groups and central controls

Integrated features

2D floorplan

How does it work?


- 1 Import 2D floorplan
- 2 Define reference point & scale
- 3 Position units
- 4 Draw pipes
- --> Pipe lengths and heights are automatically determined!
- > Accurate pipe design
- > Work faster
- > Easy compliance check



REVIT import

How does it work?

- 1 Design your building/rooms in revit
- 2 Define loads (optional)
- 3 Place Daikin BIM objects & Draw pipes
- 4 Export to Xpress
- 5 Xpress calculates
- > Model selection
- > Pipe diameters
- > and validates selection




VRV Xpress integrates seamlessly with our ventilation selection softwares

Ventilation Xpress

Selection tool for ventilation devices (VAM, VKM). The selection is based on given supply/extract airflows (including fresh up and given ESP of supply/extract ducting:

- > Determines size of electrical heaters
- > Visualisation of psychrometric chart
- > Visualisation of selected configuration
- > Required field settings mentioned in the report



Webbased ASTRA selection for air handling units

A powerful tool to select the right Air Handling Units for your needs.


- > 3D interface
- > quick selection procedures
- > new print-out possibilities and report shapes



Plugins and third-party software tools

Building Information Modelling (BIM) support

- > BIM improves efficiency of design and build phase
- Daikin is among the first to supply a full library of BIM objects for its VRV products





Energy simulation and design aid tools

Seasonal simulator


- The Seasonal Simulator is an innovative software tool that calculates and compares potential seasonal efficiency ratings.
- This user-friendly tool compares various Daikin systems, annual power consumption, CO₂ emissions, and much more, to present an accurate ROI calculation in a matter of minutes.



Psychrometrics diagram



- > The Psychrometrics Diagram Viewer demonstrates the changing properties of moist air.
- > With this tool, users can choose two points with specific conditions, plot them on the diagram and select actions to change the conditions, i.e. heat, cool and mix air.



Software service tools

Error code app

Quickly know the meaning of fault codes, for each product family and the potential cause

D-Checker

D-checker is a software application used to record and monitor operation data of Daikin applied, split, Multi-split, Sky-air units, Daikin Altherma LT, ground source heat pump, Hybrid, ZEAS, Conveni-pack & R410A Booster unit

Bluetooth adaptor **NEW**


Monitoring of Split, Sky Air and VRV data via any bluetooth device

- > No need to access the outdoor unit
- Connects with D-Checker software (for laptops)
- Connects with monitoring app (for tablets or smartphones)

VRV Service-Checker

- Connected via F1/F2 bus to check multiple systems at the same time
- > Connection of external pressure sensors possible





Diagnosis of the Bluetooth system possible:




Online support

Business portal

- > Experience our new extranet that thinks with you at my.daikin.eu
- > Find information in seconds via a powerful search
- > Customise the options so you see only info relevant for you
- > Access via mobile device or desktop

Internet

Find our solution for different applications:



- Get more commercial details on our flagship products via our dedicated minisites
- > See our references



www.daikineurope.com/references





Over 30 years of VRV History



R-22

1987

Introduction the original VRV air conditioning system to Europe, invented by Daikin in 1982

> Up to 6 indoor units connected to 1 outdoor unit



R-407C

1998

Launch inverter series with R-407C

> Up to 16 indoor units connected to 1 outdoor unit



2004

Expand to light commercial sector with VRVII-S

- > Available in 4, 5, 6HP capacities
- > 1 system can be installed in up to 9 rooms



2008

Launch of heat pump optimised for heating (VRV III-C)

- > Extended operation down to -25C
- > 2-stage compressor systems

Available in cooling, heat pump and heat recovery

> 40 units connected to single refrigerant circuit



1991

Introduce VRV heat recovery

> Simultaneous cooling and heating



2003

Introduce VRVII-- the first R-410A **VRF** system



R-410A



2005

Extends VRVII inverter range with water cooled VRV-WIII

> Available in heat pump and heat recovery



2006-2007

Launch the extensively re-engineered VRVIII

- > Available in cooling, heat pump and heat recovery
- > Automatic charging and testing
- > Up to 64 units connected to 1 system









2015

Launch of VRV IV S-series

- Most compact unit in the market
- > Widest range in the market



Launch of VRV IV i-series

- > The invisible VRV
- > Unique product concept





2019

Launch of VRV IV+ series

- New compressor for increased seasonal efficiency
- Available in heat recovery, heat pump, optimised for heating and water-cooled versions

BLUEVOLUTION



2020

VRV 5 S-series

- Completely redesign unit for R-32 refrigerant
- > Easier to handle and more flexible to install then ever!

Launch total solution concept

> Integrate hot water production

> Connectable to Daikin Emura

> 400,000 outdoors units sold

> 2.2 million indoor units sold

and Biddle air curtains into VRV

2010

2011

system

and Nexura

Launch of replacement VRV (VRVIII-Q)

> Upgrade to replace older VRV units using R-22 refrigerant



2012-2014

Setting new standards with the launch of VRV IV

- > 28% improved seasonal efficiency
- > Continuous heating on heat pumps
- Available in heat pump, heat recovery, water-cooled and replacement series





2019

Launch of L∞P by Daikin

- > Re-use of existing refrigerant
- Creating a circular economy of refrigerants



2022

VRV 5 Heat Recovery

- > Our sustainability hero
- Completely redesigned for R-32 refrigerant

BLUEVOLUTION





Technical drawings

Outdoor units	244
Indoor units	275
Hot water	327
Biddle air curtains	332
Ventilation	335




Detail -B-

Detail -A-



REYA8-12A / REMA5A



NOTES

- 1. Detail ·A· and detail ·B· indicate the dimensions after fixing the attached piping. 2. Items 4-10: Knockout hole.


۷.	items 4 – 10. Knockodi noie.		
3.	Gas pipe		
	RYYQ8U, RYMQ8U, RXYQ8U, RXYQQ8U, RXYTQ8U	Ø 19.1	brazing connection
	RYYQ10U, RYMQ10U, RXYQ10U, RXYQQ10U	Ø 22.2	brazing connection
	REMQ5U, REMA5A, REYQ8-12U, REYA8-12A	Ø 25.4	brazing connection
	RYYQ12U, RYMQ12U, RXYQ12U, RXYQQ12U	Ø 28.6	brazing connection
	Liquid pipe		-
	RYYQ8-10U, RYMQ8-10U, RXYQ8-10U, RXYQQ8-10U,	Ø 9.5	brazing connection
	REMQ5U, REMA5A, REYQ8-12U, REYA8-12A, RXYTQ8I	J	9
	RYYQ12U, RYMQ12U, RXYQ12U, RXYQQ12U	Ø 12.7	brazing connection
	Equalising pipe		-
	RÝMQ8-10Ú	Ø 19.1	brazing connection
	RYMQ12U	Ø 22.2	brazing connection
	High pressure/low pressure gas pipe		-
	REMQ5U, REMA5A, REYQ8-12U, REYA8-12A	Ø 19.1	brazing connection
			-

-	930	Model		AA	AB
		RYYQ8-12U, RXYQ8-1	12U, RXYQQ8-12U,RXYTQ8U	-	-
		REYA8-12A / REMA5/	4	240	240
No.	Part name		Remark		
-	The state of the s		c		1

No.	Part name	Remark
1	Liquid pipe connection port	See note ·3·.
2	Gas pipe connection port	See note ·3·.
3	Equalising pipe connection port High pressure/low pressure gas pipe	See note ·3·.
4	Power cord routing hole (side)	Ø65
5	Power cord routing hole (front)	Ø80
6	Power cord routing hole (front)	Ø65
7	Power cord routing hole (front)	Ø27
8	Power cord routing hole (bottom)	Ø65
9	Pipe routing hole (front)	
10	Pipe routing hole (bottom)	
11	Grounding terminal	Inside of the switch box (·M8·)

2D119001A

REYA14-20A



NOTES

- 1. Detail A and detail B indicate the dimensions after fixing the attached piping.
- 2. Items ·4 10: Knockout hole. 3. Gas pipe

٠.	items 4 – 10. Knockout noic.		
3.	Gas pipe		
	RXYTQ10U	Ø 22.2	brazing connection
	REYQ14-20U, REYA14-20A	Ø 25.4	brazing connection
	RYYQ14-20U, RYMQ14-20U RXYQ14-20U,		9
	RXYQQ14-20U, RXYTQ12-16U	Ø 28.6	brazing connection
	Liquid pipe		9
	RXYTQ10U	Ø 9.5	brazing connection
	RYYQ14-16U, RYMQ14-16U, RXYQ14-16U, RXYQQ14-	-16U,	~
	REYQ14-20U, REYA14-20A, RXYTQ12-16U	Ø 12.7	brazing connection
	RYYQ18-20U, RYMQ18-20U, RXYQ18-20U,		9
	RXYQQ18-20U	Ø 15.9	brazing connection
	Equalising pipe		-
	RYMQ14-16U	Ø 22.2	brazing connection
	RYMQ18-20U	Ø 28.6	brazing connection
	High pressure/low pressure gas pipe		
	REYQ14-20U, REYA14-20A	Ø 19.1	brazing connection
			-

No.	Part name	Remark
1	Liquid pipe connection port	See note 3.
2	Gas pipe connection port	See note 3.
3	Equalising pipe connection port High pressure/low pressure gas pipe	See note 3.
4	Power cord routing hole (side)	Ø65
5	Power cord routing hole (front)	Ø80
6	Power cord routing hole (front)	Ø65
7	Power cord routing hole (front)	Ø27
8	Power cord routing hole (bottom)	Ø65
9	Pipe routing hole (front)	
10	Pipe routing hole (bottom)	
11	Grounding terminal	Inside of the switch box (M8)

RYMQ18-20U


2D119091A

AA AB

240 192

CLICK HERE TO VIEW ALL REYA-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU


REYA-A / REMA-A



NOTES


Height of the walls in case of patterns 1 and 2: Front: 1,500mm
 Suction side: 500mm

Suction side: 500mm
Side: height unrestricted
The installation space shown on this drawing is based on cooling operation at 35°C (outdoor temperature).
When the design outdoor ambient temperature exceeds 35°C or the load exceeds maximum ability of much generation load of heat in all outdoor unit, make sure the suction-side space is broader than the space shown on this drawing.
2. If the walls are higher than mentioned above, then additional service space is needed:
- suction side: service space + h1/2
- front side: service space + h2/2
3. When installing the units, select the pattern that best fits the available space.
Always keep in mind to leave sufficient space for a person to pass between unit and wall and for the air to circulate freely.
Provide sufficient space at the front to connect refrigerant piping (comfortably).
4. If more units are to be installed than are catered for in the above patterns, your layout should take into account of the possibility of short circuits.




3D118467A







RXYSA-AV1/AY1



3D127871A



RXYSA-AV1/AY1

Single unit () | Single row of units ()

Suction side

In the illustration below, the service space at the suction side is based on 35°C DB and cooling operation. Foresee more space in the following cases:

- When the suction side temperature regularly exceeds this temperature.
- When the heat load of the outdoor units is expected to regularly exceed the maximum operating capacity.

Discharge side

Take refrigerant piping work into account when positioning the units. If your lay out does not match with any of the layouts below, contact your dealer.

Single unit () | Single row of units ()

<u> </u>				₹							
	A~E	ا ا	Hb Hd Hu	(mm)							
	A~L	'	briaria	a	Ь	С	d	е	e _B	e _D	
	В		-		≥ 100						
	A,B,C		-	≥ 100(1)	≥ 100	≥ 100					
	B,E		-		≥ 100			≥ 1,000		≤500	
e _B ∕	A,B,C,E		_	≥ 150(1)	≥ 150	≥ 150		≥ 1,000		≤500	
e _D	D		-				≥ 500				
GD	D,E		=				≥ 500	≥ 1,000	≤500		
	B,D		Hd>Hu		≥ 100		≥ 500				
e			Hd≤Hu		≥ 100		≥ 500				
1/64			Hb≤½Hu		≥ 250		≥ 750	≥ 1,000	≤500		
HILL		Hd>Hu	½Hu>Hb≤Hu		≥ 250		≥ 1,000	≥ 1,000	≤500		
H. D. I'B	B.D.E		Hb>Hu				0				1
	B,D,E		Hd≤½Hu		≥ 100		≥ 1,000	≥ 1,000		≤500	≤500 ≤500
d a		Hd≤Hu	½Hu <hd≤hu< td=""><td></td><td>≥ 200</td><td></td><td>≥ 1,000</td><td>≥ 1,000</td><td></td><td>≤500</td></hd≤hu<>		≥ 200		≥ 1,000	≥ 1,000		≤500	
			Hd>Hu				0				
	A,B,C		-	≥ 200(1)	≥ 300 ≥	1,000					1
	A,B,C,E		-	≥ 200(1)	≥ 300	≥ 1,000		≥ 1,000		≤500	1
Φ,	D		-				≥ 1,000				
OB	D,E		-				≥ 1,000	≥ 1,000	≤500		
e_{D}			Hd>Hu		≥ 300		≥ 1,000				
	B,D	Hd≤Hu	Hd≤½Hu		≥ 250		≥ 1,500				
e e		Hushu	½Hu <hd≤hu< td=""><td></td><td>≥ 300</td><td></td><td>≥ 1,500</td><td></td><td></td><td></td><td></td></hd≤hu<>		≥ 300		≥ 1,500				
			Hb≤½Hu		≥ 300		≥ 1,000	≥ 1,000	≤500		
		Hd>Hu	½Hu <hb≤hu< td=""><td></td><td>≥ 300</td><td></td><td>≥ 1,250</td><td>≥ 1,000</td><td>≤500</td><td></td><td></td></hb≤hu<>		≥ 300		≥ 1,250	≥ 1,000	≤500		
2100(1) \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			Hb>Hu				0				
1000 H _B			Hd≤½Hu		≥ 250		≥ 1,500	≥ 1,000		≤500	
H _D d a	B,D,E		½Hu <hd≤hu< td=""><td></td><td>≥ 300</td><td></td><td>≥ 1,500</td><td>≥ 1,000</td><td></td><td>≤500</td><td>1+2</td></hd≤hu<>		≥ 300		≥ 1,500	≥ 1,000		≤500	1+2
		Hd≤Hu	Hd>Hu				0				

(1) For better serviceability, use a distance ≥250 mm

A,B,C,D Obstacles (walls/baffle plates)

E Obstacle (roof)

a,b,c,d,e Minimum service space between the unit and obstacles A, B, C, D and E

 e_B Maximum distance between the unit and the edge of obstacle E, in the direction of obstacle B e_D Maximum distance between the unit and the edge of obstacle E, in the direction of obstacle D

Hu Height of the unit

Hb,Hd Height of obstacles B and D

1 Seal the bottom of the installation frame to prevent discharged air from flowing back to the suction

side through the bottom of the unit.


2 Maximum two units can be installed.

Not allowed




RXYSA-AV1/AY1

Multiple rows of units (








- (A1) If there is danger of dramage dripping and freezing between the upper and lower units. (A2) Then install a roof between the upper and lower units. Install the upper unit high enough above the lower unit to prevent ice buildup at the upper unit's bottom plate.
- B1=>B2 (B1) If there is no danger of drainage dripping and freezing between the upper and lower units... (B2) Then it is not required to install a roof, but seal the gap between the upper and lower units to prevent discharged air from flowing back to the suction side through the bottom of the unit.

REMQ5U / REYQ8-12U / RXYQQ8-12U / RXYQ8-12U / RYYQ8-12U / RYMQ8-12U / RXYTQ8UYF

CLICK HERE TO VIEW ALL RXYQQ-U TECHNICAL DRAWINGS



NOTES

- 1. Detail ·A· and detail ·B· indicate the dimensions after fixing the attached piping.


۷.	items 4 – 10: Knockout noie.		
3.	Gas pipe		
	RYYQ8U, RYMQ8U, RXYQ8U, RXYQQ8U, RXYTQ8U	Ø 19.1	brazing connection
	RYYQ10U, RYMQ10U, RXYQ10U, RXYQQ10U	Ø 22.2	brazing connection
	REMQ5U, REMA5A, REYQ8-12U, REYA8-12A	Ø 25.4	brazing connection
	RYYQ12U, RYMQ12U, RXYQ12U, RXYQQ12U	Ø 28.6	brazing connection
	Liquid pipe		
	RYYQ8-10U, RYMQ8-10U, RXYQ8-10U, RXYQQ8-10U,	Ø 9.5	brazing connection
	REMQ5U, REMA5A, REYQ8-12U, REYA8-12A, RXYTQ8I	J	
	RYYQ12U, RYMQ12U, RXYQ12U, RXYQQ12U	Ø 12.7	brazing connection
	Equalising pipe		
	RYMQ8-10U	Ø 19.1	brazing connection
	RYMQ12U	Ø 22.2	brazing connection
	High pressure/low pressure gas pipe		
	REMQ5U, REMA5A, REYQ8-12U, REYA8-12A	Ø 19.1	brazing connection

-				
-	930	Model	AA	AB
		RYYQ8-12U, RXYQ8-12U, RXYQQ8-12U,RXYTQ8U	-	-
		REYA8-12A / REMA5A	240	240
n.	Part name	Remark		1

No.	Part name	Remark
1	Liquid pipe connection port	See note -3
2	Gas pipe connection port	See note ·3·.
3	Equalising pipe connection port High pressure/low pressure gas pipe	See note ·3·.
4	Power cord routing hole (side)	Ø65
5	Power cord routing hole (front)	Ø80
6	Power cord routing hole (front)	Ø65
7	Power cord routing hole (front)	Ø27
8	Power cord routing hole (bottom)	Ø65
9	Pipe routing hole (front)	
10	Pipe routing hole (bottom)	
11	Grounding terminal	Inside of the switch box (·M8·)

2D119001A

REYQ14-20U / RXYQQ14-20U / RXYQ14-20U / RYYQ14-20U / RYMQ14-20U / RXYTQ10-16UYF



NOTES

- 1. Detail A and detail B indicate the dimensions after fixing the attached piping.

1. Detail A data b indicate the difference bigging.				
2. Items ·4 – 10: Knockout hole.				
3. Gas pipe				
RXYTQ10U	Ø 22.2	brazing connection		
REYO14-20U, REYA14-20A	Ø 25.4	brazing connection		
RYYO14-20U, RYMO14-20U RXYO14-20U,				
RXYOO14-20U. RXYTO12-16U	Ø 28.6	brazing connection		
	XD 20.0	brazing connection		
Liquid pipe	005	1		
RXYTQ10U	Ø 9.5	brazing connection		
RYYQ14-16U, RYMQ14-16U, RXYQ14-16U, RXYQQ14				
REYQ14-20U, REYA14-20A, RXYTQ12-16U	Ø 12.7	brazing connection		
RYYQ18-20U, RYMQ18-20U, RXYQ18-20U,				
RXYOO18-20U	Ø 15.9	brazing connection		
Equalising pipe				
RYMO14-16U	Ø 22.2	brazing connection		
RYMO18-20U	Ø 28.6	brazing connection		
	W 20.0	brazing connection		
High pressure/low pressure gas pipe				
REYQ14-20U, REYA14-20A	Ø 19.1	brazing connection		

No.	Part name	Remark
1	Liquid pipe connection port	See note 3.
2	Gas pipe connection port	See note 3.
3	Equalising pipe connection port High pressure/low pressure gas pipe	See note 3.
4	Power cord routing hole (side)	Ø65
5	Power cord routing hole (front)	Ø80
6	Power cord routing hole (front)	Ø65
7	Power cord routing hole (front)	Ø27
8	Power cord routing hole (bottom)	Ø65
9	Pipe routing hole (front)	
10	Pipe routing hole (bottom)	
11	Grounding terminal	Inside of the switch box (M8)

RYMQ18-20U

RXYQ14-20U, RYYQ14-20U, RXYQQ14-20U, RXYTQ10-16U


RYMQ14-16U, REYQ14-20U, REYA14-20A

2D119091A

AA AB

240

REMQ-U / REYQ-U / RXYQQ-U / RXYQ-U / RYYQ-U / RYMQ-U / RXYTQ-UYF



NOTES

Height of the walls in case of patterns 1 and 2: Front: 1,500mm
 Suction side: 500mm

Side: height unrestricted

The installation space shown on this drawing is based on cooling operation at 35°C (outdoor temperature).


When the design outdoor ambient temperature exceeds 35°C or the load exceeds maximum ability of much generation load of heat in all outdoor unit, make sure the suction-side space is broader than the space shown on this drawing.

2. If the walls are higher than mentioned above, then additional service space is needed:

- suction side: service space + h1/2


frost dideservice space + h1/2

- suction side: service space + 71/2
- front side:




3D118467A

RXYSCQ-TV1




3D098107A

RXYSQ-TV9/TY9



1 Gas pipe connection A
2 Liquid pipe connection Ø9.5 flare
3 (2X) Service port (in the unit)
4 Electronic connection and grounding terminal M5 (in the switch box)
5 Refrigerant piping intake
6 Power supply wiring intake (knockout hole Ø34)
7 Control wiring intake (knockout hole Ø27)
8 Drain outlet




A
Ø19.1 brazed connection
Ø19.1 brazed connection
Ø19.1 brazed connection
Ø15.9 flared connection
Ø15.9 flared connection
Ø19.1 brazed connection
Ø15.9 flared connection
Ø15.9 flared connection
Ø19.1 brazed connection
Ø15.9 flared connection
Ø15.9 flared connection
Ø19.1 brazed connection
Ø15.9 flared connection
Ø15.9 flared connection
Ø19.1 brazed connection


Model	A			
	RA indoor unit	VRV indoor unit		
RXYSQ4(P8/T7/T8)V(1)B	Ø19.1 brazed connection	Ø15.9 flared connection		
RXYSQ5(P8/T7/T8)V(1)B	Ø19.1 brazed connection Ø15.9 flared connection			
RXYSQ6(P8/T7/T8)V(1)B	Ø19.1 brazed	connection		
RXYSQ4(P8/T7/T8)Y(1)B	Ø19.1 brazed connection	Ø15.9 flared connection		
RXYSQ5(P8/T7/T8)Y(1)B	Ø19.1 brazed connection Ø15.9 flared connection			
RXYSQ6(P8/T7/T8)Y(1)B	Ø19.1 brazed connection			

Gas pipe connection Ø19.1 brazing

RXYSQ8TY1



3D098108






RXYSCQ-TV1

Required installation space


The unit of the values is mm.

1. Where there is an obstacle on the suction side: (a) No obstacle above

- (1) Stand-alone installation
 - · Obstacle on the suction side only




· Obstacle on both sides




(2) Series installation (2 or more)

· Obstacle on both sides




(b)Obstacle above, too


(1) Stand-alone installation



 Obstacle on the suction side and both sides




(2) Series installation (2 or more)




2. Where there is an obstacle on the discharge side:

(a) No obstacle above

(1) Stand-alone installation




(2) Series installation (2 or more)




(b)Obstacle above, too

(1) Stand-alone installation



(2) Series installaton (2 or more)



3. Where there are obstacles on both suction and discharge sides:

Pattern 1

Where the obstacles on the discharge side is higher than the unit:

(There is no height limit for obstructions on the intake side.)

(a) No obstacle above


(1) Stand-alone installation



(2) Series installation

(2 or more)





CLICK HERE TO VIEW ALL RXYSCQ-TV1TECHNICAL DRAWINGS ON MY.DAIKIN.EU


RXYSCQ-TV1

(b)Obstacle above, too

(1) Stand-alone installation

0 < L ≤ 1/2H 750 I < H 1/2H < L ≤ H Set the stand as: $L \le H$

Close the bottom of the installation frame to prevent the discharged air from being bypassed.




(2) Series installation (2 or more)

The relations between H, A and L are as follows:

	L	Α
L≤H	0 < L ≤ 1/2H	1,000
	1/2H < L ≤ H	1,250
H < L	Set the stand as: $L \le H$.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.

Only two units can be installed for this series.




Pattern 2

Where the obstacles on the discharge side is lower than the unit: (There is no height limit for obstructions on the intake side.)

(a) No obstacle above


(1) Stand-alone installation





(2) Series installation (2 or more) The relations between H, A and L are as follows.

L	А
0 < L ≤ 1/2H	250
1/2H < L ≤ H	300



(b)Obstacle above, too

(1) Stand-alone installation

The relations between H, A and L are as follows.

L≤H	L 0 < L ≤ 1/2H 1/2H < L ≤ H	A 100 200		2000 or more
H < L	Set the stand as: L	. ≤ H.		1,000,1
the inst to prev charge	Close the bottom of the installation frame to prevent the discharged air from being bypassed.			I Janu more


(2) Series installation

The relations between H, A and L are as follows.

	J L	A		\n<5 /	7	1
L≤H	0 < L ≤ 1/2H	250		500 or less		
	1/2H < L ≤ H	300]			nore
H < L	Set the stand as: L	. ≤ H.]			1,000 or more
Close the bottom of the installation frame to prevent the discharged air from being bypassed. Only two units can be installed for this series.			1,000 or mor	I		


4. Double-decker installation (a) Obstacle on the discharge side

Close the gap Z (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed. Do not stack more than two unit.




(b)Obstacle on the suctions side

Close the gap Z (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed. Do not stack more than two unit.




5. Multiple rows of series installation (on the rooftop, etc.)

(a) One row of stand-alone installation



(b) Rows of series installation (2 or more)

The relations between H, A and L are as follows.



RXYSQ-TV9/TY9

Required installation space


CLICK HERE TO VIEW ALL

RXYSQ-TV9 TECHNICAL DRAWINGS ON MY.DAIKIN.EU


The unit of the values is mm.

(A) When there are obstacles on suction sides

- No obstacle above
 - 1 Stand-alone installation
 - · Obstacle on the suction side only




· Obstacle on both sides




(2) Series installation (2 or more)


· Obstacle on both sides



- Obstacle above, too
 - 1) Stand-alone installation
 - · Obstacle on the suction side, too




· Obstacle on the suction side, and both sides




(2) Series installation (2 or more)

· Obstacle on the suction side, and both sides




(B) When there are obstacles on discharge sides


- No obstacle above
 - (1) Stand-alone installation




(2) Series installation (2 or more)



- Obstacle above, too
- (1) Stand-alone installation



(2) Series installaton (2 or more)



(C) When there are obstacles on both suction and discharge sides

Pattern 1


Where the obstacles on the discharge side is higher than the unit: (There is no height limit for obstructions on the intake side.)


No obstacle above

(1) Stand-alone installation



(2) Series installation (2 or more)








RXYSQ-TV9/TY9

• Obstacle above, too

(1) Stand-alone installation The relations between H, A and L are as follows:

	L	А
L≤H	0 < L ≤ 1/2H	750
	1/2H < L ≤ H	1,000
H < L	Set the stand as: L ≤ H.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.




(2) Series installation (2 or more) The relations between H, A and L are as follows:

	L	А
L≤H	0 < L ≤ 1/2H	1,000
	1/2H < L ≤ H	1,250
H < L	Set the stand as: $L \le H$.	


Close the bottom of the installation frame to prevent the discharged air from being bypassed.


Only two units can be installed for this series.




Pattern 2


When the obstacles on the discharge side is lower than the unit: (There is no height limit for obstructions on the intake side.)






L≤H





L	А
0 < L ≤ 1/2H	250
1/2H < L ≤ H	300




1) Stand-alone installation

The relations between H, A and L are as follows.

	L	А	
L≤H	0 < L ≤ 1/2H	100	
	1/2H < L ≤ H	200	
H < L	Set the stand as: L ≤ H.		
Cl 4h - h - 44 £4h -			

Close the bottom of the installation frame to prevent the discharged air from being bypassed.



(2) Series installation


The relations between H, A and L are as follows.

_				
L≤H	0 < L ≤ 1/2H	250		500 or less
	1/2H < L ≤ H	300		500
H < L	Set the stand as:	L ≤ H.	1	\checkmark
Close the bottom of the installation frame to prevent the discharged air from being bypassed. Only two units can be installed for this series.				
ıble-decker installation				

(D) Double-decker installation


(1) Obstacle on the discharge side Close the gap A (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed. Do not stack more than two unit.

(2) Obstacle on the suctions side Close the gap A (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed. Do not stack more than two unit.



(E) Multiple rows of series installation (on the rooftop, etc.)

(1) One row of stand-alone installation



(2) Rows of series installation (2 or more)

The relations between H, A and L are as follows.

] L	A	
L≤H	0 < L ≤ 1/2H	250	
	1/2H < L ≤ H	300	
H < L	Cannot be inst	talled.	l 📐
	K		January Market Company of the Compan




RXYSQ8TY1

Required installation space


The unit of the values is mm.

1. Where there is an obstacle on the suction side: (a) No obstacle above

- (1) Stand-alone installation
 - · Obstacle on the suction side only




· Obstacle on both sides




(2) Series installation (2 or more) (note)

• Obstacle on both sides




(b)Obstacle above, too


- (1) Stand-alone installation
 - Obstacle on the suction side, too



• Obstacle on the suction side and both sides




- (2) Series installation (2 or more) (note)
 - · Obstacle on the suction side and both sides




2. Where there is an obstacle on the discharge side: (a) No obstacle above

(1) Stand-alone installation




(2) Series installation (2 or more) (note)




(b) Obstacle above, too

(1) Stand-alone installation



(2) Series installaton (2 or more) (note)



3. Where there are obstacles on both suction and discharge sides:


Pattern 1

Where the obstacles on the discharge side is higher than the unit: (There is no height limit for obstructions on the intake side.)


(a) No obstacle above

(1) Stand-alone installation





(2) Series installation (2 or more) (note)



CLICK HERE TO VIEW ALL RXYSQ-TYI TECHNICAL DRAWINGS ON MY.DAIKIN.EU

RXYSQ8TY1


(b)Obstacle above, too

(1) Stand-alone installation

The relations between H, A and L are as follows:

	L	А
L≤H	0 < L ≤ 1/2H	1,000
	1/2H < L ≤ H	1,250
H < L	Set the stand as: L ≤ H.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.




(2) Series installation (2 or more) (note)

The relations between H, A and L are as follows:

	L	А		
L≤H	0 < L ≤ 1/2H	1,000		
	1/2H < L ≤ H	1,250		
H < L	Set the stand as	Set the stand as: L ≤ H.		

Close the bottom of the installation frame to prevent the discharged air from being bypassed.

Only two units can be installed for this series.




Pattern 2

Where the obstacles on the discharge side is lower than the unit: (There is no height limit for obstructions on the intake side.)

(c) No obstacle above

(1) Stand-alone installation



(2) Series installation (2 or more) (note) The relations between H, A and L are as follows.

 $\mathsf{L} \leq \mathsf{H}$

L	А	100 or more
0 < L ≤ 1/2H	250	/ / , ,
1/2H < L ≤ H	300	100 or
		T Story to more

(d)Obstacle above, too


(1) Stand-alone installation

The relations between H, A and L are as follows.

	L	А
L≤H	0 < L ≤ 1/2H	100
	1/2H < L ≤ H	200
H < L	Set the stand as: L ≤ H.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.

If the distance exceed the figure in the (), then it's no need to set the stand.



(2) Series installation (note)

The relations between H, A and L are as follows.


	L	А]			
L≤H	0 < L ≤ 1/2H	250		500 or less	1 <	1_
	1/2H < L ≤ H	300				1,000 or more
H < L	$H < L$ Set the stand as: $L \le H$.				} -`≿	
Close the bottom of the installation frame to prevent the discharged air from being bypassed. Only two units can be installed for this series.						
If the distance exceed the figure in the (),						
men it	then it's no need to set the stand.					

4. Double-decker installation
(a) Obstacle on the discharge side (note)


Close the gap A (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed.
Do not stack more than two unit. Set the board (field supply) as the detail A between two units to prevent the drainage from frozing.

Leave the enough space between the layer one and the board.

(b) Obstacle on the suctions side (note)
Close the gap A (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed.
Do not stack more than two unit.
Set the board (field supply) as the detail A between two units to prevent the drainage from frozing.
Leave the enough space between the layer one and the board.




5. Multiple rows of series installation (on the rooftop, etc.)
(a) One row of stand-alone installation



(b) Rows of series installation (2 or more)

The relations between H, A and L are as follows.



OUTDOOR UNIT FOR VRV SYSTEM




RXYSQ10-12TY1

Required installation space


The unit of the values is mm.

1. Where there is an obstacle on the suction side: (a) No obstacle above

- (1) Stand-alone installation
 - · Obstacle on the suction side only




· Obstacle on both sides




(2) Series installation (2 or more) (note)

· Obstacle on both sides




(b)Obstacle above, too


- (1) Stand-alone installation
 - Obstacle on the suction side, too



• Obstacle on the suction side and both sides



- (2) Series installation (2 or more) (note)
 - · Obstacle on the suction side and both sides




2. Where there is an obstacle on the discharge side: (a) No obstacle above

(1) Stand-alone installation




(2) Series installation (2 or more) (note)




(b)Obstacle above, too

(1) Stand-alone installation



(2) Series installaton (2 or more) (note)



3. Where there are obstacles on both suction and discharge sides:


Pattern 1

Where the obstacles on the discharge side is higher than the unit: (There is no height limit for obstructions on the intake side.)

(a) No obstacle above

(1) Stand-alone installation

L > H



(2) Series installation (2 or more) (note)

CLICK HERE TO VIEW ALL RXYSQ-TYI TECHNICAL DRAWINGS ON MY.DAIKIN.EU

RXYSQ10-12TY1


(b)Obstacle above, too

(1) Stand-alone installation

The relations between H, A and L are as follows:

	L	А
L≤H	0 < L ≤ 1/2H	1,000
	1/2H < L ≤ H	1,250
H < L	Set the stand as: L ≤ H.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.




(2) Series installation (2 or more) (note)

The relations between H, A and L are as follows:

	L	А
L≤H	0 < L ≤ 1/2H	1,000
	1/2H < L ≤ H	1,250
H < L	Set the stand as: L ≤ H.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.

Only two units can be installed for this series.




Pattern 2

Where the obstacles on the discharge side is lower than the unit: (There is no height limit for obstructions on the intake side.)

(c) No obstacle above

(1) Stand-alone installation



(2) Series installation (2 or more) (note) The relations between H, A and L are as follows.

	,	
L	А	100 or More
0 < L ≤ 1/2H	250	· ×/
1/2H < L ≤ H	300	100 or
		T T T T T T T T T T T T T T T T T T T

(d)Obstacle above, too


(1) Stand-alone installation

The relations between H, A and L are as follows.

		-
	L	А
L≤H	0 < L ≤ 1/2H	100
	1/2H < L ≤ H	200
H < L	Set the stand as: L ≤ H.	

Close the bottom of the installation frame to prevent the discharged air from being bypassed.

If the distance exceed the figure in the (), then it's no need to set the stand.




(2) Series installation (note)

The relations between H, A and L are as follows.

L≤H	L 0 < L ≤ 1/2H	A 250		units 1
	1/2H < L ≤ H	300] < 500'	3/KE
H < L	Set the stand as:	L ≤ H.		1,000 or more
installathe disbeing Only to installation of the configure	the bottom of to ation frame to percent of the control of the cont		Total Control of Children of C	


4. Double-decker installation
(a) Obstacle on the discharge side (note)

Close the gap A (the gap between the upper and lower outdoor units) to prevent the discharged air from being bypassed.
Do not stack more than two unit. Set the board (field supply) as the detail A between two units to prevent the drainage from frozing. Leave the enough space between the layer one and the board.




Close the gap A (the gap between the upper and lower outdoor units) to prevent the discharge air from being bypassed. Do not stack more than two unit. Set the board (field supply) as the detail A between two units to pre-

Set the board (field supply) as the detail A between two units to prevent the drainage from frozing. Leave the enough space between the layer one and the board.




5. Multiple rows of series installation (on the rooftop, etc.)
(a) One row of stand-alone installation




(b) Rows of series installation (2 or more)

The relations between H, A and L are as follows.




OUTDOOR UNIT FOR VRV SYSTEM






RKXYQ-T(8)




365




RDXYQ-T(8)






3D098834


RKXYQ-T(8)





RXMLQ-T-RXYLQ-T







lodel	AA	AB	
YMQ14-16T, RXYQQ14-16T, REYQ14-20T	240	205	
YMQ18-20T, RXYQQ18-20T	240	210	

NOTES

- 1. Detail ·A· and detail ·B· indicate the dimensions after fixing the attached piping.
- 2. Items 4 10: Knockout hole.
 3. Gas pipe
 RXMLQ8T:

- RXYTQ10T, RXYLQ10T: REYQ14-20T: RYYQ14-20T, RYMQ14-20T, RXYQ14-20T,
- RXYQQ14-20T, RXYTQ12-16T, RXYLQ12-14T: Liquid pipe RXYTQ10T, RXMLQ8T, RXYLQ10T:


- RYYQ14-16T, RYMQ14-16T, RXYQ14-16T, RXYQQ14-16T, REYQ14-20T, RXYTQ12-16T, RXYLQ12-14T:
 RYYQ18-20T, RYMQ18-20T, RXYQ18-20T, RXYQQ18-20T:
- Equalising pipe RYMQ14-16T: RYMQ18-20T
- High pressure/low pressure gas pipe REYQ14-20T:

- Ø 19.1 brazing connection Ø 22.2 brazing connection Ø 25.4 brazing connection
- Ø 28.6 brazing connection
- \emptyset 9.5 brazing connection
- Ø 12.7 brazing connection Ø 15.9 brazing connection
- Ø 22.2 brazing connection Ø 28.6 brazing connection
- Ø 22.2 brazing connection

No.	Part name	Remark
1	Liquid pipe connection port	See note ·3·.
2	Gas pipe connection port	See note ·3·.
3	Equalising pipe connection port High pressure/low pressure gas pipe	See note ·3·.
4	Power cord routing hole (side)	Ø65
5	Power cord routing hole (front)	Ø80
6	Power cord routing hole (front)	Ø65
7	Power cord routing hole (front)	Ø27
8	Power cord routing hole (bottom)	Ø65
9	Pipe routing hole (front)	
10	Pipe routing hole (bottom)	
11	Grounding terminal	Inside of the switch box (·M8·)

2D079533E

RXMLQ-T-RXYLQ-T




- 1. Heights of walls in case of patterns 1 and 2:

- 1. Heights of wails in case of patterns 1 and 2:
 Front: 1,500mm
 Suction side: 500mm
 Side: Height unrestricted
 Installation space as shown on this drawing is based on the cooling operation at 35 degrees outdoor air temperature.
 When the design outdoor air temperature exceeds 35 degrees or the load exceeds maximum ability of much generation load of heat in all outdoor unit, take the suction side space more broadly than the space as shown on this drawing.

 2. If the above wall heights are exceeded then h2/2 and h1/2 should be added to the front and suction side service spaces respectively as shown in
- the figure on the right.


 3. When installing the units most appropriate pattern should be selected from those shown above in order to obtain the best fit in the space available. Always keep in mind the need to leave enough space for a person to pass between units and wall and also for the air to circulate freely.
- (If more units are to be installed than are catered for in the above patterns your layout should take account of the possibility of short circuits).

 4. The units should be installed to leave sufficient space at the front for the on site refrigerant piping work to be carried out comfortably.





CLICK HERE TO VIEW ALL RQCEQ-P3 TECHNICAL DRAWINGS ON MY.DAIKIN.EU

RQCEQ280P3



Space example for installation





NOTES

1. Heights of walls Front: 1,500mm

freely.

Suction side: 500mm
Side: Height unrestricted
The installation space shown in this figure is based on the condition of cooling operation at the outdoor air temperature of 35°C. The installation space of suction side shown above must be expanded in the following case.

- Design outdoor temperature becomes over 35°C.

Operating over Max. operating load
(In case of causing a heavy heating load at indoor unit side)


If the above wall heights are exceeded then h2/2 and h1/2 should be added

- to the front and suction side service spaces respectively as shown in the following figure.

 3. When installing the units the most appropriate pattern should be selected
- from those shown above in order to obtain the best fit in the space available always bearing in mind the need to leave enough room for a person to pass between units and wall and for the air to circulate freely. (If more units are to be installed than are catered for in the above patterns your layout should take account of the possibility of short circuits.)

 4. The units should be installed to leave sufficient space at the front for the on
- site refrigerant piping work to be carried out comfortably.

3D066856B




3D066860B

(If more units are to be installed than are catered for in the above patterns your layout should take account of the possibility of short circuits.)

4. The units should be installed to leave sufficient space at the front for the on site refrigerant piping work to be carried out comfortably.





RQCEQ721-816P3



UNIT: mm

Space example for installation





NOTES

- 1. Heights of walls
- Front: 1.500mm
- Suction side: 500mm Side: Height unrestricted

The installation space shown in this figure is based on the condition

- The installation space shown in this figure is based on the condition of cooling operation at the outdoor air temperature of 35°C. The installation space of suction side shown above must be expanded in the following case.


 Design outdoor temperature becomes over 35°C.

 Operating over Max. operating load (In case of causing a heavy heating load at indoor unit side)

 If the above wall heights are exceeded then h2/2 and h1/2 should be added to the front and suction side service spaces respectively as shown in the following figure.

 3. When installing the units the most appropriate pattern should be selected from those shown above in order to obtain the best fit in the space available always bearing in mind the need to leave enough room for a person to pass between units and wall and for enough room for a person to pass between units and wall and for the air to circulate freely. (If more units are to be installed than are catered for in the above patterns your layout should take account of the possibility of short
- . circuits.)
- The units should be installed to leave sufficient space at the front for the on site refrigerant piping work to be carried out comfortably.

3D066865B




No.	Part name	Remark
1	Liquid pipe connection port	ø9.5 Brazing connection
2	Gas pipe connection port	See note 3.
3	Grounding terminal	Inside of switch box (M8)
4	Power cord routing hole (side)	ø62
5	Power cord routing hole (front)	ø45
6	Power cord routing hole (front)	ø27
7	Power cord routing hole (bottom)	ø50
8	Wire routing hole (front)	ø27
9	Pipe routing hole (front)	See note 2.
10	Pipe routing hole (bottom)	See note 2.

- 1. **X** shows the dimensions after fixing the accessory pipes.
- 2. For piping connection method (front and bottom sides) see the installation manual.
- 3.Gas pipe
- ø15.9 Brazing connection: RQYQ140P3

CLICK HERE TO VIEW ALL RQYQ-P TECHNICAL DRAWINGS ON MY.DAIKIN.EU

RQYQ140P



NOTES

1. Heights of walls in case of patterns 1 and 2:

Front: 1,500mm

Suction side: 500mm

Side: Height unrestricted

Installation space to be shown on this drawing is based on the cooling operation at 35 degrees outdoor air temperature.

When the design outdoor air temperature exceeds 35 degrees or the load exceeds maximum ability of much generation load of heat in all outdoor unit, take the suction side space more broadly than the space as shown on this drawing.

- 2.If the above wall heights are exceeded then h2/2 and h1/2 should be added to the front and suction side service spaces respectively as shown in the figure on the right.


 3. When installing the units most appropriate pattern should be selected from those shown above in order to obtain
- the best fit in the space available always bearing in mind the need to leave enough space for a person to pass between units and wall and for the air to circulate freely.
- (If more units are to be installed than are catered for in the above patterns your layout should take account of the possibility of short circuits).

 4.The units should be installed to leave sufficient space at the front for the on site refrigerant piping work to be carried
- out comfortably.





RWEYQ-T9



NOI


- 1. The grounding terminal is located in the switch box.
- 2. The pipe connections are brazed connections.
- 3. In case of a heat pump, the suction pipe is not used.

Table 1

Model	RWEYQ8T9		RWEYQ10T9		RWEYQ12T9		RWEYQ14T9	
Operation mode	Heat pump	Heat recovery						
Liquid pipe	Ø 9.5		Ø 9.5		Ø 12.7		Ø 12.7	
Suction pipe		Ø 19.1		Ø 22.2		Ø 28.6		Ø 28.6
Gas pipe (high/low pressure)	Ø 19.1	Ø 15.9	Ø 22.2	Ø 19.1	Ø 28.6	Ø 19.1	Ø 28.6	Ø 22.2

2D108932A

RWEYQ-T9




- \bigstar 1. This space is necessary when refrigerant piping is connected to the top of the unit.
- ★2. This ventialition space is necessary when heat rejection cancellation (Zero energy sissipation) is not active.

CLICK HERE TO VIEW ALL BS1Q-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

BS1Q10A


- Electric box can also be fixed on the other side of the unit.
 Be sure to install a inspection door at electric box side.
 Attached pipe is only used in case of connecting with a 20~50 class indoor unit,
 Small sound of refrigerant will be made, which may be disturbing.
 Do not install it at the place such as bedroom under roof.

Number	Part name	Description
1	Suction gas pipe connection port	Ø15.9mm brazing connection
2	HP/LP gas pipe connection port	Ø12.7mm brazing connection
3	Liquid pipe connection port	Ø 9.5mm brazing connection
4	Gas pipe connection port	Ø15.9mm brazing connection
5	Liquid pipe connection port	Ø 9.5mm brazing connection
6	Electric box (Note 1.)	
7	Suspension brackets	M8~M10
8	Grounding terminal	M4
9	Attached pipe(1) (Note.3)	Ø12.7mm brazing connection
10	Attached pipe(2) (Note.3)	Ø 6.4mm brazing connection



BS1Q16A

- 1. Electric box can also be fixed on the other side of the unit.
- 1. Electric box can also be lixed on the oriner side of the unit.
 2. Be sure to install an inspection door at electric box side.
 3. Attached pipe is only used in case of connecting with indoor unit capacity indey 150 or more and 160 or less.
 4. Small sound of refrigerant will be made, which may be disturbing.
 Do not install it at the place such as bedroom under roof.





BS1Q25A


- 1. Electric box can also be fixed on the other side of the unit.
 2. Be sure to install an inspection door at electric box side.
 3. Attached pipe(1) and Attached pipe(2) is used in case of connecting with indoor capacity index more than 160 and less than 200.

 In case of connecting one indoor unit of 200 type, only gas pipe connection port need Attached pipe(1).

 4. Small sound will be made when changing over the motor operated valve, which may be disturbing.

 Do not install it at the place such as bedroom under roof.

Number	Part name	Description
1	Suction gas pipe connection port	Ø15.9mm brazing connection
2	HP/LP gas pipe connection port	Ø12.7mm brazing connection
3	Liquid pipe connection port	Ø 9.5mm brazing connection
4	Gas pipe connection port	Ø15.9mm brazing connection
5	Liquid pipe connection port	Ø 9.5mm brazing connection
6	Electric box (Note 1.)	
7	Suspension brackets	M8~M10
8	Grounding terminal	M4
9	Attached pipe(1) (Note.3)	Ø19.1mm brazing connection
10	Attached pipe(2) (Note.3)	Ø 15.9 mm brazing connection




CLICK HERE TO VIEW ALL BS-Q14AV1B TECHNICAL DRAWINGS ON MY.DAIKIN.EU

BS4Q14AV1B

NOTES

- Be sure to install an inspection door at electric box side, another door is necessary to unload the product
- Install the BS box on a location where the refrigerant noise cannot disturbe the room
 - occupants.
 To avoid that refrigerant noise disturbs the people in the room, keep at least 5m piping between the occupied room and the BS box.
 - If there is no false ceiling at the room, please add sound insulation around the piping between BS box and indoor unit, or keep much longer length between BS box and occupied room.
- Occupy the space which is possible to install
- field pipes.
 In case of connection with a 20~50 type indoor unit, there is no need to cut and
 - connect as it is.
 In case of others, cut the outlet pipe and connect to the connecting pipe. Refer to figure above.
- Reducer may be required (field supply) if joint diameter does not suit on the triple piping
- Insulators are necessary (field supply) for the triple piping side.
 This space is a space to keep a top panel when
- servicing.
 Install it in a space which can be secured downwards slope of 1/100 or more.
- 9. It is a space for removing the drain pan.
 10. This is a space for removing a top panel when
- servicing.



Item	Part name	Remark
1	Outdoor unit suction gas pipe connection port (note 5, 6)	ø 22.2 mm brazing connection
2	Outdoor unit HP/LP gas pipe connection port (note 5, 6)	ø 19.1 mm brazing connection
3	Outdoor unit liquid pipe connection port (note 5, 6)	ø 9.5 mm brazing connection
4	Indoor unit gas pipe connection port (note 4)	ø 15.9 mm brazing connection
5	Indoor unit gas pipe connection port (note 4)	ø 12.7 mm brazing connection
6	Indoor unit liquid pipe connection port (note 4)	ø 9.5 mm brazing connection
7	Indoor unit liquid pipe connection port (note 4)	ø 6.4 mm brazing connection
8	Electric box (note 1)	
9	Suspension brackets	M8~M10
10	Grounding terminal	M4
11	Socket for drain	VP20 (O.D.ø 26 mm / I.D.ø 20 mm)
12	Attached pipe (note 5, 6)	ø 19.1 mm brazing connection
13	Attached pipe (note 5, 6)	ø 15.9 mm brazing connection
14	Inspection hole	
	-	-


3D106407

BS6Q14AV1B

- Be sure to install an inspection door at electric box side, another door is necessary to unload
- the product.
 Install the BS box on a location where the refrigerant noise cannot disturbe the room
 - occupants.
 -To avoid that refrigerant noise disturbs the people in the room, keep at least 5m piping between the occupied room and the BS box. If there is no false ceiling at the room, please add sound insulation around the piping between BS box and indoor unit, or keep much longer length between BS box and occupied room.
- Occupy the space which is possible to install field pipes.
 In case of connection with a 20~50 type
- indoor unit, there is no need to cut and connect as it is. In case of others, cut the outlet pipe and
- connect to the connecting pipe. Refer to figure above.
- Reducer may be required (field supply) if joint diameter does not suit on the triple piping
- Insulators are necessary (field supply) for the triple piping side.
- This space is a space to keep a top panel when servicing.
- Install it in a space which can be secured
- downwards slope of 1/100 or more.

 9. It is a space for removing the drain pan.

 10. This is a space for removing a top panel when servicing.



Item	Part name	Remark
1	Outdoor unit suction gas pipe connection port (note 5, 6)	ø 28.6 mm brazing connection
2	Outdoor unit HP/LP gas pipe connection port (note 5, 6)	ø 19.1 mm brazing connection
3	Outdoor unit liquid pipe connection port (note 5, 6)	ø 12.7 mm brazing connection
4	Indoor unit gas pipe connection port (note 4)	ø 15.9 mm brazing connection
5	Indoor unit gas pipe connection port (note 4)	ø 12.7 mm brazing connection
6	Indoor unit liquid pipe connection port (note 4)	ø 9.5 mm brazing connection
7	Indoor unit liquid pipe connection port (note 4)	ø 6.4 mm brazing connection
8	Electric box (note 1)	
9	Suspension brackets	M8~M10
10	Grounding terminal	M4
11	Socket for drain	VP20 (O.D.ø 26 mm / I.D.ø 20 mm)
12	Attached pipe (note 5, 6)	ø 22.2 mm brazing connection
13	Inspection hole	

3D106408




BS8Q14AV1B

NOTES

- Be sure to install an inspection door at electric box side, another door is
- necessary to unload the product. Install the BS box on a location where the refrigerant noise cannot disturbe
 - the room occupants.
 To avoid that refrigerant noise disturbs the people in the room, keep at least 5m piping between the occupied room and the BS box.

 If there is no false ceiling at the room,
- please add sound insulation around the piping between BS box and indoor unit, or keep much longer length between BS box and occupied room.
- Occupy the space which is possible to install field pipes.
- In case of connection with a 20~50 type indoor unit, there is no need to cut and connect as it is. In case of others, cut the outlet pipe and connect to the connecting pipe. Refer to figure above.
- Reducer may be required (field supply) if joint diameter does not suit on the triple piping side.
 Insulators are necessary (field supply)
- for the triple piping side.
 This space is a space to keep a top panel when servicing.
 Install it in a space which can be
- secured downwards slope of 1/100 or more.
- It is a space for removing the drain pan. This is a space for removing a top panel when servicing.




l	item	Part name	IKemark
[1	Outdoor unit suction gas pipe connection port (note 5, 6)	ø 28.6 mm brazing connection
[2	Outdoor unit HP/LP gas pipe connection port (note 5, 6)	ø 19.1 mm brazing connection
[3	Outdoor unit liquid pipe connection port (note 5, 6)	ø 12.7 mm brazing connection
[4	Indoor unit gas pipe connection port (note 4)	ø 15.9 mm brazing connection
[5	Indoor unit gas pipe connection port (note 4)	ø 12.7 mm brazing connection
[6	Indoor unit liquid pipe connection port (note 4)	ø 9.5 mm brazing connection
	7	Indoor unit liquid pipe connection port (note 4)	ø 6.4 mm brazing connection
[Electric box (note 1)	
[9	Suspension brackets	M8~M10
[10	Grounding terminal	M4
[11	Socket for drain	VP20 (O.D.ø 26 mm / I.D.ø 20 mm)
[12	Attached pipe (note 5, 6)	ø 28.6 mm brazing connection
[13	Attached pipe (note 5, 6)	ø 22.2 mm brazing connection
[14	Attached pipe (note 5, 6)	ø 15.9 mm brazing connection
	15	Inspection hole	

3D106409

BS10Q14AV1B

- Be sure to install an inspection door at electric box side, another door is necessary to unload the product. - Install the BS box on a location where
- the refrigerant noise cannot disturbe the room occupants.
 To avoid that refrigerant noise disturbs
 - the people in the room, keep at least 5m piping between the occupied room and the BS box.

 If there is no false ceiling at the room,
 - please add sound insulation around the piping between BS box and indoor unit, or keep much longer length between BS box and occupied room
- Occupy the space which is possible to install field pipes.
- In case of connection with a 20~50 type indoor unit, there is no need to cut and connect as it is. In case of others, cut the outlet pipe and connect to the connecting pipe. Refer to figure above.
- Reducer may be required (field supply) if joint diameter does not suit on the triple piping side.
- Insulators are necessary (field supply)
- for the triple piping side. This space is a space to keep a top
- panel when servicing. Install it in a space which can be secured downwards slope of 1/100
- or more. It is a space for removing the drain pan This is a space for removing a top panel when servicing.




CLICK HERE TO VIEW ALL BS-Q14AV1B TECHNICAL DRAWINGS ON MY.DAIKIN.EU

BS12Q14AV1B

NOTES

- Be sure to install an inspection door at electric box side, another door is necessary to unload the product.
- Install the BS box on a location where the refrigerant noise cannot disturbe the room occupants. To avoid that refrigerant noise disturbs
 - the people in the room, keep at least 5m piping between the occupied room and the BS box.
 - If there is no false ceiling at the room, please add sound insulation around the piping between BS box and indoor
- unit, or keep much longer length between BS box and occupied room. Occupy the space which is possible to install field pipes. In case of connection with a 20~50 type indoor unit, there is no need to cut and connect as it is. In case of others, cut the outlet pipe and connect to the connecting pipe.
- Refer to figure above. Reducer may be required (field supply) if joint diameter does not suit on the
- triple piping side. Insulators are necessary (field supply) for the triple piping side.
- This space is a space to keep a top
- panel when servicing.
 Install it in a space which can be secured downwards slope of 1/100 or more.
- It is a space for removing the drain pan.
 This is a space for removing a top panel when servicing.



BS16Q14AV1B

Electric box (note 1)

uspension brackets

Attached pipe (note 5, 6


Grounding terminal Socket for drain Attached pipe (note 5, 6)

NOTES

10

- Be sure to install an inspection door at electric box side, another door is
- necessary to unload the product. Install the BS box on a location where the refrigerant noise cannot disturbe
 - the room occupants.
 To avoid that refrigerant noise disturbs the people in the room, keep at least 5m piping between the occupied room and the BS box.

 - If there is no false ceiling at the room,
 - please add sound insulation around the piping between BS box and indoor unit, or keep much longer length
- between BS box and occupied room. Occupy the space which is possible to install field pipes.
- In case of connection with a 20~50 type indoor unit, there is no need to cut and connect as it is. In case of others, cut the outlet pipe and connect to the connecting pipe.
 Refer to figure above.
- Reducer may be required (field supply) if joint diameter does not suit on the triple piping side.
- Insulators are necessary (field supply)
- for the triple piping side. This space is a space to keep a top panel when servicing.
- Install it in a space which can be secured downwards slope of 1/100 or more.
- It is a space for removing the drain pan
- This is a space for removing a top panel when servicing.



Item	Part name	Remark
1	Outdoor unit suction gas pipe connection port (note 5, 6)	ø 34.9 mm brazing connection
2	Outdoor unit HP/LP gas pipe connection port (note 5, 6)	ø 28.6 mm brazing connection
3	Outdoor unit liquid pipe connection port (note 5, 6)	ø 19.1 mm brazing connection
4	Indoor unit gas pipe connection port (note 4)	ø 15.9 mm brazing connection
5	Indoor unit gas pipe connection port (note 4)	ø 12.7 mm brazing connection
6	Indoor unit liquid pipe connection port (note 4)	ø 9.5 mm brazing connection
7	Indoor unit liquid pipe connection port (note 4)	ø 6.4 mm brazing connection
8	Electric box (note 1)	
9	Suspension brackets	M8~M10
10	Grounding terminal	M4
11	Socket for drain	VP20 (O.D.ø 26 mm / I.D.ø 20 mm)
12	Inspection hole	


M8~M10 M4


VP20 (O.D.ø 26 mm / I.D.ø 20 mm) ø 34.9 mm brazing connection

ø 19.1 mm brazing connectior

3D106411







is inducted into the ceiling, additional insulation is required (polyethylene foam, thickness ≥-10 mm).

5. When installing a sensor kit, there will be a sensor on this location. For details, see the drawing of the sensor kit.

204 139

246 180

288 180

204 139

288 180

307

349

307

2,700


2,700 2,700

FXFQ20/25/32/40/50/63BVEB


FXFA20/25/32/40/50/63A2VEB

FXFQ80/100BVEB FXFQ125BVEB

FXFA125A2VEB



FXFA-A / FXFQ-B WITH FRESH AIR INTAKE




- When installing a fresh air intake kit, provide a service access panel.
- Field construction
- This corner discharge outlet needs to be closed.
 When installing a duct fan, use a wiring adapter to link the duct fan to the fan of the indoor unit.
 The intake air flow rate is recommended to be ≤20% of the air flow rate at high fan speed.
- If the intake air flow rate is too large, the operating sound may increase, and the detection of the indoor unit suction temperature may be affected.


 6. This indicates the distance between the T-joint inlet and the indoor unit inlet when the T-tube is connected.



FXZA-A / FXZQ-A NEW PANEL



FXZA-A OLD PANEL




4. Though the installation is acceptable up to maximum -660-mm square ceiling opening, keep the clearance of -45-mm or less between the indoor unit and the ceiling opening, so that the panel overlap allowance can be ensured.

278

Air suction grille Drain hose



FXZQ-A OLD PANEL




3D082161D

Inner: Ø25

CLICK HERE TO VIEW ALL FXCQ-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXCQ20-40A



Suction panel

3D079628




may fall.

under an indoor unit.

5. Please do not place the thing been damp and troubled


When the case where humidity is 80% or more, and the drain outlet are choked up and the air filter are dirty, dew



may fall.




FXCQ63A




3D079630

FXCQ80-125A


dew may fall.








3D038840A








FXDA10-32A


Service space of installation box for adaptor PCB.




















Item 1 Liquid pipe connection ·ø6.35· Flare connection Gas pipe connection ·ø9.52· Flare connection Drain pipe connection Outside diameter: •ø26-Inside diameter: •ø20-Drain hose (accessory) Inside diameter: -ø25-Transmission wiring connection Power supply connection 8 Suspension bracket Inspection door 10 Drain socket 11 Air filter (accessory)12 Heat exchanger Turbo fan 14 Fan motor Fan housing Drain pump Float switch Electronic expansion valve

NOTES

- 1. In case of bottom suction, mount the chamber cover to the backside of the unit.
- For more information, refer to the installation manual.

 2. In case of rear suction, mount the chamber cover to the bottom side of the unit. For more information, refer to the installation manual.

 3. The unit nameplate is located on the control box cover.


- 4. Mount the air filter at the suction side.


 Use an air filter with a dust collecting efficiency of at least -50% (measured by gravimetric analysis).


 When a duct is connected at the suction side, it is not possible to mount an air filter.


2D126395

FXDA40-50A













Suspension bolt pitch










- 1. In case of bottom suction, mount the chamber cover to the backside of the unit.
- For more information, refer to the installation manual.


?. In case of rear suction, mount the chamber cover to the bottom side of the unit.	
For more information, refer to the installation manual.	
3. The unit nameplate is located on the control box cover.	
I. Mount the air filter at the suction side.	
Use an air filter with a dust collecting efficiency of at least .50-% (measured by gravimetric analysis)).
When a duct is connected at the suction side, it is not possible to mount an air filter.	




Detailed technical drawings



FXDA63A



FXDA10A




NOTES

- The fan characteristics shown are in "fan only" mode.
- ESP: External Static Pressure
- 3. The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

2D126592



FXDA15A




NOTES

- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External Static Pressure
- 3. The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

3D129553


FXDA20-25A



- 1. The remote controller can be used to switch between 'high' and 'low'.
- 2. The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.



FXDA32A




NOTES

- 1. The remote controller can be used to switch between 'high'
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

3D081425C


FXDA40A



- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.



FXDA50A




NOTES

- 1. The remote controller can be used to switch between 'high' and 'low'
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

3D081427C

FXDA63A





- 1. The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

CLICK HERE TO VIEW ALL FXDQ-A3 TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXDQ15-32A3

Service space of installation box for adaptor PCB.





In case of bottom suction

NOTES

- NOTES

 1. In case of rear suction, mount the chamber cover to the bottom side of the unit. In case of bottom suction, mount the chamber cover to the backside of the unit.

 2. In case of bottom suction, no service space is required at the rear side.

 3. The unit nameplate is located on the control box cover.


 4. Mount the air filter at the suction side. Use an air filter with a dust collecting efficiency of at least .50% (measured by gravimetric analysis). When a duct is connected at the suction side, it is not possible to mount an air filter.
- possible to mount an air filter.


ltem	Name	Description
1	Liquid pipe connection port	ø 6.4 Flare connection
2	Gas pipe connection port	ø 12.7 Flare connection
3	Drain pipe connection	VP-20- (ID -20- x OD -26-)
4	Drain hose (accessory)	Inside diameter: ·25· Outlet
5	Control box	
6	Transmission wiring connection	
7	Power supply connection	
8	Suspension bracket	
9	Maintenance cover	
10	Drain socket	
11	Air filter (accessory)	


3D081435A


FXDQ40-50A3


Service space of installation box for adaptor PCB.













In case of bottom suction.

- NOTES

 1. In case of rear suction, mount the chamber cover to the bottom side of the unit.
 In case of bottom suction, mount the chamber cover to the backside of the unit.

 2. In case of bottom suction, no service space is required at the rear side.

 3. The unit nameplate is located on the control box cover.


 4. Mount the air filter at the suction side.
 Use an air filter with a dust collecting efficiency of at least 50% (measured by gravimetric analysis).
 When a duct is connected at the suction side, it is not possible to mount an air filter. possible to mount an air filter.


Item	Name	Description
1	Liquid pipe connection port	ø 6.4 Flare connection
2	Gas pipe connection port	ø 12.7 Flare connection
3	Drain pipe connection	VP-20- (ID -20- x OD -26-)
4	Drain hose (accessory)	Inside diameter: ·25· Outlet
5	Control box	
6	Transmission wiring connection	
7	Power supply connection	
8	Suspension bracket	
9	Maintenance cover	
10	Drain socket	
11	Air filter (accessory)	





FXDQ63A3


Service space of installation box for adaptor PCB.














NOTES

- In case of rear suction, mount the chamber cover to the bottom side of the unit.
 In case of bottom suction, mount the chamber cover to
- the backside of the unit.

 In case of bottom suction, no service space is required at the rear side.
- at the rear side.

 3. The unit nameplate is located on the control box cover.

 4. Mount the air filter at the suction side.


 Use an air filter with a dust collecting efficiency of at least :50-% (measured by gravimetric analysis).

 When a duct is connected at the suction side, it is not possible to mount an air filter.

ltem	Name	Description
1	Liquid pipe connection port	ø 6.4 Flare connection
2	Gas pipe connection port	ø 12.7 Flare connection
3	Drain pipe connection	VP-20- (ID -20- x OD -26-)
4	Drain hose (accessory)	Inside diameter: ·25· Outlet
5	Control box	
6	Transmission wiring connection	
7	Power supply connection	
8	Suspension bracket	
9	Maintenance cover	
10	Drain socket	
11	Air filter (accessory)	

3D081441A


FXDQ15A3



- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.



FXDQ20-25A3




NOTES

- The remote controller can be used to switch between 'high' and 'low'
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

3D086736B


FXDQ32A3



- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.



FXDQ40A3




NOTES

- 1. The remote controller can be used to switch between 'high' and 'low'
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.

3D081426C


FXDQ50A3



- 1. The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting.



FXDQ60A3




NOTES

- 1. Remote controller can be used to switch between 'HIGH' and 'LOW'. ('H', 'M' and 'L' for FDQ-A2VEB model)
- 2. The air flows is set to 'STANDARD' before leaving the factory. It is possible to switch between 'STANDARD ESP' and 'HIGH ESP' by remote controller.

3D081429C



FXSA15-32A




	·	
Item	Name	Description
KA	Liquid pipe connection port	·Ø6.35· flared connection
KB	Gas pipe connection port	·Ø9.52· flared connection
KC	Drain pipe connection	VP20 (OD Ø26, ID Ø20)
KD	Wiring connection	/
KE	Power supply connection	/
KF	Drain outlet	VP20 (OD Ø26, ID Ø20)
KG	Air filter	/
KH	Air suction side	/
KJ	Air discharge side	/
KK	Nameplate	/

NOTES

- When installing optional accessories, refer to their respective documentation.
 The ceiling depth varies according to the documentation of the specific system.
 In case of bottom suction, mount the chamber cover to the backside of the unit. For more information, refer to the installation manual.
 In case of rear suction, mount the chamber cover to the bottom side of the unit. For more information, refer to the installation manual.

3D128686A

FXSA40-50A




Item	Name	Description	
KA	Liquid pipe connection port	·Ø6.35· flared connection	
KB	Gas pipe connection port	-Ø12.70- flared connection	
KC	Drain pipe connection	VP20 (OD Ø26, ID Ø20)	
KD	Wiring connection	/	
KE	Power supply connection	/	
KF	Drain outlet	VP20 (OD Ø26, ID Ø20)	
KG	Air filter	/	
KH	Air suction side	/	
KJ	Air discharge side	/	
KK	Nameplate	/	

- . When installing optional accessories, refer to their respective documentation.
- The ceiling depth varies according to the documentation of the specific system.
 In case of bottom suction, mount the chamber cover to the backside of the unit. For more information, refer to the installation manual.
- 4. In case of rear suction, mount the chamber cover to the bottom side of the unit. For more information, refer to the installation manual.


CLICK HERE TO VIEW ALL FXSA-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXSA63-80A



FXSA100-125A

Nameplate



The ceiling depth varies according to the documentation of the specific system.
 In case of bottom suction, mount the chamber cover to the backside of the unit. For more information, refer to the installation manual.

4. In case of rear suction, mount the chamber cover to the bottom side of the unit.

For more information, refer to the installation manual


3D128716A

KG Air filter KH Air suction side KJ Air discharge side

KK Nameplate



FXSA140A



NOTES

VP20 (OD Ø26, ID Ø20)


- When installing optional accessories, refer to their respective documentation.
 The ceiling depth varies according to the documentation of the specific system.
 In case of bottom suction, mount the chamber cover to the backside of the unit. For more information, refer to the installation manual.
- For more information, refer to the installation manual.

3D128720A

FXSQ15-32A

KF Drain outlet KG Air filter KH Air suction side
KJ Air discharge side KK Nameplate

KE Power supply connection



Item	Name	Description	
KA	Liquid pipe connection port	.Ø6.35- flared connection	
KB	Gas pipe connection port	·Ø12.70· flared connection	
KC	Drain pipe connection	VP20 (OD Ø26, ID Ø20)	
KD	Wiring connection	/	
KE	Power supply connection	/	
KF	Drain outlet	VP20 (OD Ø26, ID Ø20)	
KG	Air filter	/	
KH	Air suction side	/	
KJ	Air discharge side	/	
KK	Nameplate	/	


1. When installing optional accessories, refer to their respective documentation.

2. The ceiling depth varies according to the documentation of the specific system.

3D094888B

CLICK HERE TO VIEW ALL FXSQ-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXSQ40-50A




2. The ceiling depth varies according to the documentation of the specific system.

1. When installing optional accessories, refer to their respective documentation. 2. The ceiling depth varies according to the documentation of the specific system.

3D094916B

FXSQ63-80A




KF Drain outlet KG Air filter KH Air suction side Air discharge side

KK Nameplate



FXSQ100-125A




FXSQ140A

KH Air suction side

KK Nameplate


KJ Air discharge side




NOTES

1. When installing optional accessories, refer to their respective documentation. 2. The ceiling depth varies according to the documentation of the specific system.

FXSQ15A FXSA15A



8,5 Air flow rate [m³/min]




- Upper limit of ESP by air flow auto adjustment
 Lower limit of ESP by air flow auto adjustment


- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External Static Pressure

3D096999B

FXSQ20-25A FXSA20-25A



Air flow rate [m³/min]




- 1. Upper limit of ESP by air flow auto adjustment 2. Lower limit of ESP by air flow auto adjustment


- 1. The fan characteristics shown are in "fan only" mode. 2. ESP: External Static Pressure
- 3D095680B



FXSQ32A FXSA32A





FXSQ40A FXSA40A



3D095681B


FXSQ50A FXSA50A






Air flow rate [m³/min]

Air flow rate [m³/min]






- 1. Upper limit of ESP by air flow auto adjustment 2. Lower limit of ESP by air flow auto adjustment


Λ	1ark		ESP [Pa]
	*1	Maximum	150
	*2	-	100
Г	*3	Standard	30

- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External Static Pressure


3D095688B


FXSQ63A FXSA63A





Air flow rate [m³/min]






Upper limit of ESP by air flow auto adjustment
 Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
*1	Maximum	150
*2	-	100
*3	Standard	30

- 1. The fan characteristics shown are in "fan only" mode. 2. ESP: External Static Pressure



FXSQ80A FXSA80A





Air flow rate [m³/min]

- Fan characteristics (2) Field setting with remote control
- Air flow rate range (H) External static pressure [Pa]

Air flow rate [m³/min]


Upper limit of ESP by air flow auto adjustment
 Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
*1	Maximum	150
*2	-	100
*2	Standard	40

- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External Static Pressure


3D095692B

FXSQ100A FXSA100A





Upper limit of ESP by air flow auto adjustment
 Lower limit of ESP by air flow auto adjustment





Mark		ESP [Pa]
*1	Maximum	150
*2	-	100
*3	Standard	40

- 1. The fan characteristics shown are in "fan only" mode. 2. ESP: External Static Pressure


CLICK HERE TO VIEW ALL FXSA-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXSQ125A FXSA125A





Fan characteristics (2) Field setting with remote control




- 1. Upper limit of ESP by air flow auto adjustment 2. Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
*1	Maximum	150
*2	-	100
*3	Standard	50

- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External Static Pressure


3D095697B

FXSQ140A FXSA140A





Fan characteristics (2) Field setting with remote control



Air flow rate [m3/min]


- 1. Upper limit of ESP by air flow auto adjustment 2. Lower limit of ESP by air flow auto adjustment

Mark		ESP [Pa]
*1	Maximum	150
*2	-	100
*3	Standard	50

- 1. The fan characteristics shown are in "fan only" mode. 2. ESP: External Static Pressure




FXMA50-80A




FXMA100-125A

KG Air filter KH Air suction side KJ Air discharge side KK Nameplate



CLICK HERE TO VIEW ALL FXMA-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXMA200-250A




NOTES


- 1. When installing optional accessories, refer to their respective documentation. 2. The unit nameplate is located on the control box cover.


3D140557


FXMQ50P7













Item	Name	Description	
1	Liquid pipe connection port		
2	Gas pipe connection port		
3	Drain pipe connection	VP25 (0D Ø32, ID Ø25)	
4	Remote control wiring connection	-	
5	Power supply connection	-	
6	Drain hole	VP20 (0D Ø32, ID Ø25)	
7	Air filter	-	
8	Air suction side	-	
9	Air discharge side	-	
10	Nameplate	-	


- Refer to 'outlook drawing for installing optional accessories' when installing optional accessories.
 The required ceiling depth varies according to the configuration of the specific system.
 For maintenance of the air filter, it is necessary to provide a service access panel.
 Refer to the 'filter installation method' drawing.





FXMQ63-80P7

















NOTES

1 2 10

6

<u></u> (3) (4)

DETAIL B

- Refer to the outlook drawing of optional accessories when installing them.
 The required ceiling depth varies according to the configuration of the specific 3. system.
 For maintenance of the air filter, it is necessary to provide a service access


- Optional decoration panel: BYBS71DJW1 (light ivory white 10Y9/0.5)

9


3TW31234-1B


DETAIL B

FXMQ100-125P7









-	-	1295 8×150 = 1	
		VIEW A-A	
=======================================			T

1295 8x60 = 1200	DETAIL B
V	

Item	Name	Description
1	Liquid pipe connection port	
2	Gas pipe connection port	
3	Drain pipe connection	VP25 (0D Ø32, ID Ø25)
4	Remote control wiring connection	-
5	Power supply connection	-
6	Drain hole	VP25 (OD ø 32, ID ø 25)
7	Air filter	-
8	Air suction side	-
9	Air discharge side	-
10	Nameplate	-

- Refer to the outlook drawing of optional accessories when installing them.
 The required ceiling depth varies according to the configuration of the specific.
- 3. system.4. For maintenance of the air filter, it is necessary to provide a service access
- 6. Optional decoration panel: BYBS125DJW1 (light ivory white 10Y9/0.5)

CLICK HERE TO VIEW ALL FXMQ-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXMA200A

1572 (13) 9 1526 Inspection hole 600 or more 13×100= 1300 1,143 or more (service space) 1028 10 650 or more (service space) 12×100=1200


Piping size (Field supply)

Indoor unit	Gas side	Liquid side	
FXMA200A	Ø 19.1 attached piping	Ø 9.5	

NOTE


- Location of unit's manufacturer's label: Control box surface.
 Mount the air filter at the suction side.
 (Select its dust collection efficiency (gravity method) 50% or more.)

Number	Name	Description
1	Liquid pipe connection port	Flare connection
2	Gas pipe connection	Attendant piping connection
3	Ground terminal	M5 (inside control box)
4	Control box	
5	Power supply wiring connection	
6	Transmision wiring connection	
7	Hook	M10
8	Discharge flange	
9	Suction flange	
10	Attached piping	Brazing
11	Manufacturer's label	
12	Drain piping connection	PSP 1 inch internal thread Major dia. ø33.3 Minor dia. ø30.3
13	Pre-filter service cover	



3D117990A

FXMA250A




Piping size (Field supply)

Indoor unit	Gas side	Liquid side	
FXMA250A	Ø 22.2 attached piping	Ø 9.5	

NOTE


- 1. Location of unit's manufacturer's label: Control box surface.
- 2. Mount the air filter at the suction side. (Select its dust collection efficiency (gravity method) 50% or more.)


Number	Name	Description
1	Liquid pipe connection port	Flare connection
2	Gas pipe connection	Attendant piping connection
3	Ground terminal	M5 (inside control box)
4	Control box	
5	Power supply wiring connection	
6	Transmision wiring connection	
7	Hook	M10
8	Discharge flange	
9	Suction flange	
10	Attached piping	Brazing
11	Manufacturer's label	
12	Drain piping connection	PSP 1 inch internal thread Major dia. ø33.3 Minor dia. ø30.3
13	Pre-filter service cover	






FXMA50A Upper limit of ESP ① Fan speed: Medium ①








Upper limit of ESP by air flow auto adjustment Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
1	Maximum	200
2	Standard	100
(3)	Minimum	50


- 1. The fan characteristics shown are in "fan only" mode. 2. ESP: External static pressure

4D139872

FXMA63A








Upper limit of ESP by air flow auto adjustment Lower limit of ESP by air flow auto adjustment


Mark	ESP [Pa]	
1	Maximum	200
2	Standard	100
3	Minimum	50

- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External static pressure



FXMA80A






24.0

Air flow rate [m³/min]

27.0

28.0



Air flow rate [m³/min]

Upper limit of ESP by air flow auto adjustment Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
1	Maximum	200
2	Standard	100
3	Minimum	50


- 1. The fan characteristics shown are in "fan only" mode. 2. ESP: External static pressure


4D139878

FXMA100A

22.0









Upper limit of ESP by air flow auto adjustment Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
1	Maximum	200
2	Standard	100
3	Minimum	50

- 1. The fan characteristics shown are in "fan only" mode.
- 2. ESP: External static pressure

FXMA125A







Upper limit of ESP by air flow auto adjustment
 Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
1	Maximum	200
2	Standard	100
3	Minimum	50


- The fan characteristics shown are in "fan only" mode.
 ESP: External static pressure

4D139884


CLICK HERE TO VIEW ALL FXMQ-P7 TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXMQ50P7





Fan characteristics (2 (Field setting with remote control))





NOTES

- 1. Fan characteristics as shown are in "fan only" mode.
- 2. ESP: External static pressure


3TW32698-1

FXMQ63P7





Fan characteristics (2 (Field setting with remote control))





- 1. Fan characteristics as shown are in "fan only" mode.
- 2. ESP: External static pressure




FXMQ80P7

250








Fan characteristics (2 (Field setting with remote control))

Air flow rate [m³/min]





- 1. Fan characteristics as shown are in "fan only" mode.
- 2. ESP: External static pressure

3TW32718-1


FXMQ100P7







Fan characteristics (2 (Field setting with remote control))





NOTES


- 1. Fan characteristics as shown are in "fan only" mode.
- 2. ESP: External static pressure

3TW32728-1


FXMQ125P7







Fan characteristics (2 (Field setting with remote control))





NOTES

- 1. Fan characteristics as shown are in "fan only" mode.
- 2. ESP: External static pressure

3TW32738-1

FXMA200A / FXMQ200A






				Field se	etting with	n remote cor e range (H)	ntrol	
	300							
	250							
g.	200							
External static pressure [Pa]								
essu								
cpr	150							
stati								
nal	100							
xter								
ш	50							
	.00							
	0		58	60	62	64		60
	56	0	38			64	66	68
				Α	ir flow rate [n	n"/min]		


Mark		ESP [Pa]
1	Maximum	250
2	Standard	150
3	Minimum	50


- 1. The fan characteristics shown are in "fan only" mode.
- ESP: External static pressure

CLICK HERE TO VIEW ALL FXMA-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXMA250A / FXMQ250A







Upper limit of ESP by air flow auto adjustment
 Lower limit of ESP by air flow auto adjustment


Mark		ESP [Pa]
1	Maximum	250
2	Standard	150
(3)	Minimum	50

- The fan characteristics shown are in "fan only" mode. ESP: External static pressure


4D140824

CLICK HERE TO VIEW ALL FXAA-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

FXAA15-32A



FXAA40-63A




Outside diameter: 18mm


- 1. The mark shows the piping direction.
- 2. Do not place any objects under the indoor unit. In case of high humidity (>80%), clogged drain outlets, or dirty air filters, condensate may drop out.



FXAQ15-32A



FXAQ40-50A




- 1. The \(\subset\) mark shows the piping direction.
 2. Do not place any objects under the indoor unit. In case of high humidity (>80%),
- clogged drain outlets, or dirty air filters, condensate may drop out.

Inside diameter: 15mm Outside diameter: 18mm


Detailed technical drawings




FXAQ63A









3D106574A






3D106530A




- Please do not place the thing been damp and troubled under an indoor unit. When the case where humidity is 80% or more, the drain outlet are choked up and the air filter are dirty, dew may fall.




FXHQ63A



3D069632A



3D069633D




- 1. The unit nameplate is located on the control box cover.
- 2. When installing a wireless controller, there will be a receiver on this location. For details, see the drawing of the wireless controller.

 3. When closing the discharge grille in case of ·2-way blow or ·3-way blow, there are limit ations to the piping connection direction. See the installation manual.

 4. Do not place any objects under the indoor unit. In case of high humidity (>80%), clogged drain outlets, or dirty air filters, condensate may drop out.

3D138403





- controller in detail.

 3. When closing the discharge grill (2 or 3 way discharge), direction of pipe connection will be limited, please refer to installation manual.
- 4. Please do not place the thing been damp and troubled under an indoor unit. When the case where humidity is 80% or more, and the drain outlet are choked up and the air filter are dirty, dew may fail.



FXNQ20-32A






Item	Name	Description
KA	Liquid pipe connection port	Ø6.40 flared connection
KB	Gas pipe connection port	Ø12.7 flared connection
KC	Drain pipe connection	VP20 (OD Ø26, ID Ø20)
KD	Drain hose	ID Ø25
KE	Control box	/
KF	Transmission line	/
KG	Power supply connection	/
KH	Suspension bracket	/
KJ	Air filter	/
KK	Mounting foot	/

NOTES

- 1. When installing optional accessories, refer to their respective documentation.
 2. The ceiling depth varies according to the documentation of the specific system.

3D096749A


FXNQ40-50A



- 1. When installing optional accessories, refer to their respective documentation. 2. The ceiling depth varies according to the documentation of the specific system.



FXNQ63A




NOTES

- 1. When installing optional accessories, refer to their respective documentation.
 2. The ceiling depth varies according to the documentation of the specific system.

3D096740A

FXNQ20-25A




- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting..

3D086736B



FXNQ32A




NOTES

- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting..

3D081425C


FXNQ40A



- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting..



FXNQ50A




NOTES

- 1. The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting..

3D081427C


FXNQ63A



- The remote controller can be used to switch between 'high' and 'low'.
- The air flow is factory-set to 'standard'. It is possible to switch between 'standard ESP' and 'high ESP' by remote controller setting..




FXLQ20-25P




3TW32294-1

FXLQ32-40P






FXLQ50-63P




3TW32334-1




CLICK HERE TO VIEW ALL HXY-A8 TECHNICAL DRAWINGS ON MY.DAIKIN.EU

HXY-A8



HXY-A8




ESP: External Static Pressure Flow: Water flow through the unit

- Selecting a flow outside the operating area can damage the unit or cause the unit to malfunction. See also the minimum and maximum allowed water flow range in the technical specications. Water quality must be according to EU directive 98/83 EC.




HXHD125A8




3TW59914-1B(1)

HXHD125A8






HXHD200A8





HXHD125A8



NOTES

- The ESP curves are the maximum ESP curves for different (T types (pump rpm=4,200 for (T=5°C; pump rpm=3,800 for (T=10°C).
- The pump of the indoor unit is inverter-controlled and functions to have a fixed (T between the return water temperature and the leaving water temperature.

In case of installing a domestic hot water tank, there is an additional pressure drop over the 3-way valve (delivered as an accessory with the tank).


ESP: External Static Pressure Flow: water flow through the unit

WARNING

- Selecting a flow outside the operating area can damage the unit or cause the unit to malfunction. See also the minimum and maximum allowed water flow range in the technical specications.
- 2. Water quality must be according to EU directive 98/83 EC.

3D097621

HXHD200A8



NOTES

- The ESP curves are the maximum ESP curves, with and without domestic hot water tank installed on top of the indoor unit (pump rpm: 4,000). The pump of the indoor unit is inverter-controlled and functions to have a fixed ΔT between the return water temperature and the leaving water
- 2. In case of installing a domestic hot water tank, there is an additional pressure drop over the 3-way valve (delivered as an accessory with the tank).

ESP: External Static Pressure Flow: water flow through the unit


WARNING

- Selecting a flow outside the operating area can damage the unit or cause the unit to malfunction. See also the minimum and maximum allowed water flow range in the technical specications. Water quality must be according to EU directive 98/83 EC.





CYVS_DK_FBN/FSN / CYVM_DK_FBN/FSN / CYVL_DK_FBN/FSN




NOTES

1. The 2,500mm large devices have 3 suspension brackets, where the third bracket is mounted at half the length of the device.

CU0954X-000

CYVS_DK_CBN/CSN / CYVM_DK_CBN/CSN / CYVL_DK_CBN/CSN




- 1. The 2,500mm large devices have 3 suspension brackets, where the third bracket is mounted at half the length of the device.

 2. The mounting holes for finishing profiles in a lowered ceiling (L+8) x (D+8) mm




CYVS_DK_RBN/RSN / CYVM_DK_RBN/RSN / CYVL_DK_RBN/RSN



NOTES


- 1. The 2,500mm large devices have 3 suspension brackets, where the third bracket is mounted at half the length of the device. 2. Holes (for finishing profiles) drain (L+8) \times (E+8) mm suction (L+8) \times (G+8) mm.

CU0956X-000







ALB02RBS/LBS




ALB03RBS/LBS



ALB04RBS/LBS




ALB05RBS/LBS







ALB06RBS/LBS



ALB07RBS/LBS



ALB02RBS/LBS




The diagram shows the available external pressure for the duct system given an airflow.

SFPv = Specific Fan Power (W/m3/s)

The SFPv curves are referring to the complete unit. Moreover, it includes power to both supply and extract fan divided by either the supply or extract volume whichever is the greater.

Nominal working point

ALB03RBS/LBS




The diagram shows the available external pressure for the duct system given an airflow.

SFPv = Specific Fan Power (W/m3/s)

The SFPv curves are referring to the complete unit. Moreover, it includes power to both supply and extract fan divided by either the supply or extract volume whichever is the greater.

Nominal working point

ALB04RBS/LBS




The diagram shows the available external pressure for the duct system given an airflow.

SFPv = Specific Fan Power (W/m3/s)

The SFPv curves are referring to the complete unit. Moreover, it includes power to both supply and extract fan divided by either the supply or extract volume whichever is the greater.

Nominal working point

ALB05RBS/LBS



The diagram shows the available external pressure for the duct system given an airflow.


SFPv = Specific Fan Power (W/m3/s)

The SFPv curves are referring to the complete unit. Moreover, it includes power to both supply and extract fan divided by either the supply or extract volume whichever is the greater.

Nominal working point



ALB06RBS/LBS




The diagram shows the available external pressure for the duct system given an airflow.

SFPv = Specific Fan Power (W/m3/s)

The SFPv curves are referring to the complete unit. Moreover, it includes power to both supply and extract fan divided by either the supply or extract volume whichever is the greater.

Nominal working point

ALB07RBS/LBS



The diagram shows the available external pressure for the duct system given an airflow.


SFPv = Specific Fan Power (W/m3/s)

The SFPv curves are referring to the complete unit. Moreover, it includes power to both supply and extract fan divided by either the supply or extract volume whichever is the greater.

Nominal working point

CLICK HERE TO VIEW ALL VAM-FC9 TECHNICAL DRAWINGS ON MY.DAIKIN.EU

VAM150FC9




NOTES

1. Be sure to provide the inspection hole (450x450 mm) to inspect the air filters, the exchange elements and fans.

3TW27874-1

VAM250FC9




NOTES

1. Be sure to provide the inspection hole (450x450 mm) to inspect the air filters, the exchange elements and fans.



VAM350-500J




NOTES

1. To allow for the inspection of the air filters, heat exchangers, and fans, be sure to provide the inspection hole.

3D112815C

VAM650J




NOTES

1. To allow for the inspection of the air filters, heat exchangers, and fans, be sure to provide the inspection hole.

CLICK HERE TO VIEW ALL VAM-J TECHNICAL DRAWINGS ON MY.DAIKIN.EU

VAM800-1000J




NOTES

1. To perform maintenance on the air filter, it is required to provide a service access panel.

3D112817D


VAM1500-2000J



NOTES

1. To allow for the inspection of the air filters, heat exchangers, and fans, be sure to provide the inspection hole.

VAM150FC9




NOTES

1. The fan speeds are valid for ·230·V, ·50·Hz power supply.


4D100379A

VAM250FC



CLICK HERE TO VIEW ALL VAM-J TECHNICAL DRAWINGS ON MY.DAIKIN.EU

VAM350J



NOTES


- 1. The fan curves are determined with ·1/3· of the ESP on the outdoor side (EA & OA·), and ·2/3· of the ESP on the indoor side (RA & SA·). EA = Exhaust air OA = Outdoor air
- A = Room air
 SA = Supply air
 2. Measured according to JIS B 8628 2003-

LEGEND

L1 = Low speed lower limitL8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit

3D113493B

VAM500J



NOTES


- 1. The fan curves are determined with ·1/3· of the ESP on the outdoor side (EA & OA), and ·2/3· of the ESP on the indoor side (-RA & SA-).
 - EA = Exhaust air
 - OA = Outdoor air
 - RA = Room air
- SA = Supply air 2. Measured according to JIS B 8628 2003

LEGEND

- L1 = Low speed lower limit L8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting
- H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit



VAM650J



NOTES


- 1. The fan curves are determined with 1/3 of the ESP on the outdoor side (EA & OA), and 2/3 of the ESP on the indoor side (RA & SA).
 - EA = Exhaust air OA = Outdoor air
- RA = Room air
 SA = Supply air
 2. Measured according to JIS B 8628 2003-

LEGEND

L1 = Low speed lower limit L8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit

3D113495B

VAM800J




- 1. The fan curves are determined with 1/3 of the ESP on the outdoor side (EA & OA), and 2/3 of the ESP on the indoor side (RA & SA). EA = Exhaust air OA = Outdoor air RA = Room air
- SA = Supply air 2. Measured according to JIS B 8628 - 2003-

LEGEND

- L1 = Low speed lower limit L8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting
- H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit

CLICK HERE TO VIEW ALL VAM-J TECHNICAL DRAWINGS ON MY.DAIKIN.EU

VAM1000J



NOTES


- 1. The fan curves are determined with 1/3 of the ESP on the outdoor side (EA & OA), and 2/3 of the ESP on the indoor side (RA & SA). EA = Exhaust air
 - OA = Outdoor air
- RA = Room air SA = Supply air
- 2. Measured according to JIS B 8628 2003

LEGEND

L1 = Low speed lower limit L8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit

3D112832A

VAM1500J



NOTES


- I. The fan curves are determined with 1/3 of the ESP on the outdoor side (EA & OA), and 2/3 of the ESP on the indoor side (RA & SA).

 EA = Exhaust air
 OA = Outdoor air
- OA = Outdoor all RA = Room air SA = Supply air
- SA = Supply air 2. Measured according to JIS B 8628 - 2003-

LEGEND

L1 = Low speed lower limit L8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit

VAM2000J



NOTES

I. The fan curves are determined with 1/3 of the ESP on the outdoor side (EA & OA), and 2/3 of the ESP on the indoor side (RA & SA).

EA = Exhaust air
OA = Outdoor air
RA = Room air
SA = Supply air
2. Measured according to JIS B 8628 - 2003-

LEGEND


L1 = Low speed lower limit L8 = Low speed factory setting L15 = Low speed upper limit H1 = High speed lower limit H8 = High speed factory setting

H15 = High speed upper limit UH1 = Ultra-high speed lower limit UH8 = Ultra-high speed factory setting UH15 = Ultra-high speed upper limit


3D112839A



EKVDX32A



EKVDX50A




1. When installing optional accessories, refer to their respective documentation.
2. The ceiling depth varies according to the documentation of the specific system.


3D127967



EKVDX80A



EKVDX100A



Item Name


- 1. When installing optional accessories, refer to their respective documentation.
 2. The ceiling depth varies according to the documentation of the specific system.


∙Ø9.52· flared connection •Ø15.90· flared connection KA Liquid pipe connection port KB Gas pipe connection port Drain pipe connection KD KE Wiring connection Power supply connection Drain outlet KG Air inlet flange KH Air suction side KJ Air discharge side KK Nameplate

Description

CLICK HERE TO VIEW ALL EKVDX-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

EKVDX32A





Air flow rate [m³/h]

High speed lower limitHigh speed factory setting = High speed upper limit H15 Ultra-high speed lower limit
 Ultra-high speed factory setting UH1

UH15 = Ultra-high speed upper limit

Ultra-high speed High speed



NOTES

1. The fan curves are determined with ·1/3· of the ESP on the outdoor side (·EA & OA·), and ·2/3· of the ESP on the indoor side (·RA & SA·). EA = Exhaust air

OA = Outdoor air

RA = Room air SA = Supply air

2. The designed airflow of the system at H and UH tap should be kept as shown in the graphs. If the VAM airflow is out of this range, the compressor of the outdoor unit


and the designed allowed it the system at raid of riap should be kept as shown in the graphs, in the whole allowed its starting, the compressor of the outdoor of may stop for selfprotection purposes.


3. Unit operation with R32 refrigerant is possible in the shaded area of the graphs, but the R32 safety alarm will be triggered if the system airflow drops within this area during operation. No selection in this area is allowed.

4. Measured according to JIS B 8628 - 2003.

3D138264

EKVDX50A






Ultra-high speed

LEGEND

H1 = High speed lower limit
H8 = High speed factory setting
H15 = High speed upper limit
UH1 = Ultra-high speed lower limit
UH8 = Ultra-high speed factory setting
UH15 = Ultra-high speed upper limit

Ultra-high speed High speed



NOTES

1. The fan curves are determined with ·1/3· of the ESP on the outdoor side (EA & OA), and ·2/3· of the ESP on the indoor side (RA & SA).

EA = Exhaust air

OA = Outdoor air

A = Cottoo air

RA = Room air


SA = Supply air


2. The designed airflow of the system at H and UH tap should be kept as shown in the graphs. If the -VAM- airflow is out of this range, the compressor of the outdoor unit may stop for selfprotection purposes.

3. Measured according to JIS B 8628 - 2003-



EKVDX50A






LEGEND

High speed lower limitHigh speed factory settingHigh speed upper limit H15 UH1 UH8 Ultra-high speed lower limit
 Ultra-high speed factory setting UH15 = Ultra-high speed upper limit

Ultra-high speed High speed



1. The fan curves are determined with $\cdot 1/3 \cdot$ of the ESP on the outdoor side (EA & OA·), and $\cdot 2/3 \cdot$ of the ESP on the indoor side (RA & SA).


EA = Exhaust air OA = Outdoor air RA = Room air SA = Supply air

2. The designed airflow of the system at H and UH tap should be kept as shown in the graphs. If the -VAM- airflow is out of this range, the compressor of the outdoor unit may stop for self-protection purposes.


3. Measured according to -JIS B 8628 - 2003-

3D138266

EKVDX80A



Air flow rate [m³/h]



External static pressure [Pa] H15

Air flow rate [m³/h]

LEGEND

H1 = High speed lower limit
H8 = High speed factory setting
H15 = High speed upper limit
H16 = Ultra-high speed lower limit
H17 = Ultra-high speed factory setting
H18 = Ultra-high speed upper limit

Ultra-high speed High speed

NOTES


1. The fan curves are determined with ·1/3· of the ESP on the outdoor side (EA & OA), and ·2/3· of the ESP on the indoor side (RA & SA).


EA = Exhaust air
OA = Outdoor air
RA = Room air
SA = Supply air
2. The designed airflow of the system at H and UH tap should be kept as shown in the graphs. If the ·VAM· airflow is out of this range, the compressor of the outdoor unit may stop for selfprotection purposes.

3. Measured according to JIS B 8628 - 2003-

CLICK HERE TO VIEW ALL EKVDX-A TECHNICAL DRAWINGS ON MY.DAIKIN.EU

EKVDX100A





Air flow rate [m³/h]

LEGEND

High speed lower limitHigh speed factory setting Н1 H15 = High speed upper limit Ultra-high speed lower limit
 Ultra-high speed factory setting UH1 UH15 = Ultra-high speed upper limit

Ultra-high speed High speed

1. The fan curves are determined with $\cdot 1/3 \cdot$ of the ESP on the outdoor side (EA & OA·), and $\cdot 2/3 \cdot$ of the ESP on the indoor side (RA & SA).


EA = Exhaust air OA = Outdoor air RA = Room air SA = Supply air


2. The designed airflow of the system at H and UH tap should be kept as shown in the graphs. If the -VAM- airflow is out of this range, the compressor of the outdoor unit may stop for selfprotection purposes.

3. Measured according to -JIS B 8628 - 2003-

3D138268

EKVDX100A






LEGEND

H1 = High speed lower limit
H8 = High speed factory setting
H15 = High speed upper limit
H16 = Ultra-high speed lower limit
H17 = Ultra-high speed factory setting
H18 = Ultra-high speed upper limit

Ultra-high speed High speed



NOTES


1. The fan curves are determined with ·1/3· of the ESP on the outdoor side (EA & OA), and ·2/3· of the ESP on the indoor side (RA & SA).

EA = Exhaust air
OA = Outdoor air
RA = Room air
SA = Supply air
2. The designed airflow of the system at H and UH tap should be kept as shown in the graphs. If the ·VAM· airflow is out of this range, the compressor of the outdoor unit may stop for selfprotection purposes.

3. Measured according to JIS B 8628 - 2003-




VKM50GBM



- 1. Leave space for servicing the unit and include inspection hatch. (Always open a hole on the side of the control box so that the air filters heat exchange elements, and fans can easily be inspected and serviced.)
- 2. Install the two outdoor ducts with down slope (slope of 1/30 or more) to prevent entry of rain water, also, provide insulation for three ducts (outdoor ducts and indoor supply air duct) to prevent dew condensation. (Material: glass wool of 25mm thick)
- 3. Do not turn the unit upside down.
- 4. Use city water or clean water.
 - Include water supply piping with strainer, a water supply shut-off valve, and a drain valve (both locally procured) somewhere along the water supply piping that can be reached from the inspection.
- 5. It is impossible to connect the water supply piping directly to public piping. Use a cistern tank (of the approved type), if you need to get your water supply from public piping.
- 6. Make sure the supply water 0.02MPa to 0.49MPa (0.2 kg/cm² to 5 kg/cm²)
- 7. Make sure the supply water is between 5°C and 40°C in temperature.
- 8. Insulate the water supply piping to prevent condensation from forming.
- 9. Make sure to install drain piping, and insulate drain piping to prevent dew condensation.
- 10. Keep the drain pipe short and sloping downwards at a gradient of at least 1/100 to prevent air from forming.
- 11. Install in a location where the air around the unit or taken into the umidifier will not drop below 0°C
- 12. Do not use a bent cap or a round hood as the outdoor hood if they might get rained on directly (we recommend using a deep hood) (optional accessory).
- 13. In areas where freezing may occur, always take steps to prevent the pipes from freezing.
- 14. Do not place something which shouldn't get wet at the below of this unit. The dew would fall at following case, where humidity is 80% more, or the exit of drain socket is choked up, or the air filter is very dirty.
- 15. Feed clean water. If the supply water is hard water, use a water softener because of short life.

 Life of humidifying element is about 3 years (4,000 hours), under the supply water conditions of hardness: 150 mg/L. (Life of humidifying element is about 1 years (1,500 hours), under the supply water conditions of hardness: 400 mg/L.)

VKM80GBM




- 1. Leave space for servicing the unit and include inspection hatch. (Always open a hole on the side of the control box so that the air filters heat exchange elements, and fans can easily be inspected and serviced.)
- 2. Install the two outdoor ducts with down slope (slope of 1/30 or more) to prevent entry of rain water, also, provide insulation for three ducts (outdoor ducts and indoor supply air duct) to prevent dew condensation. (Material: glass wool of 25mm thick)
- 3. Do not turn the unit upside down.
- 4. Use city water or clean water.
 - Include water supply piping with strainer, a water supply shut-off valve, and a drain valve (both locally procured) somewhere along the water supply piping that can be reached from the inspection.
- 5. It is impossible to connect the water supply piping directly to public piping. Use a cistern tank (of the approved type), if you need to get your water supply from public piping.
- 6. Make sure the supply water 0.02MPa to 0.49MPa (0.2 kg/cm² to 5 kg/cm²)
- 7. Make sure the supply water is between 5°C and 40°C in temperature.
- 8. Insulate the water supply piping to prevent condensation from forming.
- 9. Make sure to install drain piping, and insulate drain piping to prevent dew condensation.
- 10. Keep the drain pipe short and sloping downwards at a gradient of at least 1/100 to prevent air from forming.
- 11. Install in a location where the air around the unit or taken into the umidifier will not drop below 0°C.
- 12. Do not use a bent cap or a round hood as the outdoor hood if they might get rained on directly (we recommend using a deep hood) (optional accessory).
- 13. In areas where freezing may occur, always take steps to prevent the pipes from freezing.
- 14. Do not place something which shouldn't get wet at the below of this unit. The dew would fall at following case, where humidity is 80% more, or the exit of drain socket is choked up, or the air filter is very dirty.
- 15. Feed clean water. If the supply water is hard water, use a water softener because of short life.

 Life of humidifying element is about 3 years (4,000 hours), under the supply water conditions of hardness: 150 mg/L. (Life of humidifying element is about 1 years (1,500 hours), under the supply water conditions of hardness: 400 mg/L.)



VKM100GBM




- 1. Leave space for servicing the unit and include inspection hatch. (Always open a hole on the side of the control box so that the air filters, heat exchange elements, fans and humidifier elements can easily be inspected and serviced.)
- 2. Install the two outdoor ducts with down slope (slope of 1/30 or more) to prevent entry of rain water. Also, provide insulation for three ducts (outdoor ducts and indoor supply air duct) to prevent dew condensation. (Material: glass wool of 25mm thick)
- 3. Do not turn the unit upside down.
- 4. Use city water or clean water.
 - Include water supply piping with strainer, a water supply shut-off valve, and a drain valve (both locally procured) somewhere along the water supply piping that can be reached from the inspection.
- 5. It is impossible to connect the water supply piping directly to public piping. Use a cistern tank (of the approved type), if you need to get your water supply from public piping.
- 6. Make sure the supply water 0.02MPa to 0.49MPa (0.2 kg/cm² to 5 kg/cm²)
- 7. Make sure the supply water is between 5°C and 40°C in temperature.
- 8. Insulate the water supply piping to prevent condensation from forming.
- 9. Make sure to install drain piping, and insulate drain piping to prevent dew condensation.
- 10. Keep the drain pipe short and sloping downwards at a gradient of at least 1/100 to prevent air from forming.
- 11. Install in a location where the air around the unit or taken into the umidifier will not drop below 0°C
- 12. Do not use a bent cap or a round hood as the outdoor hood if they might get rained on directly (we recommend using a deep hood) (optional accessory).
- 13. In areas where freezing may occur, always take steps to prevent the pipes from freezing.
- 14. Do not place something which shouldn't get wet at the below of this unit. The dew would fall at following case, where humidity is 80% more, or the exit of drain socket is choked up, or the air filter is very dirty.
- 15. Feed clean water. If the supply water is hard water, use a water softener because of short life.

 Life of humidifying element is about 3 years (4,000 hours), under the supply water conditions of hardness: 150 mg/L. (Life of humidifying element is about 1 years (1,500 hours), under the supply water conditions of hardness: 400 mg/L.)

CLICK HERE TO VIEW ALL VKM-GBM TECHNICAL DRAWINGS ON MY.DAIKIN.EU

VKM50GBM



[READING OF PERFORMANCE CHARACTERISTICS]

1. For example: 19(29)-*****-07

Mode no.: 19(29)

First code: * (Supply [2] Exhaust [3])


Second code no.: 07

Rated point: ●

3. The characteristic of each tap becomes a setup of the characteristic of the same code number.

3D082901

VKM80GBM



[READING OF PERFORMANCE CHARACTERISTICS]

1. For example: 19(29)-*****-07

Mode no.: 19(29)

First code: * (Supply [2] Exhaust [3])
Second code no.: 07


2. Rated point: ●

3. The characteristic of each tap becomes a setup of the characteristic of the same code number.

VKM100GBM

- 50Hz, 220V-240V

Exchange efficiency



[READING OF PERFORMANCE CHARACTERISTICS]

1. For example: 19(29)-X-07 Mode no.: 19(29) First code: * (Supply [2] Exhaust [3])
Second code no.: 07

2. Rated point: ●

3. The characteristic of each tap becomes a setup of the characteristic of the same code number.

3D082903

Power supply

T1 = 3~, 220V, 50Hz V1 = 1~, 220-240V, 50Hz

VE = 1~, 220-240V/220V, 50Hz/60Hz*

 $V3 = 1\sim, 230V, 50Hz$

VM = 1~, 220~240V/220~230V, 50Hz/60Hz

W1 = $3N\sim$, 400V, 50Hz Y1 = $3\sim$, 400V, 50Hz

Conversion table refrigerant piping

inch	mm	
1/4"	6.4 mm	
3/8″	9.5 mm	
1/2"	12.7 mm	
5/8″	15.9 mm	
3/4"	19.1 mm	
⁷ / ₈ ″	22.2 mm	
1 1/8″	28.5 mm	
1 ³/ ₈ ″	34.9 mm	
1 5/8″	41.3 mm	
1 ³/₄″	44.5 mm	
2″	50.8 mm	
2 1/8"	54 mm	
2 5/8"	66.7 mm	

F-gas regulation

Any refrigeration system that contains fluorinated greenhouse gases is in scope of the F-gas regulations. For fully/partially pre-charged equipment: contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels and in the notes underneath the specification tables in this catalogue. For non pre-charged equipment (including, but not limited to racks): its functioning relies on fluorinated greenhouse gases. The F-gas regulations do not apply to systems that contain only natural refrigerants such as propane or carbon dioxide.

Measuring conditions

Air conditioning

1) Nominal cooling capacities are based on:	
Indoor temperature	27°CDB/19°CWB
Outdoor temperature	35°CDB
Refrigerant piping length	7.5m - 8/5m VRV
Level difference	0m
2) Nominal heating capacities are based on:	
Indoor temperature	20°CDB
Outdoor temperature	7°CDB/6°CWB
Refrigerant piping length	7.5m - 8/5m VRV
Level difference	0m

Refrigeration

ZEAS	Chilling		Evaporating temp10°C; outdoor temp. 32°C; Suction SH10°C		
	Freezing		Evaporating temp35°C; outdoor temp. 32°C; Suction SH10°C		
Conveni-Pack	Mix Air conditioning and refrigeration operating mode		Indoor temp. 27°CDB/19°CWB; outdoor temp. 32°CDB; piping length:7.5m; level difference: 0m;		
			refrigeration side: Evaporating temp10°C; outdoor temp. 32°CDB; Suction SH: 10°C		
	Mix heating and refrige	ration operating mode	Indoor temp. 20°C; outdoor temp. 7°CDB,6°CWB; advertised refrigerant load (Evaporating temp		
	(Heating recovery 100% mode)		-10°C; Suction SH: 10°C); piping length:7.5m; level difference: 0m		
Booster unit			Evaporating temp35°C; outdoor temp. 32°C; suction SH 10K; saturated temp. to discharge		
			pressure of booster unit -10°C		
CCU/SCU	Medium temperature application		Medium temperature application: Outside ambient temp. 32°C; Evaporating temp. = -10°C and		
			10K superheat;		
	Low temperature application		Low temperature application: Outside ambient temp. 32°C; Evaporating temp. = -35°C and 20°C		
			suction gas temperature		
Zanotti	Uni-Block, Bi-Block, Wineblock	High temperature	When normally running: +10°C / +30°C		
		Medium temperature	When normally running: 0°C / 30°C		
		Low temperature	When normally running: -20°C / +30°C		
	CU (one, twin, and more	Medium temperature	Outside ambient temp. 32°C; Evaporating temp. = -10°C and 20°C suction gas temperature		
	compressor(s))	Low temperature	Outside ambient temp. 32°C; Evaporating temp. = -35°C and 20°C suction gas temperature		

Applied systems


Air cooled	Coolin	g only	Evaporator: 12°C/7°C	Ambient: 35°CDB	
	Heat pump		Evaporator: 12°C/7°C	Ambient: 35°C	
			Condenser: 40°C/45°C	Ambient: 7°CDB/6°CWB	
Water cooled	Cooling only		Evaporator: 12°C/7°C		
			Condenser: 30°C/35°C		
	Heating only		Evaporator: 12°C/7°C		
	пеаш	ig only	Condenser: 40°C/45°C		
Condenserless chiller		Evaporator: 12°C/7°C			
		Condensing temperature: 45°C / liquid temperature: 40°C			
Fan coil units	Cooling		Indoor temperature 27°CDB, 19°CWB; entering water temperature 7°C, water temperature rise 5K		
	Heating	2-pipe	Indoor temperature 20°CDB, 15°CW	/B; entering water temperature 45°C, water temperature drop 5K	
		4-pipe	Indoor temperature 20°CDB, 15°CWB; entering water temperature 65°C, water temperature drop 10K		
Air Handling Units		Temperature and humidity conditions: Extract air 22°C / 50%; Fresh air -10°C / 90%			

The sound pressure level is measured via a microphone at a certain distance from the unit. It is a relative value, depending on the distance and acoustic environment (for measuring conditions: please refer to the technical databooks). The sound power level is an absolute value indicating the "power" which a sound source generates. For more detailed information please consult our technical databooks.

^{*} For VE power supply only 1~, 220-240V, 50Hz data is displayed in this catalogue.

Notes		





flexibility while significantly reducing a building's environmental footprint.

Stretch: With the widest range of indoor and outdoor units on the market and great piping flexibility, VRV 5 Heat Recovery suits any commercial building - and can be installed practically anywhere, thanks to its low sound levels

Shîrudo Technology: Thanks to built-in Shîrudo Technology, VRV 5 Heat Recovery offers maximum flexibility out of the box. With all measures factory-integrated, the technology takes complete care of small room applications in your buildings, without any additional considerations, field supplied equipment or time-consuming studies.


Sustainability: VRV 5 Heat Recovery is more sustainable over its lifecycle, reducing indirect emissions through market-leading seasonal efficiency and highly effective 3-pipe heat recovery. Built specifically for R-32 refrigerant, it reduces Global Warming Potential (GWP) by 71% compared to R-410A systems.

Smart: VRV 5 Heat Recovery is geared for smart comfort. Variable Refrigerant Temperature allows the system to be fully customised to the customer's requirements, ensuring maximum energy efficiency.

Support: Never fear, support is always here for you and your clients. We offer total flexibility and peace of mind from design and specification all the way through to remote monitoring and proactive system maintenance.

Learn more by visiting www.daikin.co.uk/vrv5hr

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Publisher)





FCPFN23-200







Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate www.eurovent-certification.com

VRV 5

BLUEVOLUTION

Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from